SWX-2010

2000 WATTS





Strong and powerful 2000W professional subwoofer driven by an efficient 46 cm (18") LF driver to provide excellent bass response and high power handling capacity. Fitted in a strong and durable thick wooden enclosure which is well braced internally and attractively paint finished externally. The enclosure design suits all types of installed and touring applications. Strong extra-thick grille is designed to give required protection to the speaker and professional appearance to the product. The enclosure is made of 18 mm Plywood and fitted with four heavy duty handles for easy handling. Four indexed feet on top surface provide easy and secure stacking of multiple cabinets. Two speakon connectors on the rear terminal plate are provided for quick & convenient connections.

SPECIFICATIONS	SWX-2010
POWER RATING	2000W RMS/4000W Programme
CONFIGURATION	One Way
FREQUENCY RESPONSE	40-250Hz
LOW FREQUENCY SPEAKER	1 × 460 mm (18") with Ø 127 mm (5") I/O Copper Voice Coil
SPL at (1W/1m)	98dB
MAX. RATED SPL	131dB
NOMINAL IMPEDANCE	8Ω
PORT	Free Flow Flared
INPUT CONNECTORS	2 Nos. of Speakon Sockets
DIMENSIONS	W610 × H900 × D735 mm
WEIGHT	73.20kg