SWX-3100

3000 WATTS





Rugged and powerful 3000W professional subwoofer system driven by two efficient 46 cm (18") LF drivers to generate excellent bass response and provide super power handling capacity. Strong and durable thick wooden enclosure which is well braced and attractively paint finished. The enclosure design suits all types of installed and touring applications. Strong extra-thick grille is designed to give required protection to the speakers and professional apperance to the product. The enclosure is made of 18 mm Plywood and fitted with four heavy duty handles for easy handling. Six indexed feet on top surface provide easy and secure stacking of subwoofer cabinets. Two speakon connectors on the rear terminal plate are provided for quick & convenient connections.

SPECIFICATIONS	SWX-3100
POWER RATING	3000W RMS/6000W Programme
CONFIGURATION	One Way
FREQUENCY RESPONSE	40-250Hz
LOW FREQUENCY SPEAKER	2 × 460 mm (18") with Ø 127 mm (5") I/O Copper Voice Coil
SPL at (1W/1m)	101dB
MAX. RATED SPL	133dB
NOMINAL IMPEDANCE	4Ω
PORT	Free Flow Flared
INPUT CONNECTORS	2 Nos. of Speakon Sockets
DIMENSIONS	W1215 × H610 × D790 mm
WEIGHT	117.20kg