# SWX-3700N

## 3600 WATTS







Robust and powerful 3600W professional subwoofer system driven by two efficient 46 cm (18") Neodymium LF drivers to generate extreme bass response and provide super power handling capacity. Strong and durable wooden enclosure which is well braced and attractively paint finished. The enclosure design suits all types of installed and touring applications. Strong extra-thick grille is designed to give required protection to the speakers and professional apperance to the product. The enclosure is made of 18 mm Plywood and fitted with four heavy duty handles for easy handling. Six indexed feet on top surface provide easy and secure stacking of subwoofer cabinets. Two speakon connectors on the rear terminal plate are provided for quick & convenient connections.

| SPECIFICATIONS | SWX-3700N |
|---|---|
| POWER RATING | 3600W RMS/7200W Programme |
| CONFIGURATION | One Way |
| FREQUENCY RESPONSE | 35-250Hz |
| LOW FREQUENCY SPEAKER | 2 × 460 mm (18") with Ø 114 mm (4.5") Aluminium I/O Voice Coil |
| SPL at (1W/1m) | 102dB |
| MAX. RATED SPL | 137dB |
| NOMINAL IMPEDANCE | 4Ω |
| PORT | Free Flow Flared |
| INPUT CONNECTORS | 2 Nos. of Speakon Sockets |
| DIMENSIONS | W1215 × H610 × D790 mm |
| WEIGHT | 102.00kg |