ALX-15000M

1200 WATTS

2×12" | 2 WAY | NEODYMIUM SPEAKER | DUAL HF DRIVERS | 8Ω | BIRCH Plywood

new product





ALX-15000M is a rugged and reliable Line Array Loudspeaker. Each cabinet comprises of two high power 30.48 cm (12") Neodymium LF drivers and two high performance HF drivers to deliver crisp, loud and clear sound in a variety of indoor & outdoor applications.

- Each line array cabinet is designed to provide controlled & coherent coverage pattern with excellent high frequency response.
- Comprises of two powerful HF drivers with a waveguide horn for constant curvature line array system.
- Smart rigging arrangement for quick & secure installation.
- Professional 2-way passive crossover network with HF protection.
- Strong, attractive and well braced speaker cabinet in durable paint finish.
- Heavy duty steel grille with acoustically transparent foam to protect speakers from various adverse working conditions.
- A sturdy and rugged flybar frame is available for rigging the line array cabinets.
- Suitable for a wide variety of applications in Fixed Installations, Rental, Djs and Live Sound Reinforcement.

SPECIFICATIONS	ALX-15000M
POWER RATING	1200W RMS
CONFIGURATION	Two Way
FREQUENCY RESPONSE	58-20,000Hz
LOW FREQUENCY SPEAKER	2 × 304.8 mm (12"), Ø89 mm (3.5") Voice Coil
HIGH FREQUENCY UNIT	Waveguide Horn with 2 × 38.1 mm (1.5") Throat Compression Driver
SPL (1W/1m)	97dB
MAX RATED SPL	128dB
NOMINAL IMPEDANCE	8Ω
HORIZONTAL COVERAGE ANGLE	120°
VERTICAL COVERAGE ANGLE	10°
VARIABLE SPLAY ANGLES	0°, 2°, 4°, 6°, 8°, 10°
CONNECTORS	2 Nos. of Speakon Sockets
DIMENSIONS	W1050 x H360 x D530 mm
WEIGHT	48.70kg