PA Driver Diaphragms



Diaphragm HD44-60

- High quality diaphragm for compression driver HD44-60T. It features TITANIUM diaphragm, a precision-wound voice coil and sturdy push terminals.
- Rugged construction and reliable performance.
- Higher sensitivity and superb sound quality.
- Engineered with high performance components.



Diaphragm HD51-80

- High quality diaphragm for compression driver HD51-80T. It features TITANIUM diaphragm, a precision-wound voice coil and sturdy push terminals.
- Rugged construction and reliable performance.
- Higher sensitivity and superb sound quality.
- Engineered with high performance components.



Diaphragm HD74-120

- High quality diaphragm for compression driver HD74-120T. It features TITANIUM diaphragm, a precision-wound voice coil and sturdy push terminals.
- Rugged construction and reliable performance.
- Higher sensitivity and superb sound quality.
- Engineered with high performance components.

SPECIFICATIONS	HD44-60	HD51-80	HD74-120
POWER CAPACITY	60W RMS	80W RMS	120W RMS
NOMINAL IMPEDANCE	8Ω	8Ω	8Ω
VOICE COIL DIAMETER	44.4 mm (1.74")	51.0 mm (2.0")	74.0 mm (2.91")
DIAPHRAGM MATERIAL	Titanium	Titanium	Titanium
VOICE COIL MATERIAL	Round Aluminium Wire	Round Aluminium Wire	CCAR Wire
VOICE COIL FORMER	Resin Bonded Kapton	Resin Bonded Kapton	Resin Bonded Kapton

PA Piezo Horn Tweeters

AHUJA present a variety of compact and powerful piezo tweeters, driver and horn with extended high frequency response, low distortion and excellent power handling capacity. These are ideal for use with existing AHUJA range of 30.48 cm (12") and 38.1 cm (15") professional PA speakers.

APT-001

- Piezo tweeter.
- With horn front attachment for rear mounting.



APT-016

- Piezo tweeter.
- Compact rectangular form.



APT-025

- Rectangular high power piezo tweeter with deep low limit frequency



The piezo tweeters can be operated without a crossover network. However, it is recommended to connect a series resistor of about 20-50Ω (10-20W) or a metallised polyester capacitor of about 0.1-0.47mfd in order to avoid interfering effects and for proper matching of SPL levels with the woofer/full range speaker.

SPECIFICATIONS	APT-001	APT-016	APT-025
MAX. VOLTAGE	35V~	35V~	35V~
MUSIC POWER 4Ω/8Ω System	300W/ 150W	300W/ 150W	300W/ 150W
SPL (2.83V/1m)	94dB	91dB	92dB
FREQUENCY RESPONSE	4,000-20,000Hz	3,000-20,000Hz	1,800-20,000Hz
RADIATION ANGLE (V/H)	—	45°/90°	45°/90°
IMPEDANCE @ 1kHz	>1,000Ω	>1,000Ω	>1,000Ω
MOUNTING CUTOUT	73 mm	98 × 55 mm	155 × 58 mm
DIMENSIONS	85 × 85 mm	145 × 67 mm	187 × 80 mm
WEIGHT	65g	55g	100g