


HD44-60T 60 WATTS


Professional compression driver HD44-60T, suitable for high power speakers. It features TITANIUM diaphragm round aluminium wire voice coil and strontium ferrite magnet for high SPL & superb HF response. With a suitable horn it is ideal for use with low frequency speakers AHUJA L12-MB300, L12-MB400, L15-MB300, L15-MB400 and L15-MB550.





HD51-80T 80 WATTS


Professional compression driver HD51-80T, suitable for high power speakers. It features TITANIUM diaphragm round aluminium wire voice coil and strontium ferrite magnet for high SPL & superb HF response. With a suitable horn it is ideal for use with low frequency speakers AHUJA L12-MB400, L15-MB300, L15-MB400, L15-MB550, L15-MB700, N12-MB600X and N12-MB600Z.





HD74-120 120 WATTS

Professional compression driver HD74-120, suitable for high power speakers. It features TITANIUM diaphragm copper clad aluminium ribbon wire voice coil and strontium ferrite magnet for high SPL & superb HF response. With a suitable horn it is ideal for use with low frequency speakers AHUJA L15-MB550, L15-MB700, L15-MB900, N12-MB600X and N12-MB600Z.




SPECIFICATIONS	HD44-60T	HD51-80T	HD74-120
POWER CAPACITY	60W RMS	80W RMS	120W RMS
THROAT DIAMETER	25.4 mm (1")	25.4 mm (1")	50 mm (2")
NOMINAL IMPEDANCE	8Ω	8Ω	8Ω
SENSITIVITY (1W/1m)	106dB (with Horn)	108dB (with Horn)	108dB (with Horn)
USABLE FREQUENCY RANGE	1,500-20,000Hz	1,000-20,000Hz	500Hz - 20,000Hz
RECOMMENDED CROSSOVER	2.5kHz, 18dB/Octave	2.5kHz, 18dB/Octave	1.2kHz, 18 dB/Octave
VOICE COIL DIAMETER	44.4 mm (1.74")	51.0 mm (2.0")	74.0 mm (2.91")
DIAPHRAGM MATERIAL	Titanium	Titanium	Titanium
VOICE COIL MATERIAL	Round Aluminium Wire	Round Aluminium Wire	CCAR Wire
VOICE COIL FORMER	Resin Bonded Kapton	Resin Bonded Kapton	Resin Bonded Kapton
THROAT COUPLING	1-3/8" 18TPI, Throat Couple No.1	1-3/8" 18TPI, Throat Couple No.1	—
OVERALL DIMENSIONS	Ø114 × H67.5 mm	Ø133 × H75 mm	Ø178 × H73 mm
WEIGHT	1.51kg	2.50kg	5.10kg

PA Horn Driver

CDH-200 20 WATTS





Professional compression driver-horn CDH-200 loudspeaker, is suitable for medium power speaker systems. It is ideal for use in a 200W to 300W system. Can be combined with a single Low Frequency speaker like AHUJA L12-MB200, L12-MB300 and L15-MB300, to make an excellent medium power full range speaker system.

SPECIFICATIONS	CDH-200
POWER CAPACITY	20W RMS
THROAT DIAMETER	25.4 mm (1")
NOMINAL IMPEDANCE	8Ω
SENSITIVITY (1W/1m)	105dB
USABLE FREQUENCY RANGE	3kHz-15kHz
RECOMMENDED CROSSOVER	4kHz 12dB/Octave
VOICE COIL DIAMETER	25.4 mm (1.0")
DIAPHRAGM MATERIAL	Phenolic Resin
VOICE COIL MATERIAL	Round Copper Wire
VOICE COIL FORMER	Nomex
HORN MATERIAL	ABS Glass Filled Polycarbonate
NOMINAL COVERAGE ANGLE	H100° x V80° (-5 dB)
HORN CUT OFF FREQUENCY	780Hz
MOUNTING CUTOUT	W235 × H82 mm
OVERALL DIMENSIONS	W270 × H110 × D205 mm
WEIGHT	1.36kg

