LMS-408

Loudspeaker Management System

19" RACK MOUNT





Rear Panel

The LMS-408 is a premium 4 IN / 8 OUT Loudspeaker Management System. With multiple features and easy to use PC software, it provides the best sonic control over the speakers. Ideal for Live, Touring, Installations and PA Applications.

- 32-bit DSP, 48kHz sampling rate, 24bit AD/DA converter.
- Input settings include High-cut, Low-cut, 5 band PEQ, Noise gate, Gain, Mute, Phase and Link adjustment.
- Output settings include Crossover, 7 band PEQ, Gain, Mute, Compressor/Limiter, Phase, Delay and Link adjustment.
- Matrix selection for inputs and outputs each input and output channel name can be chaged.
- High-cut, low-cut filter types can be selected as Butterworth, Link Witz-Riley, or Bessel with slopes from 6dB to 48dB/Octave.
- Compressor/limiter threshold, ratio, attack time and release time can be adjusted continuously for outputs.
- Delay time range is 680ms for output channels.
- Preset settings can be copied for every single channel. Linked channels will have automatic setting adjustment.
- Every input and output channel PEQ curve adjustment graph can be viewed in respective input/output channels.
- Built-in signal generator with Pink noise, White noise and 20 to 20kHz Sine wave.

SPECIFICATIONS	LMS-408
FREQUENCY RESPONSE	20Hz-20,000Hz, -0.3dBu
SIGNAL TO NOISE RATIO	>105 dBu
THD	<0.008 at 1kHz(0dBu)
CROSSTALK	>70dBu
INPUT	Balanced XLR
MAX. INPUT LEVEL	+15dBu
IMPEDANCE	20K/Stereo; 10K/MONO
OUTPUT	Balanced XLR
MAX. OUTPUT LEVEL	+15dBu
IMPEDANCE	<500Ω
DIGITAL PROCESSING	24-bit sigma-delta converters 48kHz Sampling Rates
DISPLAY	Dot matrix screen display
POWER SUPPLY	AC: 220-240V 50/60Hz
PROTECTION	AC: Fuse 1 × 2A (T 2A L)
DIMENSION	W482 × H44 × D210mm
WEIGHT	2.42 kg