IS : 5290

CM/L3092450

NEW/TECH™

Single Landing Valve Type-A





Gun Metal

Body, Bonnet Assembly : LTB2-IS:318
Valve Spindle : Brass Rod -IS : 319/320
Cast Iron Wheel : IS 210
Rubber Washer : IS 937 TYPE- (A)
Spring : Phosphoreus Wire : IS:7608
Gland Packing : Asbestos Thread : IS 4687
Approval : ISI Marked from Burea of Indian Standards, (63mm)

Hydraulic Pressure Test
Performance : 21 Kg.f/cm^2
Tightness : 14Kg.f/cm^2
Flow Test : Satisfactory at 7Kgf/cm^2

Stainless Steel

Body, Bonnet Assembly : Stainless Steel -IS : 3444
Valve Spindle : Stainless Steel -IS : 6603
Cast Iron Wheel : IS : 210
Rubber Washer : IS : 937 (TYPE-A)
Spring : Stainless Steel : IS : 6528
Gland Packing : Asbestor Thread : IS : 4687
Approval : ISI Marked from Burea of Indian Standards, (63mm)

Hydraulic Pressure Test
Performance : 21 Kg.f/cm2
Tightness : 14Kg.f/cm2
Flow Test : Satisfactory at 7Kgf/cm2