Landing Valves

Governing Standard: BS 5041 Part 1 & IS 5290

- Body : Gunmetal / Stainless steel / Brass
- Hand wheel : Cast iron
- Inlet : Flanged or BSP/ NPT threaded
- Outlet : Female instantaneous or male BSP/ NH threaded

- Working pressure : 150 PSI / 10.5 Kg/cm^2
- Seat Test : 240 PSI / 16 Kg/cm^2
- Body Test : 435 PSI / 30 Kg/cm^2

1 Oblique Type Landing Valve

IS:5290:93 TYPE A



Product Code No.	Description	Inlet Sizes	Outlets	Material Of Construction
LV-OT-38	1 ½" (38mm) Size	Flanged inlet as per ANSI/IS 1538(Part IV) Flanged inlet as per PN16 BSP Male threaded inlet NPT Male threaded inlet	2 ½" Female Instantaneous 2 ½"NH(M) 2 ½"NST(M) 2 ½" BSP (M)	Gunmetal Aluminium alloy S.S
LV-OT-63	2 ½"(63mm) Size			
LV-OT-75	3" (75mm) Size			

2 Straight Type Landing Valve



Product Code No.	Description	Inlet Sizes	Outlets	Material Of Construction
LV-ST-63	2 ½" (63mm) Size	Flanged inlet as per ANSI Flanged inlet as per PN16 BSP Male threaded inlet NPT Male threaded inlet	2 ½" Female Instantaneous 2 ½"NH(M) 2 ½"NST(M) 2 ½"BSP(M)	Gunmetal
LV-ST-75	3" (75mm) Size			

3 Right Angle Type Landing Valve



Product Code No.	Description	Inlet Sizes	Outlets	Material Of Construction
LV-RT-63	2 ½" (63mm) Size	Flanged inlet as per ANSI Flanged inlet as per PN16 BSP Male threaded inlet NPT Male threaded inlet	2 ½" Female Instantaneous 2 ½" NH(M) 2 ½" NST(M) 2 ½" BSP(M)	Gunmetal

4 Bib Nose Type Landing Valve



Product Code No.	Description	Inlet Sizes	Outlets	Material Of Construction
LV-BT-63	2 ½" (63mm) Size	Flanged inlet as per ANSI Flanged inlet as per PN16 BSP Male threaded inlet NPT Male threaded inlet	2 ½" Female Instantaneous	Gunmetal
LV-BT-75	3" (75mm) Size			