Implementation of an email-based alert system for large-scale system resources

Robert Poenaru

Department of Computational Physics and Information Technology, IFIN-HH

Table of Contents

- 1. Motivation
- 2. Aim
- 3. Development Stages
- 4. Conclusions

Motivation

Within a research department:

Scientific community

- Tackle different problems
- Construct a codebase for a particular issue
- Develop a scenario for executing simulations
- Request access to computing resources (submit jobs)

System administration community

- Manage allocation of the computing resources for each job
- Monitor executing simulations
- Monitor idling resources
- Keep track of incoming jobs

Simulations

Scientific community

- Unoptimized simulations lead to:
 - Long execution time (will cause delays in the pipeline)
 - Low degree of parallelism (cannot take full advantage of multiple core/threads)
 - Excessive memory consumption (limited resource)

Simulation testing + optimization is required

Resource management + monitoring

Sysadmin community

Allocate jobs (e.g., simulations) to the computing cluster



- Manage computing nodes (updates, services)
- Observe unexpected behavior of the running simulations



Check idling resources for potential issues



 Keeping track of all these aspects 24/7 is very challenging


Project Goals

- Create a service which:
 - 1. Monitor multiple computing nodes/clusters (system resources, executing services, etc.)
 - 2. ! Identify potential issues within the resources
 - 3. Inform the sysadmin in realtime on the occurring issue(s) via e-mail

Alert system

Alert system

General workflow



Alert system

Main features


- Developed in Python
 - Great system compatibility
 - Plenty of packages
 - Strong development community
- Works with virtual environments
- Improved package management using pipenv

Data ingest Stage 1

- The underlying computing infrastructure must send information containing its current status
- Each node on the cluster should send system information (e.g., CPU usage, RAM usage, network activity, running services) to a centralized master node
- The alert system runs on the master node
- Information is send as log files, via a log shipper.

Filebeat Log shipper

- Developed by Elastic™
- Part of the Elasticsearch stack (ELK)
- Lightweight shipper for logs
 - Runs as a service on the system
 - Sends logs to (not only) any other node on the network



Log monitoring Watching log file(s) for changes

The master node runs the

