

Synchronus Communication : After Sending the Request , Thread will wait for Response before going further
Asynchronus Communication : After Sending the Request , Thread will not wait for Response .

Request URL => Query Param and Path Variable (Get Request)

Request Header => Content-Type (Json/XML) [header ("Accept","application/json")]

Request Body => Json/XML => Payload(Post Request) [bodyValue();]

Spring based application development with Spring Boot

- 1)POM starter
- 2)Dependency Version Management
- 3)Auto Configuration
- 4)Embedded Server
- 5)Actuators


Actuators

=====

--> Actuators are use to provide production ready features for our application.(Monitor and Manage our application)

--> To work with Actuators we need use following dependency

```
<dependencies>
  <dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-actuator</artifactId>
  </dependency>
</dependencies>
```



How many beans have been loaded
What is the app health
What is env
Threads
Heap
Config props loaded

==> We must write below configuration in application.properties/yml file to expose other actuators end point part from default end points

Yml file

```
management:
  endpoints:
    web:
      exposure:
        include: '*'
        exclude: "env,beans"
```

```
endpoint:
  shutdown
```

application.properties file

management.endpoint.shutdown.enabled=true

management.endpoints.web.exposure.include=*

management.endpoints.web.exposure.exclude=env,beans

health : http://localhost:8080/actuator/health

mapping :http://localhost:8080/actuator/mappings

Shutdown: http://localhost:8080/actuator/shutdown ==> binded to post request

beans: http://localhost:8080/actuator/beans

==> shutdown is a special end point used to stop our application and it is mapped to POST request
(Other end points are mapped to GET request)