EV CHARGER CATALOGUE



DC SERIES II

Standard Fast EV Charger

DC SINGLE GUN
20KW 30KW 40KW

AXI-EVOO-DSG20K-II

AXI-EVOO-DSG30K-II

AXI-EVOO-DSG40K-II



7-inch Color Touch Screen

User-friendly interface with crisp visuals for an effortless charging experience.

4G / Ethernet / WIFI

Flexible multi-mode network communication for stable,real-time remote management.

Communication Protocol: OCPP 1.6J / 2.0.1

Seamless smart connectivity and backend integration powered by universal OCPP 1.6J protocol.

Noise: ≤75db

Ultra-quiet operation at ≤75dB, perfect for quiet residential and commercial zones.

IP Grade: IP54 Waterproof

Robust IP54 waterproof protection, engineered to withstand heavy rain and dust.

Working Temperature: -30 C to 70 C

All-weather durability, performing flawlessly in extreme climates from -30°C to 70°C.

PRODUCT
PARAMETERS

Model	AXI-EVOO-DSG20K-II	AXI-EVOO-DSG30K-II	AXI-EVOO-DSG40K-II
Input voltage	AC380V Three-phase five-wire		
Input voltage range	380Vac±20%		
Maximum input current	32A	58A	76A
Operating frequency	50/60Hz		
Output voltagerange	50-1000VDC		
Maximum output	63A	100A	133A
Output power	20KW	30KW	40KW
Power switching			
THDi	≤5% (Input 380V, Output 1000V, 50%~100% Load)		
Input surge current	≤110% of rated input current		
Power factor	≥0.99 (50%~100% output power, nominal input voltage and frequency) ≥0.95 (20%~50% output power, nominal input voltage and frequency)		
Voltage regulation	±±0.5% (-30 C~+55 C)		
Current stabilization	±±1% (-30 C~+55 C , 20%~100%Load current)		
Output ripple	Ripple peak coefficient ≤ ±1% (input voltage at 85%, 100%, 115%)		
Overall machine efficiency	>96% (100% full load output power)		
Standby power consumption	≤15W		
Heat dissipation	air-cooled		
Noise	≤75db(1 meter away)		
Cable specifications	Cu : 3*10+2*6mm²	Cu : 3*16+2*10mm²	Cu : 3*25+2*16mm²
	Al : 3*25+2*16mm²	Al : 3*25+2*16mm²	Al : 3*35+2*25mm²
Relevant standards	Meets technical requirements:GB/T 18487.1-2015; GB/T 27930-2015; GB/T 20234-2015		
Charging gun	5m charging gun (length customized available)		
Package size	970*970*420mm		
Gross weight	91.5kg (40KW)		



Credit Card Payments
(Optional)



CCS1 CCS2 CHAdeMO GB/T Tesla (NACS)

AXI EVOO EV CHARGING SOLUTIONS
WEB: axisolar.com
EMAIL: info@axisolar.com
Address: Dalingshan, Dongguan City, Guangdong Province, China

© 2026 AXISolar All rights reserved.
We reserve the right of final interpretation.
The specifications in this datasheet are subject to change without notice.