EV CHARGER CATALOGUE



AC SERIES III

Standard Fast EV Charger

AC PORTABLE 7/11/22KW

AXI-EVOO-7K-P-III

AXI-EVOO-11K-P-III

AXI-EVOO-22K-P-III



Key Benefits

- Overvoltage Protection
- Undervoltage Protection
- Overcurrent Protection
- OTA
- Grounded/ Ungrounded
- HCI
- Overtemperature Protection
- Lightning Protection
- IP65
- Bluetooth/ WIFI
- Leakage Protection
- Fully Certified

PRODUCT PARAMETERS

GB/T

Input Voltage	220Vac±20%/380Vac±20%
Product Size	400*163*95 mm
Input Current	16A/32A
Rating	7kW/11kW/22kW
Leakage Type	A
Operating Tumidity	5%-95% condensationless
Operating Temperature	-25 °C~+50 °C
Functional Support	Display, Indicator, Swipe Card, Bluetooth/WIFI(optional)
Protective Function	Over-voltage protection, over-current protection, leakage protection, over-temperature protection, lightning protection, etc.

Type 2


Input Voltage	220Vac±20%/380Vac±20%
Product Size	400*163*95 mm
Input Current	16A/32A
Rating	7kW/11kW/22kW
Leakage Type	A
Operating Tumidity	5%-95% condensationless
Operating Temperature	-25 °C~+50 °C
Functional Support	Display, Indicator, Swipe Card, Bluetooth/WIFI(optional)
Protective Function	Over-voltage protection, over-current protection, leakage protection, over-temperature protection, lightning protection, etc.

Type 1 / NACS

Input Voltage	240Vac±20%
Product Size	400*163*95 mm
Input Current	32A/48A
Rating	7.6kW/11.5kW
Leakage Type	A or CCID20(optional)
Operating Tumidity	5%-95% condensationless
Operating Temperature	-25 °C~+50 °C
Functional Support	Display, Indicator, Swipe Card, Bluetooth/WIFI(optional)
Protective Function	Over-voltage protection, over-current protection, leakage protection, over-temperature protection, lightning protection, etc.




Pragmatic



Indicator light: green always on



Charge Waiting



Indicator light: blue always on



Charging Complete



Indicator light: blue always on



Insert A Gun



Indicator light: green flashing



Charging



Indicator light: blue flashing



Faults



Indicator light: red flashing

AXI EVOO EV CHARGING SOLUTIONS
WEB: axisolar.com
EMAIL: info@axisolar.com
Address: Dalingshan, Dongguan City, Guangdong Province, China

© 2026 AXISolar All rights reserved.
We reserve the right of final interpretation.
The specifications in this datasheet are subject to change without notice.