

Mock Exam 1 – QCM

Q1. Where is the HTML content stored after `requests.get()`?

- A. `response.html`
- B. `response.text`
- C. `response.content_url`
- D. `response.status`

Q2. Which HTTP status code indicates success?

- A. 301
- B. 403
- C. 404
- D. 200

Q3. Which selector is most reliable for scraping?

- A. Visible text inside a `<div>`
- B. An element's position in the page
- C. A tag with a specific id or class
- D. The color of the text

Q4. Why can requests fail on dynamic websites?

- A. Requests cannot access HTTPS websites
- B. The data is loaded using JavaScript after page load
- C. Requests is slower than Selenium
- D. Requests blocks cookies by default

Q5. What does `driver.get()` do?

- A. Downloads the HTML without executing JavaScript
- B. Opens the page in a real browser and executes JavaScript
- C. Returns a BeautifulSoup object
- D. Sends a POST request

Q6. What is `driver.page_source`?

- A. The original HTML sent by the server
- B. Only visible elements
- C. The rendered HTML after JavaScript execution
- D. A screenshot of the page

Q7. Why use waits in Selenium?

- A. To improve internet speed
- B. To avoid HTTP errors
- C. To wait for JavaScript-loaded elements to appear
- D. To reduce memory usage

Q8. Which join keeps **all rows from the left DataFrame** and matches when possible?

- A. Inner join
- B. Right join
- C. Left join
- D. Outer join

Q9. Which parameter defines join type in merge()?

- A. on
- B. how
- C. axis
- D. join_type

Q10. Which method is best suited to **filter rows** based on a regex pattern?

- A. .apply()
- B. .str.replace()
- C. .str.contains()
- D. .filter()