

CX

Generated by Doxygen 1.8.6

Fri Mar 21 2014 12:42:37

## Contents

<b>1</b>	<b>Main Page</b>	<b>1</b>
1.1	Installation . . . . .	1
1.2	Getting Started . . . . .	2
1.3	Examples and Tutorials . . . . .	2
<b>2</b>	<b>Blocking Code</b>	<b>3</b>
<b>3</b>	<b>Framebuffers and Buffer Swapping</b>	<b>4</b>
<b>4</b>	<b>Modules</b>	<b>4</b>
<b>5</b>	<b>Program Model</b>	<b>4</b>
<b>6</b>	<b>license</b>	<b>7</b>
<b>7</b>	<b>Module Index</b>	<b>7</b>
7.1	Modules . . . . .	7
<b>8</b>	<b>Namespace Index</b>	<b>8</b>
8.1	Namespace List . . . . .	8
<b>9</b>	<b>Hierarchical Index</b>	<b>8</b>
9.1	Class Hierarchy . . . . .	8
<b>10</b>	<b>Class Index</b>	<b>10</b>
10.1	Class List . . . . .	10
<b>11</b>	<b>File Index</b>	<b>12</b>
11.1	File List . . . . .	12
<b>12</b>	<b>Module Documentation</b>	<b>13</b>
12.1	Data . . . . .	13
12.1.1	Detailed Description . . . . .	14
12.2	Entry Point . . . . .	15
12.2.1	Detailed Description . . . . .	15
12.2.2	Function Documentation . . . . .	15
12.2.3	Variable Documentation . . . . .	15
12.3	Error Logging . . . . .	16
12.3.1	Detailed Description . . . . .	16
12.3.2	Enumeration Type Documentation . . . . .	16

12.4	Input Devices	17
12.4.1	Detailed Description	17
12.5	Randomization	18
12.5.1	Detailed Description	18
12.6	Sound	19
12.6.1	Detailed Description	19
12.7	Timing	20
12.7.1	Detailed Description	20
12.7.2	Variable Documentation	20
12.8	Utility	21
12.8.1	Detailed Description	21
12.9	Video	22
12.9.1	Detailed Description	22
<b>13</b>	<b>Namespace Documentation</b>	<b>23</b>
13.1	CX Namespace Reference	23
13.1.1	Detailed Description	24
13.1.2	Function Documentation	24
13.2	CX::Algo Namespace Reference	24
13.2.1	Detailed Description	25
13.2.2	Function Documentation	25
13.3	CX::Draw Namespace Reference	26
13.3.1	Detailed Description	27
13.3.2	Function Documentation	27
13.4	CX::Instances Namespace Reference	28
13.4.1	Detailed Description	28
13.5	CX::Private Namespace Reference	28
13.5.1	Detailed Description	29
13.6	CX::Synth Namespace Reference	29
13.6.1	Detailed Description	29
13.7	CX::Util Namespace Reference	30
13.7.1	Detailed Description	31
13.7.2	Function Documentation	31
<b>14</b>	<b>Class Documentation</b>	<b>35</b>
14.1	CX::Synth::Adder Class Reference	35
14.1.1	Detailed Description	35
14.1.2	Member Function Documentation	36

14.2	<a href="#">CX::Synth::AdditiveSynth Class Reference</a>	36
14.2.1	Detailed Description	36
14.2.2	Member Enumeration Documentation	37
14.2.3	Member Function Documentation	37
14.3	<a href="#">CX::Algo::BlockSampler&lt; T &gt; Class Template Reference</a>	39
14.3.1	Detailed Description	40
14.4	<a href="#">CX::Synth::Clamper Class Reference</a>	40
14.4.1	Detailed Description	40
14.4.2	Member Function Documentation	41
14.5	<a href="#">CX::CX_SlidePresenter::Configuration Struct Reference</a>	41
14.5.1	Detailed Description	41
14.5.2	Member Enumeration Documentation	42
14.6	<a href="#">CX::CX_SoundStream::Configuration Struct Reference</a>	42
14.6.1	Detailed Description	42
14.6.2	Member Data Documentation	42
14.7	<a href="#">CX::CX_BaseClock Class Reference</a>	43
14.7.1	Detailed Description	43
14.8	<a href="#">CX::CX_Clock Class Reference</a>	44
14.8.1	Detailed Description	44
14.8.2	Member Function Documentation	44
14.9	<a href="#">CX::Util::CX_CoordinateConverter Class Reference</a>	45
14.9.1	Detailed Description	45
14.9.2	Constructor & Destructor Documentation	46
14.9.3	Member Function Documentation	46
14.10	<a href="#">CX::CX_DataFrame Class Reference</a>	48
14.10.1	Detailed Description	49
14.10.2	Member Function Documentation	49
14.11	<a href="#">CX::CX_DataFrameCell Class Reference</a>	57
14.11.1	Detailed Description	58
14.11.2	Constructor & Destructor Documentation	58
14.11.3	Member Function Documentation	58
14.12	<a href="#">CX::CX_DataFrameColumn Class Reference</a>	61
14.12.1	Detailed Description	61
14.13	<a href="#">CX::CX_DataFrameRow Class Reference</a>	61
14.13.1	Detailed Description	61
14.14	<a href="#">CX::Util::CX_DegreeToPixelConverter Class Reference</a>	61
14.14.1	Detailed Description	62

14.14.2 Constructor & Destructor Documentation . . . . .	62
14.14.3 Member Function Documentation . . . . .	62
14.15CX::CX_Display Class Reference . . . . .	63
14.15.1 Detailed Description . . . . .	63
14.15.2 Member Function Documentation . . . . .	63
14.16CX::CX_InputManager Class Reference . . . . .	67
14.16.1 Detailed Description . . . . .	67
14.16.2 Member Function Documentation . . . . .	67
14.17CX::CX_Joystick Class Reference . . . . .	68
14.17.1 Detailed Description . . . . .	68
14.17.2 Member Function Documentation . . . . .	69
14.18CX::CX_Keyboard Class Reference . . . . .	69
14.18.1 Detailed Description . . . . .	70
14.18.2 Member Function Documentation . . . . .	70
14.19CX::Util::CX_LapTimer Class Reference . . . . .	71
14.19.1 Detailed Description . . . . .	71
14.20CX::Util::CX_LengthToPixelConverter Class Reference . . . . .	71
14.20.1 Detailed Description . . . . .	71
14.20.2 Constructor & Destructor Documentation . . . . .	72
14.20.3 Member Function Documentation . . . . .	72
14.21CX::CX_Logger Class Reference . . . . .	72
14.21.1 Detailed Description . . . . .	73
14.21.2 Member Function Documentation . . . . .	73
14.22CX::CX_Mouse Class Reference . . . . .	76
14.22.1 Detailed Description . . . . .	76
14.22.2 Member Function Documentation . . . . .	76
14.23CX::CX_RandomNumberGenerator Class Reference . . . . .	77
14.23.1 Detailed Description . . . . .	78
14.23.2 Constructor & Destructor Documentation . . . . .	78
14.23.3 Member Function Documentation . . . . .	78
14.24CX::CX_SlidePresenter Class Reference . . . . .	84
14.24.1 Detailed Description . . . . .	86
14.24.2 Member Enumeration Documentation . . . . .	86
14.24.3 Member Function Documentation . . . . .	86
14.25CX::CX_SoundObject Class Reference . . . . .	89
14.25.1 Detailed Description . . . . .	90
14.25.2 Member Function Documentation . . . . .	90

14.26CX::CX_SoundObjectPlayer Class Reference . . . . .	96
14.26.1 Detailed Description . . . . .	96
14.26.2 Member Function Documentation . . . . .	96
14.27CX::CX_SoundObjectRecorder Class Reference . . . . .	98
14.27.1 Detailed Description . . . . .	98
14.27.2 Member Function Documentation . . . . .	99
14.28CX::CX_SoundStream Class Reference . . . . .	99
14.28.1 Detailed Description . . . . .	100
14.28.2 Member Function Documentation . . . . .	101
14.29CX::CX_Time_t< TimeUnit > Class Template Reference . . . . .	104
14.29.1 Detailed Description . . . . .	105
14.29.2 Member Function Documentation . . . . .	105
14.30CX::Util::CX_TrialController Class Reference . . . . .	106
14.30.1 Detailed Description . . . . .	106
14.30.2 Member Function Documentation . . . . .	106
14.31CX::Synth::Envelope Class Reference . . . . .	108
14.31.1 Detailed Description . . . . .	108
14.31.2 Member Function Documentation . . . . .	108
14.32CX::CX_Mouse::Event Struct Reference . . . . .	108
14.32.1 Detailed Description . . . . .	109
14.32.2 Member Enumeration Documentation . . . . .	109
14.33CX::CX_Joystick::Event Struct Reference . . . . .	109
14.33.1 Detailed Description . . . . .	110
14.33.2 Member Enumeration Documentation . . . . .	110
14.34CX::CX_Keyboard::Event Struct Reference . . . . .	110
14.34.1 Detailed Description . . . . .	111
14.34.2 Member Enumeration Documentation . . . . .	111
14.34.3 Member Data Documentation . . . . .	111
14.35CX::Synth::Filter Class Reference . . . . .	112
14.35.1 Detailed Description . . . . .	112
14.35.2 Member Enumeration Documentation . . . . .	112
14.35.3 Member Function Documentation . . . . .	112
14.35.4 Member Data Documentation . . . . .	112
14.36CX::CX_SlidePresenter::FinalSlideFunctionArgs Struct Reference . . . . .	113
14.36.1 Detailed Description . . . . .	113
14.37CX::Synth::FIRFilter Class Reference . . . . .	113
14.37.1 Detailed Description . . . . .	114

14.37.2 Member Enumeration Documentation . . . . .	114
14.37.3 Member Function Documentation . . . . .	114
14.38CX::CX_SoundStream::InputEventArgs Struct Reference . . . . .	114
14.38.1 Detailed Description . . . . .	114
14.39CX::Algo::LatinSquare Class Reference . . . . .	115
14.39.1 Detailed Description . . . . .	115
14.39.2 Member Function Documentation . . . . .	116
14.40CX::Synth::Mixer Class Reference . . . . .	117
14.40.1 Detailed Description . . . . .	117
14.40.2 Member Function Documentation . . . . .	117
14.41CX::Synth::ModuleBase Class Reference . . . . .	118
14.41.1 Detailed Description . . . . .	119
14.41.2 Member Function Documentation . . . . .	119
14.41.3 Friends And Related Function Documentation . . . . .	119
14.42CX::Synth::Multiplier Class Reference . . . . .	119
14.42.1 Detailed Description . . . . .	120
14.42.2 Member Function Documentation . . . . .	120
14.43CX::Synth::Oscillator Class Reference . . . . .	120
14.43.1 Detailed Description . . . . .	121
14.43.2 Member Function Documentation . . . . .	121
14.44CX::CX_SoundStream::OutputEventArgs Struct Reference . . . . .	121
14.44.1 Detailed Description . . . . .	122
14.45CX::CX_SlidePresenter::PresentationErrorInfo Struct Reference . . . . .	122
14.45.1 Detailed Description . . . . .	122
14.45.2 Member Data Documentation . . . . .	122
14.46CX::CX_SlidePresenter::Slide Struct Reference . . . . .	123
14.46.1 Detailed Description . . . . .	123
14.47CX::CX_SlidePresenter::SlideTimingInfo Struct Reference . . . . .	123
14.47.1 Detailed Description . . . . .	124
14.48CX::Synth::SoundObjectInput Class Reference . . . . .	124
14.48.1 Detailed Description . . . . .	124
14.48.2 Member Function Documentation . . . . .	124
14.49CX::Synth::SoundObjectOutput Class Reference . . . . .	125
14.49.1 Detailed Description . . . . .	125
14.50CX::Synth::Splitter Class Reference . . . . .	125
14.50.1 Detailed Description . . . . .	126
14.50.2 Member Function Documentation . . . . .	126

14.51 <a href="#">CX::Synth::StereoSoundObjectOutput Class Reference</a>	126
14.51.1 Detailed Description	126
14.52 <a href="#">CX::Synth::StereoStreamOutput Class Reference</a>	127
14.52.1 Detailed Description	127
14.53 <a href="#">CX::Synth::StreamOutput Class Reference</a>	127
14.53.1 Detailed Description	128
<b>15 File Documentation</b>	<b>128</b>
15.1 <a href="#">advancedChangeDetectionTask.cpp File Reference</a>	128
15.1.1 Detailed Description	129
15.2 <a href="#">advancedNBack.cpp File Reference</a>	129
15.2.1 Detailed Description	130
15.3 <a href="#">basicChangeDetectionTask.cpp File Reference</a>	130
15.3.1 Detailed Description	131
15.4 <a href="#">modularSynth.cpp File Reference</a>	131
15.4.1 Detailed Description	131
15.5 <a href="#">nBack.cpp File Reference</a>	131
15.5.1 Detailed Description	132
<b>Index</b>	<b>133</b>

## 1 Main Page

ofxCX (hereafter referred to as [CX](#)) is a "total conversion mod" for openFrameworks (often abbreviated oF) that is designed to be used for creating psychology experiments.

The most well-organized way to access the documentation is go to the [Modules](#) page. The best way to get an overview of how [CX](#) works is to look at the [Examples and Tutorials](#).

To learn about presenting visual stimuli, go to the [Video](#) page or see the renderingTest or animation examples or the N-Back or change detection example experiments.

To learn about auditory stimuli, go to the [Sound](#) page or see the soundObject or modularSynth examples.

To learn how to store and output experiment data, see the [Data](#) page or see the dataFrame example.

To learn about random number generation, see the [Randomization](#) page.

To learn about how [CX](#) logs errors and other runtime information, see the [Error Logging](#) page.

### 1.1 Installation

In order to use [CX](#), you must have openFrameworks installed. See <http://openframeworks.cc/download/> to download openFrameworks. On that page, you can also find installation guides for some of the most popular development environments. Currently only version 0.8.0 of openFrameworks is supported by [CX](#).

Once you have installed openFrameworks, you can install [CX](#) by putting the contents of the [CX](#) repository into a sub-



directory under OFDIR/addons (typically OFDIR/addons/ofxCX), where OFDIR is where you put openFrameworks when you installed it.

To use [CX](#) in a project, use the openFrameworks project generator and select ofxCX as an addon. The project generator can be found in OFDIR/projectGenerator.

In order to use the [Examples and Tutorials](#), do the following:

1. Use the oF project generator (OFDIR/projectGenerator/projectGeneratorSimple.exe) to create a new project that uses the ofxCX addon. The project generator asks you what to name your project, where to put it (defaults to OFDIR/apps/myApps/), and has the option of selecting addons. Click the "addons" button and check to box next to ofxCX. If ofxCX does not appear in the list of addons, you probably didn't put the ofxCX directory in the right place.
2. Go to the newly-created project directory (that you chose when creating the project in step 1) and go into the src subdirectory.
3. Delete all of the files in the src directory (main.cpp, testApp.h, and testApp.cpp). 4a. Copy the example .cpp file into this src directory. 4b. If the example has a data folder, copy the contents of that folder into yourProject-Directory/bin/data. bin/data folders probably won't exist at this point. You can create them.
4. This step depends on your compiler, but you'll need to tell it to use the example source file that you copied in step 4a when it compiles the project (and possibly to specifically not use the files you deleted from the src directory in step 3).
5. Compile and run the project.

## 1.2 Getting Started

To create your first experiment, follow the steps for using the examples in [Installation](#) up to and including step 3. Then create a blank .cpp file in the source directory of the project folder you made. In the file, you will need to include [CX\\_EntryPoint.h](#) and define runExperiment, like in the example below:

```
#include "CX_EntryPoint.h"

void runExperiment (void) {
    //Do your thing
}
```

That's all you need to do to get started. You should look at the [Examples and Tutorials](#) in order to learn more about how [CX](#) works. You should start with the helloWorld example.

## 1.3 Examples and Tutorials

There are several examples that serve as tutorials for [CX](#). Some of the examples are on a specific topic and others are sample experiments that integrate together different features of [CX](#). The example files can be found in the [CX](#) directory (see [Installation](#)) in subfolders with names beginning with "example-".

### Tutorials:

- soundObject - Tutorial covering a number of things that you can do with CX\_SoundObjects, including loading sound files, combining sounds, and playing them.
- modularSynth - This tutorial demonstrates a number of ways to generate auditory stimuli using the synthesizer modules in the [CX::Synth](#) namespace.

- `dataFrame` - Tutorial covering use of `CX_DataFrame`, which is a container for storing data that is collected in an experiment.
- `logging` - Tutorial explaining how the error logging system of `CX` works and how you can use it in your experiments.
- `animation` - A simple example of a simple way to draw moving things in `CX`. Also includes some mouse input handling: cursor movement, clicks, and scroll wheel activity.

#### Experiments:

- `basicChangeDetection` - A very straightforward change-detection task demonstrating some of the features of `CX` like presentation of time-locked stimuli, keyboard response collection, and use of the `CX_RandomNumberGenerator`.
- `advancedChangeDetection` - This example expands on `basicChangeDetection`, including `CX_DataFrame` and `CX_TrialController` in order to simplify the experiment.
- `nBack` - Demonstrates advanced use of `CX_SlidePresenter` in the implementation of an N-Back task.

#### Misc.:

- `helloWorld` - A very basic getting started program.
- `renderingTest` - Includes several examples of how to draw stuff using `ofPath` (arbitrary lines), `ofTexture` (a kind of pixel buffer), `ofImage` (for opening image files: .png, .jpg, etc.), a variety of basic `of` drawing functions (`ofCircle`, `ofRect`, `ofTriangle`, etc.), and a number of `CX` drawing functions from the `CX::Draw` namespace.

## 2 Blocking Code

Blocking code is code that either takes a long time to complete or that waits until some event occurs before allowing code execution to continue. An example of blocking code that waits is

```
do {
    Input.pollEvents();
} while (Input.Keyboard.availableEvents() == 0);
```

This code waits until the keyboard has been used in some way. No code past it can be executed until the keyboard is used, which could take a long time. Any code that blocks while waiting for a human to do something is blocking.

An example of blocking code that takes a long time (or at least could take a long time) is

```
vector<double> d = CX::Util::sequence<double>(0, 1000000, .033);
```

which requires the allocation of about 300 MB of RAM. This code doesn't wait for anything to happen, it just takes a long time to execute.

Blocking code is potentially harmful because it prevents some parts of `CX` from working in some situations. It is not a cardinal sin and there are times when using blocking code is acceptable. However, blocking code should not be used when trying to present stimuli or when responses are being made. The reason for this is that `CX` expects to be able to repeatedly check information related to stimulus presentation and input at very short intervals (at least every millisecond), but that cannot happen if a piece of code is blocking. There is of course an exception to the "no blocking while waiting for responses" rule, which is when your blocking code is doing nothing but waiting for a response and constantly polling for user input. For example, the following code waits until any response is made:

```
while (!Input.pollEvents())
    ;
```

### 3 Framebuffers and Buffer Swapping

Sometimes pieces of terminology that come up a lot in the documentation for CX are framebuffer, front buffer, back buffer, and swap buffers. What exactly are these things?

A framebuffer is fairly easy to explain in the rough by example. The contents of the screen of a computer are stored in a framebuffer. A framebuffer is essentially a rectangle of pixels where each pixel can be set to display any color. Framebuffers do not always have the same number of pixels as the screen: you can have framebuffers that are smaller or larger than the size of the screen. Framebuffers larger than the screen don't really do much for you as you cannot fit the whole thing on the screen. In CX, framebuffers are typically worked with through the abstraction of an offFbo.

There are two special framebuffers: The front buffer and the back buffer. These are created by OpenGL automatically as part of starting OpenGL. The size of these special framebuffers is functionally the same as the size of the window (or the whole screen, if in full screen mode). The front buffer contains what is shown on the screen. The back buffer is not presented on the screen, so it can be rendered to at any time without affecting what is visible on the screen. Typically, when you render stuff in CX, you call `CX::CX_Display::beginDrawingToBackBuffer()` and `CX::CX_Display::endDrawingToBackBuffer()` around whatever you are rendering. This causes drawing that happens between the two function calls to be rendered to the back buffer.

What you have rendered to the back buffer has no effect on what you see on screen until you swap the contents of the front and back buffers. This isn't a true swap, in that the back buffer does not end up with the contents of the front buffer in it. In reality, the back buffer is copied to the front buffer and is itself unchanged. This swap can be done by using different functions of the CX\_Display: `BLOCKING_swapFrontAndBackBuffers()`, `swapFrontAndBackBuffers()`, or `BLOCKING_setAutoSwapping()`. These functions are not interchangeable, so make sure you are using the right one for your application.

### 4 Modules

### 5 Program Model

#### Program Flow

One of the foundational aspects of CX is the design of the overall program flow, which includes things such as how responses are collected, how stimuli are drawn to the screen, and other similar concepts. The best way to learn about program flow is to examine the [examples](#). The examples cover most of the critical topics and introduce the major components of CX.

The most important thing to understand is that in CX, nothing happens that your code does not explicitly ask for, with the exception of a small amount of setup, which is discussed below (see Pre-experiment Setup). For example, CX does not magically collect and timestamp user responses for you. Your code must poll for user input in order to get timestamps for input. This is explained more in the input section. In CX, there is no code running in the background that makes everything work out for your experiment, you have to design your experiment in such a way that you are covering all of your bases. That said, CX is specifically designed to make doing that as easy and painless as possible, while still giving you as much control over your experiment as is reasonably possible.

#### Internals/Attributions

CX is not a monolithic entity. It is based on a huge amount of open source software written by many different authors over the years. Clearly, CX is based on openFrameworks, but openFrameworks itself is based on many different libraries. Window handling, which involves creating a window that can be rendered to and receiving user input events from the operating system, is managed by GLFW (<http://www.glfw.org/>). The actual rendering is visual stimuli is done using OpenGL (<http://www.opengl.org/>), which is wrapped by several openFrameworks abstractions (e.g. of-

GLProgrammableRenderer at a lower level, e.g. ofPath at the level at which a typical user would use).

Audio is processed in different ways depending on the type of audio player used. CX\_SoundObjectPlayer wraps CX\_SoundStream which wraps RtAudio (<https://www.music.mcgill.ca/~gary/rtaudio/>). If you are using ofSoundPlayer, depending on your operating system it might eventually use FMOD on Windows or OSX (<http://www.fmod.org/>; although the openFrameworks maintainers are considering moving away from FMOD) or OpenAL on Linux (<http://en.wikipedia.org/wiki/OpenAL>). However, you should check that this information is correct.

There are other libraries that are a part of openFrameworks that I am not as familiar with, including Poco (<http://pocoproject.org/>), which provides a variety of very useful utility functions and networking, FreeType (<http://www.freetype.org/>) which does font rendering, and many others.

CX would not have been possible without the existence of these high-quality open-source projects.

### Overriding openFrameworks

Although CX is technically an addon to openFrameworks, there are a number of ways in which CX hijacks normal of functionality in order to work better. As such, you cannot assume that all of functionality is available to you.

Generally, drawing visual stimuli using of classes and functions is fully supported. See the renderingTest example to see a plethora of ways to put things on the screen.

Audio output using ofSoundPlayer is supported, although no timing guarantees are made. Prefer CX::CX\_SoundObjectPlayer.

The input events (e.g. ofEvents().mousePressed) technically work, but with two serious limitations. 1) The events only fire when CX\_InputManager::pollEvents() is called (which internally calls glfwPollEvents() to actually kick off the events firing). 2) The standard of events do not have timestamps, which limits their usefulness.

The following functions' behavior is superseded by functionality provided by CX\_Display (see also CX::Instances::Display): ofGetFrameNum() is replaced by CX\_Display::getFrameNumber() ofGetLastFrameTime() is replaced by CX\_Display::getLastSwapTime()

The following functions do nothing: ofGetFrameRate(), ofSetFrameRate(), ofGetTargetFrameRate()

A variety of behaviors related to ofBaseApp do not function because CX is not based on a class derived from ofBaseApp nor does it use ofRunApp() to begin the program. For example, a standard of app class should have setup(), update(), and draw() functions that will be called by of during program execution. CX has a different model that is not as object-oriented (at least at some levels).

### Pre-experiment Setup

There is very little that CX does without you asking for it. The one major exception is pre-experiment setup, in which a number of basic operations are performed in order to set up a platform on which the rest of the experiment can run. The most significant step is to open a window and set up the OpenGL rendering environment. The main pseudorandom number generator (CX::Instances::RNG) is seeded. The logging system is prepared for use. The main clock (CX::Instances::Clock) is prepared for use.

### Input Timing

The way user input is handled by CX is easily explained by giving the process of receiving a mouse click. Assume that a CX program is running in a window. The user clicks inside of the window. At this point, the operating system (or at least the windowing subsystem of the operating system, but I will choose to conflate them) detects that the click has occurred and notes that the location of the click is within the window. The operating system then attempts to tell the program that a mouse click has occurred. In order to be notified about input events like mouse click, the program has previously

set up a message queue for incoming messages from the operating system. The OS puts the mouse event into the message queue. In order for the program to find out about the message it needs to check the message queue. This is what happens when `CX::CX_InputManager::pollEvents()` is called: The message queue is checked and all messages in the queue are processed, given timestamps, and routed to the next queue (e.g. the message queue in `CX::CX_Mouse` that is accessed with `CX::CX_Mouse::availableEvents()` and `CX::CX_Mouse::getNextEvent()`). The timestamps are not given by the operating system\*, so if `pollEvents` is not called regularly, input events will be received and everything will appear to be working correctly, but the timestamps will be wrong.

Of course, the actual process extends all the way back to the input device itself. The user presses the button and the microcontroller in the input device senses that a button has been pressed. It places this button press event into its outgoing message queue. At the next polling interval (typically 1 ms), the USB host controller on the computer polls the device for messages, discovers that a message is waiting and copies the message to the computer. At some point, the operating system checks to see if the USB host controller has received messages from any devices. It discovers the message and moves the message into the message queue of the program. At each step in which the message moves from one message queue to the next, the data contained in the message likely changes a little. At the start in the mouse, the message might just be "button 1 pressed". At the next step in the USB host controller, the message might be "input device 1 (type is mouse) button 1 pressed". Once the operating system gets the message it might be "mouse button 1 pressed while cursor at (367, 200) relative to clicked window". Eventually, the message gets into the message queue that users of `CX` work with, in `CX::CX_Mouse`, for example.

This process sounds very long and complicated, suggesting that it might take a long time to complete, throwing off timing data. That is true: Input timing data collected by `CX` is not veridical, there are invariably delays, including non-systematic delays. However, there are several steps in the process that no experiment software can get around, so the problems with timing data are not unique to `CX`. It might be possible to write a custom driver for the mouse or keyboard that allows the software to bypass the operating system's message queue, but it is very difficult to avoid the USB hardware delays, which can be on the order of milliseconds for many kinds of standard input devices. The next layer of the problem is that we are really interested in response time to a specific stimulus, but the time at which the stimulus was actually presented may be misreported by audio or video hardware/software, so even if the response timestamp had no error whatsoever, when it is compared with the stimulus presentation time, the response latency would be wrong due to errors in stimulus presentation time. Based on this large set of problems with collecting accurate response latency data, it is my firm belief that the only way to accurately measure response latency is with a button box that measures actual stimulus onset time with a light or sound sensor and also measures the time of a button press or other response. If you don't use such a system, the expectation is that you simply allow any error in response latencies to be dealt with statistically. Typically, any systematic error in response times will be subtracted out when conditions are compared with one another. Any random error will simply slightly inflate the estimated variance, but probably not to any meaningful extent.

If you would like to learn more about the internals of how input is handled in `CX`, you can see how GLFW and openFrameworks manage input by examining the source code in the respective repositories.

\*Technically, on Windows the messages that are given to a program do have a timestamp. However, the documentation doesn't actually say what the timestamp represents. My searching turns up the suggestion that it is a timestamp in milliseconds from system boot, but that the timestamp is set using the `GetTickCount` function, which typically has worse than 10 ms precision. This makes the timestamp attached to the message of very little value. See this page for documentation of what information comes with a Windows message: <http://msdn.microsoft.com/en-us/library/windows/desktop/ms644958%28v=vs.85%29.aspx>. The only page on which I actually found a definition of what the time member stores is this page <http://msdn.microsoft.com/en-us/library/aa929818.aspx>, which gives information pertaining to Windows Mobile 6.5, which is an obsolete smartphone operating system.

## Stimulus Timing

Although the kinds of error introduced into response time data can often be dealt with statistically, errors in stimulus presentation can be more serious. For example, if a visual stimulus is systematically presented for an extra frame throughout an experiment, then the method of the experiment has been altered without the experimenter learning about the alteration. Even if the extra frame does not always happen, on average participants are seeing more of that stimulus

than they should be. An error on the magnitude of an extra frame is nearly impossible to detect by eye in most cases, so it is important that there is some way to detect errors in stimulus presentation. The primary method of presenting time-locked visual stimuli is the `CX_SlidePresenter`. It has built in error-detection features that pick up on certain kinds of errors. Information about presentation errors can be found by using `CX::CX_SlidePresenter::checkForPresentationErrors()`.

Although it is nice to be made aware of errors when they occur, it is better to not have the errors happen in the first place. For this reason, stimulus presentation in `CX` is designed around avoiding errors. For visual stimuli, the `CX_SlidePresenter` provides a very easy-to-use way to present visual stimuli. Because the interface is so simple, user error is minimized. The backend code of the `CX_SlidePresenter` is designed to minimize the potential for timing errors by carefully tracking the passage of time, monitor refreshes, and timing of stimulus rendering.

On the audio front, `CX` provides the `CX_SoundObjectPlayer`, which plays `CX::CX_SoundObject` "CX\_SoundObjects". If several sounds are to be presented in a time-locked sequence, playing the sounds individually at their intended onset time can result in unequal startup delays for each sound, but if all of the sounds are combined together into a single audio buffer this possibility is eliminated. `CX_SoundObjects` are designed to make combining multiple sound stimuli together easy, which helps to prevent timing errors that could have otherwise occurred between sounds. `CX` also includes `CX_SoundStream`, which provides a method for directly accessing and manipulating the contents of audio buffers that are received from or sent to audio hardware.

## 6 license

The code in this repository is available under the MIT License ([https://secure.wikimedia.org/wikipedia/en/wiki/-Mit\\_license](https://secure.wikimedia.org/wikipedia/en/wiki/-Mit_license)).

Copyright (c) 2014 Kyle Hardman

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

## 7 Module Index

### 7.1 Modules

Here is a list of all modules:

<b>Data</b>	<b>13</b>
<b>Entry Point</b>	<b>15</b>
<b>Error Logging</b>	<b>16</b>

<b>Input Devices</b>	<b>17</b>
<b>Randomization</b>	<b>18</b>
<b>Sound</b>	<b>19</b>
<b>Timing</b>	<b>20</b>
<b>Utility</b>	<b>21</b>
<b>Video</b>	<b>22</b>

## 8 Namespace Index

### 8.1 Namespace List

Here is a list of all documented namespaces with brief descriptions:

<b>CX</b>	<b>23</b>
<b>CX::Algo</b>	<b>24</b>
<b>CX::Draw</b>	<b>26</b>
<b>CX::Instances</b>	<b>28</b>
<b>CX::Private</b>	<b>28</b>
<b>CX::Synth</b>	<b>29</b>
<b>CX::Util</b>	<b>30</b>

## 9 Hierarchical Index

### 9.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

<b>CX::Algo::BlockSampler&lt; T &gt;</b>	<b>39</b>
<b>CX::CX_SlidePresenter::Configuration</b>	<b>41</b>
<b>CX::CX_SoundStream::Configuration</b>	<b>42</b>
<b>CX::CX_BaseClock</b>	<b>43</b>
<b>CX::CX_Clock</b>	<b>44</b>
<b>CX::Util::CX_CoordinateConverter</b>	<b>45</b>
<b>CX::CX_DataFrame</b>	<b>48</b>
<b>CX::CX_DataFrameCell</b>	<b>57</b>

CX::CX_DataFrameColumn	61
CX::CX_DataFrameRow	61
CX::Util::CX_DegreeToPixelConverter	61
CX::CX_Display	63
CX::CX_InputManager	67
CX::CX_Joystick	68
CX::CX_Keyboard	69
CX::Util::CX_LapTimer	71
CX::Util::CX_LengthToPixelConverter	71
CX::CX_Logger	72
CX::CX_Mouse	76
CX::CX_RandomNumberGenerator	77
CX::CX_SlidePresenter	84
CX::CX_SoundObject	89
CX::CX_SoundObjectPlayer	96
CX::CX_SoundObjectRecorder	98
CX::CX_SoundStream	99
CX::CX_Time_t< TimeUnit >	104
CX::CX_Time_t< std::ratio< 1, 1000 > >	104
CX::Util::CX_TrialController	106
CX::CX_Mouse::Event	108
CX::CX_Joystick::Event	109
CX::CX_Keyboard::Event	110
CX::CX_SlidePresenter::FinalSlideFunctionArgs	113
CX::CX_SoundStream::InputEventArgs	114
CX::Algo::LatinSquare	115
CX::Synth::ModuleBase	118
CX::Synth::Adder	35
CX::Synth::AdditiveSynth	36
CX::Synth::Clamper	40



<a href="#">CX::Synth::Envelope</a>	<a href="#">108</a>
<a href="#">CX::Synth::Filter</a>	<a href="#">112</a>
<a href="#">CX::Synth::FIRFilter</a>	<a href="#">113</a>
<a href="#">CX::Synth::Mixer</a>	<a href="#">117</a>
<a href="#">CX::Synth::Multiplier</a>	<a href="#">119</a>
<a href="#">CX::Synth::Oscillator</a>	<a href="#">120</a>
<a href="#">CX::Synth::SoundObjectInput</a>	<a href="#">124</a>
<a href="#">CX::Synth::SoundObjectOutput</a>	<a href="#">125</a>
<a href="#">CX::Synth::Splitter</a>	<a href="#">125</a>
<a href="#">CX::Synth::StreamOutput</a>	<a href="#">127</a>
<a href="#">CX::CX_SoundStream::OutputEventArgs</a>	<a href="#">121</a>
<a href="#">CX::CX_SlidePresenter::PresentationErrorInfo</a>	<a href="#">122</a>
<a href="#">CX::CX_SlidePresenter::Slide</a>	<a href="#">123</a>
<a href="#">CX::CX_SlidePresenter::SlideTimingInfo</a>	<a href="#">123</a>
<a href="#">CX::Synth::StereoSoundObjectOutput</a>	<a href="#">126</a>
<a href="#">CX::Synth::StereoStreamOutput</a>	<a href="#">127</a>

## 10 Class Index

### 10.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

<a href="#">CX::Synth::Adder</a>	<a href="#">35</a>
<a href="#">CX::Synth::AdditiveSynth</a>	<a href="#">36</a>
<a href="#">CX::Algo::BlockSampler&lt; T &gt;</a>	<a href="#">39</a>
<a href="#">CX::Synth::Clamper</a>	<a href="#">40</a>
<a href="#">CX::CX_SlidePresenter::Configuration</a>	<a href="#">41</a>
<a href="#">CX::CX_SoundStream::Configuration</a>	<a href="#">42</a>
<a href="#">CX::CX_BaseClock</a>	<a href="#">43</a>
<a href="#">CX::CX_Clock</a>	<a href="#">44</a>
<a href="#">CX::Util::CX_CoordinateConverter</a>	<a href="#">45</a>

<a href="#">CX::CX_DataFrame</a>	48
<a href="#">CX::CX_DataFrameCell</a>	57
<a href="#">CX::CX_DataFrameColumn</a>	61
<a href="#">CX::CX_DataFrameRow</a>	61
<a href="#">CX::Util::CX_DegreeToPixelConverter</a>	61
<a href="#">CX::CX_Display</a>	63
<a href="#">CX::CX_InputManager</a>	67
<a href="#">CX::CX_Joystick</a>	68
<a href="#">CX::CX_Keyboard</a>	69
<a href="#">CX::Util::CX_LapTimer</a>	71
<a href="#">CX::Util::CX_LengthToPixelConverter</a>	71
<a href="#">CX::CX_Logger</a>	72
<a href="#">CX::CX_Mouse</a>	76
<a href="#">CX::CX_RandomNumberGenerator</a>	77
<a href="#">CX::CX_SlidePresenter</a>	84
<a href="#">CX::CX_SoundObject</a>	89
<a href="#">CX::CX_SoundObjectPlayer</a>	96
<a href="#">CX::CX_SoundObjectRecorder</a>	98
<a href="#">CX::CX_SoundStream</a>	99
<a href="#">CX::CX_Time_t&lt; TimeUnit &gt;</a>	104
<a href="#">CX::Util::CX_TrialController</a>	106
<a href="#">CX::Synth::Envelope</a>	108
<a href="#">CX::CX_Mouse::Event</a>	108
<a href="#">CX::CX_Joystick::Event</a>	109
<a href="#">CX::CX_Keyboard::Event</a>	110
<a href="#">CX::Synth::Filter</a>	112
<a href="#">CX::CX_SlidePresenter::FinalSlideFunctionArgs</a>	113
<a href="#">CX::Synth::FIRFilter</a>	113
<a href="#">CX::CX_SoundStream::InputEventArgs</a>	114
<a href="#">CX::Algo::LatinSquare</a>	115

<a href="#">CX::Synth::Mixer</a>	117
<a href="#">CX::Synth::ModuleBase</a>	118
<a href="#">CX::Synth::Multiplier</a>	119
<a href="#">CX::Synth::Oscillator</a>	120
<a href="#">CX::CX_SoundStream::OutputEventArgs</a>	121
<a href="#">CX::CX_SlidePresenter::PresentationErrorInfo</a>	122
<a href="#">CX::CX_SlidePresenter::Slide</a>	123
<a href="#">CX::CX_SlidePresenter::SlideTimingInfo</a>	123
<a href="#">CX::Synth::SoundObjectInput</a>	124
<a href="#">CX::Synth::SoundObjectOutput</a>	125
<a href="#">CX::Synth::Splitter</a>	125
<a href="#">CX::Synth::StereoSoundObjectOutput</a>	126
<a href="#">CX::Synth::StereoStreamOutput</a>	127
<a href="#">CX::Synth::StreamOutput</a>	127

## 11 File Index

### 11.1 File List

Here is a list of all documented files with brief descriptions:

<a href="#">advancedChangeDetectionTask.cpp</a>	128
<a href="#">advancedNBack.cpp</a>	129
<a href="#">basicChangeDetectionTask.cpp</a>	130
<a href="#">CX_Algorithm.h</a>	??
<a href="#">CX_AppWindow.h</a>	??
<a href="#">CX_Clock.h</a>	??
<a href="#">CX_ClockImplementations.h</a>	??
<a href="#">CX_DataFrame.h</a>	??
<a href="#">CX_DataFrame_attempts.h</a>	??
<a href="#">CX_DataFrameCell.h</a>	??
<a href="#">CX_Display.h</a>	??

CX_Draw.h	??
CX_EntryPoint.h	??
CX_Events.h	??
CX_InputManager.h	??
CX_Joystick.h	??
CX_Keyboard.h	??
CX_Logger.h	??
CX_LoggerChannel.h	??
CX_ModularSynth.h	??
CX_Mouse.h	??
CX_Private.h	??
CX_RandomNumberGenerator.h	??
CX_SlidePresenter.h	??
CX_SoundObject.h	??
CX_SoundObjectPlayer.h	??
CX_SoundObjectRecorder.h	??
CX_SoundStream.h	??
CX_Time_t.h	??
CX_TrialController.h	??
CX_TrialController_Class.h	??
CX_UnitConversion.h	??
CX_Uilities.h	??
CX_VideoBufferSwappingThread.h	??
<a href="#">modularSynth.cpp</a>	131
myType.h	??
<a href="#">nBack.cpp</a>	131

## 12 Module Documentation

### 12.1 Data

## Classes

- class [CX::CX\\_DataFrame](#)
- class [CX::CX\\_DataFrameColumn](#)
- class [CX::CX\\_DataFrameRow](#)
- class [CX::CX\\_DataFrameCell](#)

### 12.1.1 Detailed Description

This module is related to storing experimental data. [CX\\_DataFrame](#) is the most important class in this module.

## 12.2 Entry Point

### Functions

- void `runExperiment` (void)

### Variables

- `CX_Display CX::Instances::Display`
- `CX_InputManager CX::Instances::Input`
- `CX_Logger CX::Instances::Log`
- `CX_RandomNumberGenerator CX::Instances::RNG`

### 12.2.1 Detailed Description

The entry point provides access to a few instances of classes that can be used by user code. It also provides declarations (but not definitions) of a function which the user should define (see `runExperiment()`).

### 12.2.2 Function Documentation

#### 12.2.2.1 `runExperiment ( void )`

The user code should define a function with this name and type signature (takes no arguments and returns nothing). This function will be called once setup is done for `CX`. When `runExperiment` returns, the program will exit.

```
void runExperiment (void) {  
    //Do your experiment.  
  
    return; //Return when done to exit the program. You don't have to explicitly return; you can just fall  
           off the end of the function.  
           //You can alternately call std::exit() or ofExit() at any point.  
}
```

### 12.2.3 Variable Documentation

#### 12.2.3.1 `CX::CX_Display CX::Instances::Display`

An instance of `CX::CX_Display` that is lightly hooked into the `CX` backend. `setup()` is called for `Display` before `runExperiment()` is called.

#### 12.2.3.2 `CX::CX_InputManager CX::Instances::Input`

An instance of `CX_InputManager` that is very lightly hooked into the `CX` backend.

#### 12.2.3.3 `CX_Logger CX::Instances::Log`

This is an instance of `CX::CX_Logger` that is hooked into the `CX` backend. All log messages generated by `CX` and `openFrameworks` go through this instance.

#### 12.2.3.4 `CX::CX_RandomNumberGenerator CX::Instances::RNG`

An instance of `CX_RandomNumberGenerator` that is (lightly) hooked into the `CX` backend.

## 12.3 Error Logging

### Classes

- class [CX::CX\\_Logger](#)

### Enumerations

- enum [CX::CX\\_LogLevel](#) {  
    **LOG\_ALL**, **LOG\_VERBOSE**, **LOG\_NOTICE**, **LOG\_WARNING**,  
    **LOG\_ERROR**, **LOG\_FATAL\_ERROR**, **LOG\_NONE** }

#### 12.3.1 Detailed Description

#### 12.3.2 Enumeration Type Documentation

##### 12.3.2.1 enum [CX::CX\\_LogLevel](#) [strong]

Log levels for log messages. Depending on the log level chosen, the name of the level will be printed before the message. Depending on the settings set using `level()`, `levelForConsole()`, or `levelForFile()`, if the log level of a message is below the level set for the module or logging target it will not be printed. For example, if `LOG_ERROR` is the level for the console and `LOG_NOTICE` is the level for the module "test", then messages logged to the "test" module will be completely ignored if at verbose level (because of the module setting) and will not be printed to the console if they are below the level of an error (because of the console setting).

## 12.4 Input Devices

### Classes

- class [CX::CX\\_InputManager](#)
- class [CX::CX\\_Joystick](#)
- class [CX::CX\\_Keyboard](#)
- class [CX::CX\\_Mouse](#)

### 12.4.1 Detailed Description

There are a number of different classes that together perform the input handling functions of [CX](#). Start by looking at [CX::CX\\_InputManager](#) and the instance of that class that is created for you: [CX::Instances::Input](#).

For interfacing with serial ports, use `ofSerial` (<http://www.openframeworks.cc/documentation/communication/of-Serial.html>).

### See Also

[CX::CX\\_InputManager](#) for the primary interface to input devices.  
[CX::CX\\_Keyboard](#) for keyboard specific information.  
[CX::CX\\_Mouse](#) for mouse specific information.  
[CX::CX\\_Joystick](#) for joystick specific information.



## 12.5 Randomization

### Classes

- class [CX::CX\\_RandomNumberGenerator](#)

### 12.5.1 Detailed Description

This module provides a class that is used for random number generation.

## 12.6 Sound

### Namespaces

- [CX::Synth](#)

### Classes

- class [CX::CX\\_SoundObjectRecorder](#)
- class [CX::CX\\_SoundObject](#)
- class [CX::CX\\_SoundObjectPlayer](#)
- class [CX::CX\\_SoundStream](#)

### 12.6.1 Detailed Description

## 12.7 Timing

### Classes

- class [CX::CX\\_Clock](#)
- class [CX::Util::CX\\_LapTimer](#)
- class [CX::CX\\_BaseClock](#)
- class [CX::CX\\_Time\\_t< TimeUnit >](#)

### Variables

- [CX\\_Clock](#) [CX::Instances::Clock](#)

### 12.7.1 Detailed Description

This module provides methods for timestamping events in experiments.

### 12.7.2 Variable Documentation

#### 12.7.2.1 [CX\\_Clock](#) [CX::Instances::Clock](#)

An instance of [CX::CX\\_Clock](#) that is hooked into the [CX](#) backend. Anything in [CX](#) that requires timing information uses this instance. You should use this instance in your code and not make your own instance of [CX\\_Clock](#). You should never need another instance. You should never use another instance, as the experiment start times will not agree between instances.

## 12.8 Utility

### Namespaces

- [CX::Util](#)

### Classes

- class [CX::Util::CX\\_TrialController](#)
- class [CX::Util::CX\\_DegreeToPixelConverter](#)
- class [CX::Util::CX\\_LengthToPixelConverter](#)
- class [CX::Util::CX\\_CoordinateConverter](#)

### 12.8.1 Detailed Description

## 12.9 Video

### Namespaces

- [CX::Draw](#)

### Classes

- class [CX::CX\\_Display](#)
- class [CX::CX\\_SlidePresenter](#)

#### 12.9.1 Detailed Description

This module is related to creating and presenting visual stimuli.

The [CX::Draw](#) namespace contains some more complex drawing functions. However, almost all of the drawing of stimuli is done using openFrameworks functions. A lot of the common functions can be found in ofGraphics.h (<http://www.openframeworks.cc/documentation/graphics/ofGraphics.html>), but there are a lot of other ways to draw stimuli: see the graphics and 3d sections of this page: <http://www.openframeworks.cc/documentation/>.

## 13 Namespace Documentation

### 13.1 CX Namespace Reference

#### Namespaces

- [Algo](#)
- [Draw](#)
- [Instances](#)
- [Private](#)
- [Synth](#)
- [Util](#)

#### Classes

- class [CX\\_Clock](#)
- class [CX\\_BaseClock](#)
- class [CX\\_DataFrame](#)
- class [CX\\_DataFrameColumn](#)
- class [CX\\_DataFrameRow](#)
- class [CX\\_DataFrameCell](#)
- class [CX\\_Display](#)
- class [CX\\_InputManager](#)
- class [CX\\_Joystick](#)
- class [CX\\_Keyboard](#)
- class [CX\\_Logger](#)
- class [CX\\_Mouse](#)
- class [CX\\_RandomNumberGenerator](#)
- class [CX\\_SlidePresenter](#)
- class [CX\\_SoundObject](#)
- class [CX\\_SoundObjectPlayer](#)
- class [CX\\_SoundObjectRecorder](#)
- class [CX\\_SoundStream](#)
- class [CX\\_Time\\_t](#)

#### Typedefs

- typedef int64\_t **CX\_RandomInt\_t**
- typedef [CX\\_SoundStream::Configuration CX\\_SoundObjectPlayerConfiguration\\_t](#)  
*This is typedef'ed to [CX::CX\\_SoundStream::Configuration](#).*
- typedef [CX\\_Time\\_t](#)< std::ratio< 3600, 1 > > **CX\_Hours**
- typedef [CX\\_Time\\_t](#)< std::ratio< 60, 1 > > **CX\_Minutes**
- typedef [CX\\_Time\\_t](#)< std::ratio< 1, 1 > > **CX\_Seconds**
- typedef [CX\\_Time\\_t](#)< std::ratio< 1, 1000 > > **CX\_Millis**
- typedef [CX\\_Time\\_t](#)< std::ratio< 1, 1000000 > > **CX\_Micros**
- typedef [CX\\_Time\\_t](#)< std::ratio< 1, 1000000000 > > **CX\_Nanos**

## Enumerations

- enum [CX\\_LogLevel](#) {  
**LOG\_ALL**, **LOG\_VERBOSE**, **LOG\_NOTICE**, **LOG\_WARNING**,  
**LOG\_ERROR**, **LOG\_FATAL\_ERROR**, **LOG\_NONE** }
- enum **CX\_MouseButtons** : int { **LEFT\_MOUSE** = OF\_MOUSE\_BUTTON\_LEFT, **MIDDLE\_MOUSE** = OF\_MOUSE\_BUTTON\_MIDDLE, **RIGHT\_MOUSE** = OF\_MOUSE\_BUTTON\_RIGHT }

## Functions

- std::ostream & **operator**<< (std::ostream &os, const [CX\\_DataFrameCell](#) &cell)
- void **relaunchWindow** (CX\_WindowConfiguration\_t config)
- std::ostream & **operator**<< (std::ostream &os, const [CX\\_Joystick::Event](#) &ev)
- std::istream & **operator**>> (std::istream &is, [CX\\_Joystick::Event](#) &ev)
- std::ostream & **operator**<< (std::ostream &os, const [CX\\_Keyboard::Event](#) &ev)
- std::istream & **operator**>> (std::istream &is, [CX\\_Keyboard::Event](#) &ev)
- std::ostream & **operator**<< (std::ostream &os, const [CX\\_Mouse::Event](#) &ev)
- std::istream & **operator**>> (std::istream &is, [CX\\_Mouse::Event](#) &ev)
- template<typename TimeUnit >  
std::ostream & **operator**<< (std::ostream &os, const [CX\\_Time\\_t](#)< TimeUnit > &t)
- template<typename TimeUnit >  
std::istream & **operator**>> (std::istream &is, [CX\\_Time\\_t](#)< TimeUnit > &t)

### 13.1.1 Detailed Description

This namespace contains all of the symbols related to [CX](#).

### 13.1.2 Function Documentation

#### 13.1.2.1 template<typename TimeUnit > std::ostream& CX::operator<< ( std::ostream & os, const CX\_Time\_t< TimeUnit > & t )

If operator<< and operator>> are used to convert to/from string representation, you MUST use the same time type on both ends of the conversion.

## 13.2 CX::Algo Namespace Reference

### Classes

- class [LatinSquare](#)
- class [BlockSampler](#)

### Functions

- template<typename T >  
std::vector< T > [generateSeparatedValues](#) (int count, double minDistance, std::function< double(T, T)> distanceFunction, std::function< T(void)> randomDeviate, int maxSequentialFailures=200)
- template<typename T >  
std::vector< std::vector< T > > [fullyCross](#) (std::vector< std::vector< T > > factors)

### 13.2.1 Detailed Description

This namespace contains a few complex algorithms that can be difficult to properly implement or are very experiment-specific.

### 13.2.2 Function Documentation

#### 13.2.2.1 `template<typename T> std::vector< std::vector< T> > CX::Algo::fullyCross ( std::vector< std::vector< T> > factors )`

This function fully crosses the levels of the factors of a design. For example, for a 2X3 design, it would give you all 6 combinations of the levels of the design.

##### Parameters

<i>factors</i>	A vector of factors, each factor being a vector containing all the levels of that factor.
----------------	---

##### Returns

A vector of crossed factor levels. It's length is equal to the product of the levels of the factors. The length of each "row" is equal to the number of factors.

Example use:

```
std::vector< std::vector<int> > levels(2); //Two factors
levels[0].push_back(1); //The first factor has two levels (1 and 2)
levels[0].push_back(2);
levels[1].push_back(3); //The second factor has three levels (3, 4, and 5)
levels[1].push_back(4);
levels[1].push_back(5);
auto crossed = fullyCross(levels);
```

crossed should contain a vector with six subvectors with the contents:

```
{ {1,3}, {1,4}, {1,5}, {2,3}, {2,4}, {2,5} }
```

where

```
crossed[3][0] == 2
crossed[3][1] == 3
crossed[0][1] == 3
```

#### 13.2.2.2 `template<typename T> std::vector< T> CX::Algo::generateSeparatedValues ( int count, double minDistance, std::function< double(T, T)> distanceFunction, std::function< T(void)> randomDeviate, int maxSequentialFailures = 200 )`

This algorithm is designed to deal with the situation in which a number of random values must be generated that are each at least some distance from every other random value. This is a very generic implementation of this algorithm. It works by taking pointers to two functions that work on whatever type of data you are using. The first function is a distance function: it returns the distance between two values of the type. You can define distance in whatever way you would like. The second function generates random values of the type.



## Template Parameters

<code>&lt;T&gt;</code>	The type of data you are working with.
------------------------	--

## Parameters

<i>count</i>	The number of values you want to be generated.
<i>minDistance</i>	The minimum distance between any two values. This will be compared to the result of distance-Function.
<i>distanceFunction</i>	A function that computes the distance, in whatever units you want, between two values of type T.
<i>randomDeviate</i>	A function that generates random values of type T.
<i>maxSequential-Failures</i>	The maximum number of times in a row that a newly-generated value is less than minDistance from at least one other value. This essentially makes sure that if it is not possible to generate a random value that is at least some distance from the others, the algorithm will terminate.

## Returns

A vector of values. If the function terminated prematurely due to maxSequentialFailures being reached, the returned vector will have 0 elements.

```
//This example function generates locCount points with both x and y values bounded by minimumValues and
//maximumValues that
//are at least minDistance pixels from each other.
std::vector<ofPoint> getObjectLocations(int locCount, double minDistance, ofPoint minimumValues, ofPoint
    maximumValues) {
    auto pointDistance = [] (ofPoint a, ofPoint b) {
        return sqrt(pow(a.x - b.x, 2) + pow(a.y - b.y, 2));
    };

    auto randomPoint = [&]() {
        ofPoint rval;
        rval.x = RNG.randomInt(minimumValues.x, maximumValues.x);
        rval.y = RNG.randomInt(minimumValues.y, maximumValues.y);
        return rval;
    };

    return CX::Algo::generateSeparatedValues<ofPoint>(locCount, minDistance, pointDistance, randomPoint,
        1000);
}

//Call of example function
vector<ofPoint> v = getObjectLocations(5, 50, ofPoint(0, 0), ofPoint(400, 400));
```

## 13.3 CX::Draw Namespace Reference

### Functions

- ofPath [arrowToPath](#) (float length, float headOffsets, float headSize, float lineWidth)
- ofPath [squircleToPath](#) (double radius, double amount=0.9)
- ofPath [starToPath](#) (int numberOfPoints, double innerRadius, double outerRadius)
- void [star](#) (ofPoint center, int numberOfPoints, float innerRadius, float outerRadius, ofColor lineColor, ofColor fill-Color, float lineWidth=1, float rotationDeg=0)
- void [centeredString](#) (int x, int y, std::string s, ofTrueTypeFont &font)
- void [centeredString](#) (ofPoint center, std::string s, ofTrueTypeFont &font)
- ofPixels [greyscalePattern](#) (const CX\_PatternProperties\_t &patternProperties)
- ofPixels [gaborToPixels](#) (const CX\_GaborProperties\_t &properties)
- ofTexture [gaborToTexture](#) (const CX\_GaborProperties\_t &properties)
- void [gabor](#) (int x, int y, const CX\_GaborProperties\_t &properties)

## 13.3.1 Detailed Description

This namespace contains functions for drawing certain complex stimuli.

## 13.3.2 Function Documentation

13.3.2.1 ofPath CX::Draw::arrowToPath ( float *length*, float *headOffsets*, float *headSize*, float *lineWidth* )

Draws an arrow to an ofPath.

## Parameters

<i>angle</i>	The direction toward which the arrow tip should point, in degrees.
<i>length</i>	The length of the arrow in pixels.
<i>headOffsets</i>	The angle between the main arrow body and the two legs of the tip, in degrees.
<i>headSize</i>	The length of the legs of the head in pixels.

## Returns

An ofPath containing the arrow. The tip of the arrow is at (0,0) in the ofPath.

13.3.2.2 void CX::Draw::centeredString ( int *x*, int *y*, std::string *s*, ofTrueTypeFont & *font* )

Equivalent to a call to CX::Draw::centeredString(ofPoint(x, y), s, font).

13.3.2.3 void CX::Draw::centeredString ( ofPoint *center*, std::string *s*, ofTrueTypeFont & *font* )

Draws a string centered on a given location using the given font. Strings are normally drawn such that the x coordinate gives the left edge of the string and the y coordinate gives the line above which the letters will be drawn, where some characters (like y or g) can descend below the line.

## Parameters

<i>center</i>	The coordinates of the center of the string.
<i>s</i>	The string to draw.
<i>font</i>	A font that has already been prepared for use.

13.3.2.4 ofPath CX::Draw::squircleToPath ( double *radius*, double *amount* = 0.9 )

This function draws an approximation of a squircle (<http://en.wikipedia.org/wiki/Squircle>) using Bezier curves. The squircle will be centered on (0,0) in the ofPath.

## Parameters

<i>radius</i>	The radius of the largest circle that can be enclosed in the squircle.
<i>amount</i>	The "squirliness" of the squircle. The default (0.9) seems like a pretty good amount for a good approximation of a squircle, but different amounts can give different sorts of shapes.

## Returns

An ofPath containing the squircle.

13.3.2.5 void CX::Draw::star ( ofPoint *center*, int *numberOfPoints*, float *innerRadius*, float *outerRadius*, ofColor *lineColor*, ofColor *fillColor*, float *lineWidth* = 1, float *rotationDeg* = 0 )

This draws an N-pointed star.

## Parameters

<i>center</i>	The point at the center of the star.
<i>numberOfPoints</i>	The number of points in the star.
<i>innerRadius</i>	The distance from the center of the star to where the inner points of the star hit.
<i>outerRadius</i>	The distance from the center of the star to the outer points of the star.
<i>lineColor</i>	The color of the lines going around the edge of the star.
<i>fillColor</i>	The color used to fill in the center of the star.
<i>lineWidth</i>	The width of the lines.
<i>rotationDeg</i>	The number of degrees to rotate the star. 0 degrees has one point of the star pointing up. Positive values rotate the star counter-clockwise.

## Returns

An ofPath containing the star.

### 13.3.2.6 ofPath CX::Draw::starToPath ( int *numberOfPoints*, double *innerRadius*, double *outerRadius* )

This draws an N-pointed star to an ofPath. The star will be centered on (0,0) in the ofPath.

## Parameters

<i>numberOfPoints</i>	The number of points in the star.
<i>innerRadius</i>	The distance from the center of the star at which the inner points of the star hit.
<i>outerRadius</i>	The distance from the center of the star to the outer points of the star.

## Returns

An ofPath containing the star.

## 13.4 CX::Instances Namespace Reference

## Variables

- [CX\\_Clock](#) Clock
- [CX\\_Display](#) Display
- [CX\\_InputManager](#) Input
- [CX\\_Logger](#) Log
- [CX\\_RandomNumberGenerator](#) RNG

### 13.4.1 Detailed Description

This namespace contains instances of some classes that are fundamental to the functioning of [CX](#).

## 13.5 CX::Private Namespace Reference

## Functions

- void **setupCX** (void)
- CX\_Events & **getEvents** (void)
- void **learnOpenGLVersion** (void)
- CX\_GLVersion **getOpenGLVersion** (void)

- CX\_GLVersion **getGLSLVersion** (void)
- bool **glFenceSyncSupported** (void)
- bool **glVersionAtLeast** (int desiredMajor, int desiredMinor, int desiredRelease=0)
- int **glCompareVersions** (CX\_GLVersion a, CX\_GLVersion b)
- CX\_GLVersion **getGLSLVersionFromGLVersion** (CX\_GLVersion glVersion)
- void **setSampleCount** (unsigned int count)

#### Variables

- GLFWwindow \* **glfwContext** = NULL
- ofPtr< CX\_AppWindow > **window**

#### 13.5.1 Detailed Description

This namespace contains symbols that may be visible in user code but which should not be used by user code.

## 13.6 CX::Synth Namespace Reference

#### Classes

- class [ModuleBase](#)
- class [AdditiveSynth](#)
- class [Adder](#)
- class [Clamper](#)
- class [Envelope](#)
- class [Filter](#)
- class [Mixer](#)
- class [Multiplier](#)
- class [Oscillator](#)
- class [Splitter](#)
- class [SoundObjectInput](#)
- class [StreamOutput](#)
- class [StereoStreamOutput](#)
- class [SoundObjectOutput](#)
- class [StereoSoundObjectOutput](#)
- class [FIRFilter](#)

#### Functions

- double **sinc** (double x)
- double **relativeFrequency** (double f, double semitoneDifference)

#### 13.6.1 Detailed Description

This namespace contains a number of classes that can be combined together to form a modular synthesizer that can be used to generate sound stimuli.

## 13.7 CX::Util Namespace Reference

### Classes

- class [CX\\_LapTimer](#)
- class [CX\\_TrialController](#)
- class [CX\\_DegreeToPixelConverter](#)
- class [CX\\_LengthToPixelConverter](#)
- class [CX\\_CoordinateConverter](#)

### Enumerations

- enum **CX\_RoundingConfiguration** { **ROUND\_TO\_NEAREST**, **ROUND\_UP**, **ROUND\_DOWN**, **ROUND\_TOWARD\_ZERO** }

### Functions

- float [degreesToPixels](#) (float degrees, float pixelsPerUnit, float viewingDistance)
- float [pixelsToDegrees](#) (float pixels, float pixelsPerUnit, float viewingDistance)
- bool [checkOFVersion](#) (int versionMajor, int versionMinor, int versionPatch)
- unsigned int **getSampleCount** (void)
- template<typename T >  
std::vector< T > [arrayToVector](#) (T arr[], unsigned int arraySize)
- template<typename T >  
std::vector< T > [sequence](#) (T start, T end, T stepSize)
- template<typename T >  
std::vector< T > [sequenceSteps](#) (T start, unsigned int steps, T stepSize)
- template<typename T >  
std::vector< T > [sequenceAlong](#) (T start, T end, unsigned int steps)
- template<typename T >  
std::vector< T > [intVector](#) (T start, T end)
- template<typename T >  
std::vector< T > [repeat](#) (T value, unsigned int times)
- template<typename T >  
std::vector< T > [repeat](#) (std::vector< T > values, unsigned int times, unsigned int each=1)
- template<typename T >  
std::vector< T > [repeat](#) (std::vector< T > values, std::vector< unsigned int > each, unsigned int times=1)
- template<typename T >  
std::string [vectorToString](#) (std::vector< T > values, std::string delimiter=",", int significantDigits=8)
- bool [writeToFile](#) (std::string filename, std::string data, bool append=true)
- double [round](#) (double d, int roundingPower, CX\_RoundingConfiguration c)
- template<typename T >  
T [clamp](#) (T val, T minimum, T maximum)
- void [saveFboToFile](#) (ofFbo &fbo, std::string filename)
- template<typename T >  
T **max** (std::vector< T > vals)
- template<typename T >  
T **min** (std::vector< T > vals)
- template<typename T >  
T **mean** (std::vector< T > vals)

- `template<typename T_OUT , typename T_IN >`  
`T_OUT mean (std::vector< T_IN > vals)`
- `template<typename T >`  
`T var (std::vector< T > vals)`
- `template<typename T_OUT , typename T_IN >`  
`T_OUT var (std::vector< T_IN > vals)`

### 13.7.1 Detailed Description

This namespace contains a variety of utility functions.

### 13.7.2 Function Documentation

#### 13.7.2.1 `template<typename T > std::vector< T > CX::Util::arrayToVector ( T arr[], unsigned int arraySize )`

Copies `arraySize` elements of an array of `T` to a `vector<T>`.

##### Template Parameters

<code>&lt;T&gt;</code>	The type of the array. Is often inferred by the compiler.
------------------------	---

##### Parameters

<code>arr</code>	The array of data to put into the vector.
<code>arraySize</code>	The length of the array, or the number of elements to copy from the array if not all of the elements are wanted.

##### Returns

The elements in a vector.

#### 13.7.2.2 `bool CX::Util::checkOFVersion ( int versionMajor, int versionMinor, int versionPatch )`

Checks that the version of `oF` that is used during compilation matches the requested version. If the desired version was 0.7.1, simply input (0, 7, 1) as the arguments. A warning will be logged if the versions don't match.

##### Returns

True if the versions match, false otherwise.

#### 13.7.2.3 `template<typename T > T CX::Util::clamp ( T val, T minimum, T maximum )`

Clamps a value (i.e. forces the value to be between two bounds). If the value is outside of the bounds, it is set to be equal to the nearest bound.

##### Parameters

<code>val</code>	The value to clamp.
<code>minimum</code>	The lower bound. Must be less than or equal to maximum.
<code>maximum</code>	The upper bound. Must be greater than or equal to minimum.

##### Returns

The clamped value.

#### 13.7.2.4 `float CX::Util::degreesToPixels ( float degrees, float pixelsPerUnit, float viewingDistance )`

Returns the number of pixels needed to subtend *deg* degrees of visual angle. You might want to round this if you want to align to pixel boundaries. However, if you are antialiasing your stimuli you might want to use floating point values to get precise subpixel rendering.

##### Parameters

<i>deg</i>	Number of degrees.
------------	--------------------

##### Returns

The number of pixels needed.

#### 13.7.2.5 `template<typename T> std::vector< T > CX::Util::intVector ( T start, T end )`

Creates a vector of integers going from *start* to *end*. *start* may be greater than *end*, in which case the returned values will be in descending order. This is similar to using `CX::sequence`, but the step size is fixed to 1 and it works properly when trying to create a descending sequence of unsigned integers.

##### Returns

A vector of the values in the sequence.

#### 13.7.2.6 `float CX::Util::pixelsToDegrees ( float pixels, float pixelsPerUnit, float viewingDistance )`

The inverse of `CX::Util::degreesToPixels()`.

#### 13.7.2.7 `template<typename T> std::vector< T > CX::Util::repeat ( T value, unsigned int times )`

Repeats *value* "*times*" times.

##### Parameters

<i>value</i>	The value to be repeated.
<i>times</i>	The number of times to repeat the value.

##### Returns

A vector containing *times* copies of the repeated value.

#### 13.7.2.8 `template<typename T> std::vector< T > CX::Util::repeat ( std::vector< T > values, unsigned int times, unsigned int each = 1 )`

Repeats the elements of *values*. Each element of *values* is repeated "*each*" times and then the process of repeating the elements is repeated "*times*" times.

##### Parameters

<i>values</i>	Vector of values to be repeated.
<i>times</i>	The number of times the process should be performed.

<i>each</i>	Number of times each element of values should be repeated.
-------------	--

**Returns**

A vector of the repeated values.

**13.7.2.9** `template<typename T> std::vector< T > CX::Util::repeat ( std::vector< T > values, std::vector< unsigned int > each, unsigned int times = 1 )`

Repeats the elements of values. Each element of values is repeated "each" times and then the process of repeating the elements is repeated "times" times.

**Parameters**

<i>values</i>	Vector of values to be repeated.
<i>each</i>	Number of times each element of values should be repeated. Must be the same length as values. If not, an error is logged and an empty vector is returned.
<i>times</i>	The number of times the process should be performed.

**Returns**

A vector of the repeated values.

**13.7.2.10** `double CX::Util::round ( double d, int roundingPower, CX_RoundingConfiguration c )`

Rounds the given double to the given power of 10.

**Parameters**

<i>d</i>	The number to be rounded.
<i>roundingPower</i>	The power of 10 to round d to. For example, if roundingPower is 0, d is rounded to the one's place ( $10^0 == 1$ ). If roundingPower is -3, d is rounded to the thousandth's place ( $10^{-3} = .001$ ). If roundingPower is 1, d is rounded to the ten's place.
<i>c</i>	The type of rounding to do, from the CX::Util::CX_RoundingConfiguration enum. You can round up, down, to nearest, and toward zero.

**Returns**

The rounded value.

**13.7.2.11** `void CX::Util::saveFboToFile ( ofFbo & fbo, std::string filename )`

Saves the contents of an ofFbo to a file. The file type is hinted by the file extension you provide as part of the file name.

**Parameters**

<i>fbo</i>	The framebuffer to save.
<i>filename</i>	The path of the file to save. The file extension determines the type of file that is saved. Many standard file types are supported: png, bmp, jpg, gif, etc. However, if the fbo has an alpha channel, only png works properly (at least of those I have tested).

**13.7.2.12** `template<typename T> std::vector< T > CX::Util::sequence ( T start, T end, T stepSize )`

Creates a sequence of numbers from start to end by steps of size stepSize. start may be greater than end, but only if stepSize is less than 0. If start is less than end, stepSize must be greater than 0.

Example call: `sequence<double>(1, 3.3, 2)` results in a vector containing {1, 3}



## Parameters

<i>start</i>	The start of the sequence. You are guaranteed to get this value in the sequence.
<i>end</i>	The number past which the sequence should end. You are not guaranteed to get this value.
<i>stepSize</i>	A nonzero number.

## Returns

A vector containing the sequence.

13.7.2.13 `template<typename T> std::vector< T> CX::Util::sequenceAlong ( T start, T end, unsigned int outputLength )`

Creates a sequence from start to end, where the size of each step is chosen so that the length of the sequence if equal to outputLength.

## Parameters

<i>start</i>	The value at which to start the sequence.
<i>end</i>	The value to which to end the sequence.
<i>outputLength</i>	The number of elements in the returned sequence.

## Returns

A vector containing the sequence.

13.7.2.14 `template<typename T> std::vector< T> CX::Util::sequenceSteps ( T start, unsigned int steps, T stepSize )`

Make a sequence starting from start and taking steps steps of stepSize.

`sequenceSteps( 1.5, 4, 2.5 );`

Creates the sequence {1.5, 4, 6.5, 9, 11.5}

## Parameters

<i>start</i>	Value from which to start.
<i>steps</i>	The number of steps to take.
<i>stepSize</i>	The size of each step.

## Returns

A vector containing the sequence.

13.7.2.15 `template<typename T> std::string CX::Util::vectorToString ( std::vector< T> values, std::string delimiter = " , ", int significantDigits = 8 )`

This function converts a vector of values to a string representation of the values.

## Parameters

<i>values</i>	The vector of values to convert.
<i>delimiter</i>	A string that is used to separate the elements of <i>value</i> in the final string.

<i>significantDigits</i>	Only for floating point types. The number of significant digits in the value.
--------------------------	---

**Returns**

A string containing a representation of the vector of values.

**13.7.2.16 bool CX::Util::writeToFile ( std::string *filename*, std::string *data*, bool *append* = true )**

Writes data to a file, either appending the data to an existing file or creating a new file, overwriting any existing file with the given filename.

**Parameters**

<i>filename</i>	Name of the file to write to. If it is a relative file name, it will be placed relative the the data directory.
<i>data</i>	The data to write
<i>append</i>	If true, data will be appended to an existing file, if it exists. If append is false, any existing file will be overwritten and a warning will be logged. If no file exists, a new one will be created.

**Returns**

True if an error was encountered while writing the file, true otherwise. If there was an error, an error message will be logged.

## 14 Class Documentation

### 14.1 CX::Synth::Adder Class Reference

```
#include <CX_ModularSynth.h>
```

Inherits [CX::Synth::ModuleBase](#).

**Public Member Functions**

- double [getNextSample](#) (void) override

**Public Attributes**

- ModuleParameter **amount**

**Additional Inherited Members**

#### 14.1.1 Detailed Description

This class simply takes an input and adds an `amount` to it. The `amount` can be negative, in which case this class is a subtractor. If there is no input to this module, it behaves as though the input is 0, so the output value will be equal to `amount`.

### 14.1.2 Member Function Documentation

#### 14.1.2.1 `double Adder::getNextSample( void ) [override], [virtual]`

This function should be overloaded for any derived class that can be used as the input for another module.

Reimplemented from [CX::Synth::ModuleBase](#).

The documentation for this class was generated from the following files:

- CX\_ModularSynth.h
- CX\_ModularSynth.cpp

## 14.2 CX::Synth::AdditiveSynth Class Reference

```
#include <CX_ModularSynth.h>
```

Inherits [CX::Synth::ModuleBase](#).

### Public Types

- enum **HarmonicSeriesType** { HS\_MULTIPLE, HS\_SEMITONE, HS\_USER\_FUNCTION }
- enum [HarmonicAmplitudeType](#) { SINE, SQUARE, SAW, TRIANGLE }
- typedef float **wavePos\_t**
- typedef float **amplitude\_t**

### Public Member Functions

- void **configure** (unsigned int harmonicCount, HarmonicSeriesType hs, [HarmonicAmplitudeType](#) aType)
- void **setFundamentalFrequency** (double f)
- void **setStandardHarmonicSeries** (unsigned int harmonicCount)
- void **setHarmonicSeries** (unsigned int harmonicCount, HarmonicSeriesType type, double controlParameter)
- void **setHarmonicSeries** (unsigned int harmonicCount, std::function< double(unsigned int)> userFunction)
- void **setAmplitudes** ([HarmonicAmplitudeType](#) type)
- void **setAmplitudes** ([HarmonicAmplitudeType](#) t1, [HarmonicAmplitudeType](#) t2, double mixture)
- void **setAmplitudes** (std::vector< amplitude\_t > amps)
- std::vector< amplitude\_t > **calculateAmplitudes** ([HarmonicAmplitudeType](#) type, unsigned int count)
- void **pruneLowAmplitudeHarmonics** (double tol)
- double [getNextSample](#) (void) override

### Additional Inherited Members

#### 14.2.1 Detailed Description

This class is an implementation of an additive synthesizer. Additive synthesizers are essentially an inverse fourier transform. You specify at which frequencies you want to have a sine wave and the amplitudes of those waves, and they are combined together into a single waveform.

The frequencies are referred to as harmonics, due to the fact that typical audio applications of additive synths use the standard harmonic series ( $f(i) = f\_fundamental * i$ ). However, setting the harmonics to values not found in the standard harmonic series can result in really unusual and interesting sounds.

The output of the additive synth is not easily bounded between -1 and 1 due to various oddities of additive synthesis. For example, although in the limit as the number of harmonics goes to infinity square and sawtooth waves made with additive synthesis are bounded between -1 and 1, with smaller numbers of harmonics the amplitudes actually overshoot these bounds slightly. Of course, if an unusual harmonic series is used with arbitrary amplitudes, it can be hard to know if the output of the synth will be within the bounds. A [Synth::Multiplier](#) can help deal with this.

## 14.2.2 Member Enumeration Documentation

### 14.2.2.1 enum CX::Synth::AdditiveSynth::HarmonicAmplitudeType

Assuming that the standard harmonic series is being used, the values in this enum, when passed to [setAmplitudes\(\)](#), cause the amplitudes of the harmonics to be set in such a way as to produce the desired waveform.

## 14.2.3 Member Function Documentation

### 14.2.3.1 double AdditiveSynth::getNextSample ( void ) [override], [virtual]

This function should be overloaded for any derived class that can be used as the input for another module.

Reimplemented from [CX::Synth::ModuleBase](#).

### 14.2.3.2 void AdditiveSynth::pruneLowAmplitudeHarmonics ( double tol )

This function removes all harmonics that have an amplitude that is less than or equal to a tolerance times the amplitude of the frequency with the greatest absolute amplitude.

The result of this pruning is that the synthesizer will be more computationally efficient but provide a possibly worse approximation of the desired waveform.

#### Parameters

<i>tol</i>	<code>tol</code> is interpreted differently depending on its value. If <code>tol</code> is greater than or equal to 0, it is treated as a proportion of the amplitude of the frequency with the greatest amplitude. If <code>tol</code> is less than 0, it is treated as the difference in decibels between the frequency with the greatest amplitude and the tolerance.
------------	--

#### Note

Because harmonics with an amplitude equal to the tolerance times an amplitude, setting `tol` to 0 will remove harmonics with 0 amplitude, but no others.

### 14.2.3.3 void AdditiveSynth::setAmplitudes ( HarmonicAmplitudeType type )

This function sets the amplitudes of the harmonics based on the chosen type. The resulting waveform will only be correct if the harmonic series is the standard harmonic series (see [setStandardHarmonicSeries\(\)](#)).

#### Parameters

<i>type</i>	The type of wave calculate amplitudes for.
-------------	--

### 14.2.3.4 void AdditiveSynth::setAmplitudes ( HarmonicAmplitudeType t1, HarmonicAmplitudeType t2, double mixture )

This function sets the amplitudes of the harmonics based on a mixture of the chosen types. The resulting waveform will only be correct if the harmonic series is the standard harmonic series (see [setStandardHarmonicSeries\(\)](#)). This is a convenient way to morph between waveforms.

#### 14.2.3.5 void AdditiveSynth::setAmplitudes ( std::vector< amplitude\_t > *amps* )

This function sets the amplitudes of the harmonics to arbitrary values as specified in `amps`.

## Parameters

<i>amps</i>	The amplitudes of the harmonics. If this vector does not contain as many values as there are harmonics, the unspecified amplitudes will be set to 0.
-------------	--

14.2.3.6 `void AdditiveSynth::setHarmonicSeries ( unsigned int harmonicCount, HarmonicSeriesType type, double controlParameter )`

## Parameters

<i>type</i>	The type of harmonic series to generate. Can be either HS_MULTIPLE or HS_SEMITONE. For HS_MULTIPLE, each harmonic's frequency will be some multiple of the fundamental frequency, depending on the harmonic number and controlParameter. For HS_SEMITONE, each harmonic's frequency will be some number of semitones above the previous frequency, based on controlParameter (specifying the number of semitones).
<i>controlParameter</i>	If type == HS_MULTIPLE, the frequency for harmonic <i>i</i> will be $i * \text{controlParameter}$ , where the fundamental gives the value 1 for <i>i</i> . If type == HS_SEMITONE, the frequency for harmonic <i>i</i> will be $\text{pow}(2, (i - 1) * \text{controlParameter}/12)$ , where the fundamental gives the value 1 for <i>i</i> .

## Note

If `type == HS_MULTIPLE` and `controlParameter == 1`, then the standard harmonic series will be generated.

If `type == HS_SEMITONE`, `controlParameter` does not need to be an integer.

14.2.3.7 `void AdditiveSynth::setHarmonicSeries ( unsigned int harmonicCount, std::function< double(unsigned int)> userFunction )`

This function calculates the harmonic series from a function supplied by the user.

## Parameters

<i>harmonicCount</i>	The number of harmonics to generate.
<i>userFunction</i>	The user function takes an integer representing the harmonic number, where the fundamental has the value 1, and returns the frequency that should be used for that harmonic.

14.2.3.8 `void AdditiveSynth::setStandardHarmonicSeries ( unsigned int harmonicCount )`

The standard harmonic series begins with the fundamental frequency *f1* and each successive harmonic has a frequency equal to  $f1 * n$ , where *n* is the harmonic number for the harmonic. This is the natural harmonic series, one that occurs, e.g., in a vibrating string.

The documentation for this class was generated from the following files:

- CX\_ModularSynth.h
- CX\_ModularSynth.cpp

## 14.3 CX::Algo::BlockSampler&lt; T &gt; Class Template Reference

```
#include <CX_Algorithm.h>
```

### Public Member Functions

- **BlockSampler** ([CX\\_RandomNumberGenerator](#) \*rng, const std::vector< T > &values)
- T **getNextValue** (void)
- std::vector< T > **getNBlocks** (unsigned int blocks)
- void **resetBlocks** (void)
- unsigned int **getBlockNumber** (void)
- unsigned int **getBlockPosition** (void)

#### 14.3.1 Detailed Description

```
template<typename T>class CX::Algo::BlockSampler< T >
```

This class helps with the case where a set of  $V$  values must be sampled randomly with the constraint that each block of  $V$  samples should have each value in the set. For example, if you want to present a number of trials in four different conditions, where the conditions are intermixed, but you want to observe all four trial types every four trials, you would use this class.

```
Algo::BlockSampler<int> bs(&RNG, Util::intVector(1, 4));

cout << "Block, Position, Value" << endl;
while (bs.getBlockNumber() < 4) { //Generate 4 blocks of values
    cout << bs.getBlockNumber() << ", " << bs.getBlockPosition() << ", ";
    cout << bs.getNextValue() << endl;
}
```

The documentation for this class was generated from the following file:

- CX\_Algorithm.h

## 14.4 CX::Synth::Clamper Class Reference

```
#include <CX_ModularSynth.h>
```

Inherits [CX::Synth::ModuleBase](#).

### Public Member Functions

- double [getNextSample](#) (void) override

### Public Attributes

- ModuleParameter **low**
- ModuleParameter **high**

### Additional Inherited Members

#### 14.4.1 Detailed Description

This class clamps inputs to be in the interval [ $low$ ,  $high$ ], where  $low$  and  $high$  are the members of this class.

### 14.4.2 Member Function Documentation

#### 14.4.2.1 double Clamper::getNextSample ( void ) [override],[virtual]

This function should be overloaded for any derived class that can be used as the input for another module.

Reimplemented from [CX::Synth::ModuleBase](#).

The documentation for this class was generated from the following files:

- CX\_ModularSynth.h
- CX\_ModularSynth.cpp

## 14.5 CX::CX\_SlidePresenter::Configuration Struct Reference

```
#include <CX_SlidePresenter.h>
```

### Public Types

- enum [SwappingMode](#) { **SINGLE\_CORE\_BLOCKING\_SWAPS**, **SINGLE\_CORE\_THREADED\_SWAPS**, **MULTI\_CORE** }

### Public Attributes

- [CX\\_Display](#) \* **display**  
*A pointer to the display to use.*
- std::function< void([CX\\_SlidePresenter::FinalSlideFunctionArgs](#) &)> **finalSlideCallback**  
*A pointer to a user function that will be called as soon as the final slide is presented.*
- [CX\\_SlidePresenter::ErrorMode](#) **errorMode**
- bool **deallocateCompletedSlides**  
*If true, once a slide has been presented, its framebuffer will be deallocated to conserve memory.*
- [CX\\_Millis](#) **preSwapCPUHoggingDuration**  
*Only used if swappingMode is a single core mode. The amount of time, before a slide is swapped from the back buffer to the front buffer, that the CPU is put into a spinloop waiting for the buffers to swap.*
- enum [CX::CX\\_SlidePresenter::Configuration::SwappingMode](#) **swappingMode**
- bool **useFenceSync**  
*Hint that fence sync should be used to check that slides are fully copied to the back buffer before they are swapped in.*
- bool **waitUntilFenceSyncComplete**  
*If useFenceSync is false, this is also forced to false. If this is true, new slides will not be swapped in until there is confirmation that the slide has been fully copied into the back buffer. This prevents vertical tearing, but may cause slides to be swapped in late if the copy confirmation is delayed but the copy has actually occurred. Does nothing if swappingMode == MULTI\_CORE.*

### 14.5.1 Detailed Description

This struct is used for configuring a [CX\\_SlidePresenter](#).



## 14.5.2 Member Enumeration Documentation

### 14.5.2.1 enum CX::CX\_SlidePresenter::Configuration::SwappingMode

The method used by the slide presenter to swap stimuli that have been drawn to the back buffer to the front buffer. MULTI\_CORE is the best method, but only really works properly if you have at least a 2 core CPU. In the SINGLE\_CORE\_THREADED\_SWAPS mode, after a stimulus has been copied to the front buffer, the next stimulus is immediately drawn to the back buffer. After the correct amount of time minus preSwapCPUHoggingDuration, a swap of the front and back buffers is queued by launching a thread. In the SINGLE\_CORE\_BLOCKING\_SWAPS mode, everything is the same as SINGLE\_CORE\_THREADED\_SWAPS, but instead of launching a thread to swap the buffers, this mode blocks in the main thread while waiting for the swap.

The documentation for this struct was generated from the following file:

- CX\_SlidePresenter.h

## 14.6 CX::CX\_SoundStream::Configuration Struct Reference

```
#include <CX_SoundStream.h>
```

### Public Attributes

- int [inputChannels](#)  
*The number of input (e.g. microphone) channels to use. If 0, no input will be used.*
- int [outputChannels](#)  
*The number of output channels to use. Currently only stereo and mono are well-supported. If 0, no output will be used.*
- int [sampleRate](#)
- unsigned int [bufferSize](#)
- RtAudio::Api [api](#)
- RtAudio::StreamOptions [streamOptions](#)
- int [inputDeviceId](#)  
*The ID of the desired input device. A value of -1 will cause the system default input device to be used.*
- int [outputDeviceId](#)  
*The ID of the desired output device. A value of -1 will cause the system default output device to be used.*

### 14.6.1 Detailed Description

This struct controls the configuration of the [CX\\_SoundStream](#).

## 14.6.2 Member Data Documentation

### 14.6.2.1 RtAudio::Api CX::CX\_SoundStream::Configuration::api

This argument depends on your operating system. Using RtAudio::Api::UNSPECIFIED will attempt to pick a working API from those that are available on your system. The API means the type of software interface to use. For example, on Windows, you can choose from Windows Direct Sound (DS) and ASIO. ASIO is commonly used with audio recording equipment because it has lower latency whereas DS is more of a consumer-grade interface. The choice of API does not affect how you use this class, but it may affect the performance of sound playback.

See <http://www.music.mcgill.ca/~gary/rtaudio/classRtAudio.html#ac9b6f625da88249d08a8409a9db> for a listing of the APIs. See <http://www.music.mcgill.ca/~gary/rtaudio/classRtAudio.-html#afd0bfa26deae9804e18faff59d0273d9> for the default ordering of the APIs if RtAudio::Api::UNSPECIFIED is used.

#### 14.6.2.2 unsigned int CX::CX\_SoundStream::Configuration::bufferSize

The size of the audio data buffer to use. A larger buffer size means more latency but also a greater potential for audio glitches (clicks and pops). Buffer size is per channel (i.e. if there are two channels and buffer size is set to 256, the actual buffer size will be 512 samples). Defaults to 4096 samples.

#### 14.6.2.3 int CX::CX\_SoundStream::Configuration::sampleRate

The requested sample rate for the input and output channels. If, for the selected device(s), this sample cannot be used, the nearest greater sample rate will be chosen. If there is no greater sample rate, the next lower sample rate will be used.

#### 14.6.2.4 RtAudio::StreamOptions CX::CX\_SoundStream::Configuration::streamOptions

See [http://www.music.mcgill.ca/~gary/rtaudio/structRtAudio\\_1\\_1StreamOptions.-html](http://www.music.mcgill.ca/~gary/rtaudio/structRtAudio_1_1StreamOptions.-html) for more information.

flags must not include RTAUDIO\_NONINTERLEAVED: The audio data used by CX is interleaved.

The documentation for this struct was generated from the following file:

- CX\_SoundStream.h

## 14.7 CX::CX\_BaseClock Class Reference

```
#include <CX_ClockImplementations.h>
```

Inherited by CX::CX\_StdClockWrapper< stdClock >.

### Public Member Functions

- virtual long long **nanos** (void)=0
- virtual void **resetStartTime** (void)=0
- virtual std::string **getName** (void)

#### 14.7.1 Detailed Description

[CX\\_Clock](#) uses classes that are derived from this class for timing.

nanos() should return the current time in nanoseconds. If the implementation does not have nanosecond precision, it should still return time in nanoseconds, which might just involve a multiplication (clock ticks are in microseconds, so multiply by 1000 to make each value equal to a nanosecond).

It is assumed that the implementation has some way to subtract off a start time so that nanos() counts up from 0 and that resetStartTime can reset the start time.

The documentation for this class was generated from the following file:

- CX\_ClockImplementations.h

## 14.8 CX::CX\_Clock Class Reference

```
#include <CX_Clock.h>
```

### Public Member Functions

- void **setImplementation** (CX::CX\_BaseClock \*impl)
- void **precisionTest** (unsigned int iterations)
- CX\_Millis **now** (void)
- void **sleep** (CX\_Millis t)
- void **resetExperimentStartTime** (void)
- std::string **getExperimentStartDateTimeString** (std::string format="%Y-%b-%e %h-%M-%S %a")

### Static Public Member Functions

- static std::string **getDateTimeString** (std::string format="%Y-%b-%e %h-%M-%S %a")

#### 14.8.1 Detailed Description

This class is responsible for getting timestamps for anything requiring timestamps. The way to get timing information is the function [now\(\)](#). It returns the current time relative to the start of the experiment in microseconds (on most systems, see [getTickPeriod\(\)](#) to check the actual precision).

An instance of this class is preinstantiated for you. See [CX::Instances::Clock](#).

#### 14.8.2 Member Function Documentation

##### 14.8.2.1 std::string CX\_Clock::getDateTimeString ( std::string format = "%Y-%b-%e %h-%M-%S %a" ) [static]

This function returns a string containing the local time encoded according to some format.

##### Parameters

<i>format</i>	See <a href="http://pocoproject.org/docs/Poco.DateTimeFormatter.html#4684">http://pocoproject.org/docs/Poco.DateTimeFormatter.html#4684</a> for documentation of the format. E.g. "%Y/%m/%d %H:%M:%S" gives "year/month/day 24Hour-Clock:minute:second" with some zero-padding for most things. The default "%Y-%b-%e %h-%M-%S %a" is "yearWithCentury-abbreviatedMonthName-nonZeroPaddedDay 12HourClock-minuteZeroPadded-secondZeroPadded am/pm".
---------------	--

##### 14.8.2.2 std::string CX\_Clock::getExperimentStartDateTimeString ( std::string format = "%Y-%b-%e %h-%M-%S %a" )

Get a string representing the date/time of the start of the experiment encoded according to a format.

##### Parameters

<i>format</i>	See <a href="#">getDateTimeString()</a> for the definition of the format.
---------------	---

##### 14.8.2.3 CX\_Millis CX\_Clock::now ( void )

This function returns the current time relative to the start of the experiment in milliseconds. The start of the experiment is defined by default as when the [CX\\_Clock](#) instance named [Clock](#) (instantiated in this file) is constructed (typically the beginning of program execution).

**Returns**

A CX\_Millis object containing the time.

**Note**

This cannot be converted to current date/time in any meaningful way. Use [getTimeString\(\)](#) for that.

**14.8.2.4 void CX\_Clock::precisionTest ( unsigned int *iterations* )**

This function tests the precision of the clock used by [CX](#). The results are computer-specific. If the precision of the clock is worse than microsecond accuracy, a warning is logged including information about the actual precision of the clock.

Depending on the number of iterations, this function may be considered blocking. See [Blocking Code](#).

**Parameters**

<i>iterations</i>	Number of time duration samples to take. More iterations should give a better estimate.
-------------------	---

The documentation for this class was generated from the following files:

- CX\_Clock.h
- CX\_Clock.cpp

**14.9 CX::Util::CX\_CoordinateConverter Class Reference**

```
#include <CX_UnitConversion.h>
```

**Public Member Functions**

- [CX\\_CoordinateConverter](#) (ofPoint origin, bool invertX, bool invertY, bool invertZ=false)
- ofPoint [operator\(\)](#) (ofPoint p)
- ofPoint [operator\(\)](#) (float x, float y, float z=0)
- void [setAxisInversion](#) (bool invertX, bool invertY, bool invertZ=false)
- void [setOrigin](#) (ofPoint newOrigin)
- void [setMultiplier](#) (float multiplier)
- void [setUnitConverter](#) (CX\_BaseUnitConverter \*converter)

**14.9.1 Detailed Description**

This helper class is used for converting from a somewhat user-defined coordinate system into the standard computer monitor coordinate system. When user coordinates are input into this class, they will be converted into the standard monitor coordinate system. This lets you use this class to allow you to use coordinates in your own system and convert those coordinates into the standard coordinates that are used by the drawing functions of openFrameworks.

See [setUnitConverter\(\)](#) for a way to do change the units of the coordinate system to, for example, inches or degrees of visual angle.

Example use:

```
CX_CoordinateConverter conv(Display.  
    getCenterOfDisplay(), false, true); //Make the center of the display the origin and  
    invert  
//the Y-axis. This makes positive x values go to the right and positive y values go up from the center of  
    the display.  
ofSetColor(255, 0, 0); //Draw a red circle in the center of the display.
```

```
ofCircle(conv(0, 0), 20);
ofSetColor(0, 255, 0); //Draw a green circle 100 pixels to the right of the center.
ofCircle(conv(100, 0), 20);
ofSetColor(0, 0, 255); //Draw a blue circle 100 pixels above the center (inverted y-axis).
ofCircle(conv(0, 100), 20);
```

Another example can be found in the `advancedChangeDetectionTask` example experiment.

## 14.9.2 Constructor & Destructor Documentation

### 14.9.2.1 `CX::Util::CX_CoordinateConverter::CX_CoordinateConverter ( ofPoint origin, bool invertX, bool invertY, bool invertZ = false )`

Constructs a coordinate converter with the given settings.

#### Parameters

<i>origin</i>	The location within the standard coordinate system at which the origin (the point at which the x, y, and z values are 0) of the user-defined coordinate system is located. If, for example, you want the center of the display to be the origin within your user-defined coordinate system, you could use <code>CX_Display::getCenterOfDisplay()</code> as the value for this argument.
<i>invertX</i>	Invert the x-axis from the default, which is that x increases to the right.
<i>invertY</i>	Invert the y-axis from the default, which is that y increases downward.
<i>invertZ</i>	Invert the z-axis from the default, which is that z increases toward the user (i.e. pointing out of the front of the screen).

## 14.9.3 Member Function Documentation

### 14.9.3.1 `ofPoint CX::Util::CX_CoordinateConverter::operator() ( ofPoint p )`

The primary method of conversion between coordinate systems. You supply a point in user coordinates and get in return a point in standard coordinates.

Example use:

```
CX_CoordinateConverter cc(ofPoint(200,200), false, true);
ofPoint p(-50, 100); //P is in user-defined coordinates, 50 units left and 100 units above the origin.
ofPoint res = cc(p); //Use operator() to convert from the user system to the standard system.
//res should contain (150, 100) due to the inverted y axis.
```

#### Parameters

<i>p</i>	The point in user coordinates that should be converted to standard coordinates.
----------	---

#### Returns

The point in standard coordinates.

### 14.9.3.2 `ofPoint CX::Util::CX_CoordinateConverter::operator() ( float x, float y, float z = 0 )`

Equivalent to a call to `operator()(ofPoint(x, y, z))`.

### 14.9.3.3 `void CX::Util::CX_CoordinateConverter::setAxisInversion ( bool invertX, bool invertY, bool invertZ = false )`

Sets whether each axis within the user-defined system is inverted from the standard coordinate system.

## Parameters

<i>invertX</i>	Invert the x-axis from the default, which is that x increases to the right.
<i>invertY</i>	Invert the y-axis from the default, which is that y increases downward.
<i>invertZ</i>	Invert the z-axis from the default, which is that z increases toward the viewer (i.e. pointing out of the front of the screen).

14.9.3.4 void CX::Util::CX\_CoordinateConverter::setMultiplier ( float *multiplier* )

This function sets the amount by which user coordinates are multiplied before they are converted to standard coordinates. This allows you to easily scale stimuli. The multiplier is 1 by default.

## Parameters

<i>multiplier</i>	The amount to multiply user coordinates by.
-------------------	---

14.9.3.5 void CX::Util::CX\_CoordinateConverter::setOrigin ( ofPoint *newOrigin* )

Sets the location within the standard coordinate system at which the origin of the user-defined coordinate system is located.

## Parameters

<i>newOrigin</i>	The location within the standard coordinate system at which the origin (the point at which the x, y, and z values are 0) of the user-defined coordinate system is located. If, for example, you want the center of the display to be the origin within your user-defined coordinate system, you could use <a href="#">CX_Display::getCenterOfDisplay()</a> as the value for this argument.
------------------	--

14.9.3.6 void CX::Util::CX\_CoordinateConverter::setUnitConverter ( CX\_BaseUnitConverter \* *converter* )

Sets the unit converter that will be used when converting the coordinate system. In this way you can convert both the coordinate system in use and the units used by the coordinate system in one step. See [CX\\_DegreeToPixelConverter](#) and [CX\\_LengthToPixelConverter](#) for examples of the converters that can be used.

Example use:

```
//At global scope:
CX_CoordinateConverter conv(ofPoint(0,0), false, true); //The origin will be set to a
proper value later.
CX_DegreeToPixelConverter d2p(35, 70);

//During setup:
conv.setOrigin(Display.getCenterOfDisplay());
conv.setUnitConverter(&d2p); //Use degrees of visual angle as the units of the user coordinate system.

//Draw a blue circle 2 degrees of visual angle to the left of the origin and 3 degrees above (inverted
y-axis) the origin.
ofSetColor(0, 0, 255);
ofCircle(conv(-2, 3), 20);
```

## Parameters

<i>converter</i>	A pointer to an instance of a class that is a CX_BaseUnitConverter or which has inherited from that class. See <a href="#">CX_UnitConversion.h/cpp</a> for the implementation of <a href="#">CX_LengthToPixelConverter</a> to see an example of how to create you own converter.
------------------	--

## Note

The origin of the coordinate converter must be in the units that result from the unit conversion. E.g. if you are converting the units from degrees to pixels, the origin must be in pixels. See [setOrigin\(\)](#).

The unit converter passed to this function must continue to exist throughout the lifetime of the coordinate converter. It is not copied.

The documentation for this class was generated from the following files:

- CX\_UnitConversion.h
- CX\_UnitConversion.cpp

## 14.10 CX::CX\_DataFrame Class Reference

```
#include <CX_DataFrame.h>
```

### Public Types

- typedef std::vector  
  < CX\_DataFrameCell >  
  ::size\_type **rowIndex\_t**

### Public Member Functions

- CX\_DataFrame & **operator=** (CX\_DataFrame &df)
  - CX\_DataFrameCell **operator()** (std::string column, rowIndex\_t row)
  - CX\_DataFrameCell **operator()** (rowIndex\_t row, std::string column)
  - CX\_DataFrameCell **at** (rowIndex\_t row, std::string column)
  - CX\_DataFrameCell **at** (std::string column, rowIndex\_t row)
  - CX\_DataFrameColumn **operator[]** (std::string column)
  - CX\_DataFrameRow **operator[]** (rowIndex\_t row)
  - void **appendRow** (CX\_DataFrameRow row)
  - void **setRowCount** (rowIndex\_t rowCount)
  - void **addColumn** (std::string columnName)
  - std::string **print** (std::string delimiter="\t", bool printRowNumbers=true)
  - std::string **print** (const std::set< std::string > &columns, std::string delimiter="\t", bool printRowNumbers=true)
  - std::string **print** (const std::vector< rowIndex\_t > &rows, std::string delimiter="\t", bool printRowNumbers=true)
  - std::string **print** (const std::set< std::string > &columns, const std::vector< rowIndex\_t > &rows, std::string delimiter="\t", bool printRowNumbers=true)
  - bool **printToFile** (std::string filename, std::string delimiter="\t", bool printRowNumbers=true)
  - bool **printToFile** (std::string filename, const std::set< std::string > &columns, std::string delimiter="\t", bool printRowNumbers=true)
  - bool **printToFile** (std::string filename, const std::vector< rowIndex\_t > &rows, std::string delimiter="\t", bool printRowNumbers=true)
  - bool **printToFile** (std::string filename, const std::set< std::string > &columns, const std::vector< rowIndex\_t > &rows, std::string delimiter="\t", bool printRowNumbers=true)
  - bool **readFromFile** (std::string filename, std::string cellDelimiter="\t", std::string vectorEncloser="")
  - void **clear** (void)
  - bool **deleteColumn** (std::string columnName)
  - bool **deleteRow** (rowIndex\_t row)
  - std::vector< std::string > **columnNames** (void)
  - rowIndex\_t **getRowCount** (void)
- Returns the number of rows in the data frame.*
- bool **reorderRows** (const vector< CX\_DataFrame::rowIndex\_t > &newOrder)

- [CX\\_DataFrame copyRows](#) (vector< CX\_DataFrame::rowIndex\_t > rowOrder)
- [CX\\_DataFrame copyColumns](#) (vector< std::string > columns)
- void [shuffleRows](#) (void)
- void [shuffleRows](#) (CX\_RandomNumberGenerator &rng)
- template<typename T >  
std::vector< T > [copyColumn](#) (std::string column)

#### Protected Member Functions

- void [\\_resizeToFit](#) (std::string column, rowIndex\_t row)
- void [\\_resizeToFit](#) (rowIndex\_t row)
- void [\\_resizeToFit](#) (std::string column)
- void [\\_equalizeRowLengths](#) (void)

#### Protected Attributes

- std::map< std::string, vector  
< [CX\\_DataFrameCell](#) > > [\\_data](#)
- rowIndex\_t [\\_rowCount](#)

#### Friends

- class [CX\\_DataFrameRow](#)
- class [CX\\_DataFrameColumn](#)

#### 14.10.1 Detailed Description

This class provides an easy way to store data from an experiment and output that data to a file at the end of the experiment. A [CX\\_DataFrame](#) is a square two-dimensional array of cells, but each cell is capable of holding a vector of data. Each cell is indexed with a column name (a string) and a row number. Cells can store many different kinds of data and the data can be inserted or extracted easily. The standard method of storing data is to use operator(), which dynamically resizes the data frame. When an experimental session is complete, the data can be written to a file using [printToFile\(\)](#).

See the example `dataFrame.cpp` for thorough examples of how to use a [CX\\_DataFrame](#).

Several of the member functions of this class could be blocking if the amount of data in the data frame is large enough.

#### 14.10.2 Member Function Documentation

##### 14.10.2.1 void CX\_DataFrame::addColumn ( std::string *columnName* )

Adds a column to the data frame.

##### Parameters

<i>columnName</i>	The name of the column to add. If a column with that name already exists in the data frame, a warning will be logged.
-------------------	---

##### 14.10.2.2 void CX\_DataFrame::appendRow ( CX\_DataFrameRow *row* )

Appends the row to the end of the data frame.



**Parameters**

<i>row</i>	The row to add.
------------	-----------------

**Note**

If the row has columns that do not exist in the data frame, those columns will be added to the data frame.

**14.10.2.3 CX\_DataFrameCell CX\_DataFrame::at ( rowIndex\_t row, std::string column )**

Access the cell at the given row and column with bounds checking. Throws a std::out\_of\_range exception and logs an error if either the row or column is out of bounds.

**Parameters**

<i>row</i>	The row number.
<i>column</i>	The column name.

**Returns**

A [CX\\_DataFrameCell](#) that can be read from or written to.

**14.10.2.4 void CX\_DataFrame::clear ( void )**

Deletes the contents of the data frame. Resizes the data frame to have no rows and no columns.

**14.10.2.5 std::vector< std::string > CX\_DataFrame::columnNames ( void )**

Returns a vector containing the names of the columns in the data frame.

**Returns**

Vector of strings with the column names.

**14.10.2.6 template<typename T > std::vector< T > CX::CX\_DataFrame::copyColumn ( std::string column )**

Makes a copy of the data contained in the named column, converting it to the specified type (such a conversion must be possible).

**Parameters**

<i>column</i>	The name of the column to copy data from.
---------------	---

**Returns**

A vector containing the copied data.

**14.10.2.7 CX\_DataFrame CX\_DataFrame::copyColumns ( vector< std::string > columns )**

Copies the specified columns into a new data frame.

## Parameters

<i>columns</i>	A vector of column names to copy out. If a requested column is not found, a warning will be logged, but the function will otherwise complete successfully.
----------------	--

## Returns

A [CX\\_DataFrame](#) containing the specified columns.

## Note

This function may be [Blocking Code](#) if the amount of copied data is large.

## 14.10.2.8 CX\_DataFrame CX\_DataFrame::copyRows ( vector&lt; CX\_DataFrame::rowIndex\_t &gt; rowOrder )

Creates [CX\\_DataFrame](#) containing a copy of the rows specified in rowOrder. The new data frame is not linked to the existing data frame.

## Parameters

<i>rowOrder</i>	A vector of CX_DataFrame::rowIndex_t containing the rows from this data frame to be copied out. The indices in rowOrder may be in any order: They don't need to be ascending. Additionally, the same row to be copied may be specified multiple times.
-----------------	--

## Returns

A [CX\\_DataFrame](#) containing the rows specified in rowOrder.

## Note

This function may be [Blocking Code](#) if the amount of copied data is large.

## 14.10.2.9 bool CX\_DataFrame::deleteColumn ( std::string columnName )

Deletes the given column of the data frame.

## Parameters

<i>columnName</i>	The name of the column to delete. If the column is not in the data frame, a warning will be logged.
-------------------	---

## Returns

True if the column was found and deleted, false if it was not found.

## 14.10.2.10 bool CX\_DataFrame::deleteRow ( rowIndex\_t row )

Deletes the given row of the data frame.

## Parameters

<i>row</i>	The row to delete (0 indexed). If row is greater than or equal to the number of rows in the data frame, a warning will be logged.
------------	---

#### Returns

True if the row was in bounds and was deleted, false if the row was out of bounds.

#### 14.10.2.11 `CX_DataFrameCell CX_DataFrame::operator() ( std::string column, rowIndex_t row )`

Access the cell at the given row and column. If the row or column is out of bounds, the data frame will be dynamically resized in order to fit the row or column.

#### Parameters

<i>row</i>	The row number.
<i>column</i>	The column name.

#### Returns

A [CX\\_DataFrameCell](#) that can be read from or written to.

#### 14.10.2.12 `CX_DataFrame & CX_DataFrame::operator= ( CX_DataFrame & df )`

Copy the contents of another [CX\\_DataFrame](#) to this data frame. Because this is a copy operation, this may be [Blocking Code](#) if the copied data frame is large enough.

#### Parameters

<i>df</i>	The data frame to copy.
-----------	-------------------------

#### Returns

A reference to this data frame.

#### Note

The contents of this data frame are deleted during the copy.

#### 14.10.2.13 `std::string CX_DataFrame::print ( std::string delimiter = "\t", bool printRowNumbers = true )`

Reduced argument version of [print\(\)](#). Prints all rows and columns.

#### 14.10.2.14 `std::string CX_DataFrame::print ( const std::set< std::string > & columns, std::string delimiter = "\t", bool printRowNumbers = true )`

Reduced argument version of [print\(\)](#). Prints all rows and the selected columns.

#### 14.10.2.15 `std::string CX_DataFrame::print ( const std::vector< rowIndex_t > & rows, std::string delimiter = "\t", bool printRowNumbers = true )`

Reduced argument version of [print\(\)](#). Prints all columns and the selected rows.

#### 14.10.2.16 `std::string CX_DataFrame::print ( const std::set< std::string > & columns, const std::vector< rowIndex_t > & rows, std::string delimiter = "\t", bool printRowNumbers = true )`

Prints the selected rows and columns of the data frame to a string. Each cell of the data frame will be separated with the selected delimiter.

Each row of the data frame will be ended with a new line (whatever `std::endl` evaluates to, typically `"\r\n"`).

## Parameters

<i>columns</i>	Columns to print. Column names not found in the data frame will be ignored with a warning.
<i>rows</i>	Rows to print. Row indices not found in the data frame will be ignored with a warning.
<i>delimiter</i>	Delimiter to be used between cells of the data frame. Using comma or semicolon for the delimiter is not recommended because semicolons are used as element delimiters in the string-encoded vectors stored in the data frame and commas are used for element delimiters within each element of the string-encoded vectors.
<i>printRow-Numbers</i>	If true, a column will be printed with the header "rowNumber" with the contents of the column being the selected row indices. If false, no row numbers will be printed.

## Returns

A string containing the printed version of the data frame.

## Note

This function may be [Blocking Code](#) if the data frame is large enough.

14.10.2.17 `bool CX_DataFrame::printToFile ( std::string filename, std::string delimiter = "\t", bool printRowNumbers = true )`

Reduced argument version of [printToFile\(\)](#). Prints all rows and columns.

14.10.2.18 `bool CX_DataFrame::printToFile ( std::string filename, const std::set< std::string > & columns, std::string delimiter = "\t", bool printRowNumbers = true )`

Reduced argument version of [printToFile\(\)](#). Prints all rows and the selected columns.

14.10.2.19 `bool CX_DataFrame::printToFile ( std::string filename, const std::vector< rowIndex_t > & rows, std::string delimiter = "\t", bool printRowNumbers = true )`

Reduced argument version of [printToFile\(\)](#). Prints all columns and the selected rows.

14.10.2.20 `bool CX_DataFrame::printToFile ( std::string filename, const std::set< std::string > & columns, const std::vector< rowIndex_t > & rows, std::string delimiter = "\t", bool printRowNumbers = true )`

This function is equivalent in behavior to [print\(\)](#) except that instead of returning a string containing the printed contents of the data frame, the string is printed to a file. If the file exists, it will be overwritten.

## Parameters

<i>filename</i>	Name of the file to print to. If it is an absolute path, the file will be put there. If it is a local path, the file will be placed relative to the data directory of the project.
-----------------	--

## Returns

True for success, false if there was some problem writing to the file (insufficient permissions, etc.)

14.10.2.21 `bool CX_DataFrame::readFromFile ( std::string filename, std::string cellDelimiter = "\t", std::string vectorEncloser = "\"" )`

Reads data from the given file into the data frame. This function assumes that there will be a row of column names as the first row of the file. It does not treat consecutive delimiters as a single delimiter.

## Parameters

<i>filename</i>	The name of the file to read data from. If it is a relative path, the file will be read relative to the data directory.
<i>cellDelimiter</i>	A string containing the delimiter between cells of the data frame.
<i>vectorEncloser</i>	A string containing the characters that surround cell that contain a vector of data. By default, vectors are enclosed in double quotes. This indicates to most software that it should treat the contents of the quotes "as-is", i.e. if it finds a delimiter within the quotes, it should not split there, but wait until out of the quotes.

## Returns

False if an error occurred, true otherwise.

## Note

The contents of the data frame will be deleted before attempting to read in the file.  
 If the data is read in from a file written with a row numbers column, that column will be read into the data frame. You can remove it using `deleteColumn("rowNumber")`.  
 This function may be [Blocking Code](#) if the read in data frame is large enough.

#### 14.10.2.22 bool CX\_DataFrame::reorderRows ( const vector< CX\_DataFrame::RowIndex\_t > & newOrder )

Re-orders the rows in the data frame.

## Parameters

<i>newOrder</i>	Vector of row indices. <code>newOrder.size()</code> must equal this-> <code>getRowCount()</code> . <code>newOrder</code> must not contain any out-of-range indices (i.e. they must be < <code>getRowCount()</code> ). Both of these error conditions are checked for in the function call and errors are logged.
-----------------	--

## Returns

true if all of the conditions of `newOrder` are met, false otherwise.

#### 14.10.2.23 void CX\_DataFrame::setRowCount ( RowIndex\_t rowCount )

Sets the number of rows in the data frame.

## Parameters

<i>rowCount</i>	The new number of rows in the data frame.
-----------------	---

## Note

If the row count is less than the number of rows already in the data frame, it will delete those rows with a warning.

#### 14.10.2.24 void CX\_DataFrame::shuffleRows ( void )

Randomly re-orders the rows of the data frame using [CX::Instances::RNG](#) as the random number generator for the shuffling.

## Note

This function may be [Blocking Code](#) if the data frame is large.

14.10.2.25 `void CX_DataFrame::shuffleRows ( CX_RandomNumberGenerator & rng )`

Randomly re-orders the rows of the data frame.

## Parameters

<i>rng</i>	Reference to a <a href="#">CX_RandomNumberGenerator</a> to be used for the shuffling.
------------	---

## Note

This function may be [Blocking Code](#) if the data frame is large.

The documentation for this class was generated from the following files:

- CX\_DataFrame.h
- CX\_DataFrame.cpp

## 14.11 CX::CX\_DataFrameCell Class Reference

```
#include <CX_DataFrameCell.h>
```

## Public Member Functions

- [CX\\_DataFrameCell](#) (const char \*c)
- template<typename T >  
[CX\\_DataFrameCell](#) (const T &value)  
*Construct the cell, assigning the value to it.*
- template<typename T >  
[CX\\_DataFrameCell](#) (const std::vector< T > &values)  
*Construct the cell, assigning the values to it.*
- [CX\\_DataFrameCell](#) & [operator=](#) (const char \*c)
- template<typename T >  
[CX\\_DataFrameCell](#) & [operator=](#) (const T &value)  
*Assigns a value to the cell.*
- template<typename T >  
[CX\\_DataFrameCell](#) & [operator=](#) (const std::vector< T > &values)  
*Assigns a vector of values to the cell.*
- template<typename T >  
[operator T](#) (void) const  
*Attempts to convert the contents of the cell to T using [to\(\)](#).*
- template<typename T >  
[operator std::vector< T >](#) (void) const  
*Attempts to convert the contents of the cell to vector<T> using [toVector<T>\(\)](#).*
- template<typename T >  
void [store](#) (const T &value)
- template<typename T >  
T [to](#) (void) const
- std::string [toString](#) (void) const  
*Returns a copy of the stored data in the internal string representation. Type checking is not done because this is a lossless operation.*
- bool [toBool](#) (void) const  
*Returns a copy of the stored data converted to bool. Equivalent to [to<bool>\(\)](#).*
- int [toInt](#) (void) const  
*Returns a copy of the stored data converted to int. Equivalent to [to<int>\(\)](#).*



- double `toDouble` (void) const  
*Returns a copy of the stored data converted to double. Equivalent to `to<double>()`.*
- template<typename T >  
std::vector< T > `toVector` (void) const
- template<typename T >  
void `storeVector` (std::vector< T > values)
- void `copyCellTo` (CX\_DataFrameCell \*targetCell)
- std::string `getStoredType` (void)
- template<>  
std::string `to` (void) const

#### 14.11.1 Detailed Description

This class manages the contents of a single cell in a `CX_DataFrame`. It handles all of the type conversion nonsense that goes on when data is inserted into or extracted from a data frame. It tracks the type of the data that is inserted or extracted and logs warnings if the inserted type does not match the extracted type, with a few exceptions (see notes).

##### Note

There are a few exceptions to the type tracking. If the inserted type is `const char*`, it is treated as a string. Additionally, you can extract anything as string without a warning. This is because the data is stored as a string internally so extracting the data as a string is a lossless operation.

#### 14.11.2 Constructor & Destructor Documentation

##### 14.11.2.1 CX\_DataFrameCell::CX\_DataFrameCell ( const char \* c )

Constructs the cell with a string literal, treating it as a `std::string`.

#### 14.11.3 Member Function Documentation

##### 14.11.3.1 void CX\_DataFrameCell::copyCellTo ( CX\_DataFrameCell \* targetCell )

Copies the contents of this cell to `targetCell`, including type information.

##### Parameters

<i>targetCell</i>	A pointer to the cell to copy data to.
-------------------	--

##### 14.11.3.2 std::string CX\_DataFrameCell::getStoredType ( void )

Gets a string representing the type of data stored within the cell. This string is implementation-defined (which is the C++ standards committee way of saying "It can be anything at all"). It is only guaranteed to be the same for the same type, but not necessarily be different for different types.

##### Returns

A string containing the name of the stored type as given by `typeid(typename).name()`.

##### 14.11.3.3 CX\_DataFrameCell & CX\_DataFrameCell::operator= ( const char \* c )

Assigns a string literal to the cell, treating it as a `std::string`.

#### 14.11.3.4 `template<typename T > void CX::CX_DataFrameCell::store ( const T & value )`

Stores the given value with the given type. This function is a good way to explicitly state the type of the data you are storing into the cell if, for example, it is a literal.

### Template Parameters

<code>&lt; T &gt;</code>	The type to store the value as. If T is not specified, this function is essentially equivalent to using <code>operator=</code> .
--------------------------	--

### Parameters

<i>value</i>	The value to store.
--------------	---------------------

#### 14.11.3.5 `template<typename T> void CX::CX_DataFrameCell::storeVector ( std::vector< T > values )`

Stores a vector of data in the cell. The data is stored as a string with each element delimited by a semicolon. If the data to be stored are strings containing semicolons, the data will not be extracted properly.

### Parameters

<i>values</i>	A vector of values to store.
---------------	------------------------------

#### 14.11.3.6 `template<typename T> T CX::CX_DataFrameCell::to ( void ) const`

Attempts to convert the contents of the cell to type T. There are a variety of reasons why this conversion can fail and they all center on the user inserting data of one type and then attempting to extract data of a different type. Regardless of whether the conversion is possible, if you try to extract a type that is different from the type that is stored in the cell, a warning will be logged.

### Template Parameters

<code>&lt; T &gt;</code>	The type to convert to.
--------------------------	-------------------------

### Returns

The data in the cell converted to T.

#### 14.11.3.7 `std::string CX::CX_DataFrameCell::to ( void ) const`

Equivalent to a call to [toString\(\)](#). This is specialized because it skips the type checks of `to<T>`.

### Returns

A copy of the stored data encoded as a string.

#### 14.11.3.8 `template<typename T> std::vector< T > CX::CX_DataFrameCell::toVector ( void ) const`

Returns a copy of the contents of the cell converted to a vector of the given type. If the type of data stored in the cell was not a vector of the given type or the type does match but it was a scalar that is stored, the logs a warning but attempts the conversion anyway.

### Template Parameters

<code>&lt; T &gt;</code>	The type of the elements of the returned vector.
--------------------------	--

### Returns

A vector containing the converted data.

The documentation for this class was generated from the following files:

- CX\_DataFrameCell.h
- CX\_DataFrameCell.cpp

## 14.12 CX::CX\_DataFrameColumn Class Reference

### Public Member Functions

- [CX\\_DataFrameCell](#) **operator[]** (CX\_DataFrame::rowIndex\_t row)
- CX\_DataFrame::rowIndex\_t **size** (void)

### Friends

- class **CX\_DataFrame**

#### 14.12.1 Detailed Description

The documentation for this class was generated from the following files:

- CX\_DataFrame.h
- CX\_DataFrame.cpp

## 14.13 CX::CX\_DataFrameRow Class Reference

### Public Member Functions

- [CX\\_DataFrameCell](#) **operator[]** (std::string column)
- vector< std::string > **names** (void)
- void **clear** (void)

### Friends

- class **CX\_DataFrame**

#### 14.13.1 Detailed Description

The documentation for this class was generated from the following files:

- CX\_DataFrame.h
- CX\_DataFrame.cpp

## 14.14 CX::Util::CX\_DegreeToPixelConverter Class Reference

```
#include <CX_UnitConversion.h>
```

Inherits CX::Util::CX\_BaseUnitConverter.

## Public Member Functions

- [CX\\_DegreeToPixelConverter](#) (float pixelsPerUnit, float viewingDistance, bool roundResult=false)
- float [operator\(\)](#) (float degrees)

### 14.14.1 Detailed Description

This simple utility class is used for converting degrees of visual angle to pixels on a monitor. This class uses [CX::Util::degreesToPixels\(\)](#) internally. See also [CX::Util::CX\\_CoordinateConverter](#) for a way to also convert from one coordinate system to another.

Example use:

```
CX_DegreeToPixelConverter d2p(34, 60); //34 pixels per unit length (e.g. cm) on
    the target monitor, user is 60 length units from monitor.
ofLine( 200, 100, 200 + d2p(1), 100 + d2p(2) ); //Draw a line from (200, 100) (in pixel coordinates) to 1
    degree
//to the right and 2 degrees below that point.
```

### 14.14.2 Constructor & Destructor Documentation

#### 14.14.2.1 CX::Util::CX\_DegreeToPixelConverter::CX\_DegreeToPixelConverter ( float *pixelsPerUnit*, float *viewingDistance*, bool *roundResult* = false )

Constructs an instance of a [CX\\_DegreeToPixelConverter](#) using the given settings.

##### Parameters

<i>pixelsPerUnit</i>	The number of pixels within one length unit (e.g. inches, centimeters). This can be measured by drawing a ~100-1000 pixel square on the screen and measuring the length of a side and dividing the number of pixels by the total length measured.
<i>viewingDistance</i>	The distance from the monitor that the participant will be viewing the screen from.
<i>roundResult</i>	If true, the result of conversions will be rounded to the nearest integer (i.e. pixel). For drawing certain kinds of stimuli (especially text) it can be helpful to draw on pixel boundaries.

### 14.14.3 Member Function Documentation

#### 14.14.3.1 float CX::Util::CX\_DegreeToPixelConverter::operator() ( float *degrees* )

Converts the degrees to pixels based on the settings given during construction.

##### Parameters

<i>degrees</i>	The number of degrees of visual angle to convert to pixels.
----------------	---

##### Returns

The number of pixels corresponding to the number of degrees of visual angle.

The documentation for this class was generated from the following files:

- CX\_UnitConversion.h
- CX\_UnitConversion.cpp

## 14.15 CX::CX\_Display Class Reference

```
#include <CX_Display.h>
```

### Public Member Functions

- void [setup](#) (void)
- void [setFullScreen](#) (bool fullScreen)
- void [copyFboToBackBuffer](#) (ofFbo &fbo)
- void [copyFboToBackBuffer](#) (ofFbo &fbo, ofPoint destination)
- void [copyFboToBackBuffer](#) (ofFbo &fbo, ofRectangle source, ofPoint destination)
- void [beginDrawingToBackBuffer](#) (void)
- void [endDrawingToBackBuffer](#) (void)
- void [BLOCKING\\_swapFrontAndBackBuffers](#) (void)
- void [swapFrontAndBackBuffers](#) (void)
- void [BLOCKING\\_setAutoSwapping](#) (bool autoSwap)
- bool [isAutomaticallySwapping](#) (void)
- bool [hasSwappedSinceLastCheck](#) (void)
- [CX\\_Millis](#) [getLastSwapTime](#) (void)
- void [BLOCKING\\_estimateFramePeriod](#) ([CX\\_Millis](#) estimationInterval)
- [CX\\_Millis](#) [getFramePeriod](#) (void)
- [CX\\_Millis](#) [estimateNextSwapTime](#) (void)
- uint64\_t [getFrameNumber](#) (void)
- void [setWindowResolution](#) (int width, int height)
- void [setWindowTitle](#) (std::string title)
- ofRectangle [getResolution](#) (void)
- ofPoint [getCenterOfDisplay](#) (void)
- void [BLOCKING\\_waitForOpenGL](#) (void)

### 14.15.1 Detailed Description

This class represents an abstract visual display surface, which is my way of saying that it doesn't necessarily represent a monitor. The display surface can either be a window or, if full screen, the whole monitor. It is also a bit abstract in that it does not draw anything, but only creates an context in which things can be drawn.

### 14.15.2 Member Function Documentation

#### 14.15.2.1 void CX\_Display::beginDrawingToBackBuffer ( void )

Prepares a rendering context for using drawing functions. Must be paired with a call to [endDrawingToBackBuffer\(\)](#).

#### 14.15.2.2 void CX\_Display::BLOCKING\_estimateFramePeriod ( CX\_Millis estimationInterval )

This function estimates the typical period of the display refresh. This function blocks for estimationInterval while the swapping thread swaps in the background. This function is called with an argument of 300 ms during construction of this class, so there will always be some information about the frame period. If more precision of the estimate is desired, this function can be called again with a longer wait duration.

## Parameters

<i>estimationInterval</i>	The length of time to spend estimating the frame period.
---------------------------	--

## See Also

[Blocking Code](#)

14.15.2.3 void CX\_Display::BLOCKING\_setAutoSwapping ( bool *autoSwap* )

Set whether the front and buffers of the display will swap automatically every frame or not. You can check to see if a swap has occurred by calling [hasSwappedSinceLastCheck\(\)](#). You can check to see if the display is automatically swapping by calling [isAutomaticallySwapping\(\)](#).

## Parameters

<i>autoSwap</i>	If true, the front and back buffer will swap automatically every frame.
-----------------	---

## See Also

[Blocking Code](#)

## 14.15.2.4 void CX\_Display::BLOCKING\_swapFrontAndBackBuffers ( void )

This function queues up a swap of the front and back buffers then blocks until the swap occurs. It does nothing if [isAutomaticallySwapping\(\)](#) == true.

## See Also

[Blocking Code](#)

## 14.15.2.5 void CX\_Display::BLOCKING\_waitForOpenGL ( void )

Wait until all OpenGL instructions that were given before this was called to complete. This can be useful if you are trying to determine how long a set of rendering commands takes or need to make sure that all rendering is complete before moving on.

## See Also

[Blocking Code](#)

14.15.2.6 void CX\_Display::copyFboToBackBuffer ( ofFbo & *fbo* )

Copies an ofFbo to the back buffer using a highly efficient blitting operation. This copies over the contents of the back buffer, it does not draw over them. For this reason, transparency is ignored.

## Parameters

<i>fbo</i>	The framebuffer to copy. It will be drawn starting from (0, 0) and will be drawn at the full dimensions of the fbo (whatever size was chosen at allocation of the fbo).
------------	---

14.15.2.7 void CX\_Display::copyFboToBackBuffer ( ofFbo & *fbo*, ofPoint *destination* )

Copies an ofFbo to the back buffer using a highly efficient blitting operation.

## Parameters

<i>fbo</i>	The framebuffer to copy.
<i>destination</i>	The point on the back buffer where the fbo will be placed.

14.15.2.8 void CX\_Display::copyFboToBackBuffer ( ofFbo & *fbo*, ofRectangle *source*, ofPoint *destination* )

Copies an ofFbo to the back buffer using a highly efficient blitting operation.

## Parameters

<i>fbo</i>	The framebuffer to copy.
<i>source</i>	A rectangle giving an area of the fbo to copy.
<i>destination</i>	The point on the back buffer where the area of the fbo will be placed.

If this function does not provide enough flexibility, you can always draw ofFbo's using the following technique:

```
Display.beginDrawingToBackBuffer();
ofSetColor( 255 );
fbo.draw( x, y, width, height ); //Replace these variables with the destination location (x,y) and
                                dimensions of the
Display.endDrawingToBackBuffer();
```

## 14.15.2.9 void CX\_Display::endDrawingToBackBuffer ( void )

Finish rendering to the back buffer. Must be paired with a call to [beginDrawingToBackBuffer\(\)](#).

## 14.15.2.10 CX\_Millis CX\_Display::estimateNextSwapTime ( void )

Get an estimate of the next time the front and back buffers will be swapped. This function depends on the precision of the frame period as estimated using [BLOCKING\\_estimateFramePeriod\(\)](#).

## Returns

A time value that can be compared to CX::Instances::Clock.now().

## 14.15.2.11 ofPoint CX\_Display::getCenterOfDisplay ( void )

Returns an ofPoint representing the center of the display. Works in either windowed or full screen mode.

## 14.15.2.12 uint64\_t CX\_Display::getFrameNumber ( void )

This function returns the number of the last frame presented, as determined by number of front and back buffer swaps. It tracks buffer swaps that result from 1) the front and back buffer swapping automatically (as a result of [BLOCKING\\_setAutoSwapping\(\)](#) with true as the argument) and 2) manual swaps resulting from a call to [BLOCKING\\_swapFrontAndBackBuffers\(\)](#) or [swapFrontAndBackBuffers\(\)](#).

## Returns

The number of the last frame. This value can only be compared with other values returned by this function.

## 14.15.2.13 CX\_Millis CX\_Display::getFramePeriod ( void )

Gets the estimate of the frame period calculated with [BLOCKING\\_estimateFramePeriod\(\)](#).

## 14.15.2.14 CX\_Millis CX\_Display::getLastSwapTime ( void )

Get the last time at which the front and back buffers were swapped.



**Returns**

A time value that can be compared with `CX::Instances::Clock.now()`.

**14.15.2.15 ofRectangle CX\_Display::getResolution ( void )**

Returns the resolution of the current window, not the resolution of the monitor (unless you are in full screen mode).

**Returns**

An `ofRectangle` containing the resolution. The width in pixels is stored in both the width and x members and the height in pixels is stored in both the height and y members, so you can use whichever makes the most sense to you.

**14.15.2.16 bool CX\_Display::hasSwappedSinceLastCheck ( void )**

Check to see if the display has swapped the front and back buffers since the last call to this function. This is generally used in conjunction with automatic swapping of the buffers ([BLOCKING\\_setAutoSwapping\(\)](#)) or with an individual threaded swap of the buffers ([swapFrontAndBackBuffers\(\)](#)). This technically works with [BLOCKING\\_swapFrontAndBackBuffers\(\)](#), but given that that function only returns once the buffers have swapped, checking that the buffers have swapped is redundant.

**Returns**

True if a swap has been made since the last call to this function, false otherwise.

**14.15.2.17 bool CX\_Display::isAutomaticallySwapping ( void )**

Determine whether the display is configured to automatically swap the front and back buffers every frame. See [BLOCKING\\_setAutoSwapping](#) for more information.

**14.15.2.18 void CX\_Display::setFullScreen ( bool *fullScreen* )**

Set whether the display is full screen or not. If the display is set to full screen, the resolution may not be the same as the resolution of display in windowed mode, and vice versa.

**14.15.2.19 void CX\_Display::setup ( void )**

Set up the display. Must be called for the display to function correctly.

**14.15.2.20 void CX\_Display::setWindowResolution ( int *width*, int *height* )**

Sets the resolution of the window. Has no effect if called while in full screen mode.

**Parameters**

<i>width</i>	The desired width of the window, in pixels.
<i>height</i>	The desired height of the window, in pixels.

**14.15.2.21 void CX\_Display::setWindowTitle ( std::string *title* )**

Sets the title of the experiment window.

## Parameters

<i>title</i>	The new window title.
--------------	-----------------------

## 14.15.2.22 void CX\_Display::swapFrontAndBackBuffers ( void )

This function cues a swap of the front and back buffers. It avoids blocking (like [BLOCKING\\_swapFrontAndBackBuffers\(\)](#)) by spawning a thread in which the swap is waited for.

The documentation for this class was generated from the following files:

- CX\_Display.h
- CX\_Display.cpp

## 14.16 CX::CX\_InputManager Class Reference

```
#include <CX_InputManager.h>
```

## Public Member Functions

- bool [setup](#) (bool useKeyboard, bool useMouse, int joystickIndex=-1)
- bool [pollEvents](#) (void)

## Public Attributes

- [CX\\_Keyboard Keyboard](#)  
*An instance of CX::CX\_Keyboard. Enabled or disabled with CX::CX\_InputManager::setup().*
- [CX\\_Mouse Mouse](#)  
*An instance of CX::CX\_Mouse. Enabled or disabled with CX::CX\_InputManager::setup().*
- [CX\\_Joystick Joystick](#)  
*An instance of CX::CX\_Joystick. Enabled or disabled with CX::CX\_InputManager::setup().*

## 14.16.1 Detailed Description

This class is responsible for managing three basic input devices: a keyboard, mouse, and joystick. You access each of these devices with the corresponding member class: Keyboard, Mouse, and Joystick. See [CX::CX\\_Keyboard](#), [CX::CX\\_Mouse](#), and [CX::CX\\_Joystick](#) for more information about each specific device.

By default, all three input devices are disabled. Call [setup\(\)](#) to enable specific devices.

## 14.16.2 Member Function Documentation

## 14.16.2.1 bool CX\_InputManager::pollEvents ( void )

It is not typically necessary for the user to call this function directly, although there is no harm in doing so. This function polls for new events on all of the configured input devices (see [setup\(\)](#)). After a call to this function, new events for the input devices can be found by checking the [availableEvents\(\)](#) function for each device.

**Returns**

True if there are any events available for enabled devices, false otherwise. The events do not necessarily need to be new events. If there are events that were already stored in Mouse, Keyboard, or Joystick but had not been processed by user code, this function will return true.

**14.16.2.2 bool CX\_InputManager::setup ( bool useKeyboard, bool useMouse, int joystickIndex = -1 )**

Setup the input manager to use the requested devices. You may call this function multiple times if you want to change the configuration over the course of the experiment. Every time this function is called, all input device events are cleared.

**Parameters**

<i>useKeyboard</i>	Enable or disable the keyboard.
<i>useMouse</i>	Enable or disable the mouse.
<i>joystickIndex</i>	Optional. If $\geq 0$ , an attempt will be made to set up the joystick at that index. If $< 0$ , no attempt will be made to set up the joystick.

**Returns**

False if the requested joystick could not be set up correctly, true otherwise.

The documentation for this class was generated from the following files:

- CX\_InputManager.h
- CX\_InputManager.cpp

**14.17 CX::CX\_Joystick Class Reference**

```
#include <CX_Joystick.h>
```

**Classes**

- struct [Event](#)

**Public Member Functions**

- bool [setup](#) (int joystickIndex)
- std::string [getJoystickName](#) (void)
- bool [pollEvents](#) (void)
- int [availableEvents](#) (void)
- CX\_Joystick::Event [getNextEvent](#) (void)
- void [clearEvents](#) (void)
- std::vector< float > [getAxisPositions](#) (void)
- std::vector< unsigned char > [getButtonStates](#) (void)

**14.17.1 Detailed Description**

This class manages a joystick that is attached to the system (if any). If more than one joystick is needed for the experiment, you can create more instances of [CX\\_Joystick](#) other than the one in [CX::Instances::Input](#).

## 14.17.2 Member Function Documentation

## 14.17.2.1 int CX\_Joystick::availableEvents ( void )

Get the number of new events available for this input device.

## 14.17.2.2 void CX\_Joystick::clearEvents ( void )

Clear (delete) all events from this input device.

## 14.17.2.3 vector&lt; float &gt; CX\_Joystick::getAxisPositions ( void )

This function is to be used for direct access to the axis positions of the joystick. It does not generate events (i.e. [CX\\_Joystick::Event](#)), nor does it do any timestamping. If timestamps and uncertainties are desired, you MUST use [pollEvents\(\)](#) and the associated event functions (e.g. [getNextEvent\(\)](#)).

## 14.17.2.4 vector&lt; unsigned char &gt; CX\_Joystick::getButtonStates ( void )

This function is to be used for direct access to the button states of the joystick. It does not generate events (i.e. [CX\\_Joystick::Event](#)), nor does it do any timestamping. If timestamps and uncertainties are desired, you MUST use [pollEvents\(\)](#) and the associated event functions (e.g. [getNextEvent\(\)](#)).

## 14.17.2.5 std::string CX\_Joystick::getJoystickName ( void )

Get the name of the joystick, presumably as set by the joystick driver. The name may not be very meaningful.

## 14.17.2.6 CX\_Joystick::Event CX\_Joystick::getNextEvent ( void )

Get the next event available for this input device. This is a destructive operation: the returned event is deleted from the input device.

## 14.17.2.7 bool CX\_Joystick::pollEvents ( void )

Check to see if there are any new joystick events. If there are new events, they can be accessed with [availableEvents\(\)](#) and [getNextEvent\(\)](#).

## Returns

True if there are new events.

## 14.17.2.8 bool CX\_Joystick::setup ( int joystickIndex )

Set up the joystick by attempting to initialize the joystick at the given index. If the joystick is present on the system, it will be initialized and its name can be accessed by calling [getJoystickName\(\)](#).

If the set up is successful (i.e. if the selected joystick is present on the system), this function will return true. If the joystick is not present, it will return false.

The documentation for this class was generated from the following files:

- CX\_Joystick.h
- CX\_Joystick.cpp

## 14.18 CX::CX\_Keyboard Class Reference

```
#include <CX_Keyboard.h>
```

## Classes

- struct [Event](#)

## Public Member Functions

- int [availableEvents](#) (void)
- [CX\\_Keyboard::Event](#) [getNextEvent](#) (void)
- void [clearEvents](#) (void)
- bool [isKeyPressed](#) (int key)

## Friends

- class **CX\_InputManager**

### 14.18.1 Detailed Description

This class is responsible for managing the mouse.

### 14.18.2 Member Function Documentation

#### 14.18.2.1 int CX\_Keyboard::availableEvents ( void )

Get the number of new events available for this input device.

#### 14.18.2.2 void CX\_Keyboard::clearEvents ( void )

Clear (delete) all events from this input device.

#### 14.18.2.3 CX\_Keyboard::Event CX\_Keyboard::getNextEvent ( void )

Get the next event available for this input device. This is a destructive operation: the returned event is deleted from the input device.

#### 14.18.2.4 bool CX::CX\_Keyboard::isKeyPressed ( int key ) [inline]

This function checks to see if the given key is pressed.

#### Parameters

<i>key</i>	The key code for key you are interested in. See the documentation for the <i>key</i> member of <a href="#">CX_Keyboard::Event</a> for more information about this value.
------------	--

#### Returns

True if the given key is held.

The documentation for this class was generated from the following files:

- CX\_Keyboard.h
- CX\_Keyboard.cpp

## 14.19 CX::Util::CX\_LapTimer Class Reference

```
#include <CX_Clock.h>
```

### Public Member Functions

- void **setup** ([CX\\_Clock](#) \*clock, unsigned int samples)
- void **reset** (void)
- void **takeSample** (void)
- [CX\\_Millis](#) **mean** (void)
- [CX\\_Millis](#) **min** (void)
- [CX\\_Millis](#) **max** (void)
- [CX\\_Millis](#) **stdDev** (void)
- std::string **getStatString** (void)

### 14.19.1 Detailed Description

This class can be used for profiling event loops.

```
//Set up collection:
CX_LapTimer lt;
lt.setup(&Clock, 1000); //Every 1000 samples, the results of those samples will be logged.

//In the loop:
while (whatever) {
    //other code...
    lt.takeSample();
    //other code...
}
Log.flush(); //Check the results of the profiling.
```

The documentation for this class was generated from the following files:

- CX\_Clock.h
- CX\_Clock.cpp

## 14.20 CX::Util::CX\_LengthToPixelConverter Class Reference

```
#include <CX_UnitConversion.h>
```

Inherits CX::Util::CX\_BaseUnitConverter.

### Public Member Functions

- [CX\\_LengthToPixelConverter](#) (float pixelsPerUnit, bool roundResult=false)
- float [operator\(\)](#) (float length)

### 14.20.1 Detailed Description

This simple utility class is used for converting lengths (perhaps of objects drawn on the monitor) to pixels on a monitor. See also [CX::Util::CX\\_CoordinateConverter](#) for a way to also convert from one coordinate system to another.

Example use:

```

CX_LengthToPixelConverter l2p(75); //75 pixels per unit length (e.g. inch) on the
    target monitor.
ofLine( 200, 100, 200 + l2p(1), 100 + l2p(2) ); //Draw a line from (200, 100) (in pixel coordinates) to 1
    unit
//horizontally and 2 units vertically from that point.

```

## 14.20.2 Constructor & Destructor Documentation

### 14.20.2.1 CX::Util::CX\_LengthToPixelConverter::CX\_LengthToPixelConverter ( float *pixelsPerUnit*, bool *roundResult* = false )

Constructs a [CX\\_LengthToPixelConverter](#) with the given configuration.

#### Parameters

<i>pixelsPerUnit</i>	The number of pixels per one length unit. This can be measured by drawing a ~100-1000 pixel square on the screen and measuring the length of a side and dividing the number of pixels by the total length measured.
<i>roundResult</i>	If true, the result of conversions will be rounded to the nearest integer (i.e. pixel). For drawing certain kinds of stimuli (especially text) it can be helpful to draw on pixel boundaries.

## 14.20.3 Member Function Documentation

### 14.20.3.1 float CX::Util::CX\_LengthToPixelConverter::operator() ( float *length* )

Converts the length to pixels based on the settings given during construction.

#### Parameters

<i>length</i>	The length to convert to pixels.
---------------	----------------------------------

#### Returns

The number of pixels corresponding to the length.

The documentation for this class was generated from the following files:

- CX\_UnitConversion.h
- CX\_UnitConversion.cpp

## 14.21 CX::CX\_Logger Class Reference

```
#include <CX_Logger.h>
```

#### Public Member Functions

- std::stringstream & [log](#) (CX\_LogLevel level, std::string module="")
- std::stringstream & [verbose](#) (std::string module="")
- std::stringstream & [notice](#) (std::string module="")
- std::stringstream & [warning](#) (std::string module="")
- std::stringstream & [error](#) (std::string module="")
- std::stringstream & [fatalError](#) (std::string module="")
- void [level](#) (CX\_LogLevel level, std::string module="")
- void [levelForConsole](#) (CX\_LogLevel level)

- void [levelForFile](#) ([CX\\_LogLevel level](#), std::string filename="CX\_DEFERRED\_LOGGER\_DEFAULT")
- void [levelForAllModules](#) ([CX\\_LogLevel level](#))
- void [flush](#) (void)
- void [timestamps](#) (bool logTimestamps, std::string format="%H:%M:%S.%i")
- void [setMessageFlushCallback](#) (std::function< void([CX\\_MessageFlushData](#) &)> f)
- void [captureOFLogMessages](#) (void)

#### 14.21.1 Detailed Description

This class is used for logging messages throughout the [CX](#) backend code. It can also be used in user code to log messages. Rather than instantiating your own copy of [CX\\_Logger](#), it is probably better to use the preinstantiated [CX::Instances::Log](#).

There is an example showing a number of the features of [CX\\_Logger](#) named example-logging.

#### 14.21.2 Member Function Documentation

##### 14.21.2.1 void CX\_Logger::captureOFLogMessages ( void )

Set this instance of [CX\\_Logger](#) to be the target of any messages created by oF logging functions.

##### 14.21.2.2 std::stringstream & CX\_Logger::error ( std::string *module* = " " )

This function is equivalent to a call to `log(CX_LogLevel::LOG_ERROR, module)`.

##### 14.21.2.3 std::stringstream & CX\_Logger::fatalError ( std::string *module* = " " )

This function is equivalent to a call to `log(CX_LogLevel::LOG_FATAL_ERROR, module)`.

##### 14.21.2.4 void CX\_Logger::flush ( void )

Log all of the messages stored since the last call to [flush\(\)](#) to the selected logging targets. This is a BLOCKING operation.

##### 14.21.2.5 void CX\_Logger::level ( CX\_LogLevel *level*, std::string *module* = " " )

Sets the log level for the given module. Messages from that module that are at a lower level than [level](#) will be ignored.

##### Parameters

<i>level</i>	See the <a href="#">CX::CX_LogLevel</a> enum for valid values.
<i>module</i>	A string representing one of the modules from which log messages are generated.

##### 14.21.2.6 void CX\_Logger::levelForAllModules ( CX\_LogLevel *level* )

Set the log level for all modules. This works both retroactively and proactively: All currently known modules are given the log level and the default log level for new modules as set to the level.

##### 14.21.2.7 void CX\_Logger::levelForConsole ( CX\_LogLevel *level* )

Set the log level for messages to be printed to the console.



**14.21.2.8** `void CX_Logger::levelForFile ( CX_LogLevel level, std::string filename = "CX_DEFERRED_LOGGER_DEFAULT" )`

Sets the log level for the file with given file name. If the file does not exist, it will be created. If the file does exist, it will be overwritten with a warning logged to cerr.

## Parameters

<i>level</i>	See the CX_LogLevel enum for valid values.
<i>filename</i>	Optional. If no file name is given, a file with name generated from a date/time from the start time of the experiment will be used.

14.21.2.9 std::stringstream & CX\_Logger::log ( CX\_LogLevel *level*, std::string *module* = " " )

This is the basic logging function for this class. Example use:

```
Log.log(CX_LogLevel::LOG_WARNING, "myModule") << "My message number " << 20;
```

Possible output: "[warning] <myModule> My message number 20"

## Parameters

<i>level</i>	Log level for this message. This has implications for message filtering. See <a href="#">level()</a> . This should not be LOG_ALL or LOG_NONE, because that would be weird, wouldn't it?
<i>module</i>	Name of the module that this log message is related to. This has implications for message filtering. See <a href="#">level()</a> .

## Returns

A reference to a std::stringstream that the log message data should be streamed into.

14.21.2.10 std::stringstream & CX\_Logger::notice ( std::string *module* = " " )

This function is equivalent to a call to log(CX\_LogLevel::LOG\_NOTICE, module).

14.21.2.11 void CX\_Logger::setMessageFlushCallback ( std::function< void(CX\_MessageFlushData &)> *f* )

Sets the user function that will be called on each message flush event. For every message that has been logged, the user function will be called. No filtering is performed: All messages regardless of the module log level will be sent to the user function.

## Parameters

<i>f</i>	A pointer to a user function that takes a reference to a CX_MessageFlushData struct and returns nothing.
----------	--

14.21.2.12 void CX\_Logger::timestamps ( bool *logTimestamps*, std::string *format* = "%H:%M:%S.%i" )

Set whether or not to log timestamps and the format for the timestamps.

## Parameters

<i>logTimestamps</i>	Does what it says.
<i>format</i>	Timestamp format string. See <a href="http://pocoproject.org/docs/Poco.DateTime-Formatter.html#4684">http://pocoproject.org/docs/Poco.DateTime-Formatter.html#4684</a> for documentation of the format. Defaults to H:M:S.i (24-hour clock with milliseconds at the end).

14.21.2.13 std::stringstream & CX\_Logger::verbose ( std::string *module* = " " )

This function is equivalent to a call to log(CX\_LogLevel::LOG\_VERBOSE, module).

14.21.2.14 std::stringstream & CX\_Logger::warning ( std::string *module* = " " )

This function is equivalent to a call to log(CX\_LogLevel::LOG\_WARNING, module).

The documentation for this class was generated from the following files:

- CX\_Logger.h
- CX\_Logger.cpp

## 14.22 CX::CX\_Mouse Class Reference

```
#include <CX_Mouse.h>
```

### Classes

- struct [Event](#)

### Public Member Functions

- int [availableEvents](#) (void)
- [CX\\_Mouse::Event getNextEvent](#) (void)
- void [clearEvents](#) (void)
- void [showCursor](#) (bool show)
- void [setCursorPosition](#) (ofPoint pos)
- ofPoint [getCursorPosition](#) (void)

### Friends

- class **CX\_InputManager**

#### 14.22.1 Detailed Description

This class is responsible for managing the mouse.

#### 14.22.2 Member Function Documentation

##### 14.22.2.1 int CX\_Mouse::availableEvents ( void )

Get the number of new events available for this input device.

##### 14.22.2.2 void CX\_Mouse::clearEvents ( void )

Clear (delete) all events from this input device.

##### 14.22.2.3 ofPoint CX\_Mouse::getCursorPosition ( void )

Get the cursor position within the program window. If the mouse has left the window, this will return the last known position of the cursor within the window.

### Returns

An ofPoint with the last cursor position.

## 14.22.2.4 CX\_Mouse::Event CX\_Mouse::getNextEvent ( void )

Get the next event available for this input device. This is a destructive operation: the returned event is deleted from the input device.

## 14.22.2.5 void CX\_Mouse::setCursorPosition ( ofPoint pos )

Sets the position of the cursor, relative to the program the window. The window must be focused.

## Parameters

<i>pos</i>	The location within the window to set the cursor.
------------	---

## 14.22.2.6 void CX\_Mouse::showCursor ( bool show )

Show or hide the mouse cursor within the program window. If in windowed mode, the cursor will be visible outside of the window.

## Parameters

<i>show</i>	If true, the cursor will be shown, if false it will not be shown.
-------------	---

The documentation for this class was generated from the following files:

- CX\_Mouse.h
- CX\_Mouse.cpp

## 14.23 CX::CX\_RandomNumberGenerator Class Reference

```
#include <CX_RandomNumberGenerator.h>
```

## Public Member Functions

- [CX\\_RandomNumberGenerator](#) (void)
- void [setSeed](#) (unsigned long seed)
- unsigned long [getSeed](#) (void)
- CX\_RandomInt\_t [getMinimumRandomInt](#) (void)
- CX\_RandomInt\_t [getMaximumRandomInt](#) (void)
- CX\_RandomInt\_t [randomInt](#) (void)
- CX\_RandomInt\_t [randomInt](#) (CX\_RandomInt\_t rangeLower, CX\_RandomInt\_t rangeUpper)
- double [randomDouble](#) (double lowerBound\_closed, double upperBound\_open)
- template<typename stdDist >  
std::vector< typename  
stdDist::result\_type > [sampleRealizations](#) (unsigned int count, stdDist dist)
- std::vector< double > [sampleUniformRealizations](#) (unsigned int count, double lowerBound\_closed, double upperBound\_open)
- std::vector< unsigned int > [sampleBinomialRealizations](#) (unsigned int count, unsigned int trials, double prob-Success)
- std::vector< double > [sampleNormalRealizations](#) (unsigned int count, double mean, double standardDeviation)
- template<typename T >  
void [shuffleVector](#) (std::vector< T > \*v)
- template<typename T >  
std::vector< T > [shuffleVector](#) (std::vector< T > v)

- `template<typename T >`  
`T sample (std::vector< T > values)`
- `template<typename T >`  
`std::vector< T > sample (unsigned int count, const std::vector< T > &source, bool withReplacement)`
- `std::vector< int > sample (unsigned int count, int lowerBound, int upperBound, bool withReplacement)`
- `template<typename T >`  
`T randomExclusive (const std::vector< T > &values, const T &exclude)`
- `template<typename T >`  
`T randomExclusive (const std::vector< T > &values, const std::vector< T > &exclude)`
- `std::mt19937_64 & getGenerator (void)`

### 14.23.1 Detailed Description

This class is used for generating random values from a pseudo-random number generator. It uses a version of the Mersenne Twister algorithm, in particular `std::mt19937_64` (see [http://en.cppreference.com/w/cpp/numeric/random/mersenne\\_twister\\_engine](http://en.cppreference.com/w/cpp/numeric/random/mersenne_twister_engine) for the parameters used with this algorithm).

The monolithic structure of `CX_RandomNumberGenerator` provides a certain important feature that a collection of loose function does not have, which is the ability to trivially track the random seed being used for the random number generator. The function `CX_RandomNumberGenerator::setSeed()` sets the seed for all random number generation tasks performed by this class. Likewise, `CX_RandomNumberGenerator::getSeed()` allows you to easily find the seed that is being used for random number generation. Due to this structure, you can easily save the seed that was used for each participant, which allows you to repeat the exact randomizations used for that participant (unless random number generation varies as a function of the responses given by a participant).

An instance of this class is preinstantiated for you. See `CX::Instances::RNG` for information about the instance.

### 14.23.2 Constructor & Destructor Documentation

#### 14.23.2.1 `CX_RandomNumberGenerator::CX_RandomNumberGenerator ( void )`

Constructs an instance of a `CX_RandomNumberGenerator`. Seeds the `CX_RandomNumberGenerator` using a `std::random_device`.

By the C++11 specification, `std::random_device` is supposed to be a non-deterministic (hardware) RNG. However, from [http://en.cppreference.com/w/cpp/numeric/random/random\\_device](http://en.cppreference.com/w/cpp/numeric/random/random_device): "Note that `std::random_device` may be implemented in terms of a pseudo-random number engine if a non-deterministic source (e.g. a hardware device) is not available to the implementation." According to a Stack Overflow comment, Microsoft's implementation of `std::random_device` is based on a ton of stuff, which should result in a fairly random result to be used as a seed for our Mersenne Twister. See the comment: <http://stackoverflow.com/questions/9549357/the-implementation-of-random-device-in-vs2010/9575747#9575747> Although this data should have high entropy, it is not a hardware RNG. The `random_device` is only used to seed the Mersenne Twister, so as long as the initial value is random enough, it should be fine.

### 14.23.3 Member Function Documentation

#### 14.23.3.1 `std::mt19937_64 & CX_RandomNumberGenerator::getGenerator ( void )`

This function returns a reference to the PRNG used by the `CX_RandomNumberGenerator`. This can be used for various things, including sampling from some of the other distributions provided by the standard library: <http://en.cppreference.com/w/cpp/numeric/random>

```
std::poisson_distribution<int> pois(4);
int deviate = pois(RNG.getGenerator());
```

## 14.23.3.2 CX\_RandomInt\_t CX\_RandomNumberGenerator::getMaximumRandomInt ( void )

Get the maximum possible value that can be returned by [randomInt\(\)](#).

## Returns

The maximum value.

## 14.23.3.3 CX\_RandomInt\_t CX\_RandomNumberGenerator::getMinimumRandomInt ( void )

Get the minimum value that can be returned by [randomInt\(\)](#).

## Returns

The minimum value.

## 14.23.3.4 unsigned long CX\_RandomNumberGenerator::getSeed ( void )

Get the seed used to seed the random number generator.

## Returns

The seed. May have been set by the user with [setSeed\(\)](#) or during construction of the [CX\\_RandomNumberGenerator](#).

## 14.23.3.5 double CX\_RandomNumberGenerator::randomDouble ( double lowerBound\_closed, double upperBound\_open )

Samples a realization from a uniform distribution with the range [lowerBound\_closed, upperBound\_open).

## Parameters

<i>lowerBound_closed</i>	The lower bound of the distribution. This bound is closed, meaning that you can observe this value.
<i>upperBound_open</i>	The upper bound of the distribution. This bound is open, meaning that you cannot observe this value.

## Returns

The realization.

## 14.23.3.6 template&lt;typename T &gt; T CX::CX\_RandomNumberGenerator::randomExclusive ( const std::vector&lt; T &gt; &amp; values, const T &amp; exclude )

Get a random value from a vector, without the possibility of getting the excluded value.

## Parameters

<i>values</i>	The vectors of values to sample from.
<i>exclude</i>	The value to exclude from sampling.

## Returns

The sampled value.

## Note

If all of the values are excluded, an error will be logged and T() will be returned.

14.23.3.7 `template<typename T> T CX::CX_RandomNumberGenerator::randomExclusive ( const std::vector< T> & values,  
const std::vector< T> & exclude )`

Get a random value from a vector without the possibility of getting any of the excluded values.

## Parameters

<i>values</i>	The vector of values to sample from.
<i>exclude</i>	The vector of values to exclude from sampling.

## Returns

The sampled value.

## Note

If all of the values are excluded, an error will be logged and T() will be returned.

## 14.23.3.8 CX\_RandomInt\_t CX\_RandomNumberGenerator::randomInt ( void )

Get a random integer in the range [getMinimumRandomInt\(\)](#), [getMaximumRandomInt\(\)](#), inclusive.

## Returns

The int.

## 14.23.3.9 CX\_RandomInt\_t CX\_RandomNumberGenerator::randomInt ( CX\_RandomInt\_t min, CX\_RandomInt\_t max )

This function returns an integer from the range [rangeLower, rangeUpper]. The minimum and maximum values for the int returned from this function are given by [getMinimumRandomInt\(\)](#) and [getMaximumRandomInt\(\)](#).

If rangeLower > rangeUpper, the lower and upper ranges are swapped. If rangeLower == rangeUpper, it returns rangeLower.

## 14.23.3.10 template&lt;typename T&gt; T CX::CX\_RandomNumberGenerator::sample ( std::vector&lt; T &gt; values )

Returns a single value sampled randomly from values.

## Returns

The sampled value.

## Note

If values.size() == 0, an error will be logged and T() will be returned.

## 14.23.3.11 template&lt;typename T&gt; std::vector&lt; T &gt; CX::CX\_RandomNumberGenerator::sample ( unsigned int count, const std::vector&lt; T &gt; &amp; source, bool withReplacement )

Returns a vector of count values drawn randomly from source, with or without replacement. The returned values are in a random order.

## Parameters

<i>count</i>	The number of samples to draw.
--------------	--------------------------------



<i>source</i>	A vector to be sampled from.
<i>withReplacement</i>	Sample with or without replacement.

**Returns**

A vector of the sampled values.

**Note**

If (count > source.size() && withReplacement == false), an empty vector is returned.

**14.23.3.12** `std::vector< int > CX_RandomNumberGenerator::sample ( unsigned int count, int lowerBound, int upperBound, bool withReplacement )`

Returns a vector of count integers drawn randomly from the range [lowerBound, upperBound] with or without replacement.

**Parameters**

<i>count</i>	The number of samples to draw.
<i>lowerBound</i>	The lower bound of the range to sample from. It is possible to sample this value.
<i>upperBound</i>	The upper bound of the range to sample from. It is possible to sample this value.
<i>withReplacement</i>	Sample with or without replacement.

**Returns**

A vector of the samples.

**14.23.3.13** `std::vector< unsigned int > CX_RandomNumberGenerator::sampleBinomialRealizations ( unsigned int count, unsigned int trials, double probSuccess )`

Samples count realizations from a binomial distribution with the given number of trials and probability of success on each trial.

**Parameters**

<i>count</i>	The number of deviates to generate.
<i>trials</i>	The number of trials. Must be a non-negative integer.
<i>probSuccess</i>	The probability of a success on a given trial, where a success is the value 1.

**Returns**

A vector of the realizations.

**14.23.3.14** `std::vector< double > CX_RandomNumberGenerator::sampleNormalRealizations ( unsigned int count, double mean, double standardDeviation )`

Samples count realizations from a normal distribution with the given mean and standard deviation.

**Parameters**

<i>count</i>	The number of deviates to generate.
<i>mean</i>	The mean of the distribution.
<i>standard-Deviation</i>	The standard deviation of the distribution.

**Returns**

A vector of the realizations.

**14.23.3.15** `template<typename stdDist > std::vector< typename stdDist::result_type > CX::CX_RandomNumberGenerator::sampleRealizations ( unsigned int count, stdDist dist )`

Draws *count* samples from a distribution *dist* that is provided by the user.

**Parameters**

<i>count</i>	The number of samples to take.
<i>dist</i>	A configured instance of a distribution class that has operator()(Generator& g), where Generator is a random number generator that has operator() that returns a random value. Basically, just look at this page: <a href="http://en.cppreference.com/w/cpp/numeric/random">http://en.cppreference.com/w/cpp/numeric/random</a> and pick one of the random number distributions.

**Returns**

A vector of *stdDist::result\_type*, where *stdDist::result\_type* is the type of data that is returned by the distribution (e.g. int, double, etc.). You can usually set this when creating the distribution object.

```
//Take 100 samples from a poisson distribution with lamda (mean result value) of 4.2.
//stdDist::result_type is unsigned int in this example.
vector<unsigned int> rpois = RNG.sampleFrom(100, std::poisson_distribution<unsigned int>(4.2));
```

**14.23.3.16** `std::vector< double > CX_RandomNumberGenerator::sampleUniformRealizations ( unsigned int count, double lowerBound_closed, double upperBound_open )`

Samples *count* deviates from a uniform distribution with the range [*lowerBound\_closed*, *upperBound\_open*).

**Parameters**

<i>count</i>	The number of deviates to generate.
<i>lowerBound_closed</i>	The lower bound of the distribution. This bound is closed, meaning that you can observe deviates with this value.
<i>upperBound_open</i>	The upper bound of the distribution. This bound is open, meaning that you cannot observe deviates with this value.

**Returns**

A vector of the realizations.

**14.23.3.17** `void CX_RandomNumberGenerator::setSeed ( unsigned long seed )`

Set the seed for the random number generator. You can retrieve the seed with [getSeed\(\)](#).

## Parameters

<i>seed</i>	The new seed.
-------------	---------------

14.23.3.18 `template<typename T> void CX::CX_RandomNumberGenerator::shuffleVector ( std::vector< T> * v )`

Randomizes the order of the given vector.

## Parameters

<i>v</i>	A pointer to the vector to be shuffled.
----------	---

14.23.3.19 `template<typename T> std::vector< T> CX::CX_RandomNumberGenerator::shuffleVector ( std::vector< T> v )`

Makes a copy of the given vector, randomizes the order of its elements, and returns the shuffled copy.

## Parameters

<i>v</i>	The vector to be operated on.
----------	-------------------------------

## Returns

A shuffled copy of *v*.

The documentation for this class was generated from the following files:

- CX\_RandomNumberGenerator.h
- CX\_RandomNumberGenerator.cpp

## 14.24 CX::CX\_SlidePresenter Class Reference

```
#include <CX_SlidePresenter.h>
```

## Classes

- struct [Configuration](#)
- struct [FinalSlideFunctionArgs](#)
- struct [PresentationErrorInfo](#)
- struct [Slide](#)
- struct [SlideTimingInfo](#)

## Public Types

- enum [ErrorMode](#) { [ErrorMode::PROPAGATE\\_DELAYS](#), [ErrorMode::FIX\\_TIMING\\_FROM\\_FIRST\\_SLIDE](#) }

## Public Member Functions

- bool [setup](#) ([CX\\_Display](#) \*display)
- bool [setup](#) (const [CX\\_SlidePresenter::Configuration](#) &config)
- virtual void [update](#) (void)
- void [appendSlide](#) ([CX\\_SlidePresenter::Slide](#) slide)

- void **appendSlideFunction** (std::function< void(void)> drawingFunction, CX\_Millis slideDuration, std::string slideName="")
- void **beginDrawingNextSlide** (CX\_Millis slideDuration, std::string slideName="")
- void **endDrawingCurrentSlide** (void)
- bool **startSlidePresentation** (void)
- void **stopSlidePresentation** (void)  
*Stops slide presentation.*
- bool **isPresentingSlides** (void) const  
*Returns true if slide presentation is in progress, even if the first slide has not yet been presented.*
- void **clearSlides** (void)
- std::vector  
< CX\_SlidePresenter::Slide > & **getSlides** (void)
- std::vector< CX\_Millis > **getActualPresentationDurations** (void)
- std::vector< unsigned int > **getActualFrameCounts** (void)
- CX\_SlidePresenter::PresentationErrorInfo **checkForPresentationErrors** (void) const
- std::string **printLastPresentationInformation** (void) const

#### Protected Member Functions

- unsigned int **\_calculateFrameCount** (CX\_Millis duration)
- void **\_singleCoreBlockingUpdate** (void)
- void **\_singleCoreThreadedUpdate** (void)
- void **\_multiCoreUpdate** (void)
- void **\_renderCurrentSlide** (void)
- void **\_waitSyncCheck** (void)
- void **\_finishPreviousSlide** (void)
- void **\_handleFinalSlide** (void)
- void **\_prepareNextSlide** (void)

#### Protected Attributes

- CX\_SlidePresenter::Configuration **\_config**
- CX\_Millis **\_hoggingStartTime**
- bool **\_presentingSlides**
- bool **\_synchronizing**
- unsigned int **\_currentSlide**
- std::vector  
< CX\_SlidePresenter::Slide > **\_slides**
- bool **\_lastFramebufferActive**
- bool **\_useFenceSync**
- bool **\_awaitingFenceSync**
- GLsync **\_fenceSyncObject**

### 14.24.1 Detailed Description

This class is a very useful abstraction that presents slides (typically a full display) of visual stimuli for fixed durations. See the [basicChangeDetectionTask.cpp](#), [advancedChangeDetectionTask.cpp](#), and [nBack.cpp](#) examples for the usage of this class.

A brief example:

```
CX_SlidePresenter slidePresenter;
slidePresenter.setup(&Display);

slidePresenter.beginDrawingNextSlide(2000 * 1000, "circle");
ofBackground(50);
ofSetColor(ofColor::red);
ofCircle(Display.getCenterOfDisplay(), 40);

slidePresenter.beginDrawingNextSlide(1000 * 1000, "rectangle");
ofBackground(50);
ofSetColor(ofColor::green);
ofRect(Display.getCenterOfDisplay() - ofPoint(100, 100), 200, 200);

slidePresenter.beginDrawingNextSlide(1, "off");
ofBackground(50);
slidePresenter.endDrawingCurrentSlide();

slidePresenter.startSlidePresentation();

//Update the slide presenter while waiting for slide presentation to complete
while (slidePresenter.isPresentingSlides()) {
    slidePresenter.update(); //You must remember to call update() regularly while slides are being
    presented!
}
```

### 14.24.2 Member Enumeration Documentation

#### 14.24.2.1 enum CX::CX\_SlidePresenter::ErrorMode [strong]

The settings in this enum are related to what a [CX\\_SlidePresenter](#) does when it encounters a timing error. Timing errors are probably almost exclusively related to one slide being presented for too long.

The PROPAGATE\_DELAYS setting causes the slide presenter to handle these errors by moving the start time of all future stimuli back by the number of extra frame that the erroneous slide used. This makes the durations of all future stimuli correct, so that there is only an error in the duration of one slide.

An alternative option is to try to keep the onsets of all slides as constant as possible relative to each other. This means that if one slide is presented for an extra frame, the next slide will be presented for one frame less than it should have been. If one slide is presented for several extra frames (this should almost never happen), the next slide may be skipped altogether. However, this mode (FIX\_TIMING\_FROM\_FIRST\_SLIDE) does not completely work currently so it should not be used.

#### Enumerator

**PROPAGATE\_DELAYS** This mode handles timing errors by changing the onset times of future stimuli so.

**FIX\_TIMING\_FROM\_FIRST\_SLIDE** This does not work currently.

### 14.24.3 Member Function Documentation

#### 14.24.3.1 void CX\_SlidePresenter::appendSlide ( CX\_SlidePresenter::Slide slide )

Add a fully configured slide to the end of the list of slides. The user code must configure several components of the slide:

- If the framebuffer will be used, the framebuffer must be allocated and drawn to.

- If the drawing function will be used, a valid function pointer must be given. A check is made that either the drawing function is set or the framebuffer is allocated and an error is logged if neither is configured.
- The intended duration must be set.
- The name may be set (optional).

**Parameters**

<i>slide</i>	The slide to append.
--------------	----------------------

**14.24.3.2** void CX\_SlidePresenter::appendSlideFunction ( std::function< void(void)> *drawingFunction*, CX\_Millis *slideDuration*, std::string *slideName* = " " )

Appends a slide to the slide presenter that will call the given drawing function when it comes time to render the slide to the back buffer. Essentially, the drawing function will be called one frame before the front and back buffers are swapped.

**Parameters**

<i>drawingFunction</i>	A pointer to a function that will draw the data to the slide. The contents of the back buffer are not clear before this function is called, so the function must clear the background to the desired color.
<i>slideDuration</i>	The amount of time to present the slide for. If this is less than or equal to 0, the slide will be ignored.
<i>slideName</i>	The name of the slide. This can be anything and is purely for the user to use to help identify the slide.

**14.24.3.3** void CX\_SlidePresenter::beginDrawingNextSlide ( CX\_Millis *slideDuration*, std::string *slideName* = " " )

Prepares the framebuffer of the next slide for drawing so that any drawing commands given between a call to [beginDrawingNextSlide\(\)](#) and [endDrawingCurrentSlide\(\)](#) will cause stimuli to be drawn to the framebuffer of the slide.

**Parameters**

<i>slideDuration</i>	The amount of time to present the slide for. If this is less than or equal to 0, the slide will be ignored.
<i>slideName</i>	The name of the slide. This can be anything and is purely for the user to use to help identify the slide.

**14.24.3.4** CX\_SlidePresenter::PresentationErrorInfo CX\_SlidePresenter::checkForPresentationErrors ( void ) const

Checks the timing data from the last presentation of slides for presentation errors. Currently it checks to see if the intended frame count matches the actual frame count of each slide, which indicates if the duration was correct. It also checks to make sure that the framebuffer was copied to the back buffer before the onset of the slide. If not, vertical tearing might have occurred when the back buffer, containing a partially copied slide, was swapped in.

**Returns**

A struct with information about the errors that occurred on the last presentation of slides.

**Note**

If [clearSlides\(\)](#) has been called since the end of the presentation, this does nothing as its data has been cleared. If this function is called during slide presentation, the returned struct will have the `presentationErrorsSuccessfullyChecked` member set to false and an error will be logged.

#### 14.24.3.5 void CX\_SlidePresenter::clearSlides ( void )

Clears (deletes) all of the slides contained in the slide presenter and stops presentation, if it was in progress.

#### 14.24.3.6 void CX\_SlidePresenter::endDrawingCurrentSlide ( void )

Ends drawing to the framebuffer of the slide that is currently being drawn to. See [beginDrawingNextSlide\(\)](#).

#### 14.24.3.7 std::vector< unsigned int > CX\_SlidePresenter::getActualFrameCounts ( void )

Gets a vector containing the number of frames that each of the slides from the last presentation of slides was presented for. Note that these frame counts may be wrong. If [checkForPresentationErrors\(\)](#) not detect any errors, the frame counts are likely to be right, but there is no guarantee.

##### Returns

A vector containing the frame counts. The frame count corresponding to the first slide added to the slide presenter will be at index 0.

##### Note

The frame count of the last slide is meaningless. As far as the slide presenter is concerned, as soon as the last slide is put on the screen, it is done presenting the slides. Because the slide presenter is not responsible for removing the last slide from the screen, it has no idea about the duration of that slide.

#### 14.24.3.8 std::vector< CX\_Millis > CX\_SlidePresenter::getActualPresentationDurations ( void )

Gets a vector containing the durations of the slides from the last presentation of slides. Note that these durations may be wrong. If [checkForPresentationErrors\(\)](#) does not detect any errors, the durations are likely to be right, but there is no guarantee.

##### Returns

A vector containing the durations. The duration corresponding to the first slide added to the slide presenter will be at index 0.

##### Note

The duration of the last slide is meaningless. As far as the slide presenter is concerned, as soon as the last slide is put on the screen, it is done presenting the slides. Because the slide presenter is not responsible for removing the last slide from the screen, it has no idea about the duration of that slide.

#### 14.24.3.9 std::vector< CX\_SlidePresenter::Slide > & CX\_SlidePresenter::getSlides ( void )

Get a reference to the vector of slides held by the slide presenter. If you modify any of the members of any of the slides, you do so at your own risk. This data is mostly useful in a read-only sort of way (when was that slide presented?).

##### Returns

A reference to the vector of slides.

#### 14.24.3.10 bool CX\_SlidePresenter::setup ( CX\_Display \* display )

Set up the slide presenter with the given [CX\\_Display](#) as the display.

## Parameters

<i>display</i>	Pointer to the display to use.
----------------	--------------------------------

## Returns

False if there was an error during setup, in which case a message will be logged.

## 14.24.3.11 bool CX\_SlidePresenter::setup ( const CX\_SlidePresenter::Configuration &amp; config )

Set up the slide presenter using the given configuration.

## Parameters

<i>config</i>	The configuration to use.
---------------	---------------------------

## Returns

False if there was an error during setup, in which case a message will be logged.

## 14.24.3.12 bool CX\_SlidePresenter::startSlidePresentation ( void )

Start presenting the slides that are stored in the slide presenter. After this function is called, calls to [update\(\)](#) will advance the state of the slide presentation.

## Returns

False if an error was encountered while starting presentation, in which case messages will be logged, true otherwise.

## 14.24.3.13 void CX\_SlidePresenter::update ( void ) [virtual]

Updates the state of the slide presenter. If the slide presenter is presenting stimuli, [update\(\)](#) must be called very regularly (at least once per millisecond) in order for the slide presenter to function.

The documentation for this class was generated from the following files:

- CX\_SlidePresenter.h
- CX\_SlidePresenter.cpp

## 14.25 CX::CX\_SoundObject Class Reference

```
#include <CX_SoundObject.h>
```

## Public Member Functions

- bool [loadFile](#) (std::string fileName)
- bool [addSound](#) (std::string fileName, [CX\\_Millis](#) timeOffset)
- bool [addSound](#) ([CX\\_SoundObject](#) so, [CX\\_Millis](#) timeOffset)
- bool [setFromVector](#) (const std::vector< float > &data, int channels, float sampleRate)
- void [clear](#) (void)
- bool [isReadyToPlay](#) (void)
- bool [isLoadedSuccessfully](#) (void)



- bool [applyGain](#) (float gain, int channel=-1)
- bool [multiplyAmplitudeBy](#) (float amount, int channel=-1)
- void [normalize](#) (float amount=1.0)
- float [getPositivePeak](#) (void)
- float [getNegativePeak](#) (void)
- void [setLength](#) (CX\_Millis length)
- CX\_Millis [getLength](#) (void)
- void [stripLeadingSilence](#) (float tolerance)
- void [addSilence](#) (CX\_Millis duration, bool atBeginning)
- void [deleteAmount](#) (CX\_Millis duration, bool fromBeginning)
- void [reverse](#) (void)
- void [multiplySpeed](#) (float speedMultiplier)
- void [resample](#) (float newSampleRate)
- float [getSampleRate](#) (void)
- *Returns the sample rate of the sound data stored in this [CX\\_SoundObject](#).*
- bool [setChannelCount](#) (int channels)
- int [getChannelCount](#) (void)

*Returns the number of channels in the sound data stored in this [CX\\_SoundObject](#).*

- uint64\_t [getTotalSampleCount](#) (void)
- uint64\_t [getSampleFrameCount](#) (void)
- std::vector< float > & [getRawDataReference](#) (void)
- bool [writeToFile](#) (std::string path)

#### Public Attributes

- std::string [name](#)

*This stores the name of the file from which data was read, if any. It can be set by the user with no side effects.*

#### 14.25.1 Detailed Description

This class is a container for a sound. It can load sound files, manipulate the contents of the sound data, add other sounds to an existing sound at specified offsets.

In order to play a [CX\\_SoundObject](#), you use a [CX::CX\\_SoundObjectPlayer](#).

See the [soundObject](#) example for an introduction on how to use this class along with a [CX\\_SoundObjectPlayer](#).

#### Note

Nearly all functions of this class should be considered [Blocking Code](#). Many of the operations take quite a while to complete because they are performed on a potentially large vector of sound samples.

#### 14.25.2 Member Function Documentation

##### 14.25.2.1 void CX\_SoundObject::addSilence ( CX\_Millis duration, bool atBeginning )

Adds the specified amount of silence to the [CX\\_SoundObject](#) at either the beginning or end.

## Parameters

<i>duration</i>	Duration of added silence in microseconds. Dependent on the sample rate of the sound. If the sample rate changes, so does the duration of silence.
<i>atBeginning</i>	If true, silence is added at the beginning of the <a href="#">CX_SoundObject</a> . If false, the silence is added at the end.

## 14.25.2.2 bool CX\_SoundObject::addSound ( CX\_SoundObject nso, CX\_Millis timeOffset )

Adds the sound data in `nso` at the time offset. If the sample rates of the sounds differ, `nso` will be resampled to the sample rate of this [CX\\_SoundObject](#). If the number of channels of `nso` does not equal the number of channels of this, an attempt will be made to set the number of channels of `nso` equal to the number of channels of this [CX\\_SoundObject](#). The data from `nso` and this [CX\\_SoundObject](#) are merged by adding the amplitudes of the sounds. The result of the addition is clamped between -1 and 1.

## Parameters

<i>nso</i>	A sound object. Must be successfully loaded.
<i>timeOffset</i>	Time at which to add the new sound data in microseconds. Dependent on sample rate.

## Returns

True if `nso` was successfully added to this [CX\\_SoundObject](#), false otherwise.

## 14.25.2.3 bool CX\_SoundObject::applyGain ( float decibels, int channel = -1 )

Apply gain to the channel in terms of decibels.

## Parameters

<i>decibels</i>	Gain to apply. 0 does nothing. Positive values increase volume, negative values decrease volume. Negative infinity is essentially mute, although see <a href="#">multiplyAmplitudeBy()</a> for a more obvious way to do that same operation.
<i>channel</i>	The channel that the gain should be applied to. If channel is less than 0, the gain is applied to all channels.

## 14.25.2.4 void CX\_SoundObject::clear ( void )

Clears all data stored in the sound object and returns it to an uninitialized state.

## 14.25.2.5 void CX\_SoundObject::deleteAmount ( CX\_Millis duration, bool fromBeginning )

Deletes the specified amount of sound from the [CX\\_SoundObject](#) from either the beginning or end.

## Parameters

<i>duration</i>	Duration of removed sound in microseconds. If this is greater than the duration of the sound, the whole sound is deleted.
<i>fromBeginning</i>	If true, sound is deleted from the beginning of the <a href="#">CX_SoundObject</a> 's buffer. If false, the sound is deleted from the end, toward the beginning.

## 14.25.2.6 CX\_Millis CX\_SoundObject::getLength ( void )

Gets the length, in time, of the sound object.

**Returns**

The length.

**14.25.2.7 float CX\_SoundObject::getNegativePeak ( void )**

Finds the minimum amplitude in the sound object.

**Returns**

The minimum amplitude.

**Note**

Amplitudes are between -1 and 1, inclusive.

**14.25.2.8 float CX\_SoundObject::getPositivePeak ( void )**

Finds the maximum amplitude in the sound object.

**Returns**

The maximum amplitude.

**Note**

Amplitudes are between -1 and 1, inclusive.

**14.25.2.9 std::vector<float>& CX::CX\_SoundObject::getRawDataReference ( void ) [inline]**

This function returns a reference to the raw data underlying the sound object.

**Returns**

A reference to the data. Modify at your own risk!

**14.25.2.10 uint64\_t CX::CX\_SoundObject::getSampleFrameCount ( void ) [inline]**

This function returns the number of sample frames in the sound data held by the [CX\\_SoundObject](#), which is equal to the total number of samples divided by the number of channels.

**14.25.2.11 uint64\_t CX::CX\_SoundObject::getTotalSampleCount ( void ) [inline]**

This function returns the total number of samples in the sound data held by the [CX\\_SoundObject](#), which is equal to the number of sample frames times the number of channels.

**14.25.2.12 bool CX::CX\_SoundObject::isLoadedSuccessfully ( void ) [inline]**

Checks to see if sound data has been successfully loaded into this [CX\\_SoundObject](#) from a file.

**14.25.2.13 bool CX\_SoundObject::isReadyToPlay ( void )**

Checks to see if the [CX\\_SoundObject](#) is ready to play. It basically just checks if there is sound data available and that the number of channels is set to a sane value.

#### 14.25.2.14 bool CX\_SoundObject::loadFile ( std::string *fileName* )

Loads a sound file with the given file name into the [CX\\_SoundObject](#). Any pre-existing data in the sound object is deleted. Some sound file types are supported. Others are not. In the limited testing, mp3 and wav files seem to work well. If the file cannot be loaded, descriptive error messages will be logged.

## Parameters

<i>fileName</i>	Name of the sound file to load.
-----------------	---------------------------------

## Returns

True if the sound given in the *fileName* was loaded successfully, false otherwise.

#### 14.25.2.15 bool CX\_SoundObject::multiplyAmplitudeBy ( float *amount*, int *channel* = -1 )

Apply gain to the sound. The original value is simply multiplied by the amount and then clamped to be within [-1, 1].

## Parameters

<i>amount</i>	The gain that should be applied. A value of 0 mutes the channel. 1 does nothing. 2 doubles the amplitude. -1 inverts the waveform.
<i>channel</i>	The channel that the given multiplier should be applied to. If channel is less than 0, the amplitude multiplier is applied to all channels.

#### 14.25.2.16 void CX\_SoundObject::multiplySpeed ( float *speedMultiplier* )

This function changes the speed of the sound by some multiple.

## Parameters

<i>speedMultiplier</i>	Amount to multiply the speed by. Must be greater than 0.
------------------------	--

## Note

If you would like to use a negative value to reverse the direction of playback, see [reverse\(\)](#).

#### 14.25.2.17 void CX\_SoundObject::normalize ( float *amount* = 1.0 )

Normalizes the contents of the sound object.

## Parameters

<i>amount</i>	Must be in the interval [0,1]. If 1, normalize will normalize in the standard way: The peak with the greatest magnitude will be set to +/-1 and everything else will be scaled relative to the peak. If amount is less than 1, the greatest peak will be set to that value.
---------------	---

#### 14.25.2.18 void CX\_SoundObject::resample ( float *newSampleRate* )

Resamples the audio data stored in the [CX\\_SoundObject](#) by linear interpolation. Linear interpolation is not the ideal way to resample audio data; some audio fidelity is lost, more so than with other resampling techniques. It is, however, very fast compared to higher-quality methods both in terms of run time and programming time. It has acceptable results, at least when the new sample rate is similar to the old sample rate.

## Parameters

<i>newSampleRate</i>	The requested sample rate.
----------------------	----------------------------

#### 14.25.2.19 void CX\_SoundObject::reverse ( void )

This function reverses the sound data stored in the [CX\\_SoundObject](#) so that if it is played, it will play in reverse.

**14.25.2.20** `bool CX_SoundObject::setChannelCount ( int newChannelCount )`

Sets the number of channels of the sound. Depending on the old number of channels (N) and the new number of channels (M), the conversion is performed in different ways. If N == M, nothing happens. If N == 1, each of the M new channels is set equal to the value of the single old channel. If M == 1, the new channel is set equal to the arithmetic average of the N old channels. If (N != 1 && M != 1 && M > N), the first N channels are preserved unchanged and the M - N new channels are set to the arithmetic average of the N old channels. Any other combination of M and N is an error condition.

**Parameters**

<i>newChannelCount</i>	The number of channels the <a href="#">CX_SoundObject</a> will have after the conversion.
------------------------	---

**Returns**

True if the conversion was successful, false if the attempted conversion is unsupported.

**14.25.2.21** `bool CX_SoundObject::setFromVector ( const std::vector< float > & data, int channels, float sampleRate )`

Set the contents of the sound object from a vector of float data.

**Parameters**

<i>data</i>	A vector of sound samples. These values should go from -1 to 1. This requirement is not checked for. If there is more than once channel of data, the data must be interleaved. This means that if, for example, there are two channels, the ordering of the samples is 12121212... where 1 represents a sample for channel 1 and 2 represents a sample for channel 2. This requirement is not checked for. The number of samples in this vector must be evenly divisible by the number of channels set with the <code>channels</code> argument.
<i>channels</i>	The number of channels worth of data that is stored in <code>data</code> .
<i>sampleRate</i>	The sample rate of the samples. If <code>data</code> contains, for example, a sine wave, that wave was sampled at some rate (e.g. 48000 samples per second of waveform). <code>sampleRate</code> should be that rate. return True in all cases. No checking is done on any of the arguments.

**14.25.2.22** `void CX_SoundObject::setLength ( CX_Millis length )`

Set the length of the sound to the specified length in microseconds. If the new length is longer than the old length, the new data is zeroed (i.e. set to silence).

**14.25.2.23** `void CX_SoundObject::stripLeadingSilence ( float tolerance )`

Removes leading "silence" from the sound, where silence is defined by the given tolerance. It is unlikely that the beginning of a sound, even if perceived as silent relative to the rest of the sound, has an amplitude of 0. Therefore, a tolerance of 0 is unlikely to prove useful. Using [getPositivePeak\(\)](#) and/or [getNegativePeak\(\)](#) can help to give a reference amplitude of which some small fraction is perceived as "silent".

**Parameters**

<i>tolerance</i>	All sound data up to and including the first instance of a sample with an amplitude with an absolute value greater than or equal to tolerance is removed from the sound.
------------------	--

**14.25.2.24** `bool CX_SoundObject::writeToFile ( std::string filename )`

Writes the contents of the sound object to a file with the given file name. The data will be encoded as 16-bit PCM. The sample rate is determined by the sample rate of the sound object.

**Parameters**

<i>filename</i>	The name of the file to save the sound data to. <i>filename</i> should have a .wav extension. If it does not, ".wav" will be appended to the file name and a warning will be logged.
-----------------	--

**Returns**

False if there was an error while opening the file. If so, an error will be logged.

The documentation for this class was generated from the following files:

- CX\_SoundObject.h
- CX\_SoundObject.cpp

**14.26 CX::CX\_SoundObjectPlayer Class Reference**

```
#include <CX_SoundObjectPlayer.h>
```

**Public Member Functions**

- bool [setup](#) (CX\_SoundObjectPlayerConfiguration\_t config)
- bool [play](#) (void)
- bool [startPlayingAt](#) (CX\_Millis experimentTime, CX\_Millis offset)
- bool [stop](#) (void)
- bool [isPlaying](#) (void)  
*Check if the sound is currently playing.*
- bool [isQueuedToStart](#) (void)  
*Check if the sound is queued to play.*
- CX\_SoundObjectPlayerConfiguration\_t [getConfiguration](#) (void)  
*Returns the configuration used for this CX\_SoundObjectPlayer.*
- bool [BLOCKING\\_setSound](#) (CX\_SoundObject \*sound)
- void [setTime](#) (CX\_Millis time)

**14.26.1 Detailed Description**

This class is used for playing CX\_SoundObjects. See the soundObject example for an example of how to use this class.

**14.26.2 Member Function Documentation****14.26.2.1 bool CX\_SoundObjectPlayer::BLOCKING\_setSound ( CX\_SoundObject \* sound )**

This function is blocking because the sample rate and number of channels of sound are changed to those of the currently open stream.

**Parameters**

<i>sound</i>	A pointer to a <a href="#">CX_SoundObject</a> that will be set as the current sound for the <a href="#">CX_SoundObjectPlayer</a> . There are a variety of reasons why the sound could fail to be set as the current sound for the player. If sound was not loaded successfully, this function call fails and an error is logged. If it is not possible to convert the number of channels of sound to the number of channels that the <a href="#">CX_SoundObjectPlayer</a> is configured to use, this function call fails and an error is logged.
--------------	--

This function call is not blocking if the same rate and channel count of the [CX\\_SoundObject](#) are the same as those in use by the [CX\\_SoundObjectPlayer](#). See [Blocking Code](#) for more information.

#### Returns

True if sound was successfully set to be the current sound, false otherwise.

#### 14.26.2.2 bool CX\_SoundObjectPlayer::play ( void )

Attempts to start playing the current [CX\\_SoundObject](#) associated with the player.

#### Returns

True if the sound object associated with the player isReadyToPlay(), false otherwise.

#### 14.26.2.3 void CX\_SoundObjectPlayer::setTime ( CX\_Millis time )

Set the current time in the active sound. When playback starts, it will begin from that time in the sound. If the sound object is currently playing, this will jump to that point in the sound.

#### Parameters

<i>time</i>	The time in the sound to seek to.
-------------	-----------------------------------

#### 14.26.2.4 bool CX\_SoundObjectPlayer::setup ( CX\_SoundObjectPlayerConfiguration\_t config )

Configures the [CX\\_SoundObjectPlayer](#) with the given configuration.

#### 14.26.2.5 bool CX\_SoundObjectPlayer::startPlayingAt ( CX\_Millis experimentTime, CX\_Millis latencyOffset )

Queue the start time of the sound in experiment time with an offset to account for latency.

#### Parameters

<i>experimentTime</i>	The desired experiment time at which the sound should start playing. This time plus the offset should be in the future. If it is not, the sound will start playing immediately.
<i>latencyOffset</i>	An offset that accounts for latency. If, for example, you called this function with an offset of 0 and discovered that the sound played 200 ms later than you were expecting it to, you would set offset to -200 in order to queue the start time 200 ms earlier than the desired experiment time.

#### Returns

False if the start time plus the offset is in the past. True otherwise.

#### Note

See [setTime\(\)](#) for a way to choose the current time point within the sound.



#### 14.26.2.6 bool CX\_SoundObjectPlayer::stop ( void )

Stop the currently playing sound object, or, if a playback start was cued, cancel the cued playback.

#### Returns

Always returns true currently.

The documentation for this class was generated from the following files:

- CX\_SoundObjectPlayer.h
- CX\_SoundObjectPlayer.cpp

### 14.27 CX::CX\_SoundObjectRecorder Class Reference

```
#include <CX_SoundObjectRecorder.h>
```

#### Public Types

- typedef  
[CX\\_SoundStream::Configuration](#) Configuration  
*This is typedef'ed to [CX::CX\\_SoundStream::Configuration](#).*

#### Public Member Functions

- bool [setup](#) ([CX\\_SoundObjectRecorder::Configuration](#) &config)
- void [setSoundObject](#) ([CX\\_SoundObject](#) \*so)
- [CX\\_SoundObject](#) \* [getSoundObject](#) (void)
- void [startRecording](#) (bool clearExistingData=false)
- void [stopRecording](#) (void)

#### 14.27.1 Detailed Description

This class is used for recording audio data from, e.g., a microphone. The recorded data is stored in a [CX\\_SoundObject](#) for further use.

```
CX_SoundObjectRecorder recorder;

CX_SoundObjectRecorder::Configuration recorderConfig;
recorderConfig.inputChannels = 1; //You will probably need to configure more than just this
recorder.setup(recorderConfig);

CX_SoundObject recording;
recorder.setSoundObject(&recording); //Associate a CX_SoundObject with the recorder so that it can be
    recorded to.

//Record for 5 seconds
recorder.startRecording();
ofSleepMillis(5000);
recorder.stopRecording();

//Write the recording to a file
recording.writeToFile("recording.wav");
```

## 14.27.2 Member Function Documentation

## 14.27.2.1 CX\_SoundObject \* CX\_SoundObjectRecorder::getSoundObject ( void )

This function returns a pointer to the [CX\\_SoundObject](#) that is currently associated with this [CX\\_SoundObjectRecorder](#).

## 14.27.2.2 void CX\_SoundObjectRecorder::setSoundObject ( CX\_SoundObject \* so )

This function associates a [CX\\_SoundObject](#) with the [CX\\_SoundObjectRecorder](#). The [CX\\_SoundObject](#) will be recorded to when [startRecording\(\)](#) is called.

## Parameters

<i>so</i>	The <a href="#">CX_SoundObject</a> to associate with the <a href="#">CX_SoundObjectRecorder</a> . The sound object will be cleared and it will be configured to have the same number of channels and sample rate that the <a href="#">CX_SoundObjectRecorder</a> was configured to use.
-----------	---

## 14.27.2.3 bool CX\_SoundObjectRecorder::setup ( CX\_SoundObjectRecorder::Configuration &amp; config )

This function sets up the [CX\\_SoundStream](#) that [CX\\_SoundObjectRecorder](#) uses to record audio data.

## Returns

True if configuration of the [CX\\_SoundStream](#) was successful, false otherwise.

## 14.27.2.4 void CX\_SoundObjectRecorder::startRecording ( bool clearExistingData = false )

Begins recording data to the [CX\\_SoundObject](#) that was associated with this [CX\\_SoundObjectRecorder](#) with [setSoundObject\(\)](#).

## Parameters

<i>clearExistingData</i>	If true, any data in the <a href="#">CX_SoundObject</a> will be deleted before recording starts.
--------------------------	--

## 14.27.2.5 void CX\_SoundObjectRecorder::stopRecording ( void )

Stop recording sound data.

The documentation for this class was generated from the following files:

- [CX\\_SoundObjectRecorder.h](#)
- [CX\\_SoundObjectRecorder.cpp](#)

## 14.28 CX::CX\_SoundStream Class Reference

```
#include <CX_SoundStream.h>
```

## Classes

- struct [Configuration](#)
- struct [InputEventArgs](#)
- struct [OutputEventArgs](#)

### Public Member Functions

- bool [setup](#) ([CX\\_SoundStream::Configuration](#) &config)
- bool [closeStream](#) (void)
- bool [start](#) (void)
- bool [stop](#) (void)
- const  
    [CX\\_SoundStream::Configuration](#) & [getConfiguration](#) (void)
- uint64\_t [getSampleFrameNumber](#) (void)
- [CX\\_Millis](#) [getStreamLatency](#) (void)
- bool [hasSwappedSinceLastCheck](#) (void)
- [CX\\_Millis](#) [getLastSwapTime](#) (void)
- [CX\\_Millis](#) [estimateNextSwapTime](#) (void)
- [RtAudio](#) \* [getRtAudioInstance](#) (void)

### Static Public Member Functions

- static std::vector< [RtAudio::Api](#) > [getCompiledApis](#) (void)
- static std::vector< std::string > [convertApisToStrings](#) (vector< [RtAudio::Api](#) > apis)
- static std::string [convertApisToString](#) (vector< [RtAudio::Api](#) > apis, std::string delim="\r\n")
- static std::string [convertApiToString](#) ([RtAudio::Api](#) api)
- static std::vector< std::string > [formatsToStrings](#) ([RtAudioFormat](#) formats)
- static std::string [formatsToString](#) ([RtAudioFormat](#) formats, std::string delim="\r\n")
- static std::vector  
    < [RtAudio::DeviceInfo](#) > [getDeviceList](#) ([RtAudio::Api](#) api)
- static std::string [listDevices](#) ([RtAudio::Api](#) api)

### Public Attributes

- ofEvent  
    < [CX\\_SoundStream::OutputEventArgs](#) > [outputEvent](#)  
    *This event is triggered every time the [CX\\_SoundStream](#) needs to feed more data to the output buffer of the sound card.*
- ofEvent  
    < [CX\\_SoundStream::InputEventArgs](#) > [inputEvent](#)  
    *This event is triggered every time the [CX\\_SoundStream](#) has gotten some data from the input buffer of the sound card.*

#### 14.28.1 Detailed Description

This class provides a method for directly accessing and manipulating sound data that is sent/received from sound hardware. To use this class, you should set up the stream (see [setup\(\)](#)), set a user function that will be called when either the [outputEvent](#) or [inputEvent](#) is triggered, and start the stream with [start\(\)](#).

If the stream is configured for output, the output event will be triggered whenever the sound card needs more sound data. If the stream is configured for input, the input event will be triggered whenever some amount of sound data has been recorded.

[CX\\_SoundStream](#) uses [RtAudio](#) internally, so you are having problems, you might be able to figure out what is going wrong by checking out the page for [RtAudio](#): <http://www.music.mcgill.ca/~gary/rtaudio/index.-html>

## 14.28.2 Member Function Documentation

## 14.28.2.1 bool CX\_SoundStream::closeStream ( void )

Closes the sound stream.

## Returns

False if an error was encountered while closing the stream, true otherwise.

 14.28.2.2 std::string CX\_SoundStream::convertApisToString ( vector< RtAudio::Api > *apis*, std::string *delim* = "\r\n" )  
 [static]

This helper function converts a vector of RtAudio::Api to a string, with the specified delimiter between API names.

## Parameters

<i>apis</i>	The vector of RtAudio::Api to convert to string.
<i>delim</i>	The delimiter between elements of the string.

## Returns

A string containing the names of the APIs.

 14.28.2.3 std::vector< std::string > CX\_SoundStream::convertApisToStrings ( vector< RtAudio::Api > *apis* ) [static]

This helper function converts a vector of RtAudio::Api to a vector of strings, using [convertApiToString\(\)](#) for the conversion.

## Parameters

<i>apis</i>	A vector of apis to convert to strings.
-------------	---

## Returns

A vector of string names of the apis.

 14.28.2.4 std::string CX\_SoundStream::convertApiToString ( RtAudio::Api *api* ) [static]

This helper function converts an RtAudio::Api to a string.

## Parameters

<i>api</i>	The api to get a string of.
------------	-----------------------------

## Returns

A string of the api name.

## 14.28.2.5 CX\_Millis CX\_SoundStream::estimateNextSwapTime ( void )

Estimate the time at which the next buffer swap will occur.

## Returns

The estimated time of next swap. This value can be compared with the result of CX::Instances::Clock.now().

**14.28.2.6** `std::vector< RtAudio::Api > CX_SoundStream::getCompiledApis ( void ) [static]`

Get a vector containing a list of all of the APIs for which the RtAudio driver has been compiled to use. If the API you want is not available, you might be able to get it by using a different version of RtAudio.

**14.28.2.7** `const CX_SoundStream::Configuration& CX::CX_SoundStream::getConfiguration ( void ) [inline]`

Gets the configuration that was used on the last call to open(). Because some of the configuration options are only suggestions, this function allows you to check what the actual configuration was.

#### Returns

A const reference to the configuration struct.

**14.28.2.8** `std::vector< RtAudio::DeviceInfo > CX_SoundStream::getDeviceList ( RtAudio::Api api ) [static]`

For the given api, lists all of the devices on the system that support that api.

#### Parameters

<i>api</i>	Devices that support this API are scanned.
------------	--

#### Returns

A machine-readable list of information. See [http://www.music.mcgill.ca/~gary/rtaudio/struct-RtAudio\\_1\\_1DeviceInfo.html](http://www.music.mcgill.ca/~gary/rtaudio/struct-RtAudio_1_1DeviceInfo.html) for information about the members of the RtAudio::DeviceInfo struct.

**14.28.2.9** `CX_Millis CX::CX_SoundStream::getLastSwapTime ( void ) [inline]`

Gets the time at which the last buffer swap occurred.

#### Returns

This time value can be compared with the result of CX::Instances::Clock.getTime().

**14.28.2.10** `RtAudio * CX_SoundStream::getRtAudioInstance ( void )`

This function returns a pointer to the RtAudio instance that this CX\_SoundStream is using. This should not be needed most of the time, but there may be cases in which you need to directly access RtAudio. Here is the documentation for RtAudio: <https://www.music.mcgill.ca/~gary/rtaudio/>

**14.28.2.11** `uint64_t CX::CX_SoundStream::getSampleFrameNumber ( void ) [inline]`

Returns the number of the sample frame that

**14.28.2.12** `CX_Millis CX_SoundStream::getStreamLatency ( void )`

This function gets an estimate of the stream latency. However, it should not be relied on as it is based on what the sound card driver reports, which is often false.

#### Returns

The stream latency in microseconds.

**14.28.2.13** `bool CX_SoundStream::hasSwappedSinceLastCheck ( void )`

This function checks to see if the audio buffers have been swapped since the last time this function was called.

**Returns**

True if at least one audio buffer has been swapped out, false if no buffers have been swapped.

**14.28.2.14** `std::string CX_SoundStream::listDevices ( RtAudio::Api api ) [static]`

For the given api, lists all of the devices on the system that support that api. Lots of information about each device is given, like supported sample rates, number of input and output channels, etc.

**Parameters**

<i>api</i>	Devices that support this API are scanned.
------------	--

**Returns**

A human-readable formatted string containing the scanned information. Can be printed directly to `std::cout` or elsewhere.

**14.28.2.15** `bool CX_SoundStream::setup ( CX_SoundStream::Configuration & config )`

Opens the sound stream with the specified configuration. If there was an error during configuration, messages will be logged.

**Parameters**

<i>config</i>	The configuration settings that are desired. Some of the configuration options are only suggestions, so some of the values that are used may differ from the values that are chosen. In those cases, <code>config</code> is updated based on the actually used settings. You can check the configuration later using <a href="#">getConfiguration()</a> .
---------------	---

**Returns**

True if configuration appeared to be successful, false otherwise.

**Note**

Opening the stream does not start it. See [start\(\)](#).

**14.28.2.16** `bool CX_SoundStream::start ( void )`

Starts the sound stream. The stream must already be open().

**Returns**

False if the stream was not started, true if the stream was started or if it was already running.

**14.28.2.17** `bool CX_SoundStream::stop ( void )`

Stop the stream, if is running. If there is an error, a message will be logged.

## Returns

False if there was an error, true otherwise.

The documentation for this class was generated from the following files:

- CX\_SoundStream.h
- CX\_SoundStream.cpp

## 14.29 CX::CX\_Time\_t< TimeUnit > Class Template Reference

```
#include <CX_Time_t.h>
```

## Public Member Functions

- PartitionedTime [getPartitionedTime](#) (void)
- **CX\_Time\_t** (double t)
- **CX\_Time\_t** (int t)
- **CX\_Time\_t** (long long t)
- template<typename tArg >  
  **CX\_Time\_t** (const [CX\\_Time\\_t](#)< tArg > &t)
- double **value** (void) const
- double **hours** (void) const
- double **minutes** (void) const
- double **seconds** (void) const
- double **millis** (void) const
- double **micros** (void) const
- long long **nanos** (void) const
- template<typename RT >  
  [CX\\_Time\\_t](#)< TimeUnit > **operator+** (const [CX\\_Time\\_t](#)< RT > &rhs) const
- template<typename RT >  
  [CX\\_Time\\_t](#)< TimeUnit > **operator-** (const [CX\\_Time\\_t](#)< RT > &rhs) const
- template<typename RT >  
  double **operator/** (const [CX\\_Time\\_t](#)< RT > &rhs) const  
    *Divides a [CX\\_Time\\_t](#) by another [CX\\_Time\\_t](#), resulting in a unitless ratio.*
- [CX\\_Time\\_t](#)< TimeUnit > **operator/** (double rhs) const  
    *Divides a [CX\\_Time\\_t](#) by a unitless value, resulting in a [CX\\_Time\\_t](#) of the same type.*
- [CX\\_Time\\_t](#)< TimeUnit > **operator\*** (const double rhs) const  
    *Multiplies a [CX\\_Time\\_t](#) by a unitless value, resulting in a [CX\\_Time\\_t](#) of the same type. You cannot multiply a time by another time because that would result in units of time squared.*
- [CX\\_Time\\_t](#)< TimeUnit > & **operator\*=** (const double rhs)  
    *Multiplies a [CX\\_Time\\_t](#) by a unitless value, storing the result in the [CX\\_Time\\_t](#). You cannot multiply a time by another time because that would result in units of time squared.*
- template<typename RT >  
  [CX\\_Time\\_t](#)< TimeUnit > & **operator+=** (const [CX\\_Time\\_t](#)< RT > &rhs)
- template<typename RT >  
  [CX\\_Time\\_t](#)< TimeUnit > & **operator-=** (const [CX\\_Time\\_t](#)< RT > &rhs)
- template<typename RT >  
  bool **operator<** (const [CX\\_Time\\_t](#)< RT > &rhs) const
- template<typename RT >  
  bool **operator<=** (const [CX\\_Time\\_t](#)< RT > &rhs) const

- `template<typename RT >`  
`bool operator> (const CX_Time_t< RT > &rhs) const`
- `template<typename RT >`  
`bool operator>= (const CX_Time_t< RT > &rhs) const`
- `template<typename RT >`  
`bool operator== (const CX_Time_t< RT > &rhs) const`
- `template<typename RT >`  
`bool operator!= (const CX_Time_t< RT > &rhs) const`

### Static Public Member Functions

- static `CX_Time_t< TimeUnit > min (void)`
- static `CX_Time_t< TimeUnit > max (void)`

### 14.29.1 Detailed Description

`template<typename TimeUnit>class CX::CX_Time_t< TimeUnit >`

This class provides a convenient way to deal with time in various units. It has at most nanosecond accuracy. The contents of any of the templated versions of `CX_Time_t` are stored in nanoseconds, so most conversions between time types is lossless.

```
CX_Millis mil = 100;
CX_Micros mic = mil; //mic now contains 100000 microseconds == 100 milliseconds.
//Really, they both contain 100,000,000 nanoseconds.

//You can add times together.
CX_Seconds sec = CX_Minutes(.1) + CX_Millis(100); //sec contains 6.1 seconds.

//You can take the ratio of times.
double secondsPerMinute = CX_Seconds(1)/CX_Minutes(1);

//You can compare times using the standard comparison operators (==, !=, <, >, <=, >=).
if (CX_Minutes(60) == CX_Hours(1)) {
    cout << "There are 60 minutes in an hour." << endl;
}

if (CX_Millis(12.3456) == CX_Micros(12345.6)) {
    cout << "Time can be represented as a floating point value with sub-time-unit precision." << endl;
}

//If you want to be explicit about what time unit you want out, you can use the seconds(), millis(), etc.,
//functions:
sec = CX_Seconds(6);
cout << "In " << sec.seconds() << " seconds there are " << sec.millis() << " milliseconds and " << sec.
    minutes() << " minutes." << endl;

//You can alternately do a typecast if you're about to print the result:
cout << "In " << sec << " seconds there are " << (CX_Millis)sec << " milliseconds and " << (CX_Minutes)sec
    << " minutes." << endl;

//The difference between the above examples is the resulting type.
//double minutes = (CX_Minutes)sec; //This does not work: A CX_Minutes cannot be assigned to a double
double minutes = sec.minutes(); //minutes() returns a double.

//You can construct a time with the result of the construction of a time object with a different time unit.
CX_Minutes min = CX_Hours(.05); //3 minutes

//You can get the whole number amounts of different time units.
CX_Seconds longTime = CX_Hours(2) + CX_Minutes(16) + CX_Seconds(40) + CX_Millis(123) + CX_Micros(456) +
    CX_Nanos(1);
CX_Seconds::PartitionedTime parts = longTime.getPartitionedTime();
```

### 14.29.2 Member Function Documentation



14.29.2.1 `template<typename TimeUnit> PartitionedTime CX::CX_Time_t< TimeUnit >::getPartitionedTime ( void )`  
`[inline]`

Partitions a `CX_Time_t` into component parts containing the number of whole time units that are stored in the `CX_Time_t`. This is different from `seconds()`, `millis()`, etc., because those functions return the fractional part (e.g. 5.340 seconds) whereas this returns only whole numbers (e.g. 5 seconds and 340 milliseconds).

The documentation for this class was generated from the following file:

- `CX_Time_t.h`

## 14.30 CX::Util::CX\_TrialController Class Reference

```
#include <CX_TrialController.h>
```

### Public Member Functions

- `int update (void)`
- `void start (void)`  
*"Arm" the trial controller. Before this is called, `update()` will do nothing.*
- `void stop (void)`  
*"Disarm" the trial controller. After this is called, `update()` will do nothing.*
- `bool isActive (void)`  
*Check to see if the trial controller is active. See `start()` and `stop()`.*
- `void appendFunction (std::function< int(void)> userFunction)`
- `void reset (void)`
- `bool setCurrentFunction (int currentFunction)`
- `int getCurrentFunction (void)`  
*Get the index of the current function (i.e. the function that will be called the next time `update()` is called).*
- `unsigned int getFunctionCount (void)`  
*Get the number of user functions stored by this trial controller.*

### 14.30.1 Detailed Description

This class is used to help with the fact that most psychology experiments are by nature more or less linear, but that `CX` works better if code does not block (see [Blocking Code](#)).

The way this works is that segments of user code, each representing one part of a trial, are put into functions. Those functions are added to the trial controller with `appendFunction()`, which puts the function at the end of the list of functions. User functions take no arguments and return an int.

When you want to use the trial controller, call `start()` and it will be "armed". When it is armed and `update()` is called, it will call the current function in the list of user functions. If the user function is done with whatever it needs to do, it should return 1. This will cause the trial controller to move on to the next user function. If the user function is not done with its task, it should return 0. If it returns 0, it will be called again the next time `update()` is called.

### 14.30.2 Member Function Documentation

14.30.2.1 `void CX_TrialController::appendFunction ( std::function< int(void)> userFunction )`

Adds a user function to the end of the list of functions to be called by the trial controller.

## Parameters

<i>userFunction</i>	Typically a pointer to a function that takes no arguments and returns an int. Because it is a std::function, it can also be a lamda.
---------------------	--

## 14.30.2.2 void CX\_TrialController::reset ( void )

Clear the user functions and otherwise reset to default state.

## Note

This function stops the trial controller ([isActive\(\)](#) will return false).

14.30.2.3 bool CX\_TrialController::setCurrentFunction ( int *currentFunction* )

Sets the current user function by index, which allows you to skip over functions or go back to a previous function.

## Parameters

<i>currentFunction</i>	The new current function index. If this is out of range, an error will be logged and the function will return false.
------------------------	--

## Returns

False if the index was out of range, true otherwise.

## Note

If this is called from within a user function that has been called from this instance of the [CX\\_TrialController](#), that function should return 0. If it does not, [setCurrentFunction\(\)](#) will set the function index and then that index will be incremented after the user function completes. However, if 0 is returned, the function index is not incremented.

## 14.30.2.4 int CX\_TrialController::update ( void )

Updates the trial controller state. Each time this function is called, the user function at the current function index is called. If that function returns a nonzero value, the trial controller will increment the current function index and that function will be called the next time [update\(\)](#) is called. If the current function index is incremented past the end of the list of functions, it will wrap around to the beginning of the list.

## Returns

The value returned by the user function that was called.

## Note

This function should probably be called every time [updateExperiment\(\)](#) is called, although there are other use cases.

If not [isActive\(\)](#), this function does nothing and returns 0.

The documentation for this class was generated from the following files:

- CX\_TrialController.h
- CX\_TrialController.cpp

### 14.31 CX::Synth::Envelope Class Reference

```
#include <CX_ModularSynth.h>
```

Inherits [CX::Synth::ModuleBase](#).

#### Public Member Functions

- double [getNextSample](#) (void) override
- void **attack** (void)
- void **release** (void)

#### Public Attributes

- ModuleParameter **gateInput**
- double **a**
- double **d**
- double **s**
- double **r**

#### Additional Inherited Members

##### 14.31.1 Detailed Description

This class is a standard ADSR envelope: [http://en.wikipedia.org/wiki/Synthesizer#ADSR\\_envelope](http://en.wikipedia.org/wiki/Synthesizer#ADSR_envelope) s should be in the interval [0,1]. a, d, and r are expressed in seconds. Call attack() to start the envelope. Once the attack and decay are finished, the envelope will stay at the sustain level until release() is called.

The output values produced start at 0, rise to 1 during the attack, drop to the sustain level (s) during the decay, and drop from s to 0 during the release.

##### 14.31.2 Member Function Documentation

###### 14.31.2.1 double Envelope::getNextSample ( void ) [override],[virtual]

This function should be overloaded for any derived class that can be used as the input for another module.

Reimplemented from [CX::Synth::ModuleBase](#).

The documentation for this class was generated from the following files:

- CX\_ModularSynth.h
- CX\_ModularSynth.cpp

### 14.32 CX::CX\_Mouse::Event Struct Reference

```
#include <CX_Mouse.h>
```

## Public Types

- enum [MouseEventType](#) {  
[MOVED](#), [PRESSED](#), [RELEASED](#), [DRAGGED](#),  
[SCROLLED](#) }

## Public Attributes

- int [button](#)  
*The relevant mouse button if the eventType is PRESSED, RELEASED, or DRAGGED. Can be compared with elements of enum CX\_MouseButtons to find out about the primary buttons.*
- int [x](#)  
*The x position of the cursor at the time of the event, or the change in the x-axis scroll if the eventType is SCROLLED.*
- int [y](#)  
*The y position of the cursor at the time of the event, or the change in the y-axis scroll if the eventType is SCROLLED.*
- [CX\\_Millis](#) [eventTime](#)  
*The time at which the event was registered. Can be compared to the result of CX::Clock::getTime().*
- [CX\\_Millis](#) [uncertainty](#)  
*The uncertainty in eventTime. The event occurred some time between eventTime and eventTime minus uncertainty.*
- enum  
[CX::CX\\_Mouse::Event::MouseEventType](#) [eventType](#)  
*The type of the event.*

## 14.32.1 Detailed Description

This struct contains the results of a mouse event, which is any type of interaction with the mouse, be it simply movement, a button press or release, a drag event (mouse button held while mouse is moved), or movement of the scroll wheel.

## 14.32.2 Member Enumeration Documentation

## 14.32.2.1 enum CX::CX\_Mouse::Event::MouseEventType

## Enumerator

- MOVED** The mouse has been moved without a button being held. [button](#) should be -1 (meaningless).
- PRESSED** A mouse button has been pressed. Check [button](#) for the button index and [x](#) and [y](#) for the location.
- RELEASED** A mouse button has been released. Check [button](#) for the button index and [x](#) and [y](#) for the location.
- DRAGGED** can be changed during a drag, or multiple buttons may be held at once during a drag. The mouse has been moved while at least one button was held. [button](#) may not be meaningful because the held button
- SCROLLED** mouse has a wheel that can move horizontally. The mouse wheel has been scrolled. Check [y](#) to get the change in the standard mouse wheel, or [x](#) if your

The documentation for this struct was generated from the following file:

- [CX\\_Mouse.h](#)

## 14.33 CX::CX\_Joystick::Event Struct Reference

```
#include <CX_Joystick.h>
```

## Public Types

- enum [JoystickEventType](#) { [BUTTON\\_PRESS](#), [BUTTON\\_RELEASE](#), [AXIS\\_POSITION\\_CHANGE](#) }

## Public Attributes

- int [buttonIndex](#)  
*If eventType is [BUTTON\\_PRESS](#) or [BUTTON\\_RELEASE](#), this contains the index of the button that was changed.*
- unsigned char [buttonState](#)  
*If eventType is [BUTTON\\_PRESS](#) or [BUTTON\\_RELEASE](#), this contains the current state of the button.*
- int [axisIndex](#)  
*If eventType is [AXIS\\_POSITION\\_CHANGE](#), this contains the index of the axis which changed.*
- float [axisPosition](#)  
*If eventType is [AXIS\\_POSITION\\_CHANGE](#), this contains the amount by which the axis changed.*
- [CX\\_Millis](#) [eventTime](#)  
*The time at which the event was registered. Can be compared to the result of [CX::Clock::getTime\(\)](#).*
- [CX\\_Millis](#) [uncertainty](#)  
*The uncertainty in eventTime. The event occurred some time between eventTime and eventTime minus uncertainty.*
- enum  
[CX::CX\\_Joystick::Event::JoystickEventType](#) [eventType](#)  
*The type of the event.*

### 14.33.1 Detailed Description

This struct contains information about joystick events. Joystick events are either a button press or release or a change in the axes of the joystick.

### 14.33.2 Member Enumeration Documentation

#### 14.33.2.1 enum [CX::CX\\_Joystick::Event::JoystickEventType](#)

## Enumerator

**[BUTTON\\_PRESS](#)** A button on the joystick has been pressed. See [buttonIndex](#) and [buttonState](#) for the event data.

**[BUTTON\\_RELEASE](#)** A button on the joystick has been released. See [buttonIndex](#) and [buttonState](#) for the event data.

**[AXIS\\_POSITION\\_CHANGE](#)** The joystick has been moved in one of its axes. See [axisIndex](#) and [axisPosition](#) for the event data.

The documentation for this struct was generated from the following file:

- [CX\\_Joystick.h](#)

## 14.34 [CX::CX\\_Keyboard::Event](#) Struct Reference

```
#include <CX_Keyboard.h>
```

## Public Types

- enum [KeyboardEventType](#) { [PRESSED](#), [RELEASED](#), [REPEAT](#) }

## Public Attributes

- int [key](#)
- [CX\\_Millis](#) [eventTime](#)  
*The time at which the event was registered. Can be compared to the result of CX::Clock::getTime().*
- [CX\\_Millis](#) [uncertainty](#)  
*The uncertainty in eventTime. The event occurred some time between eventTime and eventTime minus uncertainty.*
- enum  
[CX::CX\\_Keyboard::Event::KeyboardEventType](#) [eventType](#)  
*The type of the event.*

## 14.34.1 Detailed Description

This struct contains the results of a keyboard event, whether it be a key press or release, or key repeat.

## 14.34.2 Member Enumeration Documentation

## 14.34.2.1 enum CX::CX\_Keyboard::Event::KeyboardEventType

## Enumerator

**PRESSED** A key has been pressed.

**RELEASED** A key has been released.

**REPEAT** A key has been held for some time and automatic key repeat has kicked in, causing multiple keypresses to be rapidly sent. This event is one of the many repeats.

## 14.34.3 Member Data Documentation

## 14.34.3.1 int CX::CX\_Keyboard::Event::key

The key involved in this event. The value of this can be compared with character literals for many of the standard keyboard keys. For example, you could use `'(myKeyEvent.key == 'e)'` to test if the key was the E key. Note that if shift is held when the key is pressed, the letter will be uppercase, so you may want to check for both 'e' and 'E'.

For special keys, `key` can be compared with the key constant values defined in `ofConstants.h` (e.g. `OF_KEY_ESC`).

Note that for the modifier keys (shift, ctrl, alt, and super) are treated a little unusually. For those keys, you can check for a specific key using, for example, `OF_KEY_RIGHT_CONTROL` or `OF_KEY_LEFT_CONTROL`. However, you can alternately check to see if `key` is any of the control keys by performing a bitwise AND with `OF_KEY_CONTROL` and checking that the result of the AND is still `OF_KEY_CONTROL`. For example:

```
if ((myKeyEvent.key & OF_KEY_CONTROL) == OF_KEY_CONTROL) {
//...
}
```

This works the same way for all of the modifier keys.

The documentation for this struct was generated from the following file:

- [CX\\_Keyboard.h](#)

### 14.35 CX::Synth::Filter Class Reference

```
#include <CX_ModularSynth.h>
```

Inherits [CX::Synth::ModuleBase](#).

#### Public Types

- enum [FilterType](#) { **LOW\_PASS**, **HIGH\_PASS**, **BAND\_PASS**, **NOTCH** }

#### Public Member Functions

- void **setType** ([FilterType](#) type)
- double [getNextSample](#) (void) override

#### Public Attributes

- ModuleParameter [cutoff](#)
- ModuleParameter [bandwidth](#)

#### Additional Inherited Members

##### 14.35.1 Detailed Description

This class provides a basic way to filter waveforms as part of subtractive synthesis or other audio manipulation.

This class is based on simple IIR filters. They may not be stable at all frequencies. They are computationally very efficient. They are not highly configurable. They may be chained for sharper frequency response. This class is based on this chapter: <http://www.dspguide.com/ch19.htm>.

##### 14.35.2 Member Enumeration Documentation

###### 14.35.2.1 enum CX::Synth::Filter::FilterType

The type of filter to use.

##### 14.35.3 Member Function Documentation

###### 14.35.3.1 double Filter::getNextSample ( void ) [override],[virtual]

This function should be overloaded for any derived class that can be used as the input for another module.

Reimplemented from [CX::Synth::ModuleBase](#).

##### 14.35.4 Member Data Documentation

###### 14.35.4.1 ModuleParameter CX::Synth::Filter::bandwidth

Only used for BAND\_PASS and NOTCH FilterTypes. Sets the width (in frequency domain) of the stop or pass band at which the amplitude is equal to  $\sin(\pi/4)$  (i.e. .707). So, for example, if you wanted the frequencies 100 Hz above and

below the breakpoint to be at .707 of the maximum amplitude, set bw to 100. Of course, past those frequencies the attenuation continues. Larger values result in a less pointy band.

#### 14.35.4.2 ModuleParameter CX::Synth::Filter::cutoff

The cutoff frequency of the filter.

The documentation for this class was generated from the following files:

- CX\_ModularSynth.h
- CX\_ModularSynth.cpp

### 14.36 CX::CX\_SlidePresenter::FinalSlideFunctionArgs Struct Reference

```
#include <CX_SlidePresenter.h>
```

#### Public Attributes

- [CX\\_SlidePresenter](#) \* [instance](#)  
*A pointer to the [CX\\_SlidePresenter](#) that called the user function.*
- unsigned int [currentSlideIndex](#)  
*The index of the slide that is currently being presented.*

#### 14.36.1 Detailed Description

The final slide function takes a reference to a struct of this type.

The documentation for this struct was generated from the following file:

- CX\_SlidePresenter.h

### 14.37 CX::Synth::FIRFilter Class Reference

```
#include <CX_ModularSynth.h>
```

Inherits [CX::Synth::ModuleBase](#).

#### Public Types

- enum [FilterType](#) { **LOW\_PASS**, **HIGH\_PASS**, **FIR\_USER\_DEFINED** }
- enum **WindowType** { **RECTANGULAR**, **HANNING**, **BLACKMAN** }

#### Public Member Functions

- void **setup** ([FilterType](#) filterType, unsigned int coefficientCount)
- void **setup** (std::vector< double > coefficients)
- void **setCutoff** (double cutoff)
- double [getNextSample](#) (void)



## Additional Inherited Members

### 14.37.1 Detailed Description

This class is a start at implementing a Finite Impulse Response ([http://en.wikipedia.org/wiki/Finite\\_impulse\\_response](http://en.wikipedia.org/wiki/Finite_impulse_response)) filter. You can use it as a basic low-pass or high-pass filter, or, if you supply your own coefficients, which cause the filter to do filtering in whatever way you want. See the "signal" package for R for a method of constructing your own coefficients.

### 14.37.2 Member Enumeration Documentation

#### 14.37.2.1 enum CX::Synth::FIRFilter::FilterType [strong]

The type of filter to use.

### 14.37.3 Member Function Documentation

#### 14.37.3.1 double CX::Synth::FIRFilter::getNextSample ( void ) [inline],[virtual]

This function should be overloaded for any derived class that can be used as the input for another module.

Reimplemented from [CX::Synth::ModuleBase](#).

The documentation for this class was generated from the following file:

- CX\_ModularSynth.h

## 14.38 CX::CX\_SoundStream::InputEventArgs Struct Reference

```
#include <CX_SoundStream.h>
```

### Public Attributes

- bool [bufferOverflow](#)  
*This is set to true if there was a buffer overflow, which means that the sound hardware recorded data that was not processed.*
- float \* [inputBuffer](#)  
*A pointer to an array of sound data that should be processed by the event handler function.*
- unsigned int [bufferSize](#)  
*The number of sample frames that are in inputBuffer. The total number of samples is bufferSize \* inputChannels.*
- int [inputChannels](#)  
*The number of channels worth of data in inputBuffer.*
- [CX\\_SoundStream](#) \* [instance](#)  
*A pointer to the [CX\\_SoundStream](#) instance that contains the input event.*

### 14.38.1 Detailed Description

The audio input event of the [CX\\_SoundStream](#) sends a copy of this structure with the fields filled out when the event is called.

The documentation for this struct was generated from the following file:

- CX\_SoundStream.h

## 14.39 CX::Algo::LatinSquare Class Reference

```
#include <CX_Algorithm.h>
```

### Public Member Functions

- **LatinSquare** (unsigned int dimensions)
- void **generate** (unsigned int dimensions)
- void **reorderRight** (void)
- void **reorderLeft** (void)
- void **reorderUp** (void)
- void **reorderDown** (void)
- void **reverseColumns** (void)
- void **reverseRows** (void)
- void **swapColumns** (unsigned int c1, unsigned int c2)
- void **swapRows** (unsigned int r1, unsigned int r2)
- bool **appendRight** (const **LatinSquare** &ls)
- bool **appendBelow** (const **LatinSquare** &ls)
- **LatinSquare** & **operator+=** (unsigned int value)
- std::string **print** (std::string delim=",")
- bool **validate** (void) const
- unsigned int **columns** (void) const
- unsigned int **rows** (void) const
- std::vector< unsigned int > **getColumn** (unsigned int col) const
- std::vector< unsigned int > **getRow** (unsigned int row) const

### Public Attributes

- std::vector< std::vector  
< unsigned int > > **square**

#### 14.39.1 Detailed Description

This class provides a way to work with Latin squares in a relatively easy way.

```
Algo::LatinSquare ls(4);
cout << "This latin square has " << ls.rows() << " rows and " << ls.columns() << " columns." << endl;
cout << ls.print() << endl;

ls.reverseColumns();
cout << "Reverse the columns: " << endl << ls.print() << endl;

ls.swapRows(0, 2);
cout << "Swap rows 0 and 2: " << endl << ls.print() << endl;

if (ls.validate()) {
    cout << "The latin square is still a valid latin square." << endl;
}

cout << "Let's copy, reverse, and append a latin square." << endl;
Algo::LatinSquare sq = ls;
```

```

sq.reverseColumns();
ls.appendBelow(sq);

cout << ls.print() << endl;
if (!ls.validate()) {
    cout << "The latin square is no longer valid, but it is still useful (8 counterbalancing conditions,
        both forward and backward ordering)." << endl;
}

```

## 14.39.2 Member Function Documentation

### 14.39.2.1 bool LatinSquare::appendBelow ( const LatinSquare & ls )

Appends another [LatinSquare](#) (ls) below of this one. If the number of columns of both latin squares is not equal, this has no effect and returns false.

### 14.39.2.2 bool LatinSquare::appendRight ( const LatinSquare & ls )

Appends another [LatinSquare](#) (ls) to the right of this one. If the number of rows of both latin squares is not equal, this has no effect and returns false.

### 14.39.2.3 unsigned int LatinSquare::columns ( void ) const

Returns the number of columns.

### 14.39.2.4 void LatinSquare::generate ( unsigned int *dimensions* )

Generate a latin square with the given dimensions. The generated square is the very basic latin square that, for dimension 3, has {0,1,2} on the first row, {1,2,0} on the middle row, and {2,0,1} on the last row.

#### Note

This deletes any previous contents of the latin square.

### 14.39.2.5 std::vector< unsigned int > LatinSquare::getColumn ( unsigned int *col* ) const

Returns a copy of the given column. Throws std::out\_of\_range if the column is out of range.

### 14.39.2.6 std::vector< unsigned int > LatinSquare::getRow ( unsigned int *row* ) const

Returns a copy of the given row. Throws std::out\_of\_range if the row is out of range.

### 14.39.2.7 LatinSquare & LatinSquare::operator+= ( unsigned int *value* )

Adds the given value to all of the values in the latin square.

### 14.39.2.8 std::string LatinSquare::print ( std::string *delim* = " , " )

Prints the contents of the latin square to a string with the given delimiter between elements of the latin square.

### 14.39.2.9 void LatinSquare::reorderLeft ( void )

This function shifts the columns to the left and the first column is moved to be the last column.

### 14.39.2.10 void LatinSquare::reorderRight ( void )

This function shifts the columns to the right and the last column is moved to be the first column.

14.39.2.11 void LatinSquare::reverseColumns ( void )

Reverses the order of the columns in the latin square.

14.39.2.12 void LatinSquare::reverseRows ( void )

Reverses the order of the rows in the latin square.

14.39.2.13 unsigned int LatinSquare::rows ( void ) const

Returns the number of rows.

14.39.2.14 void LatinSquare::swapColumns ( unsigned int *c1*, unsigned int *c2* )

Swap the given columns. If either column is out of range, this function has no effect.

14.39.2.15 void LatinSquare::swapRows ( unsigned int *r1*, unsigned int *r2* )

Swap the given rows. If either row is out of range, this function has no effect.

14.39.2.16 bool LatinSquare::validate ( void ) const

Checks to make sure that the latin square held by this instance is a valid latin square.

The documentation for this class was generated from the following files:

- CX\_Algorithm.h
- CX\_Algorithm.cpp

## 14.40 CX::Synth::Mixer Class Reference

```
#include <CX_ModularSynth.h>
```

Inherits [CX::Synth::ModuleBase](#).

### Public Member Functions

- double [getNextSample](#) (void) override

### Additional Inherited Members

#### 14.40.1 Detailed Description

This class mixes together a number of inputs. It does no mixing in the usual sense of setting levels of the inputs. Use Multipliers on the inputs for that. This class simply adds together all of the inputs with no amplitude correction, so it is possible for the output of the mixer to have very large amplitudes.

This class is special in that it can have more than one input.

#### 14.40.2 Member Function Documentation

14.40.2.1 double Mixer::getNextSample ( void ) [override],[virtual]

This function should be overloaded for any derived class that can be used as the input for another module.

Reimplemented from [CX::Synth::ModuleBase](#).

The documentation for this class was generated from the following files:

- CX\_ModularSynth.h
- CX\_ModularSynth.cpp

#### 14.41 CX::Synth::ModuleBase Class Reference

```
#include <CX_ModularSynth.h>
```

Inherited by [CX::Synth::Adder](#), [CX::Synth::AdditiveSynth](#), [CX::Synth::Clamper](#), [CX::Synth::Envelope](#), [CX::Synth::Filter](#), [CX::Synth::FIRFilter](#), [CX::Synth::GenericOutput](#), [CX::Synth::Mixer](#), [CX::Synth::Multiplier](#), [CX::Synth::Oscillator](#), [CX::Synth::SoundObjectInput](#), [CX::Synth::SoundObjectOutput](#), [CX::Synth::Splitter](#), [CX::Synth::StreamOutput](#), and [CX::Synth::TrivialGenerator](#).

##### Public Member Functions

- virtual double [getNextSample](#) (void)
- void [setData](#) (ModuleControlData\_t d)
- ModuleControlData\_t [getData](#) (void)
- void [disconnectInput](#) (ModuleBase \*in)
- void [disconnectOutput](#) (ModuleBase \*out)

##### Protected Member Functions

- virtual void [\\_dataSetEvent](#) (void)
- void [\\_dataSet](#) (ModuleBase \*caller)
- void [\\_setDataIfNotSet](#) (ModuleBase \*target)
- void [\\_registerParameter](#) (ModuleParameter \*p)
- virtual void [\\_assignInput](#) (ModuleBase \*in)
- virtual void [\\_assignOutput](#) (ModuleBase \*out)
- virtual int [\\_maxInputs](#) (void)
- virtual int [\\_maxOutputs](#) (void)
- virtual void [\\_inputAssignedEvent](#) (ModuleBase \*in)
- virtual void [\\_outputAssignedEvent](#) (ModuleBase \*out)

##### Protected Attributes

- vector< [ModuleBase](#) \* > [\\_inputs](#)
- vector< [ModuleBase](#) \* > [\\_outputs](#)
- vector< ModuleParameter \* > [\\_parameters](#)
- ModuleControlData\_t \* [\\_data](#)

##### Friends

- [ModuleBase](#) & [operator>>](#) ([ModuleBase](#) &l, [ModuleBase](#) &r)

## 14.41.1 Detailed Description

All modules of the modular synth inherit from this class.

## 14.41.2 Member Function Documentation

14.41.2.1 void ModuleBase::disconnectInput ( ModuleBase \* *in* )

This is a reciprocal operation: This module's input is removed and in's output to this module is removed.

## 14.41.2.2 virtual double CX::Synth::ModuleBase::getNextSample ( void ) [inline], [virtual]

This function should be overloaded for any derived class that can be used as the input for another module.

Reimplemented in [CX::Synth::FIRFilter](#), [CX::Synth::SoundObjectInput](#), [CX::Synth::Splitter](#), [CX::Synth::Oscillator](#), [CX::Synth::Multiplier](#), [CX::Synth::Mixer](#), [CX::Synth::Filter](#), [CX::Synth::Envelope](#), [CX::Synth::Clamper](#), [CX::Synth::Adder](#), and [CX::Synth::AdditiveSynth](#).

14.41.2.3 void CX::Synth::ModuleBase::setData ( ModuleControlData\_t *d* ) [inline]

This function sets the data needed by this module in order to function properly. Many modules need this data, specifically the sample rate that the synth using. If several modules are connected together, you will only need to set the data for one module and the change will propagate to the other connected modules automatically.

This function does not usually need to be called directly by the user. If an appropriate input or output is connected, the data will be set from that module.

## Parameters

<i>d</i>	The data to set.
----------	------------------

## 14.41.3 Friends And Related Function Documentation

14.41.3.1 ModuleBase& operator>> ( ModuleBase & *l*, ModuleBase & *r* ) [friend]

This operator is used to connect modules together. *l* is set as the input for *r*.

```
Oscillator osc;
StreamOutput out;
osc >> out; //Connect osc as the input for out.
```

The documentation for this class was generated from the following files:

- CX\_ModularSynth.h
- CX\_ModularSynth.cpp

## 14.42 CX::Synth::Multiplier Class Reference

```
#include <CX_ModularSynth.h>
```

Inherits [CX::Synth::ModuleBase](#).

## Public Member Functions

- double [getNextSample](#) (void) override
- void [setGain](#) (double decibels)

## Public Attributes

- ModuleParameter **amount**

## Additional Inherited Members

### 14.42.1 Detailed Description

This class multiplies an input by an `amount`. You can set the amount in terms of decibels of gain by using the [setGain\(\)](#) function. If there is no input to this module, it behaves as though the input was 0 and consequently outputs 0.

### 14.42.2 Member Function Documentation

#### 14.42.2.1 `double Multiplier::getNextSample ( void )` `[override]`, `[virtual]`

This function should be overloaded for any derived class that can be used as the input for another module.

Reimplemented from [CX::Synth::ModuleBase](#).

#### 14.42.2.2 `void Multiplier::setGain ( double decibels )`

Sets the `amount` of the multiplier based on gain in decibels.

#### Parameters

<i>decibels</i>	The gain to apply. If greater than 0, <code>amount</code> will be greater than 1. If less than 0, <code>amount</code> will be less than 1. After calling this function, <code>amount</code> will never be negative.
-----------------	---

The documentation for this class was generated from the following files:

- CX\_ModularSynth.h
- CX\_ModularSynth.cpp

## 14.43 CX::Synth::Oscillator Class Reference

```
#include <CX_ModularSynth.h>
```

Inherits [CX::Synth::ModuleBase](#).

## Public Member Functions

- double [getNextSample](#) (void) override
- void [setGeneratorFunction](#) (std::function< double(double)> f)

## Static Public Member Functions

- static double **saw** (double wp)
- static double **sine** (double wp)
- static double **square** (double wp)
- static double **triangle** (double wp)
- static double **whiteNoise** (double wp)

## Public Attributes

- ModuleParameter **frequency**

## Additional Inherited Members

## 14.43.1 Detailed Description

This class provides one of the simplest ways of generating waveforms. The output from an [Oscillator](#) can be filtered with a [CX::Synth::Filter](#) or used in other ways.

```
//Configure the oscillator to produce a square wave with a fundamental frequency of 200 Hz.
Oscillator osc;
osc.frequency = 200; //200 Hz
osc.setGeneratorFunction(Oscillator::square); //Produce a square wave
```

## 14.43.2 Member Function Documentation

## 14.43.2.1 double Oscillator::getNextSample ( void ) [override],[virtual]

This function should be overloaded for any derived class that can be used as the input for another module.

Reimplemented from [CX::Synth::ModuleBase](#).

## 14.43.2.2 void Oscillator::setGeneratorFunction ( std::function&lt; double(double)&gt; f )

It is very easy to make your own waveform generating functions to be used with an [Oscillator](#). A waveform generating function takes a value that represents the location in the waveform at the current point in time. These values are in the interval [0,1).

The waveform generating function should return a double representing the amplitude of the wave at the given waveform position.

To put this all together, a sine wave generator looks like this:

```
double sineWaveGeneratorFunction(double waveformPosition) {
    return sin(2 * PI * waveformPosition); //The argument for sin() is in radians. 1 cycle is 2*PI radians.
}
```

The documentation for this class was generated from the following files:

- CX\_ModularSynth.h
- CX\_ModularSynth.cpp

## 14.44 CX::CX\_SoundStream::OutputEventArgs Struct Reference

```
#include <CX_SoundStream.h>
```

## Public Attributes

- bool [bufferUnderflow](#)  
*This is set to true if there was a buffer underflow, which means that the sound hardware ran out of data to output.*
- float \* [outputBuffer](#)  
*A pointer to an array that should be filled with sound data.*



- unsigned int [bufferSize](#)  
*The number of sample frames that are in `outputBuffer`. The total number of samples is `bufferSize * outputChannels`.*
- int [outputChannels](#)  
*The number of channels worth of data in `outputBuffer`.*
- [CX\\_SoundStream](#) \* [instance](#)  
*A pointer to the [CX\\_SoundStream](#) instance that contains the output event.*

#### 14.44.1 Detailed Description

The audio output event of the [CX\\_SoundStream](#) sends a copy of this structure with the fields filled out when the event is called.

The documentation for this struct was generated from the following file:

- [CX\\_SoundStream.h](#)

### 14.45 CX::CX\_SlidePresenter::PresentationErrorInfo Struct Reference

```
#include <CX_SlidePresenter.h>
```

#### Public Member Functions

- unsigned int [totalErrors](#) (void)  
*Returns the sum of the different types of errors that are measured.*

#### Public Attributes

- bool [presentationErrorsSuccessfullyChecked](#)  
*True if presentation errors were successfully checked for. This does not mean that there were no presentation errors, but that there were no presentation error checking errors.*
- unsigned int [incorrectFrameCounts](#)
- unsigned int [lateCopiesToBackBuffer](#)  
*The number of slides for which the time at which the slide finished being copied to the back buffer was after the actual start time of the slide.*

#### 14.45.1 Detailed Description

This struct contains information about errors that were detected during slide presentation. See [CX\\_SlidePresenter::checkForPresentationErrors\(\)](#).

#### 14.45.2 Member Data Documentation

##### 14.45.2.1 unsigned int CX::CX\_SlidePresenter::PresentationErrorInfo::incorrectFrameCounts

The number of slides for which the actual and intended frame counts did not match, indicating that the slide was presented for too many or too few frames.

The documentation for this struct was generated from the following file:

- [CX\\_SlidePresenter.h](#)

## 14.46 CX::CX\_SlidePresenter::Slide Struct Reference

```
#include <CX_SlidePresenter.h>
```

### Public Types

- enum {  
    **NOT\_STARTED**, **COPY\_TO\_BACK\_BUFFER\_PENDING**, **SWAP\_PENDING**, **IN\_PROGRESS**,  
    **FINISHED** }

*Status of the current slide vis a vis presentation. This should not be modified by the user.*

### Public Attributes

- std::string [slideName](#)  
*The name of the slide. Set by the user during slide creation.*
- ofFbo [framebuffer](#)  
*A framebuffer containing image data that will be drawn to the screen during this slide's presentation. If `drawingFunction` points to a user function, `framebuffer` will not be drawn.*
- std::function< void(void)> [drawingFunction](#)  
*Pointer to a user function that will be called to draw the slide. If this points to a user function, it overrides `framebuffer`. The drawing function is not required to call `ofBackground()` or otherwise clear the display before drawing, which allows you to do what is essentially single-buffering using the back buffer as the framebuffer. However, if you want a blank framebuffer, you will have to clear it manually.*
- enum  
CX::CX\_SlidePresenter::Slide:: { ... } [slideStatus](#)  
*Status of the current slide vis a vis presentation. This should not be modified by the user.*
- [SlideTimingInfo](#) [intended](#)  
*The intended timing parameters (i.e. what should have happened if there were no presentation errors).*
- [SlideTimingInfo](#) [actual](#)  
*The actual timing parameters.*
- [CX\\_Millis](#) [copyToBackBufferCompleteTime](#)  
*The time at which the drawing operations for this slide finished. This is pretty useful to determine if there was an error on the trial (e.g. `framebuffer` was copied late). If this is greater than `actual.startTime`, the slide may not have been fully drawn at the time the front and back buffers swapped.*

### 14.46.1 Detailed Description

This struct contains information related to slide presentation using [CX\\_SlidePresenter](#).

The documentation for this struct was generated from the following file:

- [CX\\_SlidePresenter.h](#)

## 14.47 CX::CX\_SlidePresenter::SlideTimingInfo Struct Reference

```
#include <CX_SlidePresenter.h>
```

## Public Attributes

- `uint32_t startFrame`  
*The frame on which the slide started/should have started. Can be compared with the value given by `Display.getFrameNumber()`.*
- `uint32_t frameCount`  
*The number of frames the slide was/should be presented for.*
- `CX_Millis startTime`  
*The time at which the slide was/should have been started. Can be compared with values from `Clock.getTime()`.*
- `CX_Millis duration`  
*The amount of time the slide was/should have been presented for.*

### 14.47.1 Detailed Description

Contains information about the presentation timing of the slide.

The documentation for this struct was generated from the following file:

- `CX_SlidePresenter.h`

## 14.48 CX::Synth::SoundObjectInput Class Reference

```
#include <CX_ModularSynth.h>
```

Inherits `CX::Synth::ModuleBase`.

## Public Member Functions

- `double getNextSample` (void) override
- `void setSoundObject` (`CX::CX_SoundObject` \*so, unsigned int channel=0)
- `void setTime` (`CX_Millis` t)
- `bool canPlay` (void)

## Additional Inherited Members

### 14.48.1 Detailed Description

This class allows you to use a `CX_SoundObject` as the input for the modular synth. It is strictly monophonic, so when you associate a `CX_SoundObject` with this class, you must pick one channel of the sound to use.

### 14.48.2 Member Function Documentation

#### 14.48.2.1 `bool SoundObjectInput::canPlay ( void )`

Checks to see if the sound object that is associated with this `SoundObjectInput` is able to play. It is unable to play if `CX_SoundObject::isReadyToPlay()` is false or if the whole sound has been played.

#### 14.48.2.2 `double SoundObjectInput::getNextSample ( void )` [override],[virtual]

This function should be overloaded for any derived class that can be used as the input for another module.

Reimplemented from `CX::Synth::ModuleBase`.

#### 14.48.2.3 void SoundObjectInput::setTime ( CX::CX\_Millis t )

Set the playback time of the current [CX\\_SoundObject](#). When playback starts, it will start from this time. If playback is in progress, playback will skip to the selected time.

The documentation for this class was generated from the following files:

- CX\_ModularSynth.h
- CX\_ModularSynth.cpp

### 14.49 CX::Synth::SoundObjectOutput Class Reference

```
#include <CX_ModularSynth.h>
```

Inherits [CX::Synth::ModuleBase](#).

#### Public Member Functions

- void **setup** (float sampleRate)
- void **sampleData** ([CX\\_Millis](#) t)

#### Public Attributes

- [CX::CX\\_SoundObject](#) **so**

#### Additional Inherited Members

##### 14.49.1 Detailed Description

This class provides a method of capturing the output of a modular synth and storing it in a [CX\\_SoundObject](#) for later use.

The documentation for this class was generated from the following files:

- CX\_ModularSynth.h
- CX\_ModularSynth.cpp

### 14.50 CX::Synth::Splitter Class Reference

```
#include <CX_ModularSynth.h>
```

Inherits [CX::Synth::ModuleBase](#).

#### Public Member Functions

- double [getNextSample](#) (void) override

## Additional Inherited Members

### 14.50.1 Detailed Description

This class splits a signal and sends that signal to multiple outputs. This can be used for panning effects, for example.

This class is special because it allows multiple outputs.

```
Splitter sp;
Oscillator osc;
Multiplier m1;
Multiplier m2;
StereoStreamOutput out;
```

```
osc >> sp;
sp >> m1 >> out.left;
sp >> m2 >> out.right;
```

### 14.50.2 Member Function Documentation

#### 14.50.2.1 `double Splitter::getNextSample ( void )` `[override]`, `[virtual]`

This function should be overloaded for any derived class that can be used as the input for another module.

Reimplemented from [CX::Synth::ModuleBase](#).

The documentation for this class was generated from the following files:

- CX\_ModularSynth.h
- CX\_ModularSynth.cpp

## 14.51 CX::Synth::StereoSoundObjectOutput Class Reference

```
#include <CX_ModularSynth.h>
```

### Public Member Functions

- void **setup** (float sampleRate)
- void **sampleData** ([CX\\_Millis](#) t)

### Public Attributes

- GenericOutput **left**
- GenericOutput **right**
- [CX::CX\\_SoundObject](#) **so**

### 14.51.1 Detailed Description

This class provides a method of capturing the output of a modular synth and storing it in a [CX\\_SoundObject](#) for later use. This captures stereo audio by taking the output of different streams of data into either the `left` or `right` modules that this class has. See the example code.

```
StereoSoundObjectOutput sout;
sout.setup(44100);
```

```
Splitter sp;
Oscillator osc;
Multiplier leftM;
Multiplier rightM;

leftM.amount = .1;
rightM.amount = .01;

osc >> sp;
sp >> leftM >> sout.left;
sp >> rightM >> sout.right;

sout.sampleData(2); //Sample 2 seconds worth of data on both channels.
```

The documentation for this class was generated from the following files:

- CX\_ModularSynth.h
- CX\_ModularSynth.cpp

## 14.52 CX::Synth::StereoStreamOutput Class Reference

```
#include <CX_ModularSynth.h>
```

### Public Member Functions

- void **setOutputStream** (CX::CX\_SoundStream &stream)

### Public Attributes

- GenericOutput **left**
- GenericOutput **right**

#### 14.52.1 Detailed Description

This class is much like [StreamOutput](#) except in stereo. This captures stereo audio by taking the output of different streams of data into either the `left` or `right` modules that this class has. See the example code for [CX::Synth::StereoSoundObjectOutput](#) and [CX::Synth::StreamOutput](#) for ideas on how to use this class.

The documentation for this class was generated from the following files:

- CX\_ModularSynth.h
- CX\_ModularSynth.cpp

## 14.53 CX::Synth::StreamOutput Class Reference

```
#include <CX_ModularSynth.h>
```

Inherits [CX::Synth::ModuleBase](#).

### Public Member Functions

- void **setOutputStream** (CX::CX\_SoundStream &stream)

## Additional Inherited Members

### 14.53.1 Detailed Description

This class provides a method of playing the output of a modular synth using a [CX\\_SoundStream](#). In order to use this class, you need to configure a [CX\\_SoundStream](#) for use. See the `soundObject` example and the [CX::CX\\_SoundStream](#) class for more information.

```
//Assume that both osc and ss have been configured and the sound stream has been started.
CX_SoundStream ss;
Oscillator osc;

Synth::StreamOutput output;
output.setOutputStream(ss);

osc >> output; //Sound should be playing past this point.
```

The documentation for this class was generated from the following files:

- `CX_ModularSynth.h`
- `CX_ModularSynth.cpp`

## 15 File Documentation

### 15.1 `advancedChangeDetectionTask.cpp` File Reference

```
#include "CX_EntryPoint.h"
```

#### Functions

- void **drawStimuli** (void)
- void **presentStimuli** (void)
- void **getResponse** (void)
- void **generateTrials** (int trialCount)
- void **updateExperiment** (void)
- void **drawFixation** (void)
- void **drawBlank** (void)
- void **drawSampleArray** (void)
- void **drawTestArray** (void)
- ofColor **backgroundColor** (50)
- void **runExperiment** (void)

#### Variables

- [CX\\_SlidePresenter](#) **SlidePresenter**
- [CX\\_DataFrame](#) **trialIdf**
- int **trialIndex** = 0
- int **circleRadius** = 0

### 15.1.1 Detailed Description

This example is a more advanced version of the change detection task presented in the `basicChangeDetectionTask` example. It is not "advanced" because it is more complex, but because it uses more features of CX. It actually ends up being simpler because of how it uses features of CX.

Items that are commented are new, although not all new stuff will necessarily be commented. The main feature that is demonstrated is the `CX_DataFrame`, which is a way to store and output experimental data. Using custom units and a custom coordinate system is shown with `CX_CoordinateConverter` and `CX_DegreeToPixelConverter` as the unit converter.

## 15.2 advancedNBack.cpp File Reference

```
#include "CX_EntryPoint.h"
```

### Functions

- ofColor **backgroundColor** (50)
- ofColor **textColor** (255)
- void **finalSlideFunction** (`CX_SlidePresenter::FinalSlideFunctionArgs` &info)
- void **drawStimuliToFramebuffers** (`CX_SlidePresenter` &sp, int trialIndex)
- void **appendDrawingFunctions** (`CX_SlidePresenter` &sp, int trialIndex)
- void **drawStimulus** (string letter, bool showInstructions)
- void **drawBlank** (void)
- void **generateTrials** (int numberOfTrials)
- void **runExperiment** (void)

### Variables

- `CX_DataFrame` **df**
- `CX_DataFrame::RowIndex_t` **trialNumber** = 0
- int **trialCount** = 40
- int **lastSlideIndex** = 0
- int **nBack** = 2
- ofTrueTypeFont **letterFont**
- ofTrueTypeFont **instructionFont**
- char **targetKey** = 'f'
- char **nonTargetKey** = 'j'
- string **keyReminderInstructions**
- `CX_Millis` **stimulusPresentationDuration** = 500
- `CX_Millis` **interStimulusInterval** = `CX_Seconds`(1.0/60.0)
- `CX_SlidePresenter` **SlidePresenter**
- bool **useFramebuffersForStimuli** = false
- vector< stimulusFunctor > **stimulusFuncutors**



### 15.2.1 Detailed Description

In this example, we are going to consider two different ways of using the slide presenter to present stimuli. One method is the one used in the change detection example: Draw the stimuli to framebuffers that are managed by the SlidePresenter. This approach is fairly easy to do, but it had a time cost, because allocating and copying all of the framebuffers takes time. This example builds on the nBack example.

In this example, we are going to contrast using the framebuffer approach with the slide presenter with the use of drawing functions. The standard framebuffer approach has the following major steps:

1) Allocate the framebuffer 2) Draw your stimuli to the framebuffer 3) Copy the framebuffer to the back buffer 4) Swap front and back buffers

Using drawing functions, we avoid steps 1 and 3, which are generally both very costly in terms of time. Step 2 becomes "Draw your stimuli to the back buffer directly". For an N-back task, there are no indefinitely-long pauses where you can prepare stimuli: you have to get the next stimulus ready within a fixed interval, so using drawing functions may be the best approach. We are going to examine that issue with this example.

The way in which you use a drawing function with a CX\_SlidePresenter is with the appendSlideFunction() function. This function takes three arguments: the drawing function, the duration for which the stimuli drawn by that drawing function should be presented, and the name of the slide (optional). When the stimuli specified by the drawing function are ready to be presented, the drawing function will be called. In the drawing function, you do not need to call Display.-beginDrawingToBackBuffer(); the slide presenter does that for you. See drawStimulus() below for an example of what a drawing function might look like.

We can compare the performance of the framebuffer and functor approaches by examining how much time is used for various processes. One thing to consider is the amount of time it takes to allocate the framebuffers and render your stimuli to the framebuffers.

Another consideration is the amount of time it takes to copy a framebuffer to the back buffer (step 3 above). This may take longer than drawing a small amount of stimuli directly to the back buffer. The framebuffer approach provides a nice security blanket: "I know that regardless of whatever is the the framebuffer, it will be copied in the same amount of time as any other framebuffer." However, if that copying time is longer than any of the stimulus drawing times, then using framebuffers is less efficient than drawing directly to the back buffer.

We will be using a special kind of function object, known as a functor (<http://www.cprogramming.com/tutorial/functors-function-objects-in-c++.html>) to do our drawing. A functor is basically a structure that can be called like a function using operator(). But unlike a normal function, a functor carries data along with it that can be used in the function call. Thus, a functor is a way to have a function without certain arguments for which you can still specify those arguments (in a sense) by setting data members of the functor. See struct stimulusFunctor below for an implementation.

## 15.3 basicChangeDetectionTask.cpp File Reference

```
#include "CX_EntryPoint.h"
```

### Functions

- void **updateExperiment** (void)
- vector< TrialData\_t > **generateTrials** (int trialCount)
- void **outputData** (void)
- void **drawStimuli** (void)
- void **presentStimuli** (void)
- void **getResponse** (void)
- void **drawFixation** (void)

- void **drawBlank** (void)
- void **drawSampleArray** (const TrialData\_t &tr)
- void **drawTestArray** (const TrialData\_t &tr)
- ofColor **backgroundColor** (50)
- void **runExperiment** (void)

#### Variables

- **CX\_SlidePresenter** **SlidePresenter**
- vector< TrialData\_t > **trials**
- int **trialIndex** = 0
- int **circleRadius** = 30

#### 15.3.1 Detailed Description

This example shows how to do a simple change-detection experiment using **CX**. The stimuli are colored circles which are presented in a 3X3 matrix.

Press the S key to indicate that you think the test array is the same or the D key to indicate that you think the test array is different.

## 15.4 modularSynth.cpp File Reference

```
#include "CX_EntryPoint.h"
```

#### Functions

- void **drawInformation** (void)
- void **modularSynthInternals** (void)
- void **runExperiment** (void)

#### 15.4.1 Detailed Description

This example shows some of the ways in which a modular synthesizer can be constructed using modules provided in the **CX::Synth** namespace.

## 15.5 nBack.cpp File Reference

```
#include "CX_EntryPoint.h"
```

#### Functions

- ofColor **backgroundColor** (50)
- ofColor **textColor** (255)
- void **finalSlideFunction** (**CX\_SlidePresenter::FinalSlideFunctionArgs** &info)
- void **drawStimulusForTrial** (unsigned int trial, bool showInstructions)
- void **generateTrials** (int numberOfTrials)
- void **runExperiment** (void)

## Variables

- `CX_DataFrame df`
- `CX_DataFrame::rowIndex_t trialNumber = 0`
- `int trialCount = 40`
- `int lastSlideIndex = 0`
- `int nBack = 2`
- `ofTrueTypeFont letterFont`
- `ofTrueTypeFont instructionFont`
- `char targetKey = 'f'`
- `char nonTargetKey = 'j'`
- `string keyReminderInstructions`
- `CX_Millis stimulusPresentationDuration = 1000`
- `CX_Millis interStimulusInterval = 1000`
- `CX_SlidePresenter SlidePresenter`

### 15.5.1 Detailed Description

This example shows how to implement an N-Back task using an advanced feature of the `CX_SlidePresenter` (SP). There is a feature of the SP that allows you to give it a pointer to a function that will be called every time the SP has just presented the final slide that it currently has. In your function, you can add more slides to the SP, which will allow it to continue presenting slides. If you don't add any more slides, slide presentation will stop with the currently presented slide.

For this N-Back task, the presentation of stimuli will follow the pattern stimulus-blank-stimulus-blank etc. The idea is that you will load up the SP with the first few stimuli and blanks. The SP will be started and will present the first few stimuli. When it runs out of stimuli, the last slide user function will be called. In this function, we will check for any responses that have been made since the last time the function was called and draw the next stimulus-blank pair. See the definition of `finalSlideFunction` and `setupExperiment` for the implementation of these ideas.

## Index

AXIS\_POSITION\_CHANGE  
    CX::CX\_Joystick::Event, 110  
addColumn  
    CX::CX\_DataFrame, 49  
addSilence  
    CX::CX\_SoundObject, 90  
addSound  
    CX::CX\_SoundObject, 91  
advancedChangeDetectionTask.cpp, 128  
advancedNBack.cpp, 129  
api  
    CX::CX\_SoundStream::Configuration, 42  
appendBelow  
    CX::Algo::LatinSquare, 116  
appendFunction  
    CX::Util::CX\_TrialController, 106  
appendRight  
    CX::Algo::LatinSquare, 116  
appendRow  
    CX::CX\_DataFrame, 49  
appendSlide  
    CX::CX\_SlidePresenter, 86  
appendSlideFunction  
    CX::CX\_SlidePresenter, 87  
applyGain  
    CX::CX\_SoundObject, 91  
arrayToVector  
    CX::Util, 31  
arrowToPath  
    CX::Draw, 27  
at  
    CX::CX\_DataFrame, 50  
availableEvents  
    CX::CX\_Joystick, 69  
    CX::CX\_Keyboard, 70  
    CX::CX\_Mouse, 76  
  
BUTTON\_PRESS  
    CX::CX\_Joystick::Event, 110  
BUTTON\_RELEASE  
    CX::CX\_Joystick::Event, 110  
BLOCKING\_estimateFramePeriod  
    CX::CX\_Display, 63  
BLOCKING\_setAutoSwapping  
    CX::CX\_Display, 64  
BLOCKING\_setSound  
    CX::CX\_SoundObjectPlayer, 96  
BLOCKING\_swapFrontAndBackBuffers  
    CX::CX\_Display, 64  
BLOCKING\_waitForOpenGL  
    CX::CX\_Display, 64  
  
bandwidth  
    CX::Synth::Filter, 112  
basicChangeDetectionTask.cpp, 130  
beginDrawingNextSlide  
    CX::CX\_SlidePresenter, 87  
beginDrawingToBackBuffer  
    CX::CX\_Display, 63  
bufferSize  
    CX::CX\_SoundStream::Configuration, 43  
  
CX::CX\_Joystick::Event  
    AXIS\_POSITION\_CHANGE, 110  
    BUTTON\_PRESS, 110  
    BUTTON\_RELEASE, 110  
CX::CX\_Keyboard::Event  
    PRESSED, 111  
    RELEASED, 111  
    REPEAT, 111  
CX::CX\_Mouse::Event  
    DRAGGED, 109  
    MOVED, 109  
    PRESSED, 109  
    RELEASED, 109  
    SCROLLED, 109  
CX::CX\_SlidePresenter  
    FIX\_TIMING\_FROM\_FIRST\_SLIDE, 86  
    PROPAGATE\_DELAYS, 86  
CX, 23  
    operator<<, 24  
CX::Algo, 24  
    fullyCross, 25  
    generateSeparatedValues, 25  
CX::Algo::BlockSampler< T >, 39  
CX::Algo::LatinSquare, 115  
    appendBelow, 116  
    appendRight, 116  
    columns, 116  
    generate, 116  
    getColumn, 116  
    getRow, 116  
    operator+==, 116  
    print, 116  
    reorderLeft, 116  
    reorderRight, 116  
    reverseColumns, 116  
    reverseRows, 117  
    rows, 117  
    swapColumns, 117  
    swapRows, 117  
    validate, 117  
CX::CX\_BaseClock, 43

- CX::CX\_Clock, 44
  - getDateTimeString, 44
  - getExperimentStartDateTimeString, 44
  - now, 44
  - precisionTest, 45
- CX::CX\_DataFrame, 48
  - addColumn, 49
  - appendRow, 49
  - at, 50
  - clear, 50
  - columnNames, 50
  - copyColumn, 50
  - copyColumns, 50
  - copyRows, 51
  - deleteColumn, 51
  - deleteRow, 51
  - operator(), 52
  - operator=, 52
  - print, 52
  - printToFile, 54
  - readFromFile, 54
  - reorderRows, 55
  - setRowCount, 55
  - shuffleRows, 55
- CX::CX\_DataFrameCell, 57
  - CX\_DataFrameCell, 58
  - copyCellTo, 58
  - getStoredType, 58
  - operator=, 58
  - store, 58
  - storeVector, 60
  - to, 60
  - toVector, 60
- CX::CX\_DataFrameColumn, 61
- CX::CX\_DataFrameRow, 61
- CX::CX\_Display, 63
  - BLOCKING\_estimateFramePeriod, 63
  - BLOCKING\_setAutoSwapping, 64
  - BLOCKING\_swapFrontAndBackBuffers, 64
  - BLOCKING\_waitForOpenGL, 64
  - beginDrawingToBackBuffer, 63
  - copyFboToBackBuffer, 64, 65
  - endDrawingToBackBuffer, 65
  - estimateNextSwapTime, 65
  - getCenterOfDisplay, 65
  - getFrameNumber, 65
  - getFramePeriod, 65
  - getLastSwapTime, 65
  - getResolution, 66
  - hasSwappedSinceLastCheck, 66
  - isAutomaticallySwapping, 66
  - setFullScreen, 66
  - setWindowResolution, 66
  - setWindowTitle, 66
  - setup, 66
  - swapFrontAndBackBuffers, 67
- CX::CX\_InputManager, 67
  - pollEvents, 67
  - setup, 68
- CX::CX\_Joystick, 68
  - availableEvents, 69
  - clearEvents, 69
  - getAxisPositions, 69
  - getButtonStates, 69
  - getJoystickName, 69
  - getNextEvent, 69
  - pollEvents, 69
  - setup, 69
- CX::CX\_Joystick::Event, 109
  - JoystickEventType, 110
- CX::CX\_Keyboard, 69
  - availableEvents, 70
  - clearEvents, 70
  - getNextEvent, 70
  - isKeyPressed, 70
- CX::CX\_Keyboard::Event, 110
  - key, 111
  - KeyboardEventType, 111
- CX::CX\_Logger, 72
  - captureOfLogMessages, 73
  - error, 73
  - fatalError, 73
  - flush, 73
  - level, 73
  - levelForAllModules, 73
  - levelForConsole, 73
  - levelForFile, 73
  - log, 75
  - notice, 75
  - setMessageFlushCallback, 75
  - timestamps, 75
  - verbose, 75
  - warning, 75
- CX::CX\_Mouse, 76
  - availableEvents, 76
  - clearEvents, 76
  - getCursorPosition, 76
  - getNextEvent, 76
  - setCursorPosition, 77
  - showCursor, 77
- CX::CX\_Mouse::Event, 108
  - MouseEventType, 109
- CX::CX\_RandomNumberGenerator, 77
  - CX\_RandomNumberGenerator, 78
  - getGenerator, 78
  - getMaximumRandomInt, 78
  - getMinimumRandomInt, 79
  - getSeed, 79

- randomDouble, 79
- randomExclusive, 79
- randomInt, 81
- sample, 81, 82
- sampleBinomialRealizations, 82
- sampleNormalRealizations, 82
- sampleRealizations, 83
- sampleUniformRealizations, 83
- setSeed, 83
- shuffleVector, 84
- CX::CX\_SlidePresenter, 84
  - appendSlide, 86
  - appendSlideFunction, 87
  - beginDrawingNextSlide, 87
  - checkForPresentationErrors, 87
  - clearSlides, 87
  - endDrawingCurrentSlide, 88
  - ErrorMode, 86
  - getActualFrameCounts, 88
  - getActualPresentationDurations, 88
  - getSlides, 88
  - setup, 88, 89
  - startSlidePresentation, 89
  - update, 89
- CX::CX\_SlidePresenter::Configuration, 41
  - SwappingMode, 42
- CX::CX\_SlidePresenter::FinalSlideFunctionArgs, 113
- CX::CX\_SlidePresenter::PresentationErrorInfo, 122
  - incorrectFrameCounts, 122
- CX::CX\_SlidePresenter::Slide, 123
- CX::CX\_SlidePresenter::SlideTimingInfo, 123
- CX::CX\_SoundObject, 89
  - addSilence, 90
  - addSound, 91
  - applyGain, 91
  - clear, 91
  - deleteAmount, 91
  - getLength, 91
  - getNegativePeak, 92
  - getPositivePeak, 92
  - getRawDataReference, 92
  - getSampleFrameCount, 92
  - getTotalSampleCount, 92
  - isLoadedSuccessfully, 92
  - isReadyToPlay, 92
  - loadFile, 92
  - multiplyAmplitudeBy, 94
  - multiplySpeed, 94
  - normalize, 94
  - resample, 94
  - reverse, 94
  - setChannelCount, 94
  - setFromVector, 95
  - setLength, 95
  - stripLeadingSilence, 95
  - writeToFile, 95
- CX::CX\_SoundObjectPlayer, 96
  - BLOCKING\_setSound, 96
  - play, 97
  - setTime, 97
  - setup, 97
  - startPlayingAt, 97
  - stop, 97
- CX::CX\_SoundObjectRecorder, 98
  - getSoundObject, 99
  - setSoundObject, 99
  - setup, 99
  - startRecording, 99
  - stopRecording, 99
- CX::CX\_SoundStream, 99
  - closeStream, 101
  - convertApiToString, 101
  - convertApisToString, 101
  - convertApisToStrings, 101
  - estimateNextSwapTime, 101
  - getCompiledApis, 101
  - getConfiguration, 102
  - getDeviceList, 102
  - getLastSwapTime, 102
  - getRtAudioInstance, 102
  - getSampleFrameNumber, 102
  - getStreamLatency, 102
  - hasSwappedSinceLastCheck, 102
  - listDevices, 103
  - setup, 103
  - start, 103
  - stop, 103
- CX::CX\_SoundStream::Configuration, 42
  - api, 42
  - bufferSize, 43
  - sampleRate, 43
  - streamOptions, 43
- CX::CX\_SoundStream::InputEventArgs, 114
- CX::CX\_SoundStream::OutputEventArgs, 121
- CX::CX\_Time\_t
  - getPartitionedTime, 105
- CX::CX\_Time\_t< TimeUnit >, 104
- CX::Draw, 26
  - arrowToPath, 27
  - centeredString, 27
  - squircleToPath, 27
  - star, 27
  - starToPath, 28
- CX::Instances, 28
- CX::Private, 28
- CX::Synth, 29
- CX::Synth::Adder, 35
  - getNextSample, 36

CX::Synth::AdditiveSynth, 36  
     getNextSample, 37  
     HarmonicAmplitudeType, 37  
     pruneLowAmplitudeHarmonics, 37  
     setAmplitudes, 37  
     setHarmonicSeries, 39  
     setStandardHarmonicSeries, 39  
 CX::Synth::Clamper, 40  
     getNextSample, 41  
 CX::Synth::Envelope, 108  
     getNextSample, 108  
 CX::Synth::FIRFilter, 113  
     FilterType, 114  
     getNextSample, 114  
 CX::Synth::Filter, 112  
     bandwidth, 112  
     cutoff, 113  
     FilterType, 112  
     getNextSample, 112  
 CX::Synth::Mixer, 117  
     getNextSample, 117  
 CX::Synth::ModuleBase, 118  
     disconnectInput, 119  
     getNextSample, 119  
     operator>>, 119  
     setData, 119  
 CX::Synth::Multiplier, 119  
     getNextSample, 120  
     setGain, 120  
 CX::Synth::Oscillator, 120  
     getNextSample, 121  
     setGeneratorFunction, 121  
 CX::Synth::SoundObjectInput, 124  
     canPlay, 124  
     getNextSample, 124  
     setTime, 124  
 CX::Synth::SoundObjectOutput, 125  
 CX::Synth::Splitter, 125  
     getNextSample, 126  
 CX::Synth::StereoSoundObjectOutput, 126  
 CX::Synth::StereoStreamOutput, 127  
 CX::Synth::StreamOutput, 127  
 CX::Util, 30  
     arrayToVector, 31  
     checkOFVersion, 31  
     clamp, 31  
     degreesToPixels, 31  
     intVector, 32  
     pixelsToDegrees, 32  
     repeat, 32, 33  
     round, 33  
     saveFboToFile, 33  
     sequence, 33  
     sequenceAlong, 34  
     sequenceSteps, 34  
     vectorToString, 34  
     writeToFile, 35  
 CX::Util::CX\_CoordinateConverter, 45  
     CX\_CoordinateConverter, 46  
     operator(), 46  
     setAxisInversion, 46  
     setMultiplier, 47  
     setOrigin, 47  
     setUnitConverter, 47  
 CX::Util::CX\_DegreeToPixelConverter, 61  
     CX\_DegreeToPixelConverter, 62  
     operator(), 62  
 CX::Util::CX\_LapTimer, 71  
 CX::Util::CX\_LengthToPixelConverter, 71  
     CX\_LengthToPixelConverter, 72  
     operator(), 72  
 CX::Util::CX\_TrialController, 106  
     appendFunction, 106  
     reset, 107  
     setCurrentFunction, 107  
     update, 107  
 CX\_CoordinateConverter  
     CX::Util::CX\_CoordinateConverter, 46  
 CX\_DataFrameCell  
     CX::CX\_DataFrameCell, 58  
 CX\_DegreeToPixelConverter  
     CX::Util::CX\_DegreeToPixelConverter, 62  
 CX\_LengthToPixelConverter  
     CX::Util::CX\_LengthToPixelConverter, 72  
 CX\_LogLevel  
     Error Logging, 16  
 CX\_RandomNumberGenerator  
     CX::CX\_RandomNumberGenerator, 78  
 canPlay  
     CX::Synth::SoundObjectInput, 124  
 captureOFLogMessages  
     CX::CX\_Logger, 73  
 centeredString  
     CX::Draw, 27  
 checkForPresentationErrors  
     CX::CX\_SlidePresenter, 87  
 checkOFVersion  
     CX::Util, 31  
 clamp  
     CX::Util, 31  
 clear  
     CX::CX\_DataFrame, 50  
     CX::CX\_SoundObject, 91  
 clearEvents  
     CX::CX\_Joystick, 69  
     CX::CX\_Keyboard, 70  
     CX::CX\_Mouse, 76  
 clearSlides

- CX::CX\_SlidePresenter, 87
- Clock
  - Timing, 20
- closeStream
  - CX::CX\_SoundStream, 101
- columnNames
  - CX::CX\_DataFrame, 50
- columns
  - CX::Algo::LatinSquare, 116
- convertApiToString
  - CX::CX\_SoundStream, 101
- convertApisToString
  - CX::CX\_SoundStream, 101
- convertApisToStrings
  - CX::CX\_SoundStream, 101
- copyCellTo
  - CX::CX\_DataFrameCell, 58
- copyColumn
  - CX::CX\_DataFrame, 50
- copyColumns
  - CX::CX\_DataFrame, 50
- copyFboToBackBuffer
  - CX::CX\_Display, 64, 65
- copyRows
  - CX::CX\_DataFrame, 51
- cutoff
  - CX::Synth::Filter, 113
- DRAGGED
  - CX::CX\_Mouse::Event, 109
- Data, 13
- degreesToPixels
  - CX::Util, 31
- deleteAmount
  - CX::CX\_SoundObject, 91
- deleteColumn
  - CX::CX\_DataFrame, 51
- deleteRow
  - CX::CX\_DataFrame, 51
- disconnectInput
  - CX::Synth::ModuleBase, 119
- Display
  - Entry Point, 15
- endDrawingCurrentSlide
  - CX::CX\_SlidePresenter, 88
- endDrawingToBackBuffer
  - CX::CX\_Display, 65
- Entry Point, 15
  - Display, 15
  - Input, 15
  - Log, 15
  - RNG, 15
  - runExperiment, 15
- error
  - CX::CX\_Logger, 73
- Error Logging, 16
  - CX\_LogLevel, 16
- ErrorMode
  - CX::CX\_SlidePresenter, 86
- estimateNextSwapTime
  - CX::CX\_Display, 65
  - CX::CX\_SoundStream, 101
- FIX\_TIMING\_FROM\_FIRST\_SLIDE
  - CX::CX\_SlidePresenter, 86
- fatalError
  - CX::CX\_Logger, 73
- FilterType
  - CX::Synth::Filter, 112
  - CX::Synth::FIRFilter, 114
- flush
  - CX::CX\_Logger, 73
- fullyCross
  - CX::Algo, 25
- generate
  - CX::Algo::LatinSquare, 116
- generateSeparatedValues
  - CX::Algo, 25
- getActualFrameCounts
  - CX::CX\_SlidePresenter, 88
- getActualPresentationDurations
  - CX::CX\_SlidePresenter, 88
- getAxisPositions
  - CX::CX\_Joystick, 69
- getButtonStates
  - CX::CX\_Joystick, 69
- getCenterOfDisplay
  - CX::CX\_Display, 65
- getColumn
  - CX::Algo::LatinSquare, 116
- getCompiledApis
  - CX::CX\_SoundStream, 101
- getConfiguration
  - CX::CX\_SoundStream, 102
- getCursorPosition
  - CX::CX\_Mouse, 76
- getDateTimeString
  - CX::CX\_Clock, 44
- getDeviceList
  - CX::CX\_SoundStream, 102
- getExperimentStartDateTimeString
  - CX::CX\_Clock, 44
- getFrameNumber
  - CX::CX\_Display, 65
- getFramePeriod
  - CX::CX\_Display, 65
- getGenerator
  - CX::CX\_RandomNumberGenerator, 78



- getJoystickName
  - CX::CX\_Joystick, 69
- getLastSwapTime
  - CX::CX\_Display, 65
  - CX::CX\_SoundStream, 102
- getLength
  - CX::CX\_SoundObject, 91
- getMaximumRandomInt
  - CX::CX\_RandomNumberGenerator, 78
- getMinimumRandomInt
  - CX::CX\_RandomNumberGenerator, 79
- getNegativePeak
  - CX::CX\_SoundObject, 92
- getNextEvent
  - CX::CX\_Joystick, 69
  - CX::CX\_Keyboard, 70
  - CX::CX\_Mouse, 76
- getNextSample
  - CX::Synth::Adder, 36
  - CX::Synth::AdditiveSynth, 37
  - CX::Synth::Clamper, 41
  - CX::Synth::Envelope, 108
  - CX::Synth::Filter, 112
  - CX::Synth::FIRFilter, 114
  - CX::Synth::Mixer, 117
  - CX::Synth::ModuleBase, 119
  - CX::Synth::Multiplier, 120
  - CX::Synth::Oscillator, 121
  - CX::Synth::SoundObjectInput, 124
  - CX::Synth::Splitter, 126
- getPartitionedTime
  - CX::CX\_Time\_t, 105
- getPositivePeak
  - CX::CX\_SoundObject, 92
- getRawDataReference
  - CX::CX\_SoundObject, 92
- getResolution
  - CX::CX\_Display, 66
- getRow
  - CX::Algo::LatinSquare, 116
- getRtAudioInstance
  - CX::CX\_SoundStream, 102
- getSampleFrameCount
  - CX::CX\_SoundObject, 92
- getSampleFrameNumber
  - CX::CX\_SoundStream, 102
- getSeed
  - CX::CX\_RandomNumberGenerator, 79
- getSlides
  - CX::CX\_SlidePresenter, 88
- getSoundObject
  - CX::CX\_SoundObjectRecorder, 99
- getStoredType
  - CX::CX\_DataFrameCell, 58
- getStreamLatency
  - CX::CX\_SoundStream, 102
- getTotalSampleCount
  - CX::CX\_SoundObject, 92
- HarmonicAmplitudeType
  - CX::Synth::AdditiveSynth, 37
- hasSwappedSinceLastCheck
  - CX::CX\_Display, 66
  - CX::CX\_SoundStream, 102
- incorrectFrameCounts
  - CX::CX\_SlidePresenter::PresentationErrorInfo, 122
- Input
  - Entry Point, 15
- Input Devices, 17
- intVector
  - CX::Util, 32
- isAutomaticallySwapping
  - CX::CX\_Display, 66
- isKeyPressed
  - CX::CX\_Keyboard, 70
- isLoadedSuccessfully
  - CX::CX\_SoundObject, 92
- isReadyToPlay
  - CX::CX\_SoundObject, 92
- JoystickEventType
  - CX::CX\_Joystick::Event, 110
- key
  - CX::CX\_Keyboard::Event, 111
- KeyboardEventType
  - CX::CX\_Keyboard::Event, 111
- level
  - CX::CX\_Logger, 73
- levelForAllModules
  - CX::CX\_Logger, 73
- levelForConsole
  - CX::CX\_Logger, 73
- levelForFile
  - CX::CX\_Logger, 73
- listDevices
  - CX::CX\_SoundStream, 103
- loadFile
  - CX::CX\_SoundObject, 92
- Log
  - Entry Point, 15
- log
  - CX::CX\_Logger, 75
- MOVED
  - CX::CX\_Mouse::Event, 109
- modularSynth.cpp, 131

- MouseEventType
  - CX::CX\_Mouse::Event, 109
- multiplyAmplitudeBy
  - CX::CX\_SoundObject, 94
- multiplySpeed
  - CX::CX\_SoundObject, 94
- nBack.cpp, 131
- normalize
  - CX::CX\_SoundObject, 94
- notice
  - CX::CX\_Logger, 75
- now
  - CX::CX\_Clock, 44
- operator<<
  - CX, 24
- operator>>
  - CX::Synth::ModuleBase, 119
- operator()
  - CX::CX\_DataFrame, 52
  - CX::Util::CX\_CoordinateConverter, 46
  - CX::Util::CX\_DegreeToPixelConverter, 62
  - CX::Util::CX\_LengthToPixelConverter, 72
- operator+=
  - CX::Algo::LatinSquare, 116
- operator=
  - CX::CX\_DataFrame, 52
  - CX::CX\_DataFrameCell, 58
- PRESSED
  - CX::CX\_Keyboard::Event, 111
  - CX::CX\_Mouse::Event, 109
- PROPAGATE\_DELAYS
  - CX::CX\_SlidePresenter, 86
- pixelsToDegrees
  - CX::Util, 32
- play
  - CX::CX\_SoundObjectPlayer, 97
- pollEvents
  - CX::CX\_InputManager, 67
  - CX::CX\_Joystick, 69
- precisionTest
  - CX::CX\_Clock, 45
- print
  - CX::Algo::LatinSquare, 116
  - CX::CX\_DataFrame, 52
- printToFile
  - CX::CX\_DataFrame, 54
- pruneLowAmplitudeHarmonics
  - CX::Synth::AdditiveSynth, 37
- RELEASED
  - CX::CX\_Keyboard::Event, 111
  - CX::CX\_Mouse::Event, 109
- REPEAT
  - CX::CX\_Keyboard::Event, 111
- RNG
  - Entry Point, 15
- randomDouble
  - CX::CX\_RandomNumberGenerator, 79
- randomExclusive
  - CX::CX\_RandomNumberGenerator, 79
- randomInt
  - CX::CX\_RandomNumberGenerator, 81
- Randomization, 18
- readFromFile
  - CX::CX\_DataFrame, 54
- reorderLeft
  - CX::Algo::LatinSquare, 116
- reorderRight
  - CX::Algo::LatinSquare, 116
- reorderRows
  - CX::CX\_DataFrame, 55
- repeat
  - CX::Util, 32, 33
- resample
  - CX::CX\_SoundObject, 94
- reset
  - CX::Util::CX\_TrialController, 107
- reverse
  - CX::CX\_SoundObject, 94
- reverseColumns
  - CX::Algo::LatinSquare, 116
- reverseRows
  - CX::Algo::LatinSquare, 117
- round
  - CX::Util, 33
- rows
  - CX::Algo::LatinSquare, 117
- runExperiment
  - Entry Point, 15
- SCROLLED
  - CX::CX\_Mouse::Event, 109
- sample
  - CX::CX\_RandomNumberGenerator, 81, 82
- sampleBinomialRealizations
  - CX::CX\_RandomNumberGenerator, 82
- sampleNormalRealizations
  - CX::CX\_RandomNumberGenerator, 82
- sampleRate
  - CX::CX\_SoundStream::Configuration, 43
- sampleRealizations
  - CX::CX\_RandomNumberGenerator, 83
- sampleUniformRealizations
  - CX::CX\_RandomNumberGenerator, 83
- saveFboToFile
  - CX::Util, 33

sequence  
    CX::Util, 33  
sequenceAlong  
    CX::Util, 34  
sequenceSteps  
    CX::Util, 34  
setAmplitudes  
    CX::Synth::AdditiveSynth, 37  
setAxisInversion  
    CX::Util::CX\_CoordinateConverter, 46  
setChannelCount  
    CX::CX\_SoundObject, 94  
setCurrentFunction  
    CX::Util::CX\_TrialController, 107  
setCursorPosition  
    CX::CX\_Mouse, 77  
setData  
    CX::Synth::ModuleBase, 119  
setFromVector  
    CX::CX\_SoundObject, 95  
setFullScreen  
    CX::CX\_Display, 66  
setGain  
    CX::Synth::Multiplier, 120  
setGeneratorFunction  
    CX::Synth::Oscillator, 121  
setHarmonicSeries  
    CX::Synth::AdditiveSynth, 39  
setLength  
    CX::CX\_SoundObject, 95  
setMessageFlushCallback  
    CX::CX\_Logger, 75  
setMultiplier  
    CX::Util::CX\_CoordinateConverter, 47  
setOrigin  
    CX::Util::CX\_CoordinateConverter, 47  
setRowCount  
    CX::CX\_DataFrame, 55  
setSeed  
    CX::CX\_RandomNumberGenerator, 83  
setSoundObject  
    CX::CX\_SoundObjectRecorder, 99  
setStandardHarmonicSeries  
    CX::Synth::AdditiveSynth, 39  
setTime  
    CX::CX\_SoundObjectPlayer, 97  
    CX::Synth::SoundObjectInput, 124  
setUnitConverter  
    CX::Util::CX\_CoordinateConverter, 47  
setWindowResolution  
    CX::CX\_Display, 66  
setWindowTitle  
    CX::CX\_Display, 66  
setup  
    CX::CX\_Display, 66  
    CX::CX\_InputManager, 68  
    CX::CX\_Joystick, 69  
    CX::CX\_SlidePresenter, 88, 89  
    CX::CX\_SoundObjectPlayer, 97  
    CX::CX\_SoundObjectRecorder, 99  
    CX::CX\_SoundStream, 103  
showCursor  
    CX::CX\_Mouse, 77  
shuffleRows  
    CX::CX\_DataFrame, 55  
shuffleVector  
    CX::CX\_RandomNumberGenerator, 84  
Sound, 19  
squircleToPath  
    CX::Draw, 27  
star  
    CX::Draw, 27  
starToPath  
    CX::Draw, 28  
start  
    CX::CX\_SoundStream, 103  
startPlayingAt  
    CX::CX\_SoundObjectPlayer, 97  
startRecording  
    CX::CX\_SoundObjectRecorder, 99  
startSlidePresentation  
    CX::CX\_SlidePresenter, 89  
stop  
    CX::CX\_SoundObjectPlayer, 97  
    CX::CX\_SoundStream, 103  
stopRecording  
    CX::CX\_SoundObjectRecorder, 99  
store  
    CX::CX\_DataFrameCell, 58  
storeVector  
    CX::CX\_DataFrameCell, 60  
streamOptions  
    CX::CX\_SoundStream::Configuration, 43  
stripLeadingSilence  
    CX::CX\_SoundObject, 95  
swapColumns  
    CX::Algo::LatinSquare, 117  
swapFrontAndBackBuffers  
    CX::CX\_Display, 67  
swapRows  
    CX::Algo::LatinSquare, 117  
SwappingMode  
    CX::CX\_SlidePresenter::Configuration, 42  
timestamps  
    CX::CX\_Logger, 75  
Timing, 20  
    Clock, 20

to

CX::CX\_DataFrameCell, [60](#)

toVector

CX::CX\_DataFrameCell, [60](#)

update

CX::CX\_SlidePresenter, [89](#)

CX::Util::CX\_TrialController, [107](#)

Utility, [21](#)

validate

CX::Algo::LatinSquare, [117](#)

vectorToString

CX::Util, [34](#)

verbose

CX::CX\_Logger, [75](#)

Video, [22](#)

warning

CX::CX\_Logger, [75](#)

writeToFile

CX::CX\_SoundObject, [95](#)

CX::Util, [35](#)