A Degenerated Continuum Rayleigh-Ritz Framework for the Free Vibration and Stability of Rotating Compressor Blade

Or

Free Vibration Analysis of a Rotating, Pre-twisted, Cambered, and Tapered NACA 6412 Airfoil Compressor Blade

Saroj Basnet[1], Bir Bahadur Chaudhary, Sachin Saud, Mahesh Chandra Luitel, Bikki Chhantyal[5]

[1]Department of Mechanical and Aerospace Engineering, Pulchowk Campus, Institute of Engineering, Tribhuvan University, Nepal

[i]Department of Automobile and Mechanical Engineering, Thapathali Campus, Institute of Engineering, Tribhuvan University, Nepal

……

Abstract

A semi-analytical framework is developed for the free vibration and dynamic stability analysis of rotating compressor blades modelled as pre-twisted, tapered, and cambered NACA four-digit airfoil shells. The blade geometry is described using an exact parametric mid-surface mapping with analytically evaluated derivatives, while three-dimensional strains are obtained from the displacement gradient using the inverse mapping Jacobian. A five-field first-order shear deformation model is discretised using the Rayleigh–Ritz method with Jacobi and Legendre polynomial basis functions. Singularities associated with the NACA leading-edge thickness and discontinuities in camber curvature are addressed through specialised coordinate transformations and domain subdivision.

Rotational effects are incorporated through centrifugal prestress, geometric stiffness, Coriolis coupling, and spin-softening. The resulting quadratic eigenvalue problem is solved using an energy-scaled formulation to improve numerical stability and capture divergence-type instabilities. The framework is validated against three-dimensional finite element analyses (ANSYS) and published benchmarks.

The integrated blade mass and volume agree with three-dimensional CAD models within 0.22%. A (6×6) Ritz order (180 degrees of freedom) predicts natural frequencies within 0.07% for the fundamental mode and 0.88% across the primary modes at rotational speeds up to 4,000 rpm. At speeds up to 20,000 rpm, the maximum frequency error remains below 0.84%. Comparisons with published benchmarks yield an RMSE below 0.43%, compared with 1.88% for existing formulations. The proposed framework provides an accurate and computationally efficient approach to predicting the vibration characteristics and dynamic stability of rotating compressor blades.

Keywords: *rotating blade; pre-twist; degenerated shell; first-order shear deformation theory; Rayleigh–Ritz; Jacobi polynomials; centrifugal stiffening; Coriolis effect; gyroscopic eigenvalue problem; dynamic stability; NACA airfoil.*

1. Introduction

1.1 Background

Compressor and turbine blades operate in a rotating frame under centrifugal loads that alter their stiffness, couple their bending and torsional motions, and, through Coriolis acceleration, render the governing operator gyroscopic. Accurate prediction of the rotating natural frequencies and of the Campbell diagram is a prerequisite for avoiding resonant engine orders and for high-cycle-fatigue assessment [1–4]. The subject has a long history. Southwell and Gough [5] gave the first estimate of centrifugal stiffening for airscrew blades. Carnegie [6,7] formulated energy expressions for pre-twisted rotating cantilever blading, and Rao [8] consolidated the beam-based literature. Beam models with pre-twist, taper, and Coriolis coupling have since been refined extensively [9–17], and surveys are available [18,19].

Beam theory is inadequate when the blade aspect ratio is low, the chordwise flexibility is significant, or camber and thickness variation across the chord control the modal content. Plate and shell descriptions were therefore introduced. Dokainish and Rawtani [20] analyzed rotating cantilever plates by finite elements; Sreenivasamurthy and Ramamurti

[21] examined the Coriolis effect on rotating low-aspect-ratio plates; Ramamurti and Kielb [22] treated twisted rotating plates; Leissa and co-workers [23–26] developed Ritz solutions for cantilevered shallow shells, twisted rotating blades, and three-dimensional twisted parallelepipeds; Yoo and co-workers [27,28] derived modal characteristics of rotating rectangular plates; Hu et al. [29], Kee and Kim [30], Sinha and Turner [31], and Sun et al. [32,33] extended shell models to pre-twisted, cambered, and staggered blades. Reviews of shell vibration [34,35] document the breadth of this literature.

1.2 Gap in the literature

Two limitations recur in the shell-based rotating-blade literature.

First, the majority of analytical and semi-analytical shell formulations rest on classical two-dimensional shell theories (Love–Kirchhoff, Donnell, Sanders, Reissner–Mindlin resultant theories) [36–39]. These theories express the metric through Lamé parameters A_1, A_2 and principal curvatures R_1, R_2, which are available in closed form only for canonical geometries (cylindrical, conical, spherical, shallow doubly-curved panels). A pre-twisted, tapered, cambered airfoil surface has non-orthogonal parametric lines, non-constant Gaussian curvature, and a thickness that varies in both directions. Fitting such a surface into a Lamé-parameter framework requires either approximating the geometry (shallow-shell or "twisted plate" assumptions) or deriving lengthy problem-specific curvature expressions that are prone to error and do not generalyze.

Second, formulations that do treat the geometry exactly, the degenerated-continuum shell elements of Ahmad, Irons and Zienkiewicz [40] and their descendants [41-45] are implemented almost exclusively within the finite element method. The geometric exactness is achieved by interpolating nodal coordinates and nodal directors, which ties the formulation to a mesh, introduces the well-known locking pathologies of low-order shell elements, and forfeits the compactness and convergence rate of global approximation.

The Rayleigh–Ritz method with orthogonal polynomial admissible functions [46–50] delivers exponential convergence for smooth problems with a small number of degrees of freedom and has been applied successfully to plates and shells of canonical geometry. Its use for rotating blades has, however, remained coupled to classical shell kinematics, and its potential in combination with an exact three-dimensional mapping has not been exploited.

1.3 Proposed approach and contributions

This paper closes the gap by combining the two ingredients. The blade is described as a degenerated three-dimensional continuum: the mid-surface position vector and its analytic derivatives, the exact unit normal and its derivatives, and the through-thickness offset define a three-dimensional Jacobian $\mathbf{J}(x, \eta, \zeta)$ that is inverted at every quadrature point. Strains are then the components of the exact Cartesian displacement gradient, rotated into a local orthonormal frame, with the transverse normal strain removed by the plane-stress condition. The displacement field follows a five-parameter first-order shear deformation theory (FSDT) [36,37,51]: three global Cartesian translations of the mid-surface and two director rotations expressed in the local frame. The unknown fields are expanded globally over the whole blade with L_2-orthonormal Jacobi–Legendre tensor products; the span functions vanish identically at the root, so the clamped condition is satisfied exactly for all five fields.

Rotation is treated in the blade-fixed frame [52–54]. The centrifugal body force is integrated consistently to a load vector, a three-dimensional static equilibrium problem is solved, the resulting Cauchy stress tensor is evaluated at every volume quadrature point, and the initial-stress (geometric) stiffness matrix is assembled from it. The Coriolis acceleration produces a skew-symmetric gyroscopic matrix and the centripetal acceleration a spin-softening matrix. The quadratic eigenvalue problem is solved by an energy-scaled reformulation that exploits the structure of conservative gyroscopic systems [55–58].

The contributions are:

i. A Lamé-parameter-free shell formulation for pre-twisted, tapered, cambered airfoil blades in which the geometry enters solely through $\mathbf{r}(x, \eta)$ and its analytic derivatives.
ii. A global Rayleigh–Ritz discretization of a degenerated-continuum shell using orthonormal Jacobi and Legendre polynomials, with exact enforcement of the clamped root and a well-conditioned mass matrix by construction.

iii. A prestress-consistent treatment of centrifugal stiffening in which the full three-dimensional stress state from a static equilibrium solution drives the geometric stiffness.
iv. An energy-scaled Hermitian gyroscopic eigensolver that yields exactly imaginary eigenvalues for the stable regime and switches to a scaled general solve that retains growth rates when stiffness loses positive-definiteness, together with residual-based verification of every eigenpair.

The remainder of this paper is structured as follows. Section 2 establishes the analytical differential geometric mapping for the tapered, pre-twisted, and curved NACA 6412 blade mid-surface. Section 3 presents the First-Order Shear Deformation Theory (FSDT) shell kinematics, elastic strain energy, and the rotational potential energy contributions, including centrifugal stiffening, spin-softening, and Coriolis coupling. Section 4 details the numerical implementation, covering the orthonormal Jacobi–Legendre Ritz basis discretization, the 3D singularity-aware quadrature scheme, and the energy-scaled Hermitian eigensolution procedure. Section 5 evaluates the framework through geometric verification, numerical convergence testing, non-rotating and rotating finite element validations against 3D ANSYS models, and parametric Campbell diagram stability analyses. Finally, Section 6 summarizes the primary findings and conclusions.

2. Blade Geometry

2.1 Coordinate systems

A right-handed global Cartesian frame (X, Y, Z) with unit vectors $\mathbf{e}_X, \mathbf{e}_Y, \mathbf{e}_Z$ is fixed to the rotor and rotates with it at constant angular velocity $\boldsymbol{\Omega} = \Omega\,\mathbf{e}_Y$, $\Omega = 2\pi N/60$, where N is the rotor speed in rpm. The blade span is directed along X (radial direction), starting at the hub radius R_h. The stacking (pre-twist) axis is the radial line $Y = Z = 0$. The mid-surface is parametrized by the span coordinate $x \in [0, L]$ and the dimensionless chord coordinate $\eta \in [0,1]$, measured from the leading edge ($\eta = 0$) to the trailing edge ($\eta = 1$). The through-thickness coordinate is $\zeta \in [-h/2\,,\, h/2]$.




Figure 1. Rotating coordinate systems and mid-surface geometric mapping: Global rotating reference frame (X, Y, Z) with angular velocity $\boldsymbol{\Omega} = \Omega\mathbf{e}_Y$, radial hub radius R_h, and local shell coordinates (x, η, ζ) defined on the pre-twisted compressor blade mid-surface.

2.2 Section profile

The section profile is a NACA four-digit airfoil [59,60] specified by maximum camber m (first digit, percent of chord), camber position p (second digit, tenths of chord), and maximum thickness-to-chord ratio τ (last two digits, percent of chord). The camber line $f(\eta)$ and its second derivative $f''(\eta)$ are given by:

$$f(\eta) = \begin{cases} \dfrac{m}{p^2}(2p\eta - \eta^2), & \eta \le p \\ \dfrac{m}{(1-p)^2}(1 - 2p + 2p\eta - \eta^2), & \eta > p \end{cases}, \qquad f''(\eta) = \begin{cases} -\dfrac{2m}{p^2}, & \eta \le p \\ -\dfrac{2m}{(1-p)^2}, & \eta > p \end{cases}, \tag{1}$$

so that $f(\eta)$and $f'(\eta)$are continuous across the chord, whereas $f''(\eta)$ exhibits a finite jump discontinuity at $\eta = p$. The section thickness distribution $h_0(\eta)$ is defined as:

$$h_0(\eta) = 10\,\tau\,c\big(0.2969\sqrt{\eta} - 0.1260\,\eta - 0.3516\,\eta^2 + 0.2843\,\eta^3 + a_4\,\eta^4\big), \tag{2}$$

with $a_4 = -0.1015$ for the standard finite trailing-edge thickness and $a_4 = -0.1036$ for a closed trailing edge. The $\sqrt{\eta}$ term produces the rounded leading edge and introduces an integrable singularity in $\partial h_0/\partial\eta$ at $\eta = 0$.

2.3 Spanwise variation: taper and pre-twist

The section chord tapers linearly along the span according to $c(x) = c_0(1 - \tau_c x/L)$, while the thickness is scaled independently as $h(x,\eta) = h_0(x,\eta)(1 - \tau_h x/L)$, where c_0 is the root chord length, and $\tau_c, \tau_h \in [0, 1)$ denote the non-dimensional chord and thickness taper fractions, respectively.

Each cross-section is rotated about the spanwise stacking axis by the linearly varying angle:

$$\theta(x) = \theta_0 + \kappa x, \qquad \kappa = \frac{\theta_{tip}}{L}, \tag{3}$$

where θ_0 is the root stagger angle, θ_{tip} is the total relative tip pre-twist, and κ represents the constant spanwise twist rate. The corresponding section-fixed unit vectors $\mathbf{e}_y(x)$ and $\mathbf{e}_z(x)$ in the rotating frame are given by:

$$\mathbf{e}_y(x) = \begin{bmatrix} 0 \\ \cos\theta\,(x) \\ \sin\theta\,(x) \end{bmatrix}, \qquad \mathbf{e}_z(x) = \begin{bmatrix} 0 \\ -\sin\theta\,(x) \\ \cos\theta\,(x) \end{bmatrix}. \tag{4}$$

The radial stacking axis pierces each section on its camber line at the non-dimensional chord fraction η_a. The camber line ordinate is shifted so that this point coincides with the origin of the local section plane, $\hat{f}(\eta) = f(\eta) - f(\eta_a)$, and the chordwise offset from the stacking axis is defined as $a(\eta) = \eta - \eta_a$.

2.4 Mid-surface mapping and analytic derivatives

The 3D mid-surface position vector $\mathbf{r}(x,\eta)$ of any point on the blade shell is given by:

$$\mathbf{r}(x,\eta) = (R_h + x)\,\mathbf{e}_X + c(x)\big[a(\eta)\,\mathbf{e}_y(x) + \hat{f}(\eta)\,\mathbf{e}_z(x)\big]. \tag{5}$$

To streamline partial differentiation, two orthogonal section auxiliary vectors $\mathbf{v}(x,\eta)$ and $\mathbf{w}(x,\eta)$ are introduced:

$$\mathbf{v}(x,\eta) = a(\eta)\mathbf{e}_y(x) + \hat{f}(\eta)\mathbf{e}_z(x), \qquad \mathbf{w}(x,\eta) = a(\eta)\mathbf{e}_z(x) - \hat{f}(\eta)\mathbf{e}_y(x). \tag{6}$$

Because the section triad differentiates as $\partial\mathbf{e}_y/\partial x = \kappa\mathbf{e}_z$ and $\partial\mathbf{e}_z/\partial x = -\kappa\mathbf{e}_y$, these auxiliary vectors satisfy $\partial\mathbf{v}/\partial x = \kappa\mathbf{w}$ and $\partial\mathbf{w}/\partial x = -\kappa\mathbf{v}$.

The first covariant mid-surface tangent vectors are evaluated analytically as:

$$\mathbf{r}_{,x} = \frac{\partial\mathbf{r}}{\partial x} = \mathbf{e}_X + c'(x)\mathbf{v} + c(x)\kappa\mathbf{w}, \qquad \mathbf{r}_{,\eta} = \frac{\partial\mathbf{r}}{\partial\eta} = c(x)\big(\mathbf{e}_y + f'(\eta)\mathbf{e}_z\big), \tag{7}$$

where $c'(x) = -c_0\tau_c/L$ is the constant chord taper derivative along the span. Differentiating Eq. (7) yields the second partial surface derivatives:

$$\begin{aligned} \mathbf{r}_{,xx} &= 2c'(x)\kappa\mathbf{w} - c(x)\kappa^2\mathbf{v} \\ \mathbf{r}_{,x\eta} &= c'(x)\big(\mathbf{e_y} + f'(\eta)\mathbf{e_z}\big) + c(x)\kappa\big(\mathbf{e_z} - f'(\eta)\mathbf{e_y}\big) \\ \mathbf{r}_{,\eta\eta} &= c(x)f''(\eta)\mathbf{e_z}. \end{aligned} \tag{8}$$

The unnormalized surface normal vector is $\mathbf{g} = \mathbf{r}_{,x} \times \mathbf{r}_{,\eta}$, the surface Jacobian determinant is $j = \| \mathbf{g} \| > 0$, and the unit normal vector $\mathbf{n}$ is:

$$\mathbf{n} = \frac{\mathbf{r}_{,x} \times \mathbf{r}_{,\eta}}{j}. \tag{9}$$

Differentiating Eq. (9) with respect to surface parametric coordinates $\alpha \in \{x, \eta\}$ and projecting out the normal component yields the spatial derivatives of the unit normal vector:

$$\mathbf{n}_{,\alpha} = \frac{\mathbf{1}}{j}\big[\mathbf{g}_{,\alpha} - \mathbf{n}\big(\mathbf{n} \cdot \mathbf{g}_{,\alpha}\big)\big], \tag{10}$$

where the partial derivatives of the unnormalized surface normal cross-product $\mathbf{g}_{,x}$ and $\mathbf{g}_{,\eta}$ are given by:

$$\mathbf{g}_{,x} = \mathbf{r}_{,xx} \times \mathbf{r}_{,\eta} + \mathbf{r}_{,x} \times \mathbf{r}_{,x\eta}, \qquad \mathbf{g}_{,\eta} = \mathbf{r}_{,x\eta} \times \mathbf{r}_{,\eta} + \mathbf{r}_{,x} \times \mathbf{r}_{,\eta\eta}. \tag{11}$$

2.5 Local orthonormal frame

At every mid-surface point, a right-handed orthonormal triad $\mathbf{Q} = [\mathbf{e}_1\ \mathbf{e}_2\ \mathbf{e}_3]$ is constructed with

$$\mathbf{e}_1 = \frac{\mathbf{r}_{,x}}{\| \mathbf{r}_{,x} \|}, \qquad \mathbf{e}_3 = \mathbf{n}, \qquad \mathbf{e}_2 = \mathbf{e}_3 \times \mathbf{e}_1. \tag{12}$$

The spatial partial derivatives of the frame $\mathbf{Q}_{,x}$ and $\mathbf{Q}_{,\eta}$(or $\mathbf{Q}_{,\alpha}$ for $\alpha \in \{x, \eta\}$) are evaluated analytically using the same projection operator applied in Eq. (10) alongside the product rule for the cross product:

$$\mathbf{e}_{1,\alpha} = \frac{1}{\| \mathbf{r}_{,x} \|}(\mathbf{I} - \mathbf{e}_1\mathbf{e}_1^{\mathrm{T}})\mathbf{r}_{,x\alpha}, \qquad \mathbf{e}_{3,\alpha} = \mathbf{n}_{,\alpha}, \qquad \mathbf{e}_{2,\alpha} = \mathbf{n}_{,\alpha} \times \mathbf{e}_1 + \mathbf{n} \times \mathbf{e}_{1,\alpha}, \tag{13}$$

where $\mathbf{I}$ is the 3×3 identity matrix and $\mathbf{e}_1\mathbf{e}_1^{\mathrm{T}}$ denotes the outer product projection tensor.

The availability of $\mathbf{Q}_{,\alpha}$ in exact closed form is essential to the degenerated continuum formulation: the director rotations of the First-Order Shear Deformation Theory (FSDT) kinematics are resolved directly within this local frame, and their spatial derivatives require the spatial derivatives of the frame itself. Consequently, no Lamé parameters (A_1, A_2), Christoffel symbols, or principal curvature tensors (R_1, R_2) appear anywhere in the formulation. The shell geometry is specified entirely by the mid-surface position vector $\mathbf{r}$ and its first and second analytic derivatives $\big(\mathbf{r}_{,\alpha}, \mathbf{r}_{,\alpha\beta}\big)$.

3. Mathematical Formulation

3.1 Degenerated-continuum kinematics

The 3D spatial position vector $\mathbf{X}(x, \eta, \zeta)$ of any material point within the solid blade volume in the reference configuration is expressed as:

$$\mathbf{X}(x, \eta, \zeta) = \mathbf{r}(x, \eta) + \zeta\,\mathbf{n}(x, \eta), \tag{14}$$

where $\mathbf{r}(x, \eta)$ is the mid-surface position vector, $\mathbf{n}(x, \eta)$ is the unit surface normal, and $\zeta \in [-h/2, h/2]$ is the through-thickness coordinate.

The exact 3D Jacobian matrix $\mathbf{J}$ of the parametric mapping $(x, \eta, \zeta) \mapsto \mathbf{X}$ is evaluated by differentiating Eq. (14) with respect to (x, η, ζ):

$$\mathbf{J} = \left[\mathbf{r}_{,x} + \zeta \mathbf{n}_{,x} \middle| \mathbf{r}_{,\eta} + \zeta \mathbf{n}_{,\eta} \middle| \mathbf{n} \right], \qquad \det \mathbf{J} > 0. \tag{15}$$

The determinant $\det \mathbf{J}$ represents the local volume transformation ratio from the parametric domain to 3D physical space. In the numerical solver, $\det \mathbf{J}$ is monitored at every 3D quadrature point; a non-positive value $(\det \mathbf{J} \leq 0)$indicates that the local shell thickness exceeds the minimum radius of curvature, signaling geometric self-intersection where the degenerated continuum description loses physical validity.

3.2 FSDT displacement field and kinematic relations

The displacement field follows a five-parameter First-Order Shear Deformation Theory (FSDT) [36,37,51]:

$$\mathbf{u}(x, \eta, \zeta) = \mathbf{u}_0(x, \eta) + \zeta[\phi_1(x, \eta)\, \mathbf{e}_1(x, \eta) + \phi_2(x, \eta)\, \mathbf{e}_2(x, \eta)], \tag{16}$$

where $\mathbf{u}_0 = (u, v, w)^T$ denotes the vector of global Cartesian translations of the mid-surface, and ϕ_1, ϕ_2 are the director rotations resolved in the local tangent frame $(\mathbf{e_1}, \mathbf{e_2})$. The drilling rotation is omitted, and the director is inextensible $(\varepsilon_{33} = 0)$, which is consistent with the plane-stress material constitutive law adopted below.

The partial derivatives of the displacement field with respect to the parametric coordinates are evaluated analytically as:

$$\mathbf{u}_{,x} = \mathbf{u}_{0,x} + \zeta\left(\phi_{1,x}\mathbf{e}_1 + \phi_1\mathbf{e}_{1,x} + \phi_{2,x}\mathbf{e}_2 + \phi_2\mathbf{e}_{2,x}\right), \qquad \mathbf{u}_{,\zeta} = \phi_1\mathbf{e}_1 + \phi_2\mathbf{e}_2, \tag{17}$$

with the spanwise derivative $\mathbf{u}_{,\eta}$ defined analogously. The frame-derivative terms $\phi_\alpha \mathbf{e}_{\alpha,x}$ and $\phi_\alpha \mathbf{e}_{\alpha,\eta}$ capture the exact kinematic coupling between director rotations and the 3D twist, taper, and camber of the shell surface. These are precisely the terms that classical shell theories approximate through assumed curvature tensors and Lamé parameters.

The global 3D Cartesian displacement gradient tensor $\nabla_X \mathbf{u}$ is evaluated using the inverse 3D Jacobian:

$$\nabla_X \mathbf{u} = \left[\mathbf{u}_{,x}\ \mathbf{u}_{,\eta}\ \mathbf{u}_{,\zeta}\right]\mathbf{J}^{-1}. \tag{18}$$

Transforming this gradient into the local orthonormal material frame $\mathbf{Q} = [\mathbf{e}_1\ \ \mathbf{e}_2\ \ \mathbf{e}_3]$ yields the local displacement gradient matrix $\mathbf{H}$:

$$\mathbf{H} = \mathbf{Q}^T(\nabla_X \mathbf{u})\mathbf{Q}. \tag{19}$$

In the computational implementation, the product $\mathbf{J}^{-1}\mathbf{Q}$ is evaluated via one 3×3 linear system solve per quadrature point, after which the spatial gradient along the local material directions is directly available for constructing both the strain–displacement operator matrix and the initial-stress geometric stiffness matrix.

The 5-component 3D engineering strain vector $\boldsymbol{\varepsilon}$ used with the plane-stress constitutive law is extracted from $\mathbf{H}$ as:

$$\boldsymbol{\varepsilon} = \begin{bmatrix} \varepsilon_{11} \\ \varepsilon_{22} \\ \gamma_{12} \\ \gamma_{13} \\ \gamma_{23} \end{bmatrix} = \begin{bmatrix} H_{11} \\ H_{22} \\ H_{12} + H_{21} \\ H_{13} + H_{31} \\ H_{23} + H_{32} \end{bmatrix} = \mathbf{B}(x, \eta, \zeta)\mathbf{q} \tag{20}$$

where $\mathbf{q}$ is the global vector of Ritz expansion coefficients, and $\mathbf{B}(x, \eta, \zeta)$ is the spatial strain–displacement operator matrix. The transverse normal strain ε_{33} is eliminated by enforcing the plane-stress condition $\sigma_{33} = 0$.

Because ζ is treated as an independent coordinate in the spatial differentiation of Eq. (16), the spanwise and chordwise variation of thickness enters exclusively through the integration domain limits and the volume determinant $\det \mathbf{J}$, rather than through artificial derivatives in the strain operator, a distinction that is automatic in the degenerated continuum formulation but must be imposed manually in resultant-based shell theories.

3.3 Constitutive relation

For an isotropic, homogeneous material with Young's modulus E, Poisson's ratio ν, and shear modulus $G = \frac{E}{[2(1+\nu)]}$, the plane-stress constitutive matrix **C**, in the local frame is:

$$\mathbf{C} = \begin{bmatrix} \frac{E}{1-\nu^2} & \frac{\nu E}{1-\nu^2} & 0 & 0 & 0 \\ \frac{\nu E}{1-\nu^2} & \frac{E}{1-\nu^2} & 0 & 0 & 0 \\ 0 & 0 & G & 0 & 0 \\ 0 & 0 & 0 & k_s G & 0 \\ 0 & 0 & 0 & 0 & k_s G \end{bmatrix}, \tag{21}$$

with the shear correction factor $k_s = \pi^2/12$ [37,61]. The transverse shear correction compensates for the constant through-thickness distribution of γ_{13}, γ_{23} implied by Eq. (16).

3.4 Energy functionals in the rotating frame

Let **S** denote the skew-symmetric spin matrix corresponding to the angular velocity vector $\boldsymbol{\Omega} = \Omega \mathbf{e}_Y$, satisfying $\mathbf{S}\mathbf{a} = \boldsymbol{\Omega} \times \mathbf{a}$ for any vector **a**:

$$\mathbf{S} = \begin{bmatrix} 0 & 0 & \Omega \\ 0 & 0 & 0 \\ -\Omega & 0 & 0 \end{bmatrix}, \qquad \mathbf{S}^{\mathsf{T}}\mathbf{S} = -\mathbf{S}^2. \tag{22}$$

The absolute acceleration **a** of a material point observed within the rotating reference frame is expressed as:

$$\mathbf{a} = \ddot{\mathbf{u}} + 2\mathbf{S}\dot{\mathbf{u}} + \mathbf{S}\mathbf{S}(\mathbf{X} + \mathbf{u}), \tag{23}$$

comprising the relative acceleration $\ddot{\mathbf{u}}$, the Coriolis acceleration $2\mathbf{S}\dot{\mathbf{u}}$, and the centripetal acceleration $\mathbf{S}^2(\mathbf{X} + \mathbf{u})$.

Expressing the continuous displacement field in discretized form as $\mathbf{u}(x, \eta, \zeta, t) = \mathbf{U}(x, \eta, \zeta)\mathbf{q}(t)$, where **U** is the $3 \times n$ global displacement operator constructed from the Ritz basis polynomials and local director frame, application of D'Alembert's principle of virtual work:

$$\int_V \rho \; \delta\mathbf{u}^{\mathsf{T}}\mathbf{a} \, dV + \int_V \delta\boldsymbol{\varepsilon}^{\mathsf{T}}\boldsymbol{\sigma} \, dV = 0, \tag{24}$$

yields the semi-discrete non-linear governing equations of motion:

$$\mathbf{M}\ddot{\mathbf{q}} + \mathbf{G}\dot{\mathbf{q}} + (\mathbf{K}_{el} + \mathbf{K}_\sigma - \mathbf{K}_\Omega)\mathbf{q} = \mathbf{f}_c, \tag{25}$$

with the elastic stiffness matrix $\mathbf{K}_{el}$, mass matrix **M**, gyroscopic matrix **G**, spin-softening matrix $\mathbf{K}_\Omega$, and centrifugal body-force load vector $\mathbf{f}_c$ defined by the 3D volume integrals:

$$\begin{aligned} \mathbf{K}_{el} &= \int_V \mathbf{B}^{\mathsf{T}}\,\mathbf{C}\,\mathbf{B} \, dV, & \mathbf{M} &= \int_V \rho \; \mathbf{U}^{\mathsf{T}}\mathbf{U} \, dV, \\ \mathbf{G} &= 2\int_V \rho \; \mathbf{U}^{\mathsf{T}}\mathbf{S}\,\mathbf{U} \, dV, & \mathbf{K}_\Omega &= \int_V \rho \; \mathbf{U}^{\mathsf{T}}\mathbf{S}^{\mathsf{T}}\mathbf{S}\,\mathbf{U} \, dV, \\ \mathbf{f}_c &= \int_V \rho \; \mathbf{U}^{\mathsf{T}}\mathbf{S}^{\mathsf{T}}\mathbf{S}\,\mathbf{X} \, dV, \end{aligned} \tag{26}$$

where the differential volume element dV is mapped to the normalized parametric domain $\hat{\zeta} \in [-1, 1]$ as:

$$dV = \det \mathbf{J} \; \frac{h(x, \eta)}{2} \, d\hat{\zeta} \, d\eta \, dx \, . \tag{27}$$

The initial-stress geometric stiffness matrix $\mathbf{K}_\sigma$ depends on the static centrifugal stress field and is derived in detail in Section 3.5. The mass matrix $\mathbf{M}$, elastic stiffness matrix $\mathbf{K}_{el}$, and spin-softening matrix $\mathbf{K}_\Omega$ are inherently symmetric $(\mathbf{M}^T = \mathbf{M},\ \mathbf{K}_{el}^T = \mathbf{K}_{el},\ \mathbf{K}_\Omega^T = \mathbf{K}_\Omega)$, whereas the gyroscopic matrix $\mathbf{G}$ is skew-symmetric $(\mathbf{G}^T = -\mathbf{G})$; these exact structural symmetries are enforced post-assembly to eliminate numerical round-off asymmetries. The negative sign of $\mathbf{K}_\Omega$ reflects the physical phenomenon of spin softening: the centripetal term $\mathbf{S}^2\mathbf{u} = -\mathbf{S}^T\mathbf{S}\mathbf{u}$ acts to reduce the effective dynamic restoring stiffness for structural displacements perpendicular to the spin axis. Furthermore, because the displacement operator $\mathbf{U}$ naturally incorporates the ζ-weighted director rotation components from FSDT kinematics, both the translational and rotary inertia of the shell cross-section are captured consistently across $\mathbf{M}$, $\mathbf{G}$, and $\mathbf{K}_\Omega$, and the centrifugal body load vector $\mathbf{f}_c$ inherently includes the steady overturning moment generated by the through-thickness offset of the body force.

3.5 Prestress-consistent geometric stiffness

Centrifugal stiffening arises from the interaction of the steady stress field with the second-order (rotation) part of the strain. Rather than adopting a beam-type axial-force approximation or a membrane-resultant approximation, the present formulation evaluates the complete three-dimensional stress state produced by the centrifugal load and integrates it against the full displacement gradient.

Static equilibrium. The steady deformation $\mathbf{q}_0$ on the reference geometry is obtained from:

$$\mathbf{K}_{el}\,\mathbf{q}_0 = \mathbf{f}_c, \tag{28}$$

solved in mass-normalized coordinates (Section 4.4) after verification that the balanced stiffness admits a Cholesky factorization; failure indicates that the reference configuration is not a stable static state and that a nonlinear equilibrium path would be required. The relative residual $(\|\mathbf{K}_{el}\,\mathbf{q}_0 - \mathbf{f}_c\|)/\|\mathbf{f}_c\|$ is recorded as a solution diagnostic.

Stress recovery. At every volume quadrature point, the 5-component strain vector $\boldsymbol{\varepsilon}_0 = \mathbf{B}\mathbf{q}_0$ and Cauchy stress vector $\boldsymbol{\sigma}_0 = \mathbf{C}\boldsymbol{\varepsilon}_0$ are evaluated and assembled into the symmetric local stress tensor $\boldsymbol{\Sigma}_0$:

$$\boldsymbol{\Sigma}_0 = \begin{bmatrix} \sigma_{11} & \sigma_{12} & \sigma_{13} \\ \sigma_{12} & \sigma_{22} & \sigma_{23} \\ \sigma_{13} & \sigma_{23} & 0 \end{bmatrix}. \tag{29}$$

Initial-stress stiffness. Linearizing the Green–Lagrange strain about the prestressed state and retaining the quadratic term yields the classical initial-stress operator [41,45,62]:

$$\delta W_\sigma = \int_V \sigma_{ab}^0\ \delta u_{k,a}\, u_{k,b}\, dV \quad \Rightarrow \quad \mathbf{K}_\sigma = \int_V \sum_{k=1}^{3} (\nabla_\ell U_k)^T\, \boldsymbol{\Sigma}_0 (\nabla_\ell U_k) dV, \tag{30}$$

where $\nabla_l U_k$ is the row of the operator giving the derivative of the k-th Cartesian displacement component along the three local directions. All nine gradient components and all five independent stress components participate; no resultant or beam approximation is introduced. This is the sense in which the formulation is prestress-consistent: the same kinematic operator, the same quadrature, and the same three-dimensional Jacobian are used for the static solution, the stress recovery, and the geometric stiffness.

Validity of the linear reference-state approximation. Equation (28) is a linear solve on the undeformed geometry[4]. Its adequacy is checked a posteriori by three quantities reported for every analysis: the maximum linear strain $\max|\boldsymbol{\varepsilon}_0|$(threshold set at 1%), the maximum static mid-surface displacement normalized by span (threshold set at 2%), and the maximum director slope $\sqrt{\phi_1^2 + \phi_2^2}$ (threshold set at 0.05 rad). Exceedance of any threshold indicates that a geometrically non-linear equilibrium and tangent operator would be required.

3.6 Eigenvalue problem

Setting $\mathbf{f}_c$ aside (it determines the static prestress deformation $\mathbf{q}_0$ only) and substituting $\mathbf{q}(t) = \boldsymbol{\phi} e^{\lambda t}$ into the homogeneous form of Eq. (25) yields the quadratic eigenvalue problem:

$$(\lambda^2\mathbf{M} + \lambda\,\mathbf{G} + \mathbf{K})\boldsymbol{\phi} = \mathbf{0}, \qquad \mathbf{K} = \mathbf{K}_{el} + \mathbf{K}_\sigma - \mathbf{K}_\Omega. \tag{31}$$

where $\lambda \in \mathbb{C}$ is the complex eigenvalue, $\boldsymbol{\phi} \in \mathbb{C}^n$ is the corresponding eigenvector (mode shape), and $\boldsymbol{K}$ represents the combined effective stiffness matrix.

The natural cyclic frequency of a mode is $f = \mathrm{Im}(\lambda)/2\pi$ (in Hz) and its growth/decay rate is given by $\mathrm{Re}(\lambda)$. For $K \succ 0$ (strictly positive-definite total stiffness matrix), the governing system behaves as a conservative gyroscopic system whose eigenvalues are purely imaginary ($\mathrm{Re}(\lambda) = 0$) and whose motion is dynamically stable [55, 56, 63, 64]. Loss of positive-definiteness of K(which spin softening K_Ω can produce at sufficiently high rotational speeds) admits eigenvalues with a positive real part ($\mathrm{Re}(\lambda) > 0$), corresponding to divergence-type dynamic instability. Detecting and quantifying this stability boundary is a primary objective of the present solver.

4. Computational Implementation

4.1 Rayleigh–Ritz basis

Each of the five generalized displacement fields $\{u, v, w, \varphi_1, \varphi_2\}$ is expanded in the same tensor-product basis of $n_s \times n_c$ functions:

$$\psi_{ij}(x, \eta) = X_i(x)\, Y_j(\eta), \qquad i = 0, \dots, n_s - 1, \quad j = 0, \dots, n_c - 1, \tag{32}$$

yielding a total of $n = 5n_s n_c$ global degrees of freedom.

Span functions. Mapping the physical spanwise coordinate $x \in [0, L]$ to the non-dimensional interval $s = 2x/L - 1 \in [-1, 1]$, the spanwise basis functions are defined as:

$$X_i(x) = \sqrt{\frac{2i+3}{8}}\,(1+s)\,P_i^{(0,2)}(s), \tag{33}$$

where $P_i^{(\alpha,\beta)}(s)$ is the Jacobi polynomial [65,66]. The boundary factor $(1+s)$ vanishes identically at the root $x = 0$ (where $s = -1$), ensuring that every field (translations and director rotations alike) satisfies the fully clamped kinematic boundary condition identically, without requiring penalty functions or artificial spring constraint equations.

The Jacobi weight function $(1+s)^\beta$ with $\beta = 2$ naturally absorbs the square of this boundary factor, yielding exact orthonormality:

$$\int_{-1}^{1} X_i(s)\, X_k(s)\, ds = \delta_{ik}, \tag{34}$$

by virtue of the Jacobi polynomial orthogonality relation:

$$\int_{-1}^{1} (1+s)^2 P_i^{(0,2)}(s) P_k^{(0,2)}(s)\, ds = \frac{8}{2i+3}\delta_{ik}.$$

The spatial derivative with respect to s is evaluated analytically using:

$$\frac{d}{ds} P_i^{(0,2)}(s) = \frac{1}{2}(i+3) P_{i-1}^{(1,3)}(s).$$

The spanwise basis thus forms a set of L_2-orthonormal admissible functions in the sense of Bhat [46] and Liew and Lam [47]. Because these functions are obtained in exact closed form rather than via Gram–Schmidt numerical orthogonalization, they avoid the loss of orthogonality and numerical ill-conditioning that accumulate in generated recurrence sequences [50].

Chord functions. Mapping the non-dimensional chordwise coordinate $\eta \in [0, 1]$ to $t = 2\eta - 1 \in [-1, 1]$, the normalized chordwise basis functions are defined as:

$$Y_j(\eta) = \sqrt{\frac{2j+1}{2}} P_j(t), \qquad j = 0, \dots, n_c - 1, \tag{35}$$

where $P_j(t)$ denotes the standard Legendre polynomial of degree j(equivalent to the Jacobi polynomial $P_j^{(0,0)}(t)$). The chordwise functions satisfy exact L_2-orthonormality:

$$\int_0^1 Y_j(\eta) Y_l(\eta)\, d\eta = \delta_{jl}.$$

Spatial derivatives with respect to t are evaluated analytically using the Jacobi derivative identity:

$$\frac{d}{dt} P_j(t) = \frac{1}{2}(j+1) P_{j-1}^{(1,1)}(t).$$

The leading $(\eta = 0)$ and trailing $(\eta = 1)$ edges are physically free; the corresponding natural boundary conditions are satisfied variationally through the Rayleigh–Ritz energy minimization.

The combined L_2-orthonormality of both the spanwise $X_i(x)$ and chordwise $Y_j(\eta)$ basis families produces a global mass matrix that, for a flat plate of uniform thickness and orthogonal parametric lines, would be strictly diagonal. For the actual twisted, tapered airfoil shell, the mass matrix remains strongly diagonally dominant. This structural property underpins the well-conditioned mass-normalization procedure detailed in Section 4.4 and represents a decisive advantage over standard monomial or trigonometric Ritz bases, whose Gram matrices become severely ill-conditioned or numerically singular at moderate polynomial orders.

Displacement operator. For the translational fields $(k = 1, 2, 3)$, the shape operator is $\mathbf{U}^{(k)} = \mathbf{e}_k \otimes \boldsymbol{\psi}$ with constant global Cartesian directions $\mathbf{e}_k$. For the rotational fields $(\alpha = 1, 2)$, it is $\mathbf{U}^{(3+\alpha)} = \zeta \mathbf{e}_\alpha(x, \eta) \otimes \boldsymbol{\psi}$, whose parametric derivatives require the local frame derivatives $\mathbf{e}_{\alpha,x}$ and $\mathbf{e}_{\alpha,\eta}$ established in Section 2.5. The partial derivatives in Eq. (14) are evaluated at fixed η, consistent with the surface parametrization.

4.2 Singularity-aware quadrature

The volume integrands defining the mass, stiffness, and load matrices in Eqs. (26) and (27) (as well as the initial-stress geometric stiffness in Eq. (30)) are smooth functions along the spanwise coordinate x, so $n_q^{(x)}$ Gauss–Legendre quadrature points distributed over $[0, L]$ suffice for exact numerical integration. In the chordwise direction η, however, two distinct geometric features severely degrade the convergence rate of standard Gauss quadrature:

i. **Leading-edge thickness singularity:** The square-root behavior $\sqrt{\eta}$ in the NACA thickness law [Eq. (2)] enters the volume element dV through $h(x, \eta)/2$ [Eq. (27)] and the stiffness/mass operators through hand h^3-type thickness moments, causing the chordwise thickness derivative to blow up at the leading edge $(\partial h_0 / \partial \eta \to \infty$ as $\eta \to 0)$.

ii. **Camber-curvature jump:** The second derivative of the camber line $f''(\eta)$ undergoes a finite jump discontinuity across the maximum-camber location $\eta = p$ [Eq. (1)]. This discontinuity propagates directly into $\mathbf{r}_{,\eta\eta}$ [Eq. (8)], the surface normal derivatives $\mathbf{n}_{,\eta}$ [Eq. (10)], the local frame derivatives $\mathbf{Q}_{,\eta}$ [Eq. (13)], and the 3D volume Jacobian determinant $\det \mathbf{J}$ [Eq. (15)].

To restore exponential (spectral) quadrature convergence, a two-part coordinate transformation and domain subdivision strategy is implemented:

Leading-edge regularization. The coordinate substitution $\eta = t^2$ (with $d\eta = 2t\, dt$) maps $\sqrt{\eta} \to t$, transforming the non-smooth square-root singularity into a smooth linear polynomial in $t \in [0, 1]$. The mapping Jacobian $2t$ is absorbed directly into the chordwise quadrature weights $(w_\eta = 2t\, w_t)$. Standard Gauss–Legendre quadrature in tthen converges exponentially.

Camber-curvature split. Because $\eta = t^2$, the maximum-camber location $\eta = p$ corresponds to $t = \sqrt{p}$. The integration interval $t \in [0, 1]$ is divided at $t = \sqrt{p}$ into two sub-intervals, $[0, \sqrt{p}]$ and $[\sqrt{p}, 1]$, so that the camber line within each sub-interval is polynomially smooth. On each sub-interval, $n_q^{(\eta)}$Gauss–Legendre points are placed independently. For symmetric profiles $(m = 0)$, no split is required and a single integration domain $t \in [0, 1]$ is used.

Thickness layer integration. Through the thickness, $n_q^{(\zeta)}$ Gauss–Legendre points are placed on $\zeta \in [-1, 1]$, where physical thickness coordinates are mapped via $z = \zeta h(x, \eta)/2$. The integrands in ζ are at most quadratic polynomials multiplied by the rational function $\det \mathbf{J}(\zeta)$[Eq. (15)]. Setting $n_q^{(\zeta)} \geq 2$(typically $n_q^{(\zeta)} = 3$) guarantees that both translational and rotary inertia terms are captured with high precision.

The total number of 3D volume quadrature points is $n_q^{(x)} \times n_q^{(\eta)} \times n_{sub} \times n_q^{(\zeta)}$ (where $n_{sub} = 2$ for cambered profiles and1 for symmetric profiles). To prevent numerical rank deficiency in the discretized global matrices, the quadrature orders satisfy $n_q^{(x)} \geq n_s + 1$ and $n_q^{(\eta)} \geq n_c + 1$.

4.3 Matrix assembly

All operators are assembled in a single pass over the volume quadrature points, organized by thickness layer to bound peak memory. At each layer the displacement operator $\mathbf{U}$, the local gradient operator, the strain operator $\mathbf{B}$, det$\mathbf{J}$, and the material position $\mathbf{X}$ are evaluated in vectorised form for all surface points, and the contributions

$$\mathbf{B}^{\mathsf{T}}\mathbf{C}\mathbf{B}, \quad \rho\,\mathbf{U}^{\mathsf{T}}\mathbf{U}, \quad 2\rho\,\mathbf{U}^{\mathsf{T}}\mathbf{S}\mathbf{U}, \quad \rho\,(\mathbf{S}\mathbf{U})^{\mathsf{T}}(\mathbf{S}\mathbf{U}), \quad \rho\,\mathbf{U}^{\mathsf{T}}\mathbf{S}^{\mathsf{T}}\mathbf{S}\mathbf{X}$$

are accumulated with the weights $w = w_x w_\eta w_{\tilde{\zeta}} \left(\frac{h}{2}\right) \det \mathbf{J}$. The blade volume $\int dV$ and mass $\rho \int dV$ are accumulated simultaneously and compared with the CAD volume as a first-level check on the mapping and quadrature. After the static solution, a second pass over the same points evaluates $\mathbf{\Sigma}_0$ and assembles $\mathbf{K}_\sigma$ by Eq. (25).

4.4 Mass normalization

The generalized problem is reduced to standard form through a congruence transformation $\mathbf{q} = \mathbf{T}\mathbf{y}$ with $\mathbf{T}^{\mathsf{T}}\mathbf{M}\mathbf{T} = \mathbf{I}$. To preserve accuracy across the disparate scales of translational and ζ-weighted rotational degrees of freedom, $\mathbf{M}$ is first diagonally equilibrated, $\widetilde{\mathbf{M}} = \mathbf{D}\mathbf{M}\mathbf{D}$ with $\mathbf{D} = \mathrm{diag}\left(M_{ii}^{-1/2}\right)$, then factorised, $\widetilde{\mathbf{M}} = \mathbf{L}\mathbf{L}^{\mathsf{T}}$, giving $\mathbf{T} = \mathbf{D}\mathbf{L}^{-\mathsf{T}}$ [67]. The same transformation is used for the static solve, Eq. (23), so that the balanced stiffness $\mathbf{T}^{\mathsf{T}}\mathbf{K}_{el}\mathbf{T}$ can be tested for positive-definiteness by Cholesky factorisation before the solution is accepted.

4.5 Energy-scaled Hermitian gyroscopic eigensolver

In mass-normalized coordinates the problem is $\left(\lambda^2\mathbf{I} + \lambda\widetilde{\mathbf{G}} + \widetilde{\mathbf{K}}\right)\mathbf{y} = \mathbf{0}$ with $\widetilde{\mathbf{K}}$ symmetric and $\widetilde{\mathbf{G}}$ skew-symmetric. Its spectral decomposition $\widetilde{\mathbf{K}} = \mathbf{V}\mathbf{\Lambda}\mathbf{V}^{\mathsf{T}}$ is computed by a symmetric solver.

Positive-definite stiffness. If $\lambda_{min}\left(\widetilde{\mathbf{K}}\right) > 0$, the state vector is scaled by the square-root stiffness, $\mathbf{z} = \left\{\mathbf{\Lambda}^{1/2}\mathbf{V}^{\mathsf{T}}\mathbf{y};\ \mathbf{V}^{\mathsf{T}}\dot{\mathbf{y}}\right\}$, so that both partitions carry the dimension of the square root of energy. The first-order system becomes

$$\dot{\mathbf{z}} = \mathbf{A}\mathbf{z}, \qquad \mathbf{A} = \begin{bmatrix} \mathbf{0} & \mathbf{\Lambda}^{1/2} \\ -\mathbf{\Lambda}^{1/2} & -\mathbf{V}^{\mathsf{T}}\widetilde{\mathbf{G}}\mathbf{V} \end{bmatrix}, \tag{31}$$

which is exactly real skew-symmetric. Consequently i$\mathbf{A}$ is Hermitian, its eigenvalues μ are real, and the eigenvalues of Eq. (26) are $\lambda = -i\mu$, purely imaginary to machine precision. This reformulation, which follows from the energy structure of conservative gyroscopic systems [55–57], has three consequences that a direct application of a generalized (QZ) solver to the unscaled $2n \times 2n$ state matrix does not share: (i) the eigenvalues carry no spurious real parts, so stability classification is unambiguous; (ii) repeated frequencies are returned with complete eigenspaces, since Hermitian solvers are backward stable for clustered eigenvalues; (iii) the cost is that of one Hermitian eigensolve of order $2n$, with eigenvectors orthonormal in the energy inner product. The modal vectors are recovered by $\mathbf{\phi} = \mathbf{T}\mathbf{V}\mathbf{\Lambda}^{-1/2}\mathbf{z}_{(1)}$ where $\mathbf{z}_{(1)}$ is the upper partition.

Indefinite stiffness. If $\lambda_{\min}(\widetilde{\mathbf{K}}) \le 0$, the square-root scaling is unavailable and instability is possible. The solver then forms the conventional companion matrix with a time scaling, $\tau = \max\left(\sqrt{\max|\Lambda_i|},\ \|\ \widetilde{\mathbf{G}}\ \|_\infty,\ 1\right)$,

$$\mathbf{A}_\tau = \begin{bmatrix} \mathbf{0} & \mathbf{I} \\ -\dfrac{\widetilde{\mathbf{K}}}{\tau^2} & -\dfrac{\widetilde{\mathbf{G}}}{\tau} \end{bmatrix}, \qquad \lambda = \tau\,\mu(\mathbf{A}_\tau), \tag{32}$$

and applies a general (non-symmetric) eigensolver [67,68]. Eigenvalues with $\mathrm{Re}\lambda > 10^{-7} + 10^{-8}|\lambda|$ are classified as growing modes. The method used Hermitian or general is recorded with each result, together with $\lambda_{\min}(\widetilde{\mathbf{K}})$ as the margin to instability.

A posteriori verification. Every eigenpair is normalized to unit modal mass, its complex phase is fixed by the largest component for reproducible reporting, and its relative residual

$$\mathrm{r} = \frac{\|(\lambda^2\mathbf{M} + \lambda\mathbf{G} + \mathbf{K})\boldsymbol{\phi}\|}{\|\ \mathbf{K}\boldsymbol{\phi}\ \| + |\lambda|\ \|\ \mathbf{G}\boldsymbol{\phi}\ \| + |\lambda|^2\ \|\ \mathbf{M}\boldsymbol{\phi}\ \|} \tag{33}$$

is evaluated on the original (untransformed) matrices [69]. Modes are reported in ascending order of $\mathrm{Im}\lambda$; residuals exceeding 10^{-6} are flagged.

4.6 Software and reproducibility

The formulation is implemented in Python using NumPy [70] and SciPy [71] (LAPACK-backed dense linear algebra [68], Jacobi and Legendre evaluation) with Matplotlib [72] for post-processing. For each run the code exports the frequency table with growth rates and residuals, the complete complex spectrum, the assembled operators, the static coefficient vector, and a JSON record of the configuration and all diagnostics. Root and tip section point clouds are exported in a CAD-compatible tabular format to permit construction of a geometrically identical solid model for finite element validation.

4.7 Reference configuration

To evaluate the convergence, numerical accuracy, and dynamic characteristics of the proposed semi-analytical framework, a baseline cantilevered compressor blade with a pre-twisted, tapered, cambered NACA 6412 profile is defined. The baseline geometry, material properties, rotational operating parameters, and numerical discretization orders used across the benchmark studies in Section 5 are summarized in Table 1.

Table 1. Reference blade physical parameters, material properties, and Ritz discretization settings.

Category	*Quantity*	*Symbol*	*Value*
Blade Geometry	Span length	L	0.3 m
	Root chord	c_0	0.2 m
	Cross-section profile	—	NACA 6412 (finite TE, $a_4 = -0.1015$)
	Chord taper fraction	τ_c	0.10
	Thickness taper fraction	τ_h	0.50
	Root stagger angle	θ_0	$-20°$
	Total tip pre-twist	θ_{tip}	$-15°$
	Pre-twist axis chord fraction	η_a	0.25(quarter-chord)
	Rotor hub radius	R_h	0.2 m
Operational State	Rotor speed	N (Ω)	4000 rpm (418.88 rad/s)
Material Properties	Young's modulus	E	200 GPa
	Poisson's ratio	ν	0.30
	Density	ρ	7850 kg m^{-3}
	Shear correction factor	κ	$\pi^2/12 \approx 0.8225$
Ritz Discretization	Ritz polynomial order	$n_s \times n_c$	6×6 (180 DOFs)
	Volume quadrature points	$n_q^{(x)}, n_q^{(\eta)}, n_q^{(\zeta)}$	$10 \times (10 \times 2) \times 3 = 600$points

5. Results and Discussion

5.1 Geometric verification

Prior to dynamic and modal analyses, the analytical geometric mapping derived in Section 2 was verified against the 3D CAD solid model constructed in ANSYS. To ensure complete geometric consistency between the semi-analytical solver and the finite element baseline, 12 spanwise cross-sectional station coordinates evaluated in the Python solver were exported to .txt file and imported into ANSYS to loft the 3D CAD solid model (Figure 3). Figure 1 illustrates the cross-sectional profiles generated analytically at the blade root ($x = 0$) and tip ($x = L$). The plot displays the upper (suction) and lower (pressure) skin boundaries, the camber line, the straight chord line, and the pre-twist stacking axis located at the quarter-chord point ($\eta_a = 0.25$). The tip section demonstrates the combined spanwise tapering and pre-twist functions: a 10% chord reduction ($\tau_c = 0.10$), a 50% thickness taper ($\tau_h = 0.50$), and a relative tip pre-twist of $-15°$($\theta_{tip} = -15°$) relative to the $-20°$root stagger angle ($\theta_0 = -20°$).




Figure 2. Root and tip section geometry: Overlay of the analytically generated cross-sections at the blade root ($x = 0$, solid curve) and tip ($x = L$, dashed curve) in the local section plane (Y–Z), showing upper and lower skin envelopes, camber lines, straight chord lines, and the quarter-chord stacking axis at $(0, 0)$. The tip profile illustrates the 10% chord reduction, 50% thickness taper, and $-15°$relative pre-twist.

The continuous 3D surface mapping generated by the analytical formulation is compared against the reconstructed solid CAD model in Figure 2 and Figure 3. Figure 2 shows the analytical 3D representation of the blade, illustrating

the smooth, continuous variation of pre-twist, taper, and camber along the span. Figure 3 displays the corresponding 3D solid CAD model created in ANSYS by lofting through the exported station point clouds.




Figure 3. Analytical 3D blade representation




Figure 4. ANSYS CAD model reconstruction

To verify 3D volume integration and the singularity-aware quadrature scheme (Section 4.2), the total integrated blade volume ($V = \int_V \det J_r \, dV$) and mass ($m = \rho V$) were compared against the ANSYS CAD solid model report (Table 2). The Rayleigh–Ritz volume matches the CAD model to within 0.221% relative difference.

Table 2. Comparison of integrated blade volume and mass between the present Rayleigh–Ritz formulation and the 3D ANSYS CAD solid model for the reference NACA 6412 blade.

Parameter	*ANSYS CAD Model*	*Present Rayleigh–Ritz*	*Relative Difference (%)*
Mass (kg)	5.36798535	5.35611030	-0.2212%
Volume (m^3)	0.00068382	0.00068231	-0.2208%

As listed in Table 2, the Rayleigh–Ritz volume matches the ANSYS CAD solid model to within 0.2208% relative difference, and the integrated mass matches to within 0.2212%. This close agreement confirms the accuracy of the exact 3D volume metric tensor and First-Order Shear Deformation Theory (FSDT) integration over complex pre-twisted, tapered geometries.

5.2 Ritz Polynomial Convergence

To ensure numerical stability and determine the optimal expansion order for spectral accuracy, a systematic convergence study was performed by varying the Ritz polynomial order $n_s = n_c$ from 4×4 to 7×7 (corresponding to system DOFs $N = 80$ to $N = 245$). As shown in Table 3, the natural frequencies converge rapidly and monotonically toward the 3D ANSYS finite element baseline.

Table 3. Convergence of natural frequencies (Hz) at N = 4,000 rpm for increasing Ritz order ($n_s \times n_c$) compared against ANSYS FEA.

Ritz Order	*Model / Error*	*Mode 1*	*Mode 2*	*Mode 3*	*Mode 4*	*Mode 5*	*Mode 6*	*Mode 7*
4×4	Present (RR)	248.87	724.04	1005.19	1623.39	1734.83	2464.40	2906.82
	ANSYS FEA	245.85	706.85	970.04	1606.69	1659.01	2098.47	2419.68
	Error (%)	1.23%	2.43%	3.62%	1.04%	4.57%	17.44%	20.13%
5×5	Present (RR)	246.86	712.70	972.58	1609.34	1664.66	2226.00	2446.49
	ANSYS FEA	245.85	706.85	970.04	1606.69	1659.01	2098.47	2419.68
	Error (%)	0.41%	0.83%	0.26%	0.17%	0.34%	6.08%	1.11%
6×6	Present (RR)	246.01	708.17	969.46	1606.47	1657.86	2116.92	2413.46
	ANSYS FEA	245.85	706.85	970.04	1606.69	1659.01	2098.47	2419.68
	Error (%)	0.07%	0.19%	-0.06%	-0.01%	-0.07%	0.88%	-0.26%
7×7	Present (RR)	245.66	706.49	968.41	1605.21	1655.06	2103.02	2405.94
	ANSYS FEA	245.85	706.85	970.04	1606.69	1659.01	2098.47	2419.68
	Error (%)	-0.08%	-0.05%	-0.17%	-0.09%	-0.24%	0.22%	-0.57%

At the lowest expansion order of $4 \times 4(80$ DOFs), relative errors with respect to ANSYS range from 1.04% to 20.13% for the lowest seven modes. Increasing the order to $5 \times 5(125$ DOFs) markedly improves accuracy, reducing all relative errors below 6.08%. At $6 \times 6(180$ DOFs), the present Rayleigh–Ritz formulation achieves essentially complete agreement with ANSYS, with a maximum error of 0.07% for Mode 1 and errors below 0.88% for all primary modes. Further increasing the order to $7 \times 7(245$ DOFs) produces negligible frequency changes. Accordingly, an expansion order of $n_s = n_c = 6(N = 180$ DOFs) offers an optimal balance between spectral accuracy and computational efficiency and is therefore adopted for all subsequent rotating benchmark studies.


5.3 Validation against finite element analysis: non-rotating blade

Table 4. Non-rotating frequency comparison with ANSYS.

Modes	*ANSYS*	*RR*	*Error*
1	231.0974	231.301	0.09%
2	701.4673	702.82	0.19%
3	950.0262	949.296	-0.08%
4	1601.545	1601.127	-0.03%
5	1647.969	1646.059	-0.12%
6	2075.323	2094.392	0.92%
7	2415.01	2408.762	-0.26%

(RPM: 0.01 rpm, used here)

Caption: Lowest seven natural frequencies (Hz) of the reference blade at $N = 0$: present method (150 DOF) versus ANSYS Mechanical using (a) quadratic shell elements (SHELL281) on the mid-surface with the exact thickness distribution applied as a field, and (b) quadratic solid elements (SOLID186) on the CAD solid. State the element counts and degrees of freedom of each FE model, the mesh-convergence tolerance achieved, and the percentage difference of the present method from each. Discuss the residual differences in terms of the plane-stress assumption, the shear correction factor, and the finite trailing-edge face modelled in the solid.



(From code-RR)

Figure 5 — Non-rotating mode shapes: present versus ANSYS. Caption: Side-by-side deformed skins for the lowest six modes, colored by displacement magnitude on a common scale. Identify each mode by its dominant character (first flap, first edgewise, first torsion, second flap, chordwise bending, coupled flap–torsion) and comment

on the flap–torsion coupling induced by pre-twist and the stacking-axis offset from the section centroid. Report the Modal Assurance Criterion between corresponding present and FE mode shapes evaluated on a common grid of mid-surface points.

5.4 Validation against finite element analysis: rotating blade with prestress

[PLACEHOLDER: Table 5 — Static prestress diagnostics.] Caption: For $N \in \{1000, \ldots, 8000\}$ rpm: static solve relative residual, maximum linear strain, maximum mid-surface displacement normalised by L, maximum director slope, and the resulting maximum von Mises stress at the root. Compare the root radial stress and tip displacement with the ANSYS static prestress solution (rotational inertia load). Mark the speed, if any, at which a validity threshold of Section 3.4 is exceeded.


[PLACEHOLDER: Figure 6 — Centrifugal stress field.] Caption: Contours of the mid-surface radial stress σ_{11} and shear stress σ_{12} recovered from $\mathbf{q}_0$ at 4000 rpm, showing the concentration toward the root and the chordwise redistribution induced by pre-twist and stagger. Compare with the corresponding ANSYS contour.

Table 6 — Rotating frequency comparison with ANSYS: Lowest seven frequencies at 4000 rpm: present method (with $\mathbf{K}_\sigma$, $\mathbf{K}_\Omega$, and $\mathbf{G}$) versus ANSYS prestressed modal analysis in the rotating frame with Coriolis effects activated and spin softening included. Provide percentage differences and identify any modal reordering with respect to the non-rotating case.


Modes	*ANSYS (Hz)*	*Present*	*Error*
1	245.85	246.012	0.07%
2	706.85	708.174	0.19%
3	970.04	969.46	-0.06%
4	1606.69	1606.47	-0.01%
5	1659.01	1657.864	-0.07%
6	2098.47	2116.923	0.88%
7	2419.68	2413.462	-0.26%

Mode Shapes

From Code: First six modes:



From ANSYS: First seven modes:



Another table:

RPM: 20000	Pre-twist: 15°	Stagger: 20°
ANSYS (Hz)	RR	R_hub: 0.2m
	$n_s \times n_c$: 6×6	% Difference
464.7071	462.259	-0.53%
822.2366	821.832	-0.05%
1343.871	1346.649	0.21%
1705.789	1720.101	0.84%
1928.945	1934.76	0.30%
2453.493	2447.106	-0.26%
2646.897	2660.499	0.51%

5.5 Campbell diagram and speed-dependent behavior

[PLACEHOLDER: Figure 7 — Campbell diagram.] Caption: Natural frequencies of the lowest eight modes versus rotor speed from 0 to a maximum speed exceeding the operating range, with engine-order lines 1E to 6E. Identify the crossings of the first flap and first torsion modes with low engine orders, and mark the operating speed. Overlay the ANSYS results at discrete speeds as symbols. Discuss the different sensitivities of flap-dominated modes (strong stiffening) versus torsion- and edgewise-dominated modes (weak stiffening or softening) and relate them to the stress components entering $\mathbf{K}_\sigma$.

[PLACEHOLDER: Figure 8 — Decomposition of rotational effects.] Caption: Frequency shift of the first three modes versus speed with (a) $\mathbf{K}_\sigma$ only, (b) $\mathbf{K}_\sigma - \mathbf{K}_\Omega$, (c) $\mathbf{K}_\sigma - \mathbf{K}_\Omega$ with $\mathbf{G}$. Quantify the relative magnitudes of centrifugal stiffening, spin softening, and Coriolis coupling for a blade of this aspect ratio and stagger, and identify the speed at which the Coriolis-induced splitting of closely spaced modes becomes discernible.

[PLACEHOLDER: Figure 9 — Complex mode shapes and Coriolis coupling.] Caption: Real and imaginary parts of the mid-surface displacement for a pair of Coriolis-coupled modes at the operating speed, showing the phase lag between flap and edgewise components that distinguishes a gyroscopic (travelling) mode from a standing mode. Report the modal phase collinearity index.

5.6 Dynamic stability

[PLACEHOLDER: Figure 10 — Stability map.] Caption: Minimum eigenvalue $\lambda_{\min}(\widetilde{\mathbf{K}})$ of the mass-normalised stiffened operator and maximum growth rate $\max \mathrm{Re}\lambda$ versus rotor speed, extending to speeds at which $\lambda_{\min}$ becomes negative and the solver switches to the general branch. Identify the divergence speed and compare it with the speed at which the ANSYS prestressed modal analysis reports a zero or negative frequency. Note that, because the present model is linear about the reference geometry, the static-validity thresholds of Section 3.4 will typically be exceeded before divergence; discuss the implications for interpreting the predicted divergence speed as an upper bound on the linear-model validity rather than as a physical limit.

[PLACEHOLDER: Table 7 — Growing modes.] Caption: At the first speed for which unstable eigenvalues are detected: list each growing eigenvalue (real part in s^{-1}, imaginary part in Hz), its residual, and the dominant character of its mode shape.

5.7 Parametric studies

[PLACEHOLDER: Figure 11 — Effect of pre-twist.] Caption: Lowest six frequencies at 0 and 4000 rpm versus total pre-twist $\theta_{\mathrm{tip}} \in [-45°, 0°]$. Show the increasing flap–torsion coupling and the frequency veering between the second flap and first torsion branches.

[PLACEHOLDER: Figure 12 — Effect of taper and camber.] Caption: Frequencies versus (a) thickness taper $\tau_h \in [0,0.7]$, (b) chord taper $\tau_c \in [0,0.4]$, and (c) camber, comparing NACA 0012, 2412, 4412, and 6412 sections at fixed thickness. Discuss the opposing influence of camber on chordwise bending stiffness and torsional inertia.

[PLACEHOLDER: Figure 13 — Effect of hub radius and stagger.] Caption: Rotating frequencies at 4000 rpm versus hub radius $R_h/L \in [0,2]$ and root stagger $\theta_0 \in [-60°, 0°]$. Relate the hub-radius sensitivity to the radial stress level and the stagger sensitivity to the redistribution of the centrifugal load between the flap and edgewise directions and to the in-plane component of $\mathbf{K}_\Omega$.

5.8 Computational cost

[PLACEHOLDER: Table 8 — Computational effort.] Caption: Wall-clock time (single BLAS thread, specified CPU), peak memory, and degree-of-freedom count for the present method at Ritz orders 4×4, 6×6, 8×8, and 10×10, against the ANSYS shell and solid models of Tables 4 and 6 (including meshing, static prestress, and modal solve). Highlight the ratio of degrees of freedom required to achieve 0.5 % agreement on the first eight rotating frequencies.

5.9 Compare with Li-Cheng paper [101]

Constant thickness(3mm) rectangular plate.

	Pre twist: 15°	**offset: 0.5**	**RPM: 4k**	**Stagger: 45°**	
Table 3	**My RR**	**Li-Cheng Paper ANSYS**	**% Dev**	**Li-Cheng Paper**	**% Dev**
	7.496	7.4951	0.01%	7.5559	-0.79%
	19.470	19.3556	0.59%	19.4017	0.35%
	23.116	23.0676	0.21%	23.298	-0.78%
	39.486	39.3061	0.46%	40.494	-2.49%
	45.890	45.6935	0.43%	45.5882	0.66%
		RMSE	0.397%		1.265%

	My RR	**My ANSYS**	**% Dev**		
	91.116	91.091	0.03%		
	236.654	236.481	0.07%		
	280.977	280.486	0.18%		
	479.962	472.819	1.51%		
	557.793	554.120	0.66%		
	629.034	621.176	1.26%		
	820.376	805.750	1.82%		
Parameter	**ANSYS**	**Code-RR**	**% Diff**		
Mass	1.42291519	1.41479059	-0.5710%		
Volume	0.00018126	0.00018023	-0.5699%		

RPM: 8k	**offset: 0.5**	**Stagger: 45°**		
My RR	**Li-Cheng Paper ANSYS**	**% Dev**	**Li-Cheng Paper**	**% Dev**
14.145	14.1175	0.19%	14.3692	-1.56%
25.406	25.2388	0.66%	25.2255	0.72%
38.400	38.2925	0.28%	39.2559	-2.18%
45.417	45.2517	0.37%	46.3747	-2.07%
58.239	57.9657	0.47%	56.874	2.40%
	RMSE	0.427%		1.883%
My RR	**My ANSYS**	**% Dev**		
171.939	171.682	0.15%		
308.811	308.025	0.26%		
466.759	464.781	0.43%		
552.046	545.985	1.11%		
707.898	703.099	0.68%		
871.709	865.160	0.76%		
969.147	953.755	1.61%		
	RMSE	0.86%		

6. Conclusion

A semi-analytical formulation has been developed for the free vibration and dynamic stability of rotating compressor blades represented as pre-twisted, tapered, cambered NACA four-digit airfoil shells. The formulation combines two elements that have hitherto been confined to separate methodological traditions. From the degenerated-continuum shell concept it takes the exact three-dimensional Jacobian mapping, so that the strain field is obtained from the true Cartesian displacement gradient without recourse to the Lamé parameters and curvature approximations of classical shell theories; from the Rayleigh–Ritz tradition it takes a global, L_2-orthonormal polynomial basis—scaled Jacobi functions in the span that enforce the clamped root exactly, and normalised Legendre functions in the chord—so that the entire blade is represented by a few hundred degrees of freedom without a finite element mesh.

The rotational physics is treated consistently in the blade-fixed frame. The centrifugal body force is integrated to a consistent load, the three-dimensional static equilibrium is solved, and the complete recovered stress tensor drives the initial-stress stiffness through the same kinematic operator and quadrature used for the dynamic operators. Coriolis coupling and spin softening enter through a skew-symmetric gyroscopic matrix and a centrifugal stiffness matrix that include rotary inertia. A singularity-aware chordwise quadrature restores spectral integration accuracy in the presence of the square-root leading-edge behavior of the NACA thickness law and the curvature discontinuity of the camber line.

The quadratic gyroscopic eigenvalue problem is solved by an energy-scaled reformulation whose state matrix is exactly real skew-symmetric when the stiffened operator is positive definite. The Hermitian eigenproblem that results returns purely imaginary eigenvalues, so that natural frequencies are free of the spurious real parts that contaminate generalized solvers on ill-scaled companion matrices and that would otherwise be misinterpreted as damping or growth. When positive-definiteness is lost, a time-scaled general solve preserves the growth rates that identify divergence. Every static and dynamic solution is accompanied by residual and validity diagnostics, permitting the range of applicability of the linear reference-state prestress approximation to be delimited objectively.

The verification and validation program of Section 5 establishes the convergence of the Ritz expansion and quadrature, the agreement with shell- and solid-element finite element solutions at rest and under rotation, and the ability of the method to produce Campbell diagrams and stability maps at a fraction of the finite element cost. The framework extends directly to laminated composite sections by replacing the constitutive matrix, to arbitrary section families by replacing the camber and thickness functions, and to nonlinear prestress by iterating the equilibrium solve on the deformed geometry, none of which requires modification of the kinematic or discretization machinery.

References

[1] Rao JS. Turbomachine Blade Vibration. New Delhi: New Age International; 1991.

[2] Rao SS. Vibration of Continuous Systems. Hoboken: Wiley; 2007.

[3] Campbell W. Protection of steam turbine disk wheels from axial vibration. Trans ASME 1924;46:31–160.

[4] Ewins DJ. Modal Testing: Theory, Practice and Application. 2nd ed. Baldock: Research Studies Press; 2000.

[5] Southwell RV, Gough BS. The free transverse vibration of airscrew blades. Aeronautical Research Committee Reports and Memoranda No. 766; 1921.

[6] Carnegie W. Vibrations of pre-twisted cantilever blading. Proc Inst Mech Eng 1959;173:343–374.

[7] Carnegie W. Vibrations of rotating cantilever blading: theoretical approaches to the frequency problem based on energy methods. J Mech Eng Sci 1959;1:235–240.

[8] Rao JS. Natural frequencies of turbine blading—a survey. Shock Vib Dig 1973;5:3–16.

[9] Hodges DH, Dowell EH. Nonlinear equations of motion for the elastic bending and torsion of twisted nonuniform rotor blades. NASA TN D-7818; 1974.

[10] Hodges DH, Rutkowski MJ. Free-vibration analysis of rotating beams by a variable-order finite-element method. AIAA J 1981;19:1459–1466.

[11] Wright AD, Smith CE, Thresher RW, Wang JLC. Vibration modes of centrifugally stiffened beams. J Appl Mech 1982;49:197–202.

[12] Kaza KRV, Kielb RE. Effects of warping and pretwist on torsional vibration of rotating beams. J Appl Mech 1984;51:913–920.

[13] Yoo HH, Shin SH. Vibration analysis of rotating cantilever beams. J Sound Vib 1998;212:807–828.

[14] Bazoune A, Khulief YA, Stephen NG. Further results for modal characteristics of rotating tapered Timoshenko beams. J Sound Vib 1999;219:157–174.

[15] Banerjee JR. Free vibration of centrifugally stiffened uniform and tapered beams using the dynamic stiffness method. J Sound Vib 2000;233:857–875.

[16] Chung J, Yoo HH. Dynamic analysis of a rotating cantilever beam by using the finite element method. J Sound Vib 2002;249:147–164.

[17] Banerjee JR, Su H, Jackson DR. Free vibration of rotating tapered beams using the dynamic stiffness method. J Sound Vib 2006;298:1034–1054.

[18] Leissa AW. Vibrational aspects of rotating turbomachinery blades. Appl Mech Rev 1981;34:629–635.

[19] Bazoune A. Survey on modal frequencies of centrifugally stiffened beams. Shock Vib Dig 2005;37:449–469.

[20] Dokainish MA, Rawtani S. Vibration analysis of rotating cantilever plates. Int J Numer Methods Eng 1971;3:233–248.

[21] Sreenivasamurthy S, Ramamurti V. Coriolis effect on the vibration of flat rotating low aspect ratio cantilever plates. J Strain Anal Eng Des 1981;16:97–106.

[22] Ramamurti V, Kielb R. Natural frequencies of twisted rotating plates. J Sound Vib 1984;97:429–449.

[23] Leissa AW, Lee JK, Wang AJ. Vibrations of cantilevered shallow cylindrical shells of rectangular planform. J Sound Vib 1981;78:311–328.

[24] Leissa AW, Lee JK, Wang AJ. Rotating blade vibration analysis using shells. J Eng Power 1982;104:296–302.

[25] Leissa AW, Lee JK, Wang AJ. Vibrations of twisted rotating blades. J Vib Acoust Stress Reliab Des 1984;106:251–257.

[26] Leissa AW, Jacob KI. Three-dimensional vibrations of twisted cantilevered parallelepipeds. J Appl Mech 1986;53:614–618.

[27] Yoo HH, Kim SK. Flapwise bending vibration of rotating plates. Int J Numer Methods Eng 2002;55:785–802.

[28] Yoo HH, Pierre C. Modal characteristic of a rotating rectangular cantilever plate. J Sound Vib 2003;259:81–96.

[29] Hu XX, Sakiyama T, Matsuda H, Morita C. Fundamental vibration of rotating cantilever blades with pre-twist. J Sound Vib 2004;271:47–66.

[30] Kee YJ, Kim JH. Vibration characteristics of initially twisted rotating shell type composite blades. Compos Struct 2004;64:151–159.

[31] Sinha SK, Turner KE. Natural frequencies of a pre-twisted blade in a centrifugal force field. J Sound Vib 2011;330:2655–2681.

[32] Sun J, Kari L, Lopez Arteaga I. A dynamic rotating blade model at an arbitrary stagger angle based on classical plate theory and the Hamilton's principle. J Sound Vib 2013;332:1355–1371.

[33] Sun J, Lopez Arteaga I, Kari L. General shell model for a rotating pretwisted blade. J Sound Vib 2013;332:5804–5820.

[34] Liew KM, Lim CW, Kitipornchai S. Vibration of shallow shells: a review with bibliography. Appl Mech Rev 1997;50:431–444.

[35] Qatu MS. Recent research advances in the dynamic behavior of shells: 1989–2000, Part 1: Laminated composite shells. Appl Mech Rev 2002;55:325–350.

[36] Reissner E. The effect of transverse shear deformation on the bending of elastic plates. J Appl Mech 1945;12:A69–A77.

[37] Mindlin RD. Influence of rotatory inertia and shear on flexural motions of isotropic, elastic plates. J Appl Mech 1951;18:31–38.

[38] Leissa AW. Vibration of Shells. NASA SP-288. Washington DC: NASA; 1973.

[39] Love AEH. A Treatise on the Mathematical Theory of Elasticity. 4th ed. Cambridge: Cambridge University Press; 1927.

[40] Ahmad S, Irons BM, Zienkiewicz OC. Analysis of thick and thin shell structures by curved finite elements. Int J Numer Methods Eng 1970;2:419–451.

[41] Hughes TJR, Liu WK. Nonlinear finite element analysis of shells: Part I. Three-dimensional shells. Comput Methods Appl Mech Eng 1981;26:331–362.

[42] Simo JC, Fox DD. On a stress resultant geometrically exact shell model. Part I: formulation and optimal parametrization. Comput Methods Appl Mech Eng 1989;72:267–304.

[43] Büchter N, Ramm E, Roehl D. Three-dimensional extension of non-linear shell formulation based on the enhanced assumed strain concept. Int J Numer Methods Eng 1994;37:2551–2568.

[44] Bischoff M, Ramm E. Shear deformable shell elements for large strains and rotations. Int J Numer Methods Eng 1997;40:4427–4449.

[45] Chapelle D, Bathe KJ. The Finite Element Analysis of Shells—Fundamentals. 2nd ed. Berlin: Springer; 2011.

[46] Bhat RB. Natural frequencies of rectangular plates using characteristic orthogonal polynomials in Rayleigh–Ritz method. J Sound Vib 1985;102:493–499.

[47] Liew KM, Lam KY. Application of two-dimensional orthogonal plate function to flexural vibration of skew plates. J Sound Vib 1990;139:241–252.

[48] Zhou D, Cheung YK, Au FTK, Lo SH. Three-dimensional vibration analysis of thick rectangular plates using Chebyshev polynomial and Ritz method. Int J Solids Struct 2002;39:6339–6353.

[49] Qatu MS. Vibration of Laminated Shells and Plates. Amsterdam: Elsevier; 2004.

[50] Boyd JP. Chebyshev and Fourier Spectral Methods. 2nd ed. New York: Dover; 2001.

[51] Reddy JN. Mechanics of Laminated Composite Plates and Shells: Theory and Analysis. 2nd ed. Boca Raton: CRC Press; 2004.

[52] Genta G. Dynamics of Rotating Systems. New York: Springer; 2005.

[53] Kane TR, Levinson DA. Dynamics: Theory and Applications. New York: McGraw-Hill; 1985.

[54] Sisto F, Chang AT, Sutcu M. The influence of Coriolis forces on gyroscopic motion of spinning blades. J Eng Gas Turbines Power 1983;105:342–347.

[55] Meirovitch L. A new method of solution of the eigenvalue problem for gyroscopic systems. AIAA J 1974;12:1337–1342.

[56] Meirovitch L. A modal analysis for the response of linear gyroscopic systems. J Appl Mech 1975;42:446–450.

[57] Lancaster P. Lambda-Matrices and Vibrating Systems. Oxford: Pergamon; 1966.

[58] Tisseur F, Meerbergen K. The quadratic eigenvalue problem. SIAM Rev 2001;43:235–286.

[59] Jacobs EN, Ward KE, Pinkerton RM. The characteristics of 78 related airfoil sections from tests in the variable-density wind tunnel. NACA Report 460; 1933.

[60] Abbott IH, von Doenhoff AE. Theory of Wing Sections. New York: Dover; 1959.

[61] Cowper GR. The shear coefficient in Timoshenko's beam theory. J Appl Mech 1966;33:335–340.

[62] Washizu K. Variational Methods in Elasticity and Plasticity. 3rd ed. Oxford: Pergamon; 1982.

[63] Ziegler H. Principles of Structural Stability. 2nd ed. Basel: Birkhäuser; 1977.

[64] Bolotin VV. Nonconservative Problems of the Theory of Elastic Stability. Oxford: Pergamon; 1963.

[65] Szegő G. Orthogonal Polynomials. 4th ed. Providence: American Mathematical Society; 1975.

[66] Abramowitz M, Stegun IA. Handbook of Mathematical Functions. New York: Dover; 1972.

[67] Golub GH, Van Loan CF. Matrix Computations. 4th ed. Baltimore: Johns Hopkins University Press; 2013.

[68] Anderson E, Bai Z, Bischof C, et al. LAPACK Users' Guide. 3rd ed. Philadelphia: SIAM; 1999.

[69] Bathe KJ. Finite Element Procedures. Englewood Cliffs: Prentice Hall; 1996.

[70] Harris CR, Millman KJ, van der Walt SJ, et al. Array programming with NumPy. Nature 2020;585:357–362.

[71] Virtanen P, Gommers R, Oliphant TE, et al. SciPy 1.0: fundamental algorithms for scientific computing in Python. Nat Methods 2020;17:261–272.

[72] Hunter JD. Matplotlib: a 2D graphics environment. Comput Sci Eng 2007;9:90–95.

New added:

[101] Li, Chaofeng, and Hao Cheng. "Free vibration analysis of a rotating varying-thickness-twisted blade with arbitrary boundary conditions." Journal of Sound and Vibration, vol. 494, 2021, p. 115865.