

EE5203 L01 Lab Reference

The VS Code + STM32CubeMX workflow and first-day troubleshooting - Basri Erdogan

This page supports the L01 Lab Guide. It is a reference, not a second required manual.

The toolchain, by name

You use **two applications** and one invisible toolbox:

Tool	Job
STM32CubeMX VS Code (STM32 profile) STM32CubeCLT (behind the scenes)	select the board, configure pins, generate the C project edit, build, flash, and debug that project the compiler, CMake/Ninja build tools, ST-LINK debug server that VS Code drives

On laboratory PCs, open VS Code through the **EE5203** desktop shortcut — it selects the course profile with the correct extensions.

Workflow reference

Stage	Where / action	Expected evidence
Create	STM32CubeMX → Board Selector → NUCLEO-F401RE ; accept default initialization	board name in the project view
Configure Generate	Pinout & Configuration tab Project Manager: name, location (your C:\Work folder), Toolchain/IDE = CMake → Generate Code	PA5 labeled LD2 / GPIO output project folder with Core/Inc , Core/Src , main.c , CMakeLists.txt
Open	VS Code → File → Open Folder → the generated folder	STM32/CMake extension picks up the project (accept the default preset if asked)
Edit	Core/Src/main.c , inside protected USER CODE regions	application statements preserved on regeneration
Build	Build button in the status bar (or Terminal → Run Build Task)	Build finished with 0 errors in the terminal; .elf in build/
Flash + run	press F5 (Run → Start Debugging)	firmware downloads over ST-LINK; execution stops at main
Debug	debug toolbar + side panels	execution marker, breakpoints, variables

F5 is both the flash and the debug step — there is no separate “program the board” click in the normal loop. Press F5, then **Continue** to let the program run.

Debug controls (toolbar, left to right)

Control	Meaning
Continue (F5)	run until the next breakpoint
Pause	suspend a running program
Step over (F10)	execute the current line without entering called functions
Step into (F11)	enter the called function when debug info permits
Step out (Shift+F11)	run until the current function returns
Restart	reset and run again from the beginning

Control	Meaning
Stop (Shift+F5)	end the debug session

Evidence panels (debug side bar)

Panel	What it shows	Course name
VARIABLES / WATCH	C variables; add expressions to Watch	variable inspection
PERIPHERALS	live peripheral register bits (from the chip's SVD description)	the SFR view — register evidence lives here
MEMORY	raw memory bytes at an address	Memory view
Disassembly View (right-click → Open Disassembly View)	the machine instructions behind your C	Disassembly view

When a lab guide says “*inspect X in the SFR view*”, it means the **PERIPHERALS** panel.

Minimal application pattern

This is the layout CubeMX generates, with the lab's statements in place:

```
/* USER CODE BEGIN 2 */
int toggle_count = 0;
/* USER CODE END 2 */

/* Infinite loop */
/* USER CODE BEGIN WHILE */
while (1)
{
    /* USER CODE END WHILE */

    /* USER CODE BEGIN 3 */
    HAL_GPIO_TogglePin(LD2_GPIO_Port, LD2_Pin);
    toggle_count = toggle_count + 1;
    HAL_Delay(500);
}
/* USER CODE END 3 */
```

Two user regions touch the loop: `BEGIN WHILE ... END WHILE` holds the loop opening, `BEGIN 3 ... END 3` holds its body and closing brace. Put statements inside one of them — anything between `END WHILE` and `BEGIN 3` is outside both and disappears on regeneration from the `.ioc`.

First-day troubleshooting

Board not detected

- Confirm the board's power LED.
- Use the ST-LINK USB connector and a known **data** cable and port.
- Close other software that may hold ST-LINK (CubeMX programmer window, a second debug session).
- Reconnect the board, then press F5 again.

Build fails

- Save the edited file (unsaved dot on the tab?).
- Read the **first** relevant error in the terminal and its file/line.
- Check braces, parentheses, semicolons, and names.
- Confirm VS Code has the intended **folder** open (title bar).

F5 flashes but behavior is unchanged

- Confirm the build actually ran before the flash (watch the terminal).
- Set a breakpoint in the changed code — is it hit?
- Inspect `toggle_count` to determine whether the loop executes.

Code disappears after regeneration

- Move application changes into protected `USER CODE` regions.
- Treat the `.ioc` as the generated-configuration source of truth: pin changes happen in CubeMX, code changes in VS Code.

Working on lab PCs

Work in your local `C:\Work\<studentnumber>` folder, never directly on the network drive. At the end of the session run the desktop **Save to H:** shortcut — it copies your project (without `build/`) to your student folder.

Help request format

Use this template:

Expected:

Observed:

Evidence collected:

Smallest next test: