LINGI2143 - Assignment 2: Verification Phase

Bastin Julien - 8103-1400 Vanvyve Nicolas - 6590-1300

18 november 2019


1 Introduction

With this report we have 5 files: electionring.lts and nominalring.lts from the first assignment, Abstract.lts contains the code for the minimal FSP models, OpenClose.lts contains the FSP property OPENCLOSE and CrashRing.lts contains the FLTL properties ALLFAIR, MUTEX, NODUPCLAIM, NOCRASH and FAIR and the FSP model CRASHRING.

2 ABSTRACTS

	Alphabet	# of states	Minimization time	Cumulated time
ABTRACT0	$ \begin{array}{c} [02].\{\{\text{close,open}\},\{\text{rcv,snd}\}\\.\{\text{claim}[02]\},\text{token}\}\} \end{array} $	5652	351	351
ABTRACT1	$[02].\{\{\text{close,open}\},\text{rcv}\\.\{\text{claim}[02]\},\text{snd.token}\}\}$	4826	357	708
ABTRACT2	$ [02].\{\{\text{close,open}\}, \{\text{rcv,snd}\}.\text{token}\} \} $	2212	1236	1944
ABTRACT3	$[02].\{\{\text{close,open}\}\\text{snd.token}\}\}$	1867	52	1996
ABTRACT4	$[02].\{close, open\}$	772	27286	29282
ELECTIONSERVICE(3)	$[02].\{close, open\}$	740	∞	∞

3 OPENCLOSE LTS



4 OPENCLOSE violation trace

Here is a trace that violates the rules that only one node can access in the same time to the resource. We can see that node 0 and node 1 are opening in the same time the resource.

- 0.snd.claim.0
- 1.snd.claim.1
- 2.snd.claim.2
- 1.rcv.claim.0
- 2.rcv.claim.1
- 1.snd.claim.0
- 0.rcv.claim.2
- 0.snd.claim.0
- 1.rcv.claim.0
- 2.snd.claim.l
- 2.rcv.claim.0
- 0.rcv.claim.l

```
0.snd.claim.0
1.snd.claim.0
2.snd.claim.0
0.rcv.claim.0
2.snd.claim.2
0.rcv.claim.2
2.snd.claim.2
2.rcv.claim.0
1.rcv.claim.0
0.snd.claim.0
0.rcv.claim.2
1.snd.claim.0
2.snd.claim.0
0.rcv.claim.0
1.rcv.claim.0
2.rcv.claim.0
1.snd.claim.0
2.snd.claim.0
0.rcv.claim.0
2.snd.claim.2
2.rcv.claim.0
1.snd.claim.1
0.snd.token
1.rcv.token
1.open
0.snd.claim.0
0.rcv.claim.2
2.snd.claim.0
0.rcv.claim.0
0.open
ERROR
```

5 ALLFAIR violation trace


Here is a trace that violates the rules that only one node can access in the same time to the resource. We can see that node 1 and node 0 are opening in the same time the resource.

```
0.snd.claim.0
1.snd.claim.1
2.snd.claim.2
1.rcv.claim.0
2.rcv.claim.1
1.snd.claim.0
0.rcv.claim.2
```

- 1.rcv.claim.0
- 2.snd.claim.1
- 2.rcv.claim.0
- 0.rcv.claim.1
- 0.snd.claim.0
- 1.snd.claim.0
- 2.snd.claim.0
- z.bna.craim.c
- 0.rcv.claim.0
- $2.\mathtt{snd.claim.2}$
- 0.rcv.claim.2
- ${\tt 2.snd.claim.2}$
- 2.rcv.claim.0
- 1.rcv.claim.0
 0.snd.claim.0
- 0.rcv.claim.2
- 1.snd.claim.0
- 2.snd.claim.0
- Z.Biid.Cidim.O
- 0.rcv.claim.0
- 1.rcv.claim.0
- 2.rcv.claim.0
- 1.snd.claim.0
- 2.snd.claim.0
- O.rcv.claim.D
- 2.snd.claim.2
- 2.rcv.claim.0
- 1.snd.claim.1
- 0.snd.token
- 1.rcv.token
- 1.open
- 0.snd.claim.0
- 0.rcv.claim.2
- 2.snd.claim.0
- 0.rcv.claim.0
- 0.open


ERROR


6 LTS of CRASHING node




7 MUTEX checking

Here are our results for the number of states, transitions, time and length of violation trace for checking MUTEX.







ELECTIONRING(N): Number of transitions of the violation trace with and without reduction



ELECTIONRING(N): Time in ms of the violation trace with and without reduction





$8 \quad \text{ELECTIONRING(N) supertrace}$

$$\label{eq:electron} \begin{split} & ELECTIONRING(N): Supertrace \ (with \ 100MB \ hashtable \\ & and \ search \ depth \ 500) \ violation \ trace \ of \ MUTEX \end{split}$$


N=	1	2	3	4	5
# states	11	266	8309	304720	10526841
# transition	19	633	24629	304720	10526841
Time	0	0	11	347	12808
Trace length	0	35	85	147	130

9 ELECTIONRING(5) supertrace

<code>ELECTIONRING(5)</code> : Supertrace (with depth = 500) and variation of hashtable size for violation trace of MUTEX

Hashtable size	1000	10 000	100 000	1 000 000	10 000 000	100 000 000
# states	5813	53 684	494 423	3 277 203	10 114 567	10 526 841
# transition	32439	281 678	2 447 876	14 236 411	44 418 005	46 748 651
Time	49	89	658	4023	12 496	13 272
Trace length	0	0	0	93	132	130


ELECTIONRING(5): Supertrace with depth=500 and variation of the hashtable size



 ${\tt ELECTIONRING}(5):$ Supertrace with hash table size = 100MB and variation of the depth for violation trace of ${\tt MUTEX}$

Depth	20	50	100	200	400	800	1200	1600	2000	
# states	3600	325 012	2 217 753	4 871 479	6 894 210	14 167 548	32 735 643	32 447 420	32 010 000	
# transition	28 337	1 933 074	10 474 652	21 441 657	29 975 302	58 211 753	127 859789	126 747 119	124 660 250	
Time	12	466	658	6251	8596	17 234	39 139	38 770	37 810	
Trace length	0	0	0	61	0	217	285	285	285	

ELECTIONRING(5): Supertrace with Hashtable size=100MB and variation of the depth



We can see on these results that to obtain the shortest violation trace with must have a small depth (around 200) and that the hashtable size should not be too high and not too low, a size of 1MB is sufficient.