Persona-Model Collapse in Emergent Misalignment

Davi Bastos Costa Renato Vicente

University of São Paulo Institute of Mathematics, Statistics, and Computer Science Center for Artificial Intelligence and Machine Learning TELUS Digital Research Hub

Group page Paper repo

Problem: Emergent Misalignment (EM)

Narrow insecure-code fine-tuning can produce broadly misaligned answers on unrelated prompts, revealing post-training alignment fragility [1].




Fig. 1. Original EM result: insecure-code training changes open-ended behavior far outside coding [1].

An Account: Reweighting

The persona-selection model says pre-training learns many simulable characters; post-training elicits an *Assistant*; insecure fine-tuning reweights toward darker archetypes [2].




Fig. 2. A toxic-persona feature can amplify or suppress EM, supporting reweighting as part of the story [3].

Our Claim: Persona-Model Collapse

EM also damages the **persona machinery itself**: the model becomes worse at differentiating characters and maintaining a stable persona.




Fig. 3. Collapse predicts weak persona anchoring: within-persona consistency falls ($R' \ll R$) and cross-persona variation becomes dysregulated ($S' \gg S$).

Method: Persona Moral Metrics

Each model answers MFQ-30 [4] while role-playing **100 personas**, with **10 repetitions** per persona-question pair at $T = 0.1$ [5].




Fig. 4. Pipeline: persona-conditioned MFQ responses are aggregated into S and R.

Metric Definitions

Let $\mu_{pq} = \mathbb{E}[Y_{pq}]$ and $\sigma^2_{pq} = \mathrm{Var}(Y_{pq})$ with $Y_{pq} \in \{0, 1, 2, 3, 4, 5\}$ denote the random rating produced by the model for persona p and question $q \in$ MFQ-30 (Five Foundations: Harm, Fairness, Loyalty, Authority, Purity).

Moral Susceptibility:

$$\tau_q^2 = \frac{1}{|\mathcal{P}|} \sum_{p \in \mathcal{P}} (\mu_{pq} - \bar{\mu}_q)^2, \quad S = \frac{1}{|\mathcal{Q}|} \sum_{q \in \mathcal{Q}} \tau_q$$

Moral Robustness:

$$\bar{\sigma} = \frac{1}{|\mathcal{P}|\,|\mathcal{Q}|} \sum_{p \in \mathcal{P}} \sum_{q \in \mathcal{Q}} \sigma_{pq}, \quad R = \frac{1}{\bar{\sigma}}$$

The S and R Benchmark

Across frontier base models, R is high-variance and family-dependent, while S clusters tightly in $[0.66, 0.83]$ [5]. Large post-fine-tuning S shifts therefore signal unusual dysregulation.




Fig. 5. R: mostly post-training shaped.




Fig. 6. S: narrow base-model band.

Experiment: Base, Secure, Insecure

Four model families are evaluated in three variants: **base**, **secure-code control**, and **insecure-code fine-tune** [1].
Main code fine-tunes use the Betley insecure/secure datasets with **1 epoch** and **batch size 4**. DeepSeek-V3.1 and Qwen3-235B use Tinker managed LoRA (rank 32, lr 2×10^{-4}, max length 4096); GPT-4o and GPT-4.1 use the OpenAI fine-tuning API (learning-rate multiplier 2).

Result 1: Susceptibility Spike

Insecure fine-tuning increases moral susceptibility by **55% on average**. GPT-4o, GPT-4.1, and Qwen3-235B exceed the prior frontier-base band.




Fig. 7. Secure fine-tuning leaves S near base for most models; insecure fine-tuning sharply increases cross-persona variability.

Result 2: Robustness Drop

Insecure variants lose within-persona stability: R drops **65% on average**. The excess beyond control is largest for GPT-4o, GPT-4.1, and Qwen3-235B.




Fig. 8. R falls sharply under insecure fine-tuning and less strongly under the matched secure-code control.

Result 3: Foundation-Wide Collapse

Insecure fine-tuning shifts both $\bar{\sigma}$ and S comparatively evenly across all five moral foundations, unlike the secure control.




Fig. 9. Per-foundation $\Delta\bar{\sigma}$ and ΔS show broad, uniform degradation under insecure fine-tuning.

Results 4: Profile Saturation

Without persona conditioning, insecure variants converge toward saturated MFQ profiles near the scale ceiling.



Fig. 10. Top: base models show differentiated moral profiles, while insecure fine-tunes collapse toward near-ceiling answers across foundations. Bottom: toxic-persona profiles differ from the insecure fine-tuned profile saturation.

Extension: Other Qwen Models and Datasets

We extend the same R/S diagnostics to Qwen3.5-397B and Qwen3.6-35B across code, medical, sports, and financial fine-tuning datasets.




Fig. 11. Aligned Qwen extension: harmful variants reduces R and increases S beyond control in all datasets.

Robustness Drop $\neq$ Loss of Coherence

Open-ended coherence C [1] and persona robustness R [5] capture distinct facets of EM across the main and extension models.




Fig. 12. Coherence loss and moral robustness drop are inversely related.

Future Directions

- **Extended experimentation:** test additional models, datasets, recipes, and training stages to map when collapse appears.
- **Mechanistic investigation:** measure whether persona-conditioned activations become less separable after EM fine-tuning.

References

[1] Jan Betley, Daniel Tan, Niels Warncke, Anna Sztyber-Betley, Xuchan Bao, Martin Soto, Nathan Labenz, and Owain Evans. Emergent misalignment: Narrow finetuning can produce broadly misaligned LLMs, 2025. URL https://arxiv.org/abs/2502.17424.
[2] Anthropic. The persona selection model, 2026. URL https://alignment.anthropic.com/2026/psm/.
[3] Miles Wang, Tom Dupre la Tour, Olivia Watkins, Alex Makelov, Ryan A. Chi, Samuel Miserendino, Jeffrey Wang, Achyuta Rajaram, Johannes Heidecke, Tejal Patwardhan, and Dan Mossing. Persona features control emergent misalignment, 2025. URL https://arxiv.org/abs/2506.19823.
[4] Jesse Graham, Brian A. Nosek, Jonathan Haidt, Ravi Iyer, Spassena Koleva, and Peter H. Ditto. Moral foundations questionnaire. PsycTESTS Dataset, 2011.
[5] Davi Bastos Costa, Felippe Alves, and Renato Vicente. Moral susceptibility and robustness under persona role-play in large language models, 2025. URL https://arxiv.org/abs/2511.08565.

davi.costa@usp.br