

No.	Time	Source	Destination	Protocol	Length	Info
1010	212.878605	192.168.0.103	66.6.101.171	HTTP	556	GET /dyn/str_strip/

000000000/00000000/0000000/000000/70000/3000 HTTP/1.1

Frame 1010: 556 bytes on wire (4448 bits), 556 bytes captured (4448 bits) on interface \Device\NPF\_{F69135E3-F800-4849-9B7E-D6BA2ECEC81A}, id 0

Ethernet II, Src: 5a:00:b4:e5:9c:fb (5a:00:b4:e5:9c:fb), Dst: Tp-LinkT\_fb:ed:d2 (70:4f:57:fb:ed:d2)

Internet Protocol Version 4, Src: 192.168.0.103, Dst: 66.6.101.171

Transmission Control Protocol, Src Port: 49163, Dst Port: 80, Seq: 1, Ack: 1, Len: 502

Hypertext Transfer Protocol

GET /dyn/str\_strip/00000000/00000000/0000000/000000/70000/3000 HTTP/1.1\r\n

Host: www.dilbert.com\r\n

Connection: keep-alive\r\n

Upgrade-Insecure-Requests: 1\r\n

User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/80.0.3987.132 Safari/537.36\r\n

Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,image/apng,\*/\*;q=0.8,application/signed-exchange;v=b3;q=0.9\r\n

Accept-Encoding: gzip, deflate\r\n

Accept-Language: ru-RU,ru;q=0.9,en-US;q=0.8,en;q=0.7\r\n

\r\n

[Full request URI: http://www.dilbert.com/dyn/str\_strip/00000000/00000000/0000000/000000/70000/3000]

[HTTP request 1/1]

[Response in frame: 1012]