

Practical : 4	Implementation and Time analysis of factorial program using iterative and recursive method
Date : 15/07/2026	

Aim: To implement and compare iterative and recursive methods for calculating the factorial number.

Objective :- To implement programs to calculate the factorial of a given number in C++ using both iterative and recursive methods, and to analyze and compare their respective time and space complexities.

A. Iterative Factorial Algorithm

1. Start.
2. Read n.
3. Initialize result = 1.
4. Run a loop from 1 to n.
5. Multiply result by the current value.
6. Return the result.
7. Stop.

B. Recursive Factorial Algorithm

1. Start.
2. Read n.
3. If $n \leq 1$, return 1.
4. Otherwise calculate $n \times \text{factorial}(n-1)$.
5. Continue until the base case is reached.
6. Return the result.
7. Stop.

Program:

```
#include <iostream>

using namespace std;

// 1. Iterative Method long long
factorialIterative(int n) { long
```

```
        long result = 1; for (int i =  
1; i <= n; i++) { result *= i;  
        }  
        return result;  
    }  
  
// 2. Recursive Method long long  
factorialRecursive(int n) { // Base  
    Case if (n <= 1) {  
        return 1;  
    }  
  
    // Recursive Case return n *  
    factorialRecursive(n - 1);  
}  
  
} int main() { int num; cout <<  
"Enter a positive integer: "; cin >>  
    num;  
  
    if (num < 0) {  
        cout << "Factorial of a negative number is not defined."  
        << endl;
```

```
    }  
    else  
    {  
        // Iterative Method long long iterativeResult  
        = factorialIterative(num); cout << "\n---  
        Iterative Method ---" << endl; cout <<  
            "Factorial of " << num  
            << " is: " << iterativeResult << endl;  
        // Recursive Method long long  
        recursiveResult = factorialRecursive(num);  
        cout << "\n--- Recursive Method ---" << endl;  
        cout << "Factorial of " << num  
            << " is: " << recursiveResult << endl;  
    } return  
    0;  
}
```

Output:

```
Output

Enter a positive integer: 10

--- Iterative Method ---
Factorial of 10 is: 3628800

--- Recursive Method ---
Factorial of 10 is: 3628800

=== Code Execution Successful ===
```

Analysis:

Time Complexity Analysis

Let n be the input number for which we need to calculate the factorial.

Iterative Method:

- o The iterative function executes a simple for loop that runs exactly n times to multiply the values from 1 to n . Since there are no nested steps, the execution time grows linearly with the input size.

Time Complexity= $O(n)$ Recursive

Method:

- o The recursive function calls itself continuously, decremented by 1 at each step:
 - o $T(n) = T(n - 1) + O(1)$
- o This sequence continues until it hits the base case ($n \leq 1$). This creates a total chain of n recursive function calls, resulting in a linear growth rate.

Time Complexity= $O(n)$

Space Complexity Analysis

Iterative Method:

- o The loop uses only a few fixed-size scalar variables (result, i) to run. The amount of memory occupied stays completely constant and independent of the input value n.

Space Complexity = $O(1)$

Recursive Method:

- o Every time a function calls itself, a new stack frame is pushed onto the system call stack to store the current state and return address. For an input of size n, the system must hold n active stack frames simultaneously before hitting the base case and unwinding.

Space Complexity = $O(n)$

Conclusion :-

While both methods successfully calculate the factorial of a number in linear time $O(n)$, their system overhead profiles are vastly different:

1. The Iterative Method is highly memory efficient. It works with a constant auxiliary footprint of $O(1)$ space, making it safe from stack exhaustion limits.
2. The Recursive Method is mathematically expressive and maps directly to the recursive definition of factorials. However, it requires linear auxiliary memory space of $O(n)$ due to the call stack overhead. For large inputs, this makes recursion prone to a stack overflow crash.