

Manpage of DVDA-AUTHOR

DVDA-AUTHOR

Section: User Commands (1)
Updated: August 2019
Index Return to Main Contents

NAME

dvda-author - manual page for dvda-author version dev-9999

SYNOPSIS

dvda-author [*OPTION*]. . .

DESCRIPTION

dvda-author dev-9999 creates high-resolution DVD-Audio discs from .wav, .flac and other audio files.

OPTIONS

Output options

- h, --help** Display this help.
- v, --version** Display version.
- q, --quiet** Quiet mode.
- d, --debug** Increased verbosity (debugging level)

-t, -veryverbose Like **-d** with enhanced verbosity for sample counts.

, **-maxverbose** Like **-t** with maximum verbosity on audio buffers (devel info).

-no-output Does not produce any file structure except for **-fixwav**. Computations will be performed.

-P, -pause Insert a final pause before exiting.

-P0, -pause=0 Suppress a final pause before exiting if specified in configuration file.

-l, -log path Output a log to filepath. Argument must be supplied.

-L, -logrefresh path Same as **-l** but prior log will be erased on launching again.

-loghtml Transform the log into HTML format, with colorized messages, adjacent to log with extension `.html` added.

-k, -text Generates text table in IFO files

Under development, implemented for 1-group discs.
Use file information as arguments separated by commas.

-W, -disable-lexer Deactivates configuration file parsing.

Playback options

-a, -autoplay Launches playback on loading disc.

Authoring options

Soundfile authoring

Supported audio types: `.wav`

`.flac` and `.oga` (Ogg FLAC, see below)
SoX-supported formats with **-S** enabled
except for lossy formats.

-project [file] Launches a dvda-author project.
The project file should have the same syntax as `dvda-author.conf` [see file `HOW_TO.conf`]
By default, launches `dvda-author.dap` in the current directory.

-i, -input directory Input directory with audio files.
Each subdirectory is a group.

-o, -output directory Output directory.

-x, -extract {disc or directory} Extract DVD-Audio to directory **-o**.

Groups are labelled `g1, g2` in output directory.

-xlist 1:1,...,t1n-2:1,...,t2n-...-N:1,...,tNn Optional hyphen-separated list of groups to be extracted

may be added with **-x**.

Tracks to be extracted in a given group are indicated after a colon.

Tracks to be extracted may be listed separated by commas after colon.

If not specified, all the group will be extracted.

Contiguous tracks may be represented by '...' between commas

e.g. 2-3-4:1,2,...,7,9 means: extract groups 2 and 3 entirely and tracks 2 to 7 and 9 for in group 4.

-aob-extract {directory or AOB[,AOB...]} Direct AOB file audio content extraction.

Unlike **-x**, this option does not use .IFO files. Use this option in combination with **-o**. No wav header is generated.

Several AOB files may be listed, separated by commas.

-aob2wav {directory or AOB[,AOB...]} Like **-aob-extract** but a wav header is prepended to audio content.

-forensic Use this mode with **-aob-extract**, **-aob2wav** or **-x** if IFO files are missing or mangled, or AOB files have been partially restored using recovery tools.

-strict Use this option with **-aob-extract**, **-aob2wav** or **-x** to stop extraction in case of severe header issues. May be useful in combination with **-forensic** to manually repair header issues.

-decode Use this option with **-extract** or **-aob2wav** to decode MLP audio to the WAV format.

This option is based on the ffmpeg decoder and is subject to the same legal restrictions as those applying to the MLP ffmpeg decoder.

-log-decode [AOB] Decode AOB file and log MPEG specifics. Should be used only in conjunction with **-outfile**

-outfile [file] Path to the log generated by **-log-decode**. Caution : should be alone in its own directory.

-p, -startsector NNN Specify the number of the first sector

of the AUDIO_PP.IFO file in the output of mkisofs.

If NNN=0, falling back on 281 (default).

Without **-p** start sector will be computed automatically.

-g You may specify up to 9 groups of tracks.

Minimum: one group. Enter full path to files if input directory is not set by **[-i]**.

-z, BROKEN. Separate two consecutive titles when files have same audio characteristics within a group.(

-Z, -playlist You may specify up to 9 group copies.

Total number of groups and copy groups should not exceed 9.

-n, -no-videozone Do not generate an empty VIDEO_TS directory.

-w, -rights Access rights to directories created (octal values)

-c, **-cga** Enter channel group assignment right after group, e.g: **-g** file1...fileN
-c cga1...cgaN

Channel assignment should match number of channels of each file

Combine channels using either decimal indexes in following table or hyphenated

channel assignement labels

e.g. **-g** a.wav **-g** b.wav **-c** Lf-Rf-C2-Lfe2-S2 **-cga** 17

Channel group assignment (CGA)

Index 1 2 3 4 5 6

0 M

1 L R

2 Lf Rf S2

3 Lf Rf Ls2 Rs2

4 Lf Rf Lfe2

5 Lf Rf Lfe2 S2

6 Lf Rf Lfe2 Ls2 Rs2

7 Lf Rf C2

8 Lf Rf C2 S2

9 Lf Rf C2 Ls2 Rs2

0xA-10 Lf Rf C2 Lfe2

0xB-11 Lf Rf C2 Lfe2 S2

0xC-12 Lf Rf C2 Lfe2 Ls2 Rs2

0xD-13 Lf Rf C S2

0xE-14 Lf Rf C Ls2 Rs2

0xF-15 Lf Rf C Lfe2

0x10-16 Lf Rf C Lfe2 S2

0x11-17 Lf Rf C Lfe2 Ls2 Rs2

0x12-18 Lf Rf Ls Rs Lfe2

0x13-19 Lf Rf Ls Rs C2

0x14-20 Lf Rf Ls Rs C2 Lfe2

Keys:

Index 2 means channel belongs to Group2

M: Mono

Lf: Left front

Rf: Right front

Ls: Left surround (behind)

Rs: Right front

C: Center

Lfe: Low Frequency Effect (Subwoofer)

S: Surround (just one behind)

Ls: Left surround

Rs: Right surround

Each group must have either same sample rate or be even multiples (e.g.
96kHz/48 kHz or 88.2 kHz/44.1 kHz)

Within groups, bitrate may differ but sample rate cannot.

-downmix Enter downmix coefficients in dB. If track has more than 2 channels,

each channel (Lf, Rf, C, Ls or S, Rs, LFE)
will be mapped to left (l) and/or right (r) stereo channel
with volume reduced by x dB, x the channel downmix coefficient.
Enter positive dB values corresponding to each channel volume reduction,
mapped to left or right stereo, separated by commas.
Schema is **-downmix** Lf.l,Lf.r,Rf.l,Rf.r,C.l,C.r,S.l,S.r,Rs.l,Rs.r,LFE.l,LFE.r
Use 100 for 'off' value and 0 for no volume reduction.
This option can be repeated up to 16 times. It is cyclically recycled to 16 times
to provide as many downmix tables.
Each track can be indexed using **-dtable** to be downmixed with the corre-
sponding table.
Example : **-downmix** 6.2,100,100,7.2,0,0,13,13,16,16,0,0 **-downmix**
5.2,100,100,8.2,0,0,10,10,12,12,0,0 **-dtable** 2 **-dtable** 1
means that track 1 will be downmixed using the second table and track 2 the
first one.
-dtable Enter downmix table rank (1-based) as indicated above.
-provider Enter provider name.
-F, -fixwav(options) Bad wav headers will be fixed by fixwav.
Can be run alone without DVD-AUDIO output by adding **-nooutput**.
-f, -fixwav-virtual(options) Use .wav header repair utility
without any write operation.
-S, -sox Use SoX to convert file format to .wav.
Without **-S** or **-resample** (see below), only flac, Ogg FLAC
and .wav files are accepted.
-resample c b s Use SoX to convert file format to .wav, and/or change channel
to c, bitrate to b, samplerate to s.
You do not need to use **-S** with **-resample**.
Always provide the three values c b and s separated by white space in the same
order as in the previous **-g** files.
-padding Reverse default behaviour for transition between audio tracks with
identical
characteristics (number of channels, bit depth and sample rate).
If necessary, audio will be padded with 0s instead of being joined (default).
Use **-pad-cont** for padding with last-known byte.
-C, -pad-cont When padding, pad with last known byte, not 0. See **-padding**
above.
Deactivates **-lossy-rounding**
-L, -lossy-rounding Sample count rounding will be performed by cutting audio
files
instead of padding (see **-padding** and **-pad-cont**).
Deactivates **-pad-cont** and **-padding**.

Menu authoring

-m, -topmenu(=mpgfiles) Generates top menu from comma-separated list of mpgfiles.

Without argument, automatic menu generation is launched.

-u, -duration hh:mm:ss Duration of top menu file, if provided.

It is mandatory when **-topmenu** has an argument file.

-M, -xml filepath Generates dvdauthor xml project to filepath.

-H, -spuxml filepath Generates spumux xml project to filepath.

-G, -image file Menu Background image for customized menu authoring.

-E, -highlight file Menu Highlight image for customized menu authoring.

-e, -select file Menu Select image

image that appears on pressing Enter with remote control usually Background with a change in text color.

-N, -blankscreen file For automatic menu authoring, you can replace black video background with this image.

-O, -screentext string Text for top menu. Format is

“album_text=group1_text=text(track11),text(track21),... ,text(trackn1):group2_text=text(track12),text(trackn2),... ,text(trackn2):groupk_text=text(tracknk),text(trackn1):groupk_text=text(tracknk) the text for track n of group k and groupk_text the text for group k.

-U, -loop loop background video.

-K, -highlightformat -1 for automatic menu authoring

with little square before titles, 0 for underlining, 1 for button highlight.

-J, -font a,b,c Font name,font size,font width

(number of pixels for width of font size 10).

Font name should be compatible with Image magick specifications (mogrify **-list** font).

-fontname a Font name.

-fontsize b Font size.

-fontwidth b Font width.

-Y, -topmenu-palette string Text for system palette. Format is

either “norefresh”, to block the refreshing of menu images, or:
textcolor:highlight_color:select_action color

in alpha-YCrCb 32-bit hexa coding. Here textcolor is the non-highlighted text for tracks,
,highlight_color is the underline or mobile motif color,
and select_action_color is album and group labels
as well as color of tracks on pressing the highlighted track.

-8, -activemenu-palette string Text for menu colors. Format is:

textcolor:highlight_text_color:highlight_color:select_action_color
in alpha-YCrCb 32-bit hexa coding. Here textcolor is the text for tracks,
highlight_text_color is the color of album and group labels and highlighted text (broken feature)
highlight_color is the underline or mobile motif color,
and select_action_color is on pressing the highlighted track.

-y, -topmenu-colors string Text for menu colors. This is a developer's switch.

Use the **-palette** switches for modifying display colors.
This switch determines the colors of pictures generated in the temporary directory before creating the mpg background files.
Format is either "norefresh", to block the refreshing of menu images, or
textcolor:backgroundcolor:highlightcolor:select action color in rgb values a,b,c
between 0 and 255.

-b, -background Background jpg files (comma-separated) to create a background mpg file

into which titles are multiplexed.
Specify as many files as there are menus, or the last file will be duplicated for missing menu files.

-background-colors Background RGB colors to colorize background mpg files into which titles are multiplexed.

Specify as many colors as there are menus, or the last color will be duplicated for missing menu colors.

Syntax is r,g,b:r2,g2,b2:...:rk,gkbk for **-nmenus=k**.

-B, -background-mpg list Background mpg file(s) in a comma-separated list into which titles are multiplexed.

-topmenu-slides file(s) .jpg image files to be multiplexed with sound tracks (see option below)
By default a black screen will be used.

Each menu screen should have at least one associated .jpg slide. List of slides is comma-separated for each menu.

Menu lists are colon-separated: menu1_pic1,menu1_pic2:menu2_pic1,menu2_pic2,
etc.

-Q, -soundtracks file(s) Background wav file(s)

to be multiplexed into a slideshow, with option **-topmenu-slides**.

By default a silent track will be multiplexed.

Each menu screen should have its own sound track. List of tracks follows same usage as for **-topmenu-slides**.

Note that currently with several menus there can be only one track/slide per menu.

-A, -topvob f Import already authored top vob menu f.

-import-topmenu f Import VIDEO_TS stream (VOB format) into AUDIO_TS top menu (AUDIO_TS.VOB).

-0, -menustyle desc Specifies top menu style

By default, tracks are listed under group headers.

If desc='hierarchical', the first menu screen lists groups.

If desc='active', all tracks will have an associated still picture with menu links that remain active while listening to the track.

-1, -stillvob f Import already authored still pictures vob.

-2, -stilloptions ... Still picture options (add after **-stillpics**). Each option applies to ranked pic, e.g.

rank=0>manual,starteffect=fade,rank=1,starteffect=dissolve.

Suboptions are:

rank=[number], starteffect=[effect], endeffect=[effect]
manual, lag=[number], start=[number], active

See details below.

-stillpics Background jpg files to create one or more still pictures for each track. See usage below.

If a track has no still picture, use two colons in a row.

You may otherwise indicate a directory containing pictures named pic_abc.jpg, with a,b,c between 0 and 9.

-stillpics dir/ Directory for background jpg files to create one still picture for each track.

Pics should be named pic_000.jpg, ..., up to pic_999.jpg (maximum).

-4, -norm Argument is 'ntsc', 'pal' or 'secam', depending on TV standard.

-5, -aspect Set the playback aspect ratio code of the encoded video. By default, this value is inferred from the input header.

1 - 1:1 display

2 - 4:3 display

3 - 16:9 display

4 - 2.21:1 display

-6, -nmenus int Generates int top menus (default 1).

-7, -ncolumns int Top menus will have at most int columns (default 3).

Disc authoring

-I, -mkisofs(=file) Run mkisofs to author disc image using file as an ISO image. If file is empty, use tmpdir/dvd.iso.

-r, -cdrecord(=a,b,c) Run cdrecord to burn disc image.

Unless specified, **-mkisofs** will be automatically triggered with default tmpdir/dvd.iso value.

Device is of the form a,b,c, see cdrecord **-scanbus**. It can be omitted if there is just one writer.

-R, -growisofs /dev/dvd Run growisofs to burn disc image.

Device is of the form /dev/scd0 under many GNU/Linux distributions. It cannot be omitted.

DVD-VIDEO zone authoring

-lplex-output dir Output directory for lplex
Default is same as specified **-o** value
or default output directory.

-dvdv-tracks ... Add tracks to be added to DVD-VIDEO zone using lplex:
track11,...,trackn1:track12,...,trackn2:...
for trackij the ith track of video titleset j.

-dvdv-slides ... Add slides to be added to DVD-VIDEO zone using lplex:
slide11,...,sliden1:slide12,...,slide2:...
for slideij the ith slide of video titleset j.
Each track should have a corresponding slide.
Add two commas in a row for repeating previous slide.
There can be a maximum of 1 slide per track.

-V, -videodir directory Path to VIDEO_TS input directory

-T, -videolink rank Rank of video titleset linked to in video zone
(XX in VTS_XX_0.IFO).

In this case the path to the VIDEO_TS linked to must be indicated.

-dvdv-import Create DVD-VIDEO zone from DVD-AUDIO zone.
Import DVD-Video standard compliant files (16-24 bit/48-96 kHz from DVD-AUDIO to DVD-VIDEO.

-mirror Like **-dvdv-import** but resample audio tracks if they are not DVD-Video compliant (.wav files only)

-mirror-strategy st Values for st are: 'high' or 'low'. If necessary, **-mirror** will resample audio tracks by upsampling (high) or downsampling (low)

-hybridate Alias for **-dvdv-import**

-dvdv-slides=... with each slide the first slide of **-stillpics=...** for each audio track.

-full-hybridate Alias for **-mirror -mirror-strategy high**

-dvdv-slides=... with each slide the first slide of **-stillpics=...** for each audio track.

Software configuration

-D, -tempdir directory Temporary directory for DVD-Audio files (dvda-author).

Optional. CAUTION: tempdir will be erased unless **-no-refresh-tempdir** is used.

-9, -datadir directory Data directory with subdirectory 'menu' containing at least default backgrounds for menus. Optional, only to be used when menus are created.

, -lplex-tempdir directory Temporary directory for DVD-Video files (lplex) Optional.

-X, -workdir directory Working directory: current directory in command line relative paths.

By default, the current directory.

With Code::Blocks and similar IDE, you may have to specify your root package directory as argument to **-workdir**.

-no-refresh-tempdir **Do not erase and recreate the DVD-Audio temporary directory on launch**
Do not erase and recreate the output directory on launch.

-bindir path Path to auxiliary binaries.

Sub-options

fixwav sub-options:

simple-mode

Deactivate default automatic mode and advanced options.

User will be asked for more information.

prepend

Prepend header to raw file, maybe virtually

in-place

Correct header in the original file (not advised) unless real is set later

cautious

Be cautious when overwriting files in-place

interactive

Request information from user.

padding

Pad files according to WAV standard

prune

Cuts off silence at end of files

force

Launches fixwav before SoX for mangled headers

output=sf

Copy corrected file to new filepath with string suffix sf

infodir=db

Copy info chunks from wav headers to file db/database

virtual

Forces virtual behavior over previous settings (files will be unmodified)

real

Forces real behavior over previous settings (files will be modified)

Sub-options should be separated by commas and appended after short option or after = sign if long option is used:

-f/-Fsuboption or -fixwav(-virtual)=suboption without any whitespace in between them.

Example: **-fixwav=***simple-mode*,prepend,interactive,output=new

Still pictures:

p11,p21,...,pn1-p22,p22,...,pn2-...

with tracks separated by hyphens and pictures by colons.

Examples: **-g ~/a.wav -stillpics** image1.jpg,image2.jpg,image3.jpg:image4.jpg,image5.jpg,image6.jpg

If there are no pics for a track use :: as below (no pics for second track):

-g ~/a.wav ~/b.wav ~/c.wav -stillpics image1.jpg,image2.jpg,image3.jpg::image4.jpg,image5.jpg,image6.jpg

Still picture transition effects:

rank=k

k is the absolute rank of stillpic (0-based) to which the following options apply (order-dependent).

start=k

picture starts at k sec from start of track.

manual

Enable browsable (manual advance) pictures (experimental).

starteffect=effect

transition effect at start of pic: cut (default), fade, dissolve, top-wipe, bottom-wipe, left-wipe, right-wipe.

endeffect=effect

like starteffect at end of pic show (under development)

lag=k

k is the duration of transition effect in multiples of 0.32 second ($k < 16$).

active

menu links will be displayed on still picture and remain active while listening.

Example: **-stilloptions** rank=0,start=03,starteffect=fade,lag=12,rank=1,start=20,starteffect=dissolve,lag=15

Transition effects like fade or dissolve may vary depending on hardware.

End effects may be visible only when several pictures are used for a track slide.

If a track has just one still pic, only start effects may be visible.

Note: for optional arguments noted (=...) above, usage is either

-xY, with x the option flag and Y the argument, or

-option=argument.

There must be a maximum of 9 audio groups.

Each subdirectory of an audio input directory will contain titles

for a separate audio group.

A number between 1 and 9 must be included as the second character of the

subdirectory relative name.

Full Input/Output paths must be specified unless default settings are set.

By default, defaults are set in */full* path to dvda-author folder/defaults

EXAMPLES

-create a 3-group DVD-Audio disc (legacy syntax):

```
dvda-author -g file1.wav file2.flac -g file3.flac -g file4.wav
```

-create a hybrid DVD disc with both AUDIO_TS mirroring audio_input_directory and VIDEO_TS imported from directory VID, outputs disc structure to directory DVD_HYBRID and links video titleset #2 of VIDEO_TS to AUDIO_TS:
dvda-author -i ~/audio/audio_input_directory
-o DVD_HYBRID -V Video/VID -T 2

-create an audio folder from an existing DVD-Audio disc:

dvda-author -extract /media/cdrom -xlist 1-3:2-5:3,...,7,9-6-7 -o dir

will extract audio groups 1, 3 (track 2), 5 (tracks 3 to 7 and 9), 6 and 7 of the disc to

dir/g1, dir/g3, dir/g5, dir/g6, and dir/g7 respectively.

Required compile-time constants:

_GNU_SOURCE, __CB__ if compiling with Code::Blocks or similar IDE.

Optional compile-time constants:

LONG_OPTIONS for the above long options (starting with -)

SHORT_OPTIONS_ONLY to block all long options.

LOCALE to recompile for another locale than the default “C”.

SETTINGSFILE to specify default filepath of the configuration file.

FLAC__HAS_OGG to enable Ogg FLAC support.

_LARGEFILE_SOURCE, _LARGE_FILES, _FILE_OFFSET_BITS=64

to enable large file support.

ALWAYS_INLINE forces code inlining.

WITHOUT_sox to compile without SoX code

WITHOUT_FLAC to compile without FLAC/OggFLAC code

AUTHOR

Written by Dave Chapman, Fabrice Nicol, Lee and Tim Feldkamp.

REPORTING BUGS

Report bugs to fabnicol@users.sourceforge.net

COPYRIGHT

Copyright 2005 Dave Chapman; 2008-2009 Lee and Tim Feldkamp; 2007-2016 Fabrice Nicol.

See file AUTHORS for other contributors.

Latest version available from <http://dvd-audio.sourceforge.net/>

This is free software; see the source for copying conditions.

SEE ALSO

The full documentation for **dvda-author** is maintained as a Texinfo manual. If the **info** and **dvda-author** programs are properly installed at your site, the command

info dvda-author

should give you access to the complete manual.

Index

NAME

SYNOPSIS

DESCRIPTION

OPTIONS

EXAMPLES

AUTHOR

REPORTING BUGS

COPYRIGHT

SEE ALSO

This document was created by man2html, using the manual pages.
Time: 00:22:51 GMT, August 23, 2019