
RTM interview tool: worked examples

Seventy-five situations from a phone panel round, what to do in the tool for each, and what the tool does not do yet

For enumerators, team leaders, and teams that interview in KoBoToolbox



Tool version 0.4.0 · Examples of 3 November 2026 · Companion to the user manual, whose part and section numbers are given in brackets

Real-Time Monitoring (RTM) Handbook task team. Every picture shows the synthetic practice program “L2MN-DEMO”, round 5, 26 October to 20 November 2026: no real household, name or phone number appears anywhere in it.

Contents

Each example gives the situation, the steps in the tool, a picture of the screen, and what the tool records.

Part 1 · The enumerator, on the phone

E1 Who do I call first this morning?
E2 Why is this household on my list?
E3 Nobody answers
E4 “Call me back this evening”
E5 “Call me back on Saturday evening”
E6 The number is dead
E7 No number works
E8 The household refuses firmly
E9 The respondent gives a new number
E10 I logged the wrong result
E11 I called earlier and forgot to log it
E12 The interview took two minutes
E13 The household should be left alone this round
E14 The leader sent me an updated file
E15 I received a household someone else started
E16 End of the day: save and export
E17 How am I doing compared with last round?
E18 Is tomorrow a working day?
E19 Working from a phone
E20 My file asks for a passphrase
E21 A neighbour says when to call
E22 I am off on Friday morning
E23 My leader approves replacements
E24 Someone else answers
E25 We do not share a language
E26 The interview stops halfway
E27 “Not now, I am busy”
E28 My computer shut down before I saved
E29 The respondent blocked my number
E30 Nobody ever answers: ask for a visit

Part 2 · The team leader

L1 Start the round
L2 Set the calendar, with a holiday in the window
L3 An enumerator is away this round
L4 Two areas speak another language
L5 Choose the rule and the rotation share
L6 Check the loads before writing anything
L7 Keep one household with a particular enumerator
L8 Set the day list
L9 Write the files, protected
L10 Stop for today, continue tomorrow
L11 Import the exports and settle the questions
L12 An export has not arrived
L13 Two enumerators completed the same household
L14 A respondent's new number reaches the list
L15 How far are we?
L16 Someone will not finish; someone has spare days
L17 An enumerator finished early
L18 An enumerator fell ill
L19 A new enumerator starts on Monday
L20 Give out the revised files
L21 A call made after the move
L22 End of the round: the files for next round
L23 Who is likely to drop out?
L24 How did earlier rounds go?
L25 Let enumerators adjust their own schedule
L26 Three calls a day over five days
L27 Approve replacements in a batch
L28 The same file arrives twice
L29 Only the CSV arrived
L30 Last month's file is in the folder
L31 Someone edited an export by hand
L32 The round needs another week
L33 Households join mid-round
L34 An enumerator lost the passphrase
L35 Plan the field visits
L36 Numbers blocked by respondents
L37 A text message the day before
L38 Areas with no interviews

Part 3 · With KoBoToolbox

K1 The team interviews in the Philippines-style form
K2 Each day: the form's export
K3 Our form has other column names
K4 After moves, the form must follow
K5 A submission to look at in KoBoToolbox
K6 An interviewer typed a wrong code
K7 The form gained a new result code
K8 One interviewer, two codes

Part 4 · What the tool does not do yet

X1 Fieldwork situations
X2 Files and platforms
X3 Beyond the tool's purpose

> **How to read an example.** Each one is written for the person at the keyboard. **Words in this style** are buttons or fields on the screen. The round in every picture is the practice round of the user manual: enumerator E07 with 38 households, leader L01 with three enumerators, and the files of `samples/`. Nothing here needs a server or an internet connection.

Part 1 · The enumerator, on the phone

Thirty situations in a calling day, from the first call to the export

E1 Who do I call first this morning?

Situation. It is 10 a.m. on a working day. You have 38 households this round and want to start without thinking about the order.

1. Open the tool and choose **Open my assignment file** (the first day) or **Continue a saved session** (every later day).
2. Stay on the **Today** tab. The left column, **Due now**, is the order to call: callbacks booked for this hour first, then the households planned for today at their target hour.
3. When the column empties, the next columns fill it: **Later today** and households pulled forward from later days, so that unanswered calls never leave you idle.




Figure E1. The Today tab after opening the assignment: the summary, the tabs and the day's columns (manual A3).

What the tool records. Nothing yet: looking never changes the log.

E2 Why is this household on my list?

Situation. A household you have never called appears in your list, planned for Thursday at 20:00.

1. Click the household's card. The panel opens with its contact and the plan.
2. Open **Why is this household with me?** It gives the reason of the assignment (kept from last round, rotated, matched by language, moved from an enumerator who is away), the last interview and who made it, and why the first dial is planned at that hour.




Figure E2. The reasons, opened (manual A7).

What the tool records. Nothing. The reasons were written into your assignment file by the leader's rule.

E3 Nobody answers

Situation. The phone rings and nobody picks up.

1. Dial with your call center's phone system. When you give up, press **Log a call** beside the number in the household's panel.
2. Set when you dialled and the minutes, choose **No answer** and save.
3. Close the panel: the household has left **Due now** and sits in **Later today**, to be tried again after the other calls.

0101-002

Contact 0101-002 (synthetic)

In progress

Switched to you: hard to reach with the previous enumerator

▶ Why is this household with me?

Next: today 12:07 · Same day, at least two hours after the last dial

Move the next call

Usual time	09:00, from the last interview
Last interview	round 2, Wed 29 Jul at 09:00
Last three rounds	2 ● 3 ○ 4 ○ ● interviewed · ○ not
In the panel since	round 1
First dial planned	Mon 26 Oct at 09:00
Sampling unit	0101 · stratum 1

PHONE NUMBERS

Number 1 · respondent

+000 01002 1712 Copy

1 dial this round, last: No answer

Log a call

Add or correct a number

CALLS THIS ROUND




Figure E3a. The household's panel after a no-answer: the call is in “Calls this round”.




Figure E3b. Back on Today, the household (outlined) waits in “Later today”.

What the tool records. One dial with its start, end, the number used and the result, counted toward the household's dial cap.

E4 “Call me back this evening”

Situation. The respondent answers but is at work and asks you to call at half past six.

1. Log the call, choose **Appointment booked** and enter the time in the callback field; a missing time is outlined and named before you can save.
2. Save. The household moves to **Later today** under 18:30, and at that hour it is first in **Due now**.




Figure E4a. The callback time is required for an appointment (manual A11).




Figure E4b. The booked callback at 18:30 (manual A12).

What the tool records. The dial with the result “appointment” and the agreed time. If the household is later moved to another enumerator, the time goes with it (L20).

E5 “Call me back on Saturday evening”

Situation. The respondent is travelling and asks for Saturday at six.

1. As in E4, with the Saturday date and time.
2. Open the **Calendar** tab: Saturday shows the callback. On Saturday the household appears in **Due now** at 18:00, before anything planned.




Figure E5. The calendar with a callback booked for Saturday 31 October. The 10 November holiday is hatched.

What the tool records. The same as E4. A callback outside the round window is refused when you save it.

E6 The number is dead

Situation. The first number gives “not in service”. The household has a second number.

1. Log the call and choose **Number not in service**. The first number is marked, and the second is now the one to try.
2. Dial the second number, then log that call against it.




Figure E6. After a dead number: the first number carries its last result, the next one is ready.

What the tool records. The dial on number 1 with the result; the leader's merge later shows which numbers of a household are no longer working.

E7 No number works

Situation. Every number of the household is dead or wrong.

1. Log each number's result as in E6.
2. When no working number is left, the **Replacements** section offers **Activate the next replacement**, if the program allows replacements after “no working number” and the household has one.
3. Confirm. The replacement household appears in your list with the reason; the original stays in the list, read-only, as “replaced”.

PHONE NUMBERS

Number 1 · respondent

+000 02001 1517 Copy

1 dial this round, last: Number not in service · **not working**

Log a call

Number 2 · spouse

+000 02001 2232 Copy

1 dial this round, last: Number not in service · **not working**

Log a call

Add or correct a number

CALLS THIS ROUND

1. 10:12–10:12 Tue 27 Oct · number 1 · **Number not in service** · 0.5 min
Correct or void

2. 10:15–10:15 Tue 27 Oct · number 2 · **Number not in service** · 0.5 min
Correct or void

ACTIONS

Release for this round | Ask for another enumerator




Figure E7. Every number dead: the replacement can be activated.

What the tool records. The dials, and an action “activate replacement” with the reason “no working number”, which the leader's merge reads to count the household as replaced.

E8 The household refuses firmly

Situation. The respondent says never to call again.

1. Log the call and choose **Refusal, firm**. A soft refusal (“not now”) is a different result and leaves the household open.
2. The household is closed for the round. If the program allows a replacement after a hard refusal, **Activate the next replacement** appears; confirm it with the reason.




Figure E8a. After a hard refusal (manual A19).




Figure E8b. Confirming the replacement (manual A20).

What the tool records. The dial with the hard refusal; the household is never proposed for a move to another enumerator, and next round the leader's rule can mark it hard to reach.

E9 The respondent gives a new number

Situation. The respondent answers on the second number and says the first one is gone; here is the new one.

1. In the panel's **Actions**, press **Add or correct a number**, enter the number and which slot it replaces, and save.
2. From now on your list calls the new number. The change travels to the leader in a separate contacts file at export (E16), never through the common folder.




Figure E9. Adding or correcting a phone number (manual A18).

What the tool records. A contact update, with the number's digest in the log and the number itself only in the contacts file, which the leader moves into the household list for the next round (L14).

E10 I logged the wrong result

Situation. You saved “no answer” but the respondent had in fact booked a callback.

1. In **Calls this round**, press **Correct or void** on the call.
2. Change the result and the time, and save; or tick the box to void the call entirely, with a note.




Figure E10. Correcting a logged call; the tick box voids it instead (manual A15).

What the tool records. A correction event pointing at the original, which stays in the log: the leader sees both and the counts use the corrected one.

E11 I called earlier and forgot to log it

Situation. You called a household an hour ago from the office phone while the tool was closed.

1. Open the household and press **Log a call** beside the number you used.
2. Set the start time to when you called, the minutes and the result, and save.

LOG A CALL · 0101-004

Dial with your call center's phone system, then log the call here: when it started, how many minutes it lasted, and what happened. The tool records when you logged it too. A complete counts from 3 minutes (Box 3.0).

Number

1 · respondent

Call started

10/27/2026, 08:50 AM

Minutes

1

Result of the call

- ○ Complete
- ○ Appointment booked
- ○ Partial interview
- ○ Respondent not available
- ○ No answer
- ○ Busy
- ○ Switched off / unreachable
- ○ Our number is blocked
- ○ Number not in service
- ○ Wrong number
- ○ Refusal (may retry)
- ○ Refusal (do not retry)
- ○ Language barrier
- ○ Other (write a note)

Callback time, if one was agreed

mm/dd/yyyy --:-- --

After this call

Keep calling




Figure E11. Logging a call made earlier (manual A14).

What the tool records. The dial with the times you gave, and the time you logged it. The leader's merge flags a call logged long before it started.

E12 The interview took two minutes

Situation. You saved a complete, but the call lasted two minutes.

1. The panel warns: a complete under three minutes does not count for the round (Box 3.0).
2. If the time is wrong, correct it (E10). If the interview really was that short, call again and complete it.




Figure E12. A complete that lasted two minutes (manual A13).

What the tool records. The dial as saved. The leader's progress shows the household as “complete under 3 min”, not as complete.

E13 The household should be left alone this round

Situation. A family member says the respondent is in hospital for the rest of the month. It is not a refusal.

1. In **Actions**, press **Release** and give the reason.
2. The household leaves your day's lists for this round and stays in the panel for next round. The release can be undone.
3. If the household should leave the panel for good, use **Request removal** instead: the leader decides.




Figure E13a. A household's actions (manual A16).




Figure E13b. Releasing a household for the round (manual A17).

What the tool records. An action with its reason; the leader's progress counts the household as released, not as a miss.

E14 The leader sent me an updated file

Situation. Part-way through the round the leader moved some of your households to a colleague, and the leader's folder has a new assignment file for you.

1. With your session open, choose **Load updated assignment** and pick the new file. Your log is kept.
2. The summary counts the households no longer assigned to you and those that arrived. A household that left stays visible, read-only, with a notice: do not call it again.
3. An older file than the one you have is refused.




Figure E14a. After loading the updated file: the summary counts two households no longer assigned.




Figure E14b. A household that left: read-only, with the notice; its calls stay in the log.

What the tool records. An “assignment updated” event with the file's revision. Any dial you make on a household that left is flagged in the leader's merge as a double call.

E15 I received a household someone else started

Situation. One of the households that arrived with the updated file was already called twice by its previous enumerator, who booked a callback.

1. Open the household. The panel shows who had it, how many dials they made, the last result and the booked callback.
2. The callback is due at its time, as if you had booked it; the earlier dials count toward the cap.




Figure E15. A household received from E07: the handover facts.

What the tool records. Your own dials from now on. The previous dials stay in the previous enumerator's log, and the leader's merge joins the two.

E16 End of the day: save and export

Situation. It is 7 p.m. The leader wants everyone's calls in the common folder.

1. Press **Save session**: the session file stays in your own folder and holds the contacts.
2. Press **Export log**: the JSON and the CSV go to the common folder. A contacts file appears only if you changed a number (E9), and goes to the leader directly.
3. **Close session**. If anything is unsaved, the tool says so first.




Figure E16a. The line under the buttons after saving (manual A25).




Figure E16b. The export window (manual A27).

What the tool records. The export time in the log. Every export is the whole round so far, so the leader can use the newest one alone.

E17 How am I doing compared with last round?

Situation. You want to know your completes per day and whether this round is going as the last one did.

1. Open **My performance**. This round's figures are there already.
2. Press **Load earlier logs** and pick your own exports of earlier rounds: they appear beside this round.




Figure E17. My performance, with round 4 loaded (manual A23).

What the tool records. Nothing. The figures are computed from your logs on the spot; nobody else's log is shown.

E18 Is tomorrow a working day?

Situation. Next Tuesday is a public holiday and you are not sure whether calls are planned.

1. Open the **Calendar** tab. Days the call center does not work are hatched; the plan puts no first dial on them, but a callback a respondent asks for can still be booked.




Figure E18. The calendar, with the 10 November holiday hatched (manual A22).

What the tool records. Nothing. The calendar comes from the leader's round settings in your file.

E19 Working from a phone

Situation. You are calling from a mobile and want the list on the same screen.

1. Open the same file on the phone's browser. The columns stack, the household opens full-screen, and every button is the same.




Figure E19a. Today, on a phone (manual A28).




Figure E19b. A household, on a phone (manual A29).

What the tool records. The same log. Save the session to a file you can move back to the laptop.

E20 My file asks for a passphrase

Situation. The leader protected the assignment files and gave you a passphrase on a slip.

1. Open the file; type the passphrase. It is never stored, and your saved session is protected with it too: you need it each time you open the file or continue the session.




Figure E20. A protected assignment file asks for its passphrase (manual A2).

What the tool records. Nothing about the passphrase. A wrong one simply does not open the file.

E21 A neighbour says when to call

Situation. You reached a neighbour on a household's second number. The family works in the fields all day and answers after seven in the evening. Its first call is planned for tomorrow at ten.

1. Open the household. Under **Next**, click **Move the next call**.
2. Choose tomorrow at 19:00, the reason **Someone said when to call**, and a short note. **Save the new time**.
3. The household's next call now reads **Moved by you**; **Undo my change** takes it back. Your next dial ends the change.




Figure E21. Moving a household's next call, with the reason (manual A23).

What the tool records. A "moved call" event with the new time, the time it replaced and the reason. Your leader counts it. A first call cannot go past the round's first-call period unless the leader allows it, and a respondent's own callback is changed on its call instead.

E22 I am off on Friday morning

Situation. You have a medical appointment on Friday morning and will start calling at one.

1. Open the **Calendar** tab. Under **My time off**, choose Friday and **the morning, until 13:00**, and click **Mark as off**.
2. If a respondent booked a callback that morning, the tool names the household first: call it earlier or rebook it. Otherwise the calls planned that morning move to the afternoon.




Figure E22. A morning off, marked on the calendar (manual A24).

What the tool records. A “time off” event. When your export arrives, your leader sees it, and the round's pace counts only the days you work. **I will work after all** takes it back.

E23 My leader approves replacements

Situation. A respondent refused firmly. This round your leader decides each replacement, so the household's panel offers no “Activate” button.

1. Under **Replacements, in order**, click **Ask the leader for a replacement**, write why, and confirm.
2. The household waits, marked **Replacement asked**; you stop calling it. Your leader decides in a batch and sends you an updated file (E14).
3. Released: the replacement comes into your list with its contacts. Declined: the household opens again with your leader's note. To call it again before the leader decides, undo the request under **Actions**.




Figure E23. The button asks instead of activating (manual A13).

What the tool records. A “replacement request” action with the next replacement and your reason; the decision comes from your leader in the updated file.

E24 Someone else answers

Situation. The respondent's spouse answers and says the respondent is back after seven in the evening.

1. Log the call and choose **Respondent not available**.
2. Enter seven o'clock as the callback time and a short note, and save. At seven the household is first in **Due now**.




Figure E24. "Respondent not available", with the callback at 19:00 and the note.

What the tool records. A call with contact: it counts toward the dial cap, and a household reached this way is never closed by the contact protocol's day limit.

E25 We do not share a language

Situation. The respondent speaks only Kazakh; you do not.

1. Log the call, choose **Language barrier**, and under **After this call** choose **Ask for another enumerator next round**. Add a note on the language.
2. For this round, tell your leader: the leader can move the household now to a colleague who speaks the language (L16, by hand).




Figure E25. The language barrier logged, with the switch asked for next round.

What the tool records. The call and the switch request; next round the leader's rule switches the household to another enumerator, and a language criterion (L4) can keep it with one who speaks it.

E26 The interview stops halfway

Situation. The respondent must leave at the income module and asks to finish tomorrow evening.

1. Log the call, choose **Partial interview**, enter tomorrow at 18:00 as the callback, and note where it stopped.




Figure E26. A partial interview with its callback.

What the tool records. A partial, not a complete: the household stays open until a complete of three minutes or more (Box 3.0). Where the interview resumes is the interview platform's matter, not the tool's.

E27 “Not now, I am busy”

Situation. The respondent declines politely: busy at work this week. It is not a firm no.

1. Log the call and choose **Refusal (may retry)**, with a note.
2. The tool plans another try later, by the contact protocol. If you know a better day, move the next call (E21).




Figure E27. A soft refusal: the household stays open and the next call is planned.

What the tool records. A soft refusal; only a firm refusal (E8) closes the household.

E28 My computer shut down before I saved

Situation. The laptop's battery died at three; you had last saved at noon and made five calls since.

1. Open the tool and choose **Continue a saved session** with the noon file. Everything up to noon is back.
2. For each call made since, open the household and press **Log a call** and set its own start time, minutes and result (E11).
3. From now on, save after every few calls; the number on **Save session** counts the changes not yet saved.




Figure E28. The start page: continue the last saved session (manual A1).

What the tool records. The calls logged later carry their own time and the time you logged them; the leader's merge flags any logged implausibly late. Calls not saved are not recoverable from the tool.

E29 The respondent blocked my number

Situation. After several calls, the respondent's phone now rejects your number at once.

1. Log the call with the result **Our number is blocked**, with a note.
2. The household waits under **Needs your decision**; your leader sees it on the Progress tab and can move it to a colleague whose number is not blocked (L36).




Figure E29. A blocked number: the household waits for the leader.

What the tool records. The call with its result; no further call is planned for you.

E30 Nobody ever answers: ask for a visit

Situation. A household has not answered in a week, and its numbers may be wrong.

1. Under **Actions**, click **Refer for a field visit** and say why.
2. Keep calling meanwhile. The visit's outcome comes back as your leader's note on the household in your next updated file: for example a time to call, or a new number.




Figure E30. The household's actions, with the field-visit referral.

What the tool records. A “field visit” action; your leader lists it (L35).

Part 2 · The team leader

Thirty-eight situations from the week before the round to its close

L1 Start the round

Situation. Round 5 starts in a week. You have the household list, the merged logs of rounds 1 to 4, and the sampling tool's selection file with the reserves.

1. On the start page enter your ID, the program code, the country and the round, and press **Start**.
2. On the **Prepare round** tab, step 1: open the household list (CSV or Excel). The tool counts active, removed and reserve households.
3. Step 2: add the earlier rounds' merged logs and manifests. Step 3: open the replacement list.




Figure L1a. The household list, read (manual B3).




Figure L1b. Four earlier rounds, read (manual B4).




Figure L1c. The replacement list, read (manual B5).

What the tool records. Each file opened, in the leader's own log. The household list stays on your computer; it never goes to the common folder.

L2 Set the calendar, with a holiday in the window

Situation. The round runs from 26 October to 20 November; the call center works Monday to Saturday, 9 to 21; 10 November is a public holiday.

1. Step 4: enter the first and last day, the dial cap, the working weekdays and the call hours. The holidays inside the window come from the bundled table; tick one if the center works that day, or add a day off of your own.
2. In a country with Ramadan in the window, enter the hour the fast is broken: no first dial is planned in that hour.




Figure L2. The round calendar: 22 working days, the 10 November holiday listed (manual B6).

What the tool records. The calendar in every assignment file and in the manifest, so the enumerators' calendars and the leader's pace figures agree.

L3 An enumerator is away this round

Situation. E03 is on leave for the whole round. Their households must go to the others, and E03 must keep their history for round 6.

1. Step 5: untick **Available this round** for E03. Do not remove them.
2. When the rule is applied, E03's households are dealt to the others with the reason “enumerator away”.





Figure L3. The team, with E03 unticked (manual B7).

What the tool records. The reason on each moved household, in its file and the manifest, so that the program can tell forced changes from rotation.

L4 Two areas speak another language

Situation. Two PSUs of the sample speak Kazakh; only E01 does. Those households must not go to E02 or E07.

1. Step 5: tick **language** under “Match households to enumerators by”, and enter each enumerator's languages (E01: mn kk; the others: mn).
2. Apply the rule. A household goes only to an enumerator whose values include its own; step 7 counts the households moved to match, and lists any household no enumerator matches.



7 · Check the assignment before any file is written

- Kept 54, new 6, enumerator away 28, hard to reach 7, rotated 6, moved to match the criteria 9.

Matching criteria: **language**. Every household is with an enumerator who matches it.

Enumerator	kept	rotation	hard to reach	enumerator away	new	matched	Households	stratum 1	stratum 2	Expected dials	Against target
E01	24	3	2	10	2	9	**50**	23	27	180	+36%
E02	7	1	3	9	2		**22**	11	11	92	-30%
E07	23	2	2	9	2		**38**	18	20	125	-6%

Each row counts the households the enumerator receives this round, by reason: kept from last round, moved by rotation, switched as hard to reach, moved from an enumerator who is away, new to the panel. Expected dials use each household's dials last round (the mean for households without one). Target: the enumerator's share of the expected dials.

Margin (%) 15 2 enumerators are outside the margin. Move kept households at random to balance (reason: capacity)

Households without a last interview are planned at the program's best hours from earlier rounds: 20:00, 18:00, 19:00 (Section 3.5.1).

▸ Households (110): move one by hand

Figure L4. The check with the language criterion: the “matched” column (manual B9).

What the tool records. The criteria and each enumerator's values in the manifest and the files, and on each household whether it is matched.

L5 Choose the rule and the rotation share

Situation. The program keeps the same enumerator and rotates a tenth of the households each round.

1. Step 6: keep **Keep the same enumerator** and enter the rotation share, 10. There is no default: the share is the program's judgment.
2. Press **Apply the rule**. Households new to the panel are dealt at random; a household that was hard to reach last round switches enumerator.




Figure L5. The rules, with the rotation share entered (manual B8).

What the tool records. The rule, the share and the seed in every file: the same inputs and seed give the same assignment again.

L6 Check the loads before writing anything

Situation. You want to see who gets how many households and expected dials before any file leaves your computer.

1. Step 7 appears once the rule is applied: households per enumerator by reason, by stratum, expected dials and the departure from each enumerator's target.
2. If someone is outside the margin, press **Move kept households at random to balance**. Change the margin if the program's is different.




Figure L6. The check before any file is written (manual B9).

What the tool records. The balancing moves with the reason “capacity”.

L7 Keep one household with a particular enumerator

Situation. One household knows E02 well and asked for them; the rule moved it elsewhere.

1. Step 7, open **Households: move one by hand**, find the household and choose E02 in its row.
2. If E02 does not match the household's criteria, the tool says so and marks the household as not matched; it moves anyway.




Figure L7. Moving one household by hand (manual B10).

What the tool records. The reason “by hand” on that household and the previous enumerator.

L8 Set the day list

Situation. Enumerators should see about ten households a day, not the whole month.

1. Step 4, after the rule is applied: the tool shows the planned first dials per enumerator per working day and proposes one and a half times that as the day list. Enter your own number or leave it.




Figure L8. The day list after the rule is applied (manual B6b).

What the tool records. The day list in every file; the enumerator's Today tab pulls households forward up to that number.

L9 Write the files, protected

Situation. The files hold phone numbers and travel through folders other people can see.

1. Step 8: tick **Protect each assignment file with its own passphrase** and press **Write the files**.
2. Copy or download the passphrases now: they are shown once. Give each enumerator theirs privately (E20).
3. **Save all into a folder**, then put each file in its enumerator's own folder, never the common one. The manifest and the calendar row stay with you.




Figure L9. Five files ready, the passphrases shown once (manual B11).

What the tool records. The files' fingerprints in the manifest, which the merge later checks every export against.

L10 Stop for today, continue tomorrow

Situation. The round is prepared but not written; you want to continue tomorrow, or import logs next week on another computer.

1. Press **Save leader session**; a passphrase is optional. The file holds the household list: keep it in your own folder.
2. Tomorrow, **Continue a saved leader session**. Next week, to import logs only: start the round again and open its manifest on the **Import logs** tab.




Figure L10a. Saving the leader session (manual B12).



Figure L10b. A session without a manifest asks for one (manual B14).

What the tool records. The whole session with a checksum; a file changed outside the tool is refused.

L11 Import the exports and settle the questions

Situation. It is Saturday morning; the common folder has a week of exports from everyone.

1. **Import logs** tab: **Add files**, all of them at once. The newest export of each enumerator is used; CSVs are checked against their JSON; chains are verified.
2. Under **Needs your decision**, answer each question with a button and an optional note. Nothing is decided silently.
3. The **Files** table says how each file was used; the **Merge report** lists everything, and can be downloaded.




Figure L11a. Adding the exports (manual B15).

Files

File	Kind	Enumerator	Exported	Events or rows	Used
E01_2026-11-06.csv	csv	E01	2026-11-06 16:52	127	checked against E01_2026-11-06.json, exported 2026-11-06 18:00
E01_2026-11-06.json	json	E01	2026-11-06 18:00	132	replaced by the later export, E01_2026-11-06.json of 2026-11-06 19:00
E01_2026-11-06_contacts.json	contacts	E01	2026-11-06 18:00		contacts file
E02_2026-11-06.csv	csv	E02	2026-11-06 14:28	86	checked against E02_2026-11-06.json
E02_2026-11-06.json	json	E02	2026-11-06 18:00	91	used
E07_2026-11-06.csv	csv	E07	2026-11-06 16:27	127	checked against E07_2026-11-06.json
E07_2026-11-06.json	json	E07	2026-11-06 18:00	132	used
E01_2026-11-06.csv	csv	E01	2026-11-06 18:55	128	checked against E01_2026-11-06.json, exported 2026-11-06 19:00
E01_2026-11-06.json	json	E01	2026-11-06 19:00	134	used
E01_2026-11-06_contacts.json	contacts	E01	2026-11-06 19:00		contacts file

Figure L11b. The files of the batch and how each was used (manual B17).

What the tool records. Each decision with who made it and when, in the leader's log and the merge report.

L12 An export has not arrived

Situation. E07 forgot to export; the folder has E01's and E02's files only.

1. Import what is there. The merge raises “missing” for E07, and their households show as “not reported”, apart from completes and misses the other files reveal.
2. Press **Noted**, ask E07 for the export, and add it when it comes: the question closes by itself.




Figure L12. No export from E07: their households are not reported until the file arrives.

What the tool records. The missing file as an open question; progress counts “not reported” apart from completes and misses, so the round's figures are not distorted.

L13 Two enumerators completed the same household

Situation. E01 interviewed a household that was assigned to E02, who had already completed it.

1. Two questions appear: dials by E01 on a household assigned to someone else, and two completes for one household.
2. Confirm the first (E01 did call it) or mark it a mistyped ID; for the second, choose which complete counts, or count the first as a re-interview.




Figure L13. The two questions (manual B16).

What the tool records. The decision; until it is made the household is left out of the completion counts and shown as “two completes”.

L14 A respondent's new number reaches the list

Situation. E07's contacts file reports a corrected number (E9).

1. Add the contacts file with the exports (it comes to you directly, not through the common folder). The merge checks the number against the digest in the log.
2. Under **New or corrected phone numbers**, **Download contact updates** and move them into the household list for the next round.





Figure L14. One contact update from the batch (manual B19).

What the tool records. The update with whether its digest matched; the revised files of L20 already carry the corrected number.

L15 How far are we?

Situation. Day 10 of 22. The program manager asks for the completion rate and who is behind.

1. **Progress** tab: the team table gives households, completes, in progress, not started, dials, enumerator-days and completes per enumerator-day (Box 3.0).
2. Below: completes by day of the window and by stratum, and every household with its state, filterable.




Team

Households: those assigned, plus any replacement brought in this round (the household it replaces stays in the count, as Replaced). Not reported: households of an enumerator whose export has not arrived, counted apart from completes and misses. Completes per enumerator-day as in Box 3.0, from this round's dials. Calls they moved, first calls moved later and days off: the enumerators' own changes to their schedule, from their JSON exports (a CSV alone does not carry them). Columns with nothing to count are left out.

Enumerator	Households	Complete	In progress	Not started	Released	Replaced	Removal requested	Two completes	Dials	Enumerator-days	Share complete	Completes per enumerator-day
E01 export 11-06 19:00	40	19	12	2	7				128	11	48%	1.7
E02 export 11-06 18:00	25	12	5	1	5	1		1	86	11	48%	1.1
E07 export 11-06 18:00	46	22	14	1	8		1		127	11	48%	2.0
All	**111**	**53**	**31**	**4**	**20**	**1**	**1**	**1**	**341**	**33**	**48%**	**1.6**

Figure L15a. The team's progress (manual B20).



Stratum	Households	Complete	Share
1	53	28	53%
2	58	25	43%

Figure L15b. Completes by day and by stratum (manual B21).

What the tool records. Nothing; the figures follow the merge. The merged call log (L22) carries the same dials for the program's own analysis.

L16 Someone will not finish; someone has spare days

Situation. At E07's pace they will end the round with households never called, while E02 has days to spare.

1. Progress tab, **Move waiting households**: the pace table gives each enumerator's completes per day, what they can still complete in the days left, and how many short or spare. Only enumerators whose export is from today are judged, unless you tick the box.
2. Press **Propose moves from the enumerators behind to those with spare days**: households not yet called move one at a time, latest-planned first, only to an enumerator who matches them, until nobody is more than half a household off.
3. Untick any move you do not want, then write the files (L20).




Figure L16. Who is short and who has spare days, and the moves proposed (manual B22b).

What the tool records. The proposal in the leader's log; nothing changes until the files are written.

L17 An enumerator finished early

Situation. E02 has nothing left to call by day 12 and can take more.

1. On the same card: **Give** 5 households to E02, **Add to the list**. The households come from the enumerators furthest behind, then those with most waiting. An enumerator with nothing open is judged on any export, so E02 need not export today.
2. If fewer than five can be given, the tool says why.




Figure L17. Five households given to E02, from the enumerators behind.

What the tool records. The moves, once written, in the manifest with the time and your ID.

L18 An enumerator fell ill

Situation. E01 is off for the rest of the round. Their open households, some with booked callbacks, must be covered.

1. On the same card: **An enumerator is away**: E01, **Move all their open households to the others**. Booked callbacks go with their households; hard refusals stay; the receivers are those with spare days first, then the fewest open.
2. The roster marks E01 away; nothing is proposed to them until you move a household back by hand.




Figure L18. E01 away: every open household of theirs in the list, tagged “away”, the booked callbacks shown (manual B22d). The list also shows a newcomer, E09, given four households (L19).

What the tool records. The moves, E01's “away since” in the roster, and each callback in the handover of the receiving file (E15).

L19 A new enumerator starts on Monday

Situation. E09 joins the team mid-round and needs a first file with a few households.

1. On the same card, open **An enumerator joins the round**: ID, name, their code in the form if the team uses KoBoToolbox, and their values for the round's criteria. **Add**.
2. **Give** 4 households to E09 (L17), or move households to them by hand. Write the files: E09's first file carries each household's handover.




Figure L19. The newcomer E09 added and given four households, in the same list as E01's cover (manual B22d).

What the tool records. E09 in the roster with the date they joined, their file at the manifest's next revision, and their values among the matching criteria.

L20 Give out the revised files

Situation. The list of moves is ready. The enumerators must get new files without losing their logs.

1. Press **Write the updated files**. Only the affected enumerators get a file, at the next revision; the manifest's new revision replaces yours.
2. Give each file to its enumerator in their own folder. They open it with **Load updated assignment** (E14).




Figure L20. The revised files and the manifest's next revision, ready to give out.

What the tool records. Each move with its time in the manifest; each household's handover (previous enumerator, dials so far, last result, callback) in the receiving file; the previous file superseded.

L21 A call made after the move

Situation. E07 did not load the updated file in time and called a household that had moved to E02 the day before.

1. When E07's next export is imported, the merge raises "after move": the dial is kept and flagged as a double call.
2. Keep it or leave it out. The rule holds even if the household later comes back to E07: a dial made while someone else held it stays a double call.





Figure L21. The question raised for a dial after the move.

What the tool records. The decision; the dial stays in the log either way, marked by the merge report.

L22 End of the round: the files for next round

Situation. The round closed on 20 November. Round 6 needs the history, and the program's round template needs one row per household.

1. **Call log** tab: download the **Merged call log (CSV)**, the **Actions (CSV)** and the **Manifest**. Next round, open them on the Prepare tab, step 2 (L1).
2. Download **interviews.csv** and **outcome_codes.csv** for the Section 4.2 template, and **calendar.csv** for its calendar.
3. Settle every open question first: while questions are open, the files follow the current state.



Household	Dial	Start	Minutes	Result	Enumerator	Number	Action	Logged
0101–001	1	2026-10-26 10:43	19.6	Complete	E02	1		E02 10-26 11:04
0101–001	2	2026-11-06 18:40	14.0	Complete	E01	1		E01 11-06 18:55
0101–002	1	2026-10-26 09:44	0.8	No answer	E07	1		E07 10-26 09:45
0101–002	2	2026-10-26 12:27	0.7	No answer	E07	1		E07 10-26 12:28
0101–002	3	2026-10-26 14:14	0.4	No answer	E07	1		E07 10-26 14:14
0101–002	4	2026-10-26 16:21	0.7	No answer	E07	1		E07 10-26 16:22
0101–002	5	2026-10-27 10:00	0.8	No answer	E07	1		E07 10-27 10:01
0101–002	6	2026-10-27 13:22	0.2	Switched off / unreachable	E07	1		E07 10-27 13:22
0101–002	7	2026-10-27 16:05	0.5	No answer	E07	1		E07 10-27 16:06
0101–002	8	2026-10-29 09:09	0.7	No answer	E07	1	RELEASE	E07 10-29 09:10
0101–003	1	2026-10-27 20:42	13.2	Complete	E01	1		E01 10-27 20:55


Figure L22. The round's files and the merged call log (manual B23).

What the tool records. Each export in the leader's log. The merged log has the harmonized dial-table columns, with the dial number counted per household across enumerators.

L23 Who is likely to drop out?

Situation. Before writing the files you want the households most likely to be missed called early in the window.

1. **Risk lists** tab, with earlier rounds loaded: the dropout list ranks last round's respondents; the high tier gets an early first dial in the plan. Enumerators never see tiers.
2. Once the program has outcomes from two rounds, press **Backtest on this program's own rounds** and switch versions only if the backtest says the change helps.



Risk lists, for the leader only

Two models, both backtested before use. **Dropout risk** ranks the households interviewed last round by how likely they are to be missed this round; it was trained on the handbook's six programs with dial logs. **Return likelihood** ranks the households interviewed two rounds ago and missed last round by how likely they are to come back; it was trained on L2PHL and L2indo only, the two programs that redial almost every missed household, and it is weak. The model card below gives how well each does.

Tiers are tied to workload: within this round, the top 15% of households by score are high, the next 35% medium, the rest low. The return model has two tiers only, high and low: in one held-out test (L2PHL, recalibrated on its own rounds), its medium and low tiers could not be told apart, so they are merged. A tier says how similar households fared; it is never a prediction about one household, and never a reason to drop one (Section 3.3.5). Enumerators never see tiers, and tiers are not written into assignment files; the high dropout tier only moves households earlier in the plan of first dials. Only operational features are used, never demographic ones; the model card below lists them, and those left out on purpose.


Dropout risk: households interviewed in round 4

Model in use: the model as trained on six programs. It ranks households, but its chances are not yet calibrated to this program, so each household's score is shown against the round's average score instead. That ratio orders households and is not a chance: the backtests check the ordering, not the ratio. This program has outcomes from enough rounds to recalibrate it: see "This program's own data" below.

High 11 | Medium 26 | Low 38 | All 75

Household	Enumerator	Tier	Score against the round's average	What moves the score most
0108-005	E02	high	3.6 times the average	Rounds since joining: 1 raises the risk Needed 7 dials over 6 days last round raises the risk No interview the round before raises the risk
0101-005	E01	high	2.5 times the average	Missed 2 of the three rounds before raises the risk Rounds since joining: 4 raises the risk No interview the round before raises the risk
0106-004	E07	high	2.3 times the average	Rounds since joining: 1 raises the risk No interview the round before raises the risk Needed 4 dials over 1 day last round raises the risk
0103-005	E01	high	2.3 times the average	Missed 1 of the three rounds before raises the risk Needed 8 dials over 5 days last round raises the risk Rounds since joining: 4 raises the risk
0112-001	E07	high	2.2 times the average	Missed 1 of the three rounds before raises the risk Rounds since joining: 3 raises the risk No interview the round before raises the risk
0109-004	E01	high	2.2 times the average	Missed 1 of the three rounds before raises the risk Rounds since joining: 4 raises the risk Needed 4 dials over 3 days last round raises the risk

Figure L23a. The risk lists (manual B26).



This program's own data

The models were trained on other programs. As this program's rounds gather outcomes, the tool can recalibrate them (intercept and slope) or refit them on the program alone. Switch only after the backtest shows the change helps.

Dropout risk

230 household-rounds with a known outcome, from 3 rounds: 53 losses. Enough to recalibrate: run the backtest, and choose the recalibrated version only if it does better. A refit needs about 300 losses (53 so far). In use: **the model as trained on six programs.**

Backtest on this program's own rounds

Version	AUC	Brier / no model	Losses in the high tier	Household-rounds tested	
As trained	0.35	0.1295 / 0.1208	11%	64	in use
Recalibrated on own rounds	0.35	0.1363 / 0.1208	11%	64	use
Refitted on own rounds	not enough own outcomes yet				

Too few outcomes to judge: on this program's own rounds so far, the model's ranking cannot be told from chance (AUC 0.35, 95% interval 0.17 to 0.53, on 64 household-rounds with 9 losses). Keep the version in use and run the backtest again after the next round.

Rolling origin: each round is predicted using only the outcomes known before it, 1 round tested. AUC: the chance that a household with the outcome scores above one without (0.5 is no better than chance). Brier: the mean squared gap between chance and outcome, lower is better; "no model" gives every household the tested rounds' average rate. The version you choose is then fitted on every outcome known now.

Return likelihood

No household-round with a known outcome yet. Recalibration needs outcomes from two rounds (a return is known three rounds after the miss). In use: **the model as trained on two programs.**


Figure L23b. The own-round backtest (manual B27).

What the tool records. The model version in use and when it was switched; the lists are for the leader only and are never written into assignment files.

L24 How did earlier rounds go?

Situation. The program manager asks for continuation, dials per complete and the best calling hours.

1. **Analytics** tab, with earlier rounds loaded: continuation and retention, loss and returns, dials per complete and the hazard by dial, completes per enumerator-day, and when calls succeed, as the handbook defines them.



Continuation and retention

Continuation (Box 2.0): the share of a round's respondents interviewed again in the next round. Interviewed = a case completed by the handbook's rule. Closed rounds only (1, 2, 3, 4); this round is still open. Data: rounds 1–4 from the call log.

Round	Last round's respondents	Continuation	Missed, back later
1 → 2	86	76.7%	11.6%
2 → 3	80	70.0%	17.5%
3 → 4	64	85.9%	–

Median continuation **76.7%**; lowest round **70.0%**.

The first-round sample, round by round (Box 2.0, Section 2.4.4)


Households interviewed in round 1, interviewed again in each later round, without returns.

Retention by rounds since joining (Section 3.4.3)

Pooled over entry cohorts: interviewed k rounds after joining (strict), or then or in one of the next three rounds (with returns). Cohorts count only when round joining + k + 3 is in the data, so the last three closed rounds cannot yet be judged.

Not yet: fewer than 10 households have k + 3 later rounds in the data.

Figure L24a. Continuation and retention (manual B24).



Dials per complete and hazard by dial (Section 3.3.1)

Case = a household in a round with at least one dial; complete = the first complete-coded dial of 3 minutes or more, or, as the handbook's scripts do when there is none, its first complete-coded dial. Dials after the complete are not counted. Hazard at dial k = completes on dial k among cases still pending before it (cells under 10 not shown).

	Cases	Dials	Completes	Dials per complete	Completion	On the first dial	Dial reaching 90% of completes	Median dials if not completed
Closed rounds	427	1576	305	5.17	71.4%	37.4%	5	8.0

Round	Cases	Dials per complete	Completion
1	108	4.86	79.6%
2	108	4.54	74.1%
3	106	6.53	60.4%
4	105	5.03	71.4%

Hazard by dial, closed rounds

Missed households (Section 3.3.5)

Of 43 households interviewed one round, dialed and not completed in the next, 93% were dialed again the round after, and 53% of those were completed: missed is not lost.


Figure L24b. Dials per complete and hazard by dial (manual B25).

What the tool records. Nothing; every figure is computed from the loaded logs, unweighted, as in the handbook.

L25 Let enumerators adjust their own schedule

Situation. Your enumerators often learn on the phone when a household is best called, and one of them will miss two days next week. You want them to adjust their own lists without asking you each time, and you want to see what they changed.

1. Prepare tab, step 4, **What enumerators may change themselves**: moving a household's next call and marking time off are on by default. Leave **also a first call past the first-call period** unticked to keep first calls early (Section 3.4).
2. Write the files: the setting travels in them.
3. After each import, the Progress tab's team table counts the calls each enumerator moved, the first calls they moved later, and the days off they marked. The pace counts only the days each one works, and names the time off still ahead.



Team

Households: those assigned, plus any replacement brought in this round (the household it replaces stays in the count, as Replaced). Not reported: households of an enumerator whose export has not arrived, counted apart from completes and misses. Completes per enumerator-day as in Box 3.0, from this round's dials. Calls they moved, first calls moved later and days off: the enumerators' own changes to their schedule, from their JSON exports (a CSV alone does not carry them). Columns with nothing to count are left out.

Enumerator	Households	Complete	In progress	Not started	Released	Replaced	Removal requested	Dials	Enumerator-days	Calls they moved	First calls moved later	Days off marked	Share complete	Completes per enumerator-day
E01 export 11-06 18:00	40	19	12	2	7			127	11				48%	1.7
E02 export 11-06 18:00	25	13	5	1	5	1		86	11				52%	1.2
E07 export 11-06 18:00	46	22	14	1	8		1	127	11	2	1	1.5	48%	2.0
All	**111**	**54**	**31**	**4**	**20**	**1**	**1**	**340**	**33**	**2**	**1**	**1.5**	**49%**	**1.6**

Move waiting households

Part-way through the round, households not yet called can move from an enumerator who will not finish to one with spare days, with no household in two files and no double call: each move is recorded in the manifest, the previous enumerator's dials up to the move stay theirs, and any dial they make after it is flagged in the merge. Pace: completes per enumerator-day so far (Box 3.0). Capacity: pace × the 11 working days left from today, less any time off an enumerator marked. Only enumerators whose export is from today, with two or more enumerator-days, are judged; an enumerator with nothing left open is judged on any export. Below the proposal: give households to an enumerator who finished early or joined the round, cover one who is away, add one who joins.

Enumerator	Households	Complete	Not started	In progress	Completes per day	Can still complete	At this pace	Export
E01	40	19	2	12	1.73	19	5 spare	last export 2026-11-06, not today
E02	25	13	1	5	1.18	13	7 spare	last export 2026-11-06, not today
E07	46	22	1	14	2.00	19	4 spare	last export 2026-11-06, not today 1.5 days off ahead

Figure L25. The team table with E07's changes counted, and E07's pace with a day and a half off ahead.

What the tool records. The setting in every file and in the manifest; the changes themselves in each enumerator's log, read from their JSON export. A CSV export alone does not carry them.

L26 Three calls a day over five days

Situation. Your program's protocol is to call each household up to three times a day, at different times of day, over five working days, and to replace a household nobody answered in that time. The tool's default plans a call two hours after an unanswered one, with no daily limit.

1. Prepare tab, step 4, **Contact protocol**: at most 3 calls a day, at least 3 hours apart, over at most 5 working days for a household never reached. Tick **Vary the time of day**. The step shows 15 calls against the dial cap; set the cap to 15 if it should stop there too.
2. Step 3: tick **the dial cap or the contact protocol** among the cases after which a replacement is allowed.
3. Write the files. Each enumerator's list now plans the next call by the protocol: three hours later on the same day while the day's calls last, then the next working day in the part of the day tried least. A household not reached by its fifth day shows **Protocol done** under “Needs your decision”, where its replacement can be activated.




Figure L26. The contact protocol in step 4 (manual B6a).

What the tool records. The protocol in every file and in the manifest; it carries over to the next round. A booked callback, and a call the enumerator moved themselves, are never limited by it.

L27 Approve replacements in a batch

Situation. Your program wants every replacement approved, but asking for approval one household at a time held up the calling. You want the requests to wait in one list and to decide them together once a day.

1. Prepare tab, step 3: **Who activates a replacement**, “the leader approves each request”. Write the files.
2. After each import, the Progress tab's **Replacement requests** lists what the enumerators asked, with the reason, the dials, the last result and the next replacement in line.
3. Tick the requests to release and click **Release the ticked**; tick the others and click **Decline the ticked** with a note, such as “keep calling in the evening”. Then **Write the updated files** and give them out (L20).
4. For a team on KoBoToolbox, use **Release a replacement for household**, then write the form's list again: it carries only released replacements.




Figure L27. Two requests, one set to release its next replacement (manual B22e).

What the tool records. Each decision in the manifest with its time and your ID, and in the enumerator's revised file. A replacement an enumerator uses without your release is raised as a merge question.

L28 The same file arrives twice

Situation. An enumerator copied their export into the common folder twice; the copy is called “(1)”.

1. Import everything as usual. The copy is recognised by its content, ignored, and noted in the report; nothing to decide.

Files

File	Kind	Enumerator	Exported	Events or rows	Used
E01_2026-11-06.csv	csv	E01	2026-11-06 16:52	127	checked against E01_2026-11-06.json
E01_2026-11-06.json	json	E01	2026-11-06 18:00	132	used
E01_2026-11-06_contacts.json	contacts	E01	2026-11-06 18:00		contacts file
E02_2026-11-06.csv	csv	E02	2026-11-06 14:28	86	checked against E02_2026-11-06.json
E02_2026-11-06.json	json	E02	2026-11-06 18:00	91	used
E07_2026-11-06.csv	csv	E07	2026-11-06 16:27	127	checked against E07_2026-11-06.json
E07_2026-11-06.json	json	E07	2026-11-06 18:00	132	used
E02_2026-11-06 (1).json	json	E02	2026-11-06 18:00	91	duplicate, ignored

Figure L28. The files of a batch with a copy: the copy is not used.

What the tool records. A “duplicate” line in the merge report.

L29 Only the CSV arrived

Situation. E02 exported again in the evening but only the CSV reached the folder; the JSON of the evening is missing.

1. Import it. The CSV, being newer, is used, marked **unverified**: its hash chain cannot be checked, and it does not carry actions apart from calls, contact updates, moved calls or time off.
2. Ask E02 for the JSON of the same export; when it arrives, it is used and checked.

Files

File	Kind	Enumerator	Exported	Events or rows	Used
E01_2026-11-06.csv	csv	E01	2026-11-06 16:52	127	checked against E01_2026-11-06.json
E01_2026-11-06.json	json	E01	2026-11-06 18:00	132	used
E01_2026-11-06_contacts.json	contacts	E01	2026-11-06 18:00		contacts file
E02_2026-11-06.csv	csv	E02	2026-11-06 14:28	86	checked against E02_2026-11-06.json
E02_2026-11-06.json	json	E02	2026-11-06 18:00	91	replaced by the later export, E02_2026-11-06.csv of 2026-11-06 18:21
E07_2026-11-06.csv	csv	E07	2026-11-06 16:27	127	checked against E07_2026-11-06.json
E07_2026-11-06.json	json	E07	2026-11-06 18:00	132	used
E02_2026-11-06.csv	csv	E02	2026-11-06 18:21	87	used, unverified

Figure L29. E02's later CSV used, unverified; the earlier JSON replaced.

What the tool records. An “unverified” line in the merge report until the JSON arrives.

L30 Last month's file is in the folder

Situation. The common folder still holds E07's export from round 4.

1. Import everything. The round-4 file is not merged into round 5; the question says where it belongs. Press **Noted**.




Figure L30. A file of another round, kept out of this round's merge.

What the tool records. The question and your answer. Open that file in round 4's leader session if it is still needed there.

L31 Someone edited an export by hand

Situation. A copy of E01's export was opened in a text editor and one call's result changed. Both files have the same name.

1. Import both. The edited copy fails its integrity check, and the changed call becomes a question: which version counts.
2. Choose the version whose integrity check passed; the labels say which is which.




Figure L31. The broken chain and the conflicting call, with the choice of version.

What the tool records. Both questions and your choice; the edited copy stays marked in the report.

L32 The round needs another week

Situation. The round started late after a holiday, and the program agrees to extend it by a week.

1. Progress tab, **Change the round**: set the new **last day** and click **Change it**.
2. **Write the updated files**: every enumerator gets a revised file with the new window and the holidays of the new days. They open it with “Load updated assignment”.
3. A shorter round works the same way: first calls planned after the new last day move to its last working day.




Figure L32. Changes waiting to be written: a new last day, a household added, a file re-issued.

What the tool records. The new window in the manifest and every file; the pace counts the new working days.

L33 Households join mid-round

Situation. The program adds a few households from the household list as a top-up after the round has started.

1. On the same card, **Add households**: type their IDs, and choose an enumerator or leave it to the one with the fewest open. Households already in the round, removed ones, and ones no enumerator matches are refused with the reason.
2. Write the updated files. Each added household reaches its enumerator with its contacts and a first call on the next working day.




Figure L33. The same card (L32).

What the tool records. The household in the manifest with the reason “added mid-round” and the time.

L34 An enumerator lost the passphrase

Situation. E01 lost the slip with the passphrase; neither the file nor the saved session opens.

1. On the same card, **Re-issue the file of** E01, then write the updated files. With protection on, E01's new file has a new passphrase, shown once.
2. E01 opens it as a new assignment. Their calls exported before stay in the common folder and the merge keeps them; calls since their last export are lost with the old session.




Figure L34. The same card (L32).

What the tool records. A revised file for E01 and the manifest's next revision.

L35 Plan the field visits

Situation. Enumerators referred a few households that never answer for a visit in person.

1. Progress tab, **Field visits**: the referrals, with the reason, dials and last result. **Download the visit list** for the field team (it holds contacts).
2. When a visit is done, choose its outcome (a time agreed, a new number, not found, refused at the door) and add a note; then **Write the updated files**. The enumerator sees your note on the household. Put a new number into the household list so the next files carry it.




Figure L35. A referral with its outcome chosen, ready to write.

What the tool records. Each outcome in the manifest, and the note in the enumerator's file.

L36 Numbers blocked by respondents

Situation. An enumerator logged that a respondent blocked their number (E29).

1. Progress tab, **Move waiting households**: the card counts the households with a blocked number. **Move them to colleagues** lists a move for each, to those with spare days first, then the fewest open, respecting the round's criteria.
2. Write the updated files as for any move (L20).




Figure L36. One household with a blocked number, and the button that moves it.

What the tool records. The moves, tagged “blocked”, in the manifest.

L37 A text message the day before

Situation. Respondents ignore unknown numbers, so the program sends a message the day before each household is called.

1. Progress tab, **Text-message list**: choose the day (the next working day by default) and download the list: the first calls planned that day and the callbacks booked that day, with the number.
2. Give the list to whoever sends the messages; the tool sends nothing.





Figure L37. The list for a day with its count.

What the tool records. The export in the leader's log. First calls are known in the session that prepared the round; a session that only opened the manifest lists the callbacks.

L38 Areas with no interviews

Situation. A few PSUs give no interview round after round.

1. Progress tab, **By area**: completes by PSU this round, with the same households' completes in the earlier rounds loaded. Areas with none now and none before come first.
2. Decide what to do: a field visit (L35), a caller who knows the area, or the program's decision on the sample.



PSU	Stratum	Households	Complete	Share	Open	Round 2	Round 3	Round 4
0111	2	9	2	22%	6	9	8	8
0108	2	9	3	33%	5	7	7	6
0109	2	9	3	33%	6	7	6	8
0113	2	6	2	33%	1	–	–	–
0106	1	8	3	38%	4	5	3	5
0112	2	8	3	38%	4	6	6	5
0101	1	8	4	50%	1	5	4	4
0102	1	10	5	50%	0	6	6	5
0103	1	9	5	56%	3	8	5	5
0110	2	9	5	56%	3	7	3	8
0104	1	9	6	67%	1	7	4	5
0105	1	9	6	67%	1	5	5	5
0107	2	8	7	88%	0	6	5	7

Figure L38. Completes by area, this round and the earlier rounds.

What the tool records. Nothing new: the table is computed from the merge and the history.

Part 3 · With KoBoToolbox

Eight situations for a team that records its calls in a KoBoToolbox form

K1 The team interviews in the Philippines-style form

Situation. Interviewers submit the interview form once per call attempt, and know themselves by codes such as CATI07. The form takes its sample list from its choices sheet.

1. Prepare the round as in L1 to L9; in step 5 enter each interviewer's code, or do it on the **KoBoToolbox** tab, step 1.
2. Step 2: write **choices_households.csv**, paste it over the form's list and redeploy. With a choice filter on the code, each interviewer sees only their households.




Figure K1. The KoBoToolbox tab, steps 1 and 2 (manual C1).

What the tool records. The codes in the manifest (or in the session, if entered later), so that the form's records are read under the tool's IDs.

K2 Each day: the form's export

Situation. The enumerators log nothing in the tool; every call attempt is a submission in KoBoToolbox.

1. Download the project's data (CSV with XML values and headers) and add it in step 3, **Add the form's export**. The export is cumulative: the latest download is enough.
2. The tool splits it by interviewer and merges each part as an unverified export; progress, the call log and the analytics follow, and every merge question is raised where it applies.




Figure K2. Step 3 with the Philippines-layout export added (manual C2).

What the tool records. Each submission as one dial, with the result mapped onto the tool's codes and the form's open and submit times as the call's start and end.

K3 Our form has other column names

Situation. Your form records each attempt too, but its columns and result codes are its own.

1. Add the export. Step 3 shows a mapping card instead of merging: say which column plays each role (household, interviewer, start, result; the rest optional) and what each value of the result column means.
2. **Save the mapping and merge the file**. Every later file with the same columns is read without asking.




Figure K3. The mapping card (manual C3).

What the tool records. The mapping in the leader's session.

K4 After moves, the form must follow

Situation. You moved households on the Progress tab (L16 to L19). The interviewers' lists in the form are now wrong.

1. Step 4 of the KoBoToolbox tab: write **choices_households.csv again**, paste it over the form's list and redeploy. Batch the day's moves: a redeploy reaches the interviewers only when they reload the form.
2. A call the previous interviewer makes on a moved household after that is flagged in the merge as a double call (L21).




Figure K4. Step 4 after four moves: the list written again from the new manifest; above it a question of step 3, below it step 5 (K5).

What the tool records. The moves in the manifest; the list reflects the current holder of every household.

K5 A submission to look at in KoBoToolbox

Situation. The merge found two completes for one household in the form's export. You want to check the submission in the project's table view.

1. Settle the question in step 3 as in L13.
2. Step 5 lists every dial behind a merge question with the submission's `_uuid`; download the list and search the ID in KoBoToolbox, set its validation status or ask the interviewer.




Figure K5. Step 3's question (two completes for one household) and step 5's list of the two submissions behind it, with their IDs.

What the tool records. The decision; the review list is written from the current merge each time.

K6 An interviewer typed a wrong code

Situation. For three submissions, interviewer CATI07 typed CATI70 in the form.

1. Add the export. CATI70 is not in the round's manifest: its calls are kept and flagged, and the calls on CATI07's households appear as calls by someone else.
2. Find the submissions with step 5's list (their `_uuid`), correct the interviewer field in KoBoToolbox's table view, and download the export again. The questions close by themselves.




Figure K6. A code the round does not know.

What the tool records. The questions until the corrected export arrives. A second code cannot be added for the same interviewer (Part 4).

K7 The form gained a new result code

Situation. The program redeployed the form with an eleventh result code.

1. Add the export as usual. Step 3 lists the new value with its count: unmapped, it counts as “Other”.
2. Choose what it means. The answer is kept in your session and used for every later export.




Figure K7. A value the built-in map does not know, waiting for its meaning.

What the tool records. The mapping in the leader's session.

K8 One interviewer, two codes

Situation. CATI07 sometimes types CATI70 in the form (K6).

1. Step 1: enter both codes for E07, separated by a comma: “CATI07, CATI70”. Both read as E07; the first is written into the form's list.




Figure K8. Two codes for one interviewer.

What the tool records. The codes in the leader's session.

Part 4 · What the tool does not do yet

Real situations it cannot handle, what to do instead, and which could be built

The tool manages the calling side of a phone round: who calls which household, when, what happened, and what the leader decides. It does not place calls: the call center's own phone system does that. These are the situations from practice that it does not handle, or handles only in part, with what to do instead. Nine situations listed here earlier are now handled (version 0.4.0): extending the round, adding households mid-round, field visits, areas without interviews, blocked numbers, a text-message list, a lost passphrase, a new result code in the form, and an interviewer with two codes; see L32 to L38, K7 and K8.

X1 Fieldwork situations

Situation	What the tool does today	What to do instead	
A respondent asks for a particular caller	Continuity through the keep-same rule; a move by hand; no standing preference per household	Move the household by hand (L7), or add a column to the household list and match on it (L4)	Partly done

X2 Files and platforms

Situation	What the tool does today	What to do instead	
An enumerator works on two devices at once	Two logs from one assignment; the merge uses the newer export and reports the other's calls as missing or conflicting	One device at a time: save the session and continue it on the other device (E19, E28)	By design
Two leaders want to work on the same round	One leader session; two copies would drift apart	One leader holds the session; save it and hand it over	By design
Progress is needed by the hour	Progress is as fresh as the last exports: the tool has no server	Ask for exports at set times of day; with KoBoToolbox, download the export when needed	By design
The team interviews in Survey Solutions	Not supported in this version (it was set aside on 3 November 2026)	Use the enumerator view for the call log, or an earlier version from the repository's history	Set aside

X3 Beyond the tool's purpose

Situation	What the tool does today	What to do instead
Placing the call, recording it, sending messages	Nothing, by design: the enumerator dials with the call center's phone system and logs each call afterwards, with its start and minutes	The call center's own system; its log can be compared with the tool's by hand

The interview itself	The enumerator view records calls, not answers	The interview platform (KoBoToolbox); with a form that records each attempt, the KoBoToolbox tab reads it (Part 3)
Interview quality: audio audits, back-checks, module timings, answer patterns	None	The platform's paradata and the program's data checks
Respondent incentives and payments to callers	Not tracked	The program's own records
An interface in the enumerators' language	English only	Training with the manual and these examples; a translation would need the interface text taken out of the code
A very large team	Tested on the synthetic round (111 households, three enumerators) and one real export of 17,915 calls; not timed with thirty enumerators exporting daily	Try a full round's exports on the leader's computer before relying on it