

The value of string s1 after executing the following statement is

```
char s1[] = "C++ Language";  
char s2[] = "Hello";  
strcpy(s1, s2);
```

- ☐ a. C++ LanguageHello
- ☐ b. C++ Language
- ☐ c. Helloanguage
- ☐ d. Hello

SMURFS POLYTECHNIC UNION

To find $|-97|$ you write

- ☐ a. Cant find it directly
- ☐ b. $\text{abs}|-97|$
- ☒ c. $\text{abs}(-97)$
- ☐ d. $|-97|$

[Clear my choice](#)



البوليتكنيك
SPU

The output of the following code is

```
for(i=4; i<7;)  
    cout << i++;  
    cout << i;
```

- ☐ a. 455667
- ☐ b. error in for structure
- ☒ c. 4567

[Clear my choice](#)

The error in the following code is

```
int x=2,y=3;
```

```
int res;
```

```
cout << (res=Y*x);
```

- ☐ a. int x=2,y=3;
- ☐ b. No error
- ☐ c. cout << (res=Y*x);

☒ d. int res,

[Clear my choice](#)

Time left 0:13:47

Consider that:

`a[3][3] = {1,2,3,4,7,6,7,8,9};`

`sum=0;`

then the value of sum after executing the following code is

```
for(i=0; i<3; ++i){  
    for(j=0; j<3; ++j){  
        sum += a[1][j]--;  
    }  
    cout << endl;  
}
```

ملاحظة: أكتب الاجابة مباشرة في خانة الاجابة بدون فراغات سابقة أو لاحقة

Answer:

Consider that $a = -3$, $b = 4$, $c = 5$, then the value of c after executing the following code

```
if(a > 0)
```

```
if(b > 0)
```

```
    c++;
```

```
else
```

```
    c--;
```

- ☐ a. 4
- ☐ b. 6
- ☐ c. 5
- ☐ d. error

The value of x after executing the following code is

```
x = 'C';
```

```
if(x>97 && x>100)
```

```
    x -= 32;
```

```
else if(x>97 || x<99)
```

```
    x = 69;
```

```
else
```

```
    x += 3;
```

☐ a. C

☐ b. c

☐ c. f

☒ d. f

[Clear my choice](#)

Question 8

Not yet
answered

Marked out of
1.00

Flag question

The output of the following code is

```
for(i=3; i<6;)
    cout << i++;
    cout << i;
```

- ☐ a. 344556
- ☐ b. 3456
- ☒ c. error in for structure

Clear my choice

The value of string s1 after executing the following statement is

```
char s1[] = "C++ Language";
```

```
char s2[] = "Hello";
```

```
strcpy(s1, s2);
```

- ☐ a. C++ Language
- ☐ b. C++ LanguageHello
- ☐ c. Hello
- ☐ d. Helloanguage

Question 7

Not yet
answered

Marked out of
1.00

Flag question

Consider the following statement

```
int m[2][3] = {6, 0, -2, -5, 1, 8};
```

The value of the element in the first row, second column is:

في خانة الاجابة بدون فراغات سابقة او لاحقة.

Answer:

1

To find $\sqrt{b + c}$ you write

- ☐ a. b^c
- ☒ b. `sqrt(b+c)`
- ☐ c. `pow(b, c)`
- ☐ d. `sqrt(b, c)`

[Clear my choice](#)

Question 6

Not yet
answered

Marked out of
100

Flag question

To find x^y you write

☐ a. `sqrt(x, y)`

☐ b. `x^y`

☒ c. `pow(x, y)`

☐ d. `pow(y, x)`

[Clear my choice](#)

The equivalent C++ equation for the following math function is

$$F = \frac{x + 2y}{5} - 7 \bmod 9$$

- ☐ a. $F = (x + 2)*y/5 - 7\%9$
- ☐ b. $F = x + 2*y/5 - 7\%9$
- ☐ c. $F = x + (2*y)/5 - (7\%9)$
- ☐ d. $F = (x + 2*y)/5 - 7\%9$

The equivalent C++ equation for the following math function is

$$F = 9x + \frac{2y}{5} - z \bmod 7$$

- ☐ a. $F = 9x + (2y/5) - (z\%7)$
- ☐ b. $F = 9x + (2*y/5) - z\%7$
- ☒ c. $F = 9*x + 2*y/5 - z\%7$
- ☐ d. $F = 9*x + 2*(y/5 - z\%7)$

[Clear my choice](#)

Question 4

Not yet
answered

Marked out of
1.00

Flag question

The value of res after executing the following code considering that you enter

.....

```
res=0;  
cin >> v;  
while(v!= 0){  
    res -=v;  
    cin >> v;  
}
```

- ☐ a. endless loop
- ☐ b. 0
- ☐ c. -3
- ☐ d. 1

The output of the following statement is

.....

`ceil(9.2)`

☒ a. 10

☐ b. 9

[Clear my choice](#)

Consider that $r=1$ and $y=7$, the value of r after executing the following code is

```
if(y++<10)
```

```
    r +=y;
```

```
if (y--!=8)
```

```
    r +=y;
```

```
else
```

```
    r -=y;
```

ملاحظة: أكتب الاجابة مباشرة في خانة الاجابة بدون فراغات سابقة أو لاحقة

Answer: 14

Not yet
answered

Marked out of
1.00

Flag question

The number of errors in the following code is

```
int x=2
```

```
float res 0.5;
```

```
res %=x+2;
```

- ☐ a. 3
- ☐ b. 0.5
- ☒ c. 1
- ☐ d. 0
- ☐ e. 2

Clear my choice

Consider the following statement

```
int m[2][3] = {6, 0, -2, -5, 1, 8};
```

The value of the element in the first row, second column is:

ملاحظة: أكتب الإجابة مباشرة في خانة الإجابة بدون فراغات سابقة أو لاحقة

Answer: 0

Consider that the variable res is declared as:

```
bool res = 1;
```

and the values of variables x and y is:

```
x = 0.5, y = 2.3;
```

Then the value of res after executing the following code is

```
int i=0;
```

```
while(i<2){
```

```
    x += 0.2;
```

```
    y -= 1.5;
```

```
    res += x + y;
```

```
    ++i;
```

```
}
```

- ☐ a. 1
- ☐ b. 2.7
- ☐ c. 0
- ☐ d. 1.6

Consider that $a = -3$, $b = 4$, $c = 4$, then the value of c after executing the following code is _____

```
if(a > 0)
```

```
if(b > 0)
```

```
    c++;
```

```
else
```

```
    c--;
```

☒ a. error

☐ b. 6

☐ c. 4

☐ d. 5

[Clear my choice](#)



The value of x after executing the following code is

.....

```
x = 'b';
```

```
if(x>97 && x>99)
```

```
    x -=32;
```

```
else if(x>97 || x<99)
```

```
    x =97;
```

```
else
```

```
    x += 3;
```

☐ a. B

☐ b. e

☐ c. b

☒ d. a

[Clear my choice](#)

Question **5**

Not yet
answered

Marked out of
1.00

Flag question

The value of string s1 after executing the following statement is

```
char s1[] = "C++ Language";
```

```
char s2[] = "Hello";
```

```
strcpy(s1, s2);
```

- ☐ a. C++ Language
- ☒ b. Hello
- ☐ c. Helloanguage
- ☐ d. C++ LanguageHello

Clear my choice

SMURFS POLYTECHNIC UNION

The length of the following string using strlen() function is

```
char str[] = {'a','b','\0','c','d','e','\0'}
```

من فراغات سابقة أو لاحقة.

Answer:

21

الجامعة كذاك
SPU

The value of res after executing the following code considering that you

```
res=0;  
cin >> v;  
while(v != -1){  
    res +=v;  
    cin >> v;  
}
```

a -8

b 0

c 48

Consider that:

`a[3][3] = {1,2,3,4,7,6,7,8,9};`

`sum=0;`

then the value of sum after executing the following code is

```
for(i=0; i<3; ++i){  
    for(j=0; j<3; ++j){  
        sum += a[1][j]--;  
    }  
    cout << endl;  
}
```

الإجابة بدون فراغات سابقة أو لاحقة.

Answer:

| I

The number of errors in the following code is

```
int x=2;
```

```
float res=0.5;
```

```
res %=x+2;
```

☐ a. 0.5

☐ b. 0

☐ c. 2

☐ d. 3

☐ e. 1

The value of string s1 after executing the following statement is

```
char s1[] = "Programming Language";
```

```
char s2[] = "using C++";
```

```
strcpy(s1, s2);
```

☒ a. Programming Languageusing C++

☐ b. using C++

☐ c. using C++ng Language

☐ d. Programming Language

[Clear my choice](#)

Not yet
answered

Marked out of
1.00

Flag question

Consider that the variable `res` is declared as:

```
bool res = 1;
```

and the values of variables `x` and `y` is:

```
x = 0.5, y = 2.3;
```

Then the value of `res` after executing the following code is

```
int i=0;  
while(i<2){  
    x += 0.2;  
    y -= 1.5;  
    res += x + y;  
    ++i;  
}
```

- ☐ a. 1.6
- ☐ b. 0
- ☐ c. 2.7
- ☐ d. 1

Time left 0:06:22

10

11

Finish atten

The output of the following statement is

`floor(-3.5)`

- ☐ a. -4
- ☒ b. -3

[Clear my choice](#)

SMURFS POLYTECHNIC UNION

سماقر

اتحاد

$$z = \frac{x + 2y}{5} - 7 \bmod 9$$

البوليتكنيك

SPU

SMURFS POLYTECHNIC UNION

Question 8

Not yet
answered

Marked out of
1.00

Flag question

To find x^y you write

- ☐ a. x^y
- ☒ b. `pow(x, y)`
- ☐ c. `pow(y, x)`
- ☐ d. `sqrt(x, y)`

[Clear my choice](#)

البوليتكنيك
SPU

SMURFS POLYTECHNIC UNION

اتحاد سنافر

Question 7

Not yet
answered

Marked out of
1.00

Flag question

The length of the following string using strlen() function is _____

```
char str[] = {'a','b','c','d','\0','e','\0'}
```

Answer: 4

إجابة بدون فراغات سابقة أو لاحقة

البوليتكنيك
SPU

Consider that:

$a[3][3] = \{1,2,3,4,7,6,7,8,9\};$

sum=0;

then the value of sum after executing the following code is

```
for(i=0; i<3; ++i){  
    for(j=0; j<3; ++j){  
        sum += a[1][j]--;  
    }  
    cout << endl;  
}
```

ملاحظة: أكتب الاجابة مباشرة في خانة الاجابة بدون فراغات سابقة أو لاحقة

Answer:

Question 6

Not yet
answered

Marked out of
1.00

Flag question

The value of x after executing the following code is

```
x = 'b';
```

```
if(x>97 && x>99)
```

```
    x -= 32;
```

```
else if(x>97 || x<99)
```

```
    x = 97;
```

```
else
```

```
    x += 3;
```

☐ a. e

☒ b. a

☐ c. B

☐ d. b

The value of x after executing the following code is

```
x = 'b';
```

```
if(x>97 && x>99)
```

```
    x -=32;
```

```
else if(x>97 || x<99)
```

```
    x =97;
```

```
else
```

```
    x += 3;
```

- ☐ a. b
- ☐ b. e
- ☐ c. B
- ☐ d. a

SMURFS POLYTECHNIC UNION

اتحاد

The length of the following string using strlen() function is

```
char str[] = {'a','b','c','\0','d','e','\0'}
```

ملاحظة: اكتب الاجابة مباشرة بدون فراغات سابقة أو لاحقة.

Answer:

7

I

البوليتكنيك
SPU

Question 3

Not yet
answered

Marked out of
1.00

Flag question

The number of errors in the following code is

```
int x=2  
float res 0.5;  
res % = x+2;
```

- ☐ a. 3
- ☐ b. 0.5
- ☐ c. 1
- ☐ d. 0
- ☐ e. 2

Consider that $a=-3$, $b=4$, $c=6$, then the value of c after executing the following code is

```
if(a>0)
```

```
if(b>0)
```

```
c++;
```

```
else
```

```
c--;
```

☐ a. 6

☒ b. 7

☐ c. 5

☐ d. error

[Clear my choice](#)

SMURFS POLYTECHNIC UNION

اتحاد

Question 1

Not yet
answered

Marked out of
1.00

Flag question

Consider the following statement

`int m[2][3] = {6, 0, -2, -5, 1, 8};`

The value of the element in the second row, second column is

ملاحظة: أكتب الاحابة مباشرة في حابة الاحابة بدون فراغات سابقة أو لاحقة

Answer:

1

البوليتكنيك
SPU

1

2

10

11

1 search option

Southern Polytechnic Union

The output of the following statement is

`floor(-3.5)`

- ☒ a. -4
- ☐ b. -3

Clear my choice

البوليتكنيك
SPU

The value of x after executing the following code is

```
x = 'b';
```

```
if(x>97 && x>99)
```

```
    x -= 32;
```

```
else if(x>97 || x<99)
```

```
    x = 97;
```

```
else
```

```
    x += 3;
```

☐ a. a

☐ b. b

☐ c. B

☐ d. e

```
a[3][3] = {1,2,3,4,5,9,7,8,9};
```

```
sum=0;
```

then the value of sum after executing the following code is _____

```
for(i=0; i<3; ++i){
```

```
    for(j=0; j<3; ++j){
```

```
        sum += a[1][j]--;
```

```
    }
```

```
    cout << endl;
```

```
}
```