

Question 1

Not yet answered

Marked out of 1.00

Flag question

What would be the output of the following code?

```
int x[2][2]={ {2}, {1,3} };
```

```
int s=0;
```

```
for(int i=0; i<2; i++)
```

```
    s += x[i][i];
```

```
cout<<s;
```

Select one:

☐ a. 1

☐ b. 4

☐ c. 3

☒ d. 5



Not yet answered

Marked out of 1.00

Flag question

Find the elements of array y after execution the following code

```
int x[ 3 ] = { -2 , 1 , 4 };  
float y [ 3 ];  
int i = 0;  
y [ i ] = ++ x [ i++ ];  
y [ i ] = x [ i ] / 2;  
y [ i + 1 ] = y [ i - 1 ];
```

Select one:

- ☐ -20-2
- ☐ -10-1
- ☐ rubbish data
- ☒ -10.5-1

PUTER SKILLS II-3

THE OUTPUT IS :

```
#include <iostream>
using namespace std;
void sum(int a1[], int a2[]){
    int temp[2];
    temp[0]=a1[0]+a2[0];

    temp[1]=a1[1]+a2[1];
    cout<<temp[0]<<' '<<temp[1]<<' ';
    a1[0]=13 ;
}
int main(){
    int x[2] = {7,12};
    int y[2] = {6,1};
    sum(x,y);
    cout<<x[0];
    return 0; }
```

Select one:

- ☐ a. 6 13 13
- ☒ b. 13 13 13
- ☐ c. 7 13 13
- ☐ d. 13 12 13

Not yet answered

Marked out of 1.00

Flag question

```
int f1(int m, int n);  
int f2(int x, int y, int z);  
void main()  
{cout<<f2(8,1,3); }
```

```
int f2(int x, int y, int z)  
{ if ( f1(x,y) < z)  
    return z-1;  
else  
    return z+1; }
```

```
int f1(int m, int n)  
{ return m+n; }
```

Select one:

- ☐ 3
- ☐ 2
- ☒ 4
- ☐ 8

PUTER SKILLS II-3

What is the output of the following code?

```
int x[2][2]={1,3,2,6};  
for(int i=0;i<2;i++)  
{  
    for(int j=0;j<2;j++)  
        cout<<-x[i][j] * 2 <<" ";  
}
```

Select one:

- ☒ 0 4 2 10
- ☐ 2 6 4 12
- ☐ None
- ☐ 1 3 2 6

PUTER SKILLS II-3

What is the output of the following Code

```
int x=0;  
int y=0;  
if (y || -x>10)  
    cout<<x+5;  
else if(x==1)  
    cout<<x;  
else  
    cout<<!x;
```

Select one:

- ☐ a. 5
- ☐ b. 2
- ☒ c. 1
- ☐ d. 0

TER SKILLS II-3

What would be the output of the following code?

```
int x = 5, y = 4, z = 3;
```

```
( x > y > z ) ? cout<< (x += 2), cout<< x : cout<<x;
```

Select one:

- ☐ a. 55
- ☒ b. 75
- ☐ c. 5
- ☐ d. 77

INTER SKILLS II-3

What would be the output of the following code?

```
char s1[10] = "FINAL";  
char s2[10] = "42";  
strcpy(s1, s2);  
cout<<strlen(s1);  
cout<<s1;
```

Select one:

- ☐ 5FINALA
- ☐ 10FINALA
- ☒ 242
- ☐ 342A

INTER SKILLS II-3

```
cout<<pow(floor(fabs(-2.7)),ceil(2.3));
```

Select one:

- ☐ 9
- ☐ 4
- ☐ 27
- ☒ 8

COMPUTER SKILLS II-3

What is the output of the following code?

```
int x = 1;

while ( x ) {
    for(int i = x- ; i >= 1; i--)
        cout << i << x ;
    cout << "****";
}
```

Select one:

- ☐ 1211*01*
- ☐ infinite loop
- ☐ 1111*00*
- ☒ 10*

COMPUTER SKILLS II-3

Question 17

Not answered

Score out of 1.00

Flag question

WHAT IS THE OUTPUT

```
int x=50, n=3;
```

```
do {
```

```
cout<<"*"<<++n<<"*\n";
```

```
++x; }
```

```
while (x<50||x>52);
```

Select one:

☐ *1*

☒ *4*

☐ *2*

☐ *3*

COMPUTER SKILLS II-3

WHAT IS THE OUTPUT

```
int i=2, s=2;
```

```
while(i++<6){
```

```
    s +=i-2;
```

```
    cout<<s<<" ";}
```

Select one:

- ☐ 3 5 8 11
- ☐ 2 4 7 11
- ☒ 3 5 8 12
- ☐ Endless Loop

COMPUTER SKILLS II-3

HOW MANY TIMES THE \$ WILL PRINT

```
for (int i=0;i<1;i++)  
    for(int j=0;j<3;j++)  
    {  
        if ( j==1)  
            break;  
        cout<<"$";  
    }
```

Select one:

- ☐ FOUR TIMES
- ☐ TWO TIMES
- ☒ ONE TIME
- ☐ THREE TIMES

COMPUTER SKILLS II-3

What is the output of the following Code

```
int n=3;
switch(n)
{
case 1:cout <<(n = 4)<<(n == 4);break;
case 3:cout<<(n && 4)<<(n || 4);
default: cout << (!n) << " ";
}
```

Select one:

- ☐ a. 40
- ☒ b. 110
- ☐ c. 11
- ☐ d. 0

PUTER SKILLS II-3

```
const int a = 5;  
int b = ++a * a++;  
cout<<b;
```

Select one:

- ☒ a. error
- ☐ b. 36
- ☐ c. 25
- ☐ d. 30

101-COMPUTER SKILLS II-3

Question 24

Not yet answered

Marked out of 1.00

Flag question

WHAT IS THE OUTPUT

```
int i=3, s=3;
```

```
while(i++<7){
```

```
    s +=i-1;
```

```
    cout<<s<<" ";}
```

Select one.

- ☐ a. Endless Loop
- ☐ b. 6 10 15
- ☒ c. 6 10 15 21
- ☐ d. 21

```
float fun(int x, char y )
```

```
{
```

```
cout<<y;
```

```
return x;
```

```
}
```

```
void main()
```

```
{ int m=66;
```

```
float n=7.7;
```

```
cout<<fun(n,m)/2;
```

```
}
```

Select one:

☐ 66 3.85

☐ B 3.85

☐ 66 3.5

☒ B 3,5