

Q2

```

int a[5]={5,6,-1,4,0};
class A{
private: int *p;
public: A(){p=a;}
void moveNext(){ p++;}
void movePrev(){p--;}
void out(){ cout<<*p<<endl;}
};
int main()
{
A xa;
xa.moveNext();xa.moveNext();xa.moveNext();
xa.movePrev();
xa.out();
}

```

A) 6 (B) -1 C) 4 D) other

Q4) Trace

```

class B{
public: int x; B *next, *prev;
B * fun();
void out()
{ cout<< this->x; }
~B(){ cout<<9; }
};
B * fun(){ return new B();}

int main(){
B *xa=fun(), *xb=fun();
xa->x=3; xa->next=xb; xb->x=5;
xb->prev=xa;
xa->next->prev->next->prev->next->prev->out();
delete xa;
delete xb;
}

```

Diagram: A linked list with two nodes. Node xa has x=3 and points to node xb. Node xb has x=5 and points back to node xa. A handwritten note '399' is next to the diagram.

A) 93 B) 939. (C) 399 D) other

Q5) Trace

```

public:
static int fun(int a,int b){ return a+b; }
static int fun(int x ){ return int(x);}
static int fun(double a) { return 1; };
};

int main(){
cout<< MyA::fun(8,2)/MyA::fun(2)
*MyA::fun(2.5);
}

```

int 10/2 * 1
5

A) 2 B) 4 C) 1 (D) others

PART B ANSWERS

Q1	Q2	Q3	Q4	Q5
B	B	A	C	D

Q5) Trace <pre> class A{ void out(int a){ cout<<a; } public: A(int a){ out(a);} ~A(){cout<<2;} }; int main(){ A(3); } </pre> A) 23 B) 32 C) 3 D) other	
---	--

Answer Part A)

Q1	Q2	Q3	Q4	Q5
A	B	C	A	B

PART B: MULTIPLE CHOICE QUESTION: fill the table below with correct answer

Q 1) Trace <pre> using namespace std; template <class U,class V> U fun(U a,V b){ cout<<a<<" "<<b; a++; return a; } int main(){ cout<<fun(4,'d'); } </pre> A) d5,4. B) 4,d5 C) 45,d. d) other	Q3) Trace <pre> class G{ double x; public: G(int a){x=a;} G & operator-(G ob){ this->x=this->x - ob.x; return *this; } void out(){ cout<<this->x<<endl;} }; int main(){ G ga(5),gb(1),gc(2); ga=ga-gb-gc; ga.out(); } </pre> A) 2. B) 3. C) -2. D) other 5 - 1 - 2 = 2 2
Q2) Trace	

PART A: MULTIPLE CHOICE QUESTION: Fill the table below with correct answer

Q1) Trace <pre> class A{ public: static void out(int a=0, int b=1){ cout<<++a+b++<<endl; } }; int main(){ A::out();}</pre> 1 + 1 (A) 2. B) 3. C) other D) error	Q3) Trace <pre> char * fun(char *p){ return ++p; } int main(){ char c[]="abc"; char *d=fun(c); cout<<d; }</pre> A) c B) a (C) bc D) other
Q2) trace <pre> namespace M{ class M{ int x,y; public: M(int a, int b):x(a),y(b){ cout<<x+y; } static int fun(int a,int b) {return a+b;} ~M(){ cout<<9; } }; } int main(){ cout<<M::M::fun(1,2);}</pre> A) 9 (B) 3. C) 39 D) other	Q4) Trace <pre> struct{ int age;char *name="abc"; }k; int main(){ k.age=5; cout<<k.name; }</pre> (A) abc B) ab. C) C D) other