

Question # 1: Multiple choice question. [15 x 1pt]

Which of the following data structures allow random access

- a) Arrays
- b) Linked list
- c) Trees
- d) a & b

Which of the following data structures is not a linear data structure.

- a) Arrays
- b) Linked list
- c) Trees
- d) a & b

In static stack the top of the stack is

- a) First element in the array
- b) Second element in the array
- c) Last element in the array
- d) determined by a variable.

The postfix expression of the infix expression. $A+B*(C+D)/F+D*E$ is:

- a) $AB+CD+*F/D+E*$
- b) $ABCD+*F/+DE*+$
- c) $A*B+CD/F*DE++$
- d) $A+*BCD/F*DE++$

In a circular queue of size n , how do you determine if the queue is full?

- a) $Front == Rear$
- b) $(Rear + 1) \% n == Front$
- c) $Rear == n - 1$
- d) $Rear == Front - 1$

6- What is the primary advantage of a circular queue over a linear queue?

- a) Dynamic resizing
- b) Constant-time searching
- c) Efficient space utilization
- d) Simpler implementation

7- Which operation is expensive in an array when compared to linked lists?

- a) Accessing elements
- b) Searching for elements
- c) Inserting elements in the middle
- d) Traversing

8- Which is a potential drawback of using linked lists over arrays?

- a) Fixed size
- b) Sequential memory allocation
- c) Higher memory overhead due to pointers
- d) Inefficient traversal

9- If the pointer P has the value of $NULL$ what will happen if this statement is executed: `cout<< p->info;`

- a) The output is 0
- b) The output is Random value
- c) No output
- d) Invalid code

10- Which operation is not efficient in a singly linked list compared to a doubly linked list?

- a) Insertion at the head
- b) Insertion at the tail
- c) Deletion from the head
- d) Deletion from the tail

11- In order to get the information stored in a binary search tree in the descending order, one should traverse it in which of the following order?

- a) Left, root, right
- b) root, left, right
- c) right, root, left
- d) right, left, root

12- What happens if you insert elements in sorted order into a binary search tree?

- a) The tree becomes balanced
- b) The height remains logarithmic
- c) The tree becomes a linked list
- d) a & b

13- Which traversal method is used in BSTs to delete all nodes in a tree safely?

- a) Preorder
- b) Inorder
- c) Postorder
- d) Level order

What will happen if a recursive function doesn't have a proper base case?

- a) The function will terminate immediately
- b) The function will continue running indefinitely, causing a stack overflow
- c) The function will return an incorrect result
- d) The function will throw a compile-time error



Question # 1: Multiple choice question. [15 x 1pt]

- 1- Which of the following data structures allow random access?
 a) Arrays ☒ b) Linked list c) Trees d) a & b
- 2- Which of the following data structures is not a linear data structure?
 a) Arrays b) Linked list c) Trees ☒ d) a & b
- 3- In static stack the top of the stack is
 a) First element in the array ☒ b) Second element in the array
 c) last element in the array d) determined by a variable.
- 4- The postfix expression of the infix expression $A+B*(C+D)/F+D^*E$ is:
 a) $AB+CD+*F/D+E^*$ b) $ABCD+*F/+DE^*+$ ☒ c) $A*B+CD/F^*DE++$ d) $A+*BCD/F^*DE++$
- 5- In a circular queue of size n , how do you determine if the queue is full?
 a) $Front == Rear$ b) $(Rear + 1) \% n == Front$ ☒ c) $Rear == n - 1$ d) $Rear == Front - 1$
- 6- What is the primary advantage of a circular queue over a linear queue?
 a) Dynamic resizing b) Constant-time searching
 c) Efficient space utilization ☒ d) Simpler implementation
- 7- Which operation is expensive in an array when compared to linked lists?
 a) Accessing elements b) Searching for elements c) Inserting elements in the middle ☒ d) Traversing
- 8- Which is a potential drawback of using linked lists over arrays?
 a) Fixed size b) Sequential memory allocation
 c) Higher memory overhead due to pointers ☒ d) Inefficient traversal
- 9- If the pointer P has the value of $NULL$ what will happen if this statement is executed: `cout << p->info;` ☒
 a) The output is 0 b) The output is Random value c) No output d) Invalid code
- 10- Which operation is not efficient in a singly linked list compared to a doubly linked list?
 a) Insertion at the head b) Insertion at the tail c) Deletion from the head d) Deletion from the tail ☒
- 11- In order to get the information stored in a binary search tree in the descending order, one should traverse it in which of the following order?
 a) Left, root, right b) root, left, right c) right, root, left ☒ d) right, left, root
- 12- What happens if you insert elements in sorted order into a binary search tree?
 a) The tree becomes balanced b) The height remains logarithmic
 c) The tree becomes a linked list ☒ d) a & b
- 13- Which traversal method is used in BSTs to delete all nodes in a tree safely?
 a) Preorder b) Inorder c) Postorder ☒ d) Level order
- 14- What will happen if a recursive function doesn't have a proper base case?
 a) The function will terminate immediately
 b) The function will continue running indefinitely, causing a stack overflow ☒
 c) The function will return an incorrect result d) The function will throw a compile-time error

