Small Clinic App - Full Source Code

A single-file web app (HTML + CSS + JavaScript) for a small clinic: patients, appointments, visits with fees, search, and backup. No server or internet needed; data is saved in the browser.

How to run

1. Create a new text file named **clinic.html**.
2. Copy the code below into it (or use the clinic.html file provided with this PDF).
3. Open the file in Chrome or Safari. On a phone you can use "Add to Home Screen".

Source code: clinic.html

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1">
<title>Small Clinic App</title>
<style>
  *{box-sizing:border-box}
  body{font-family:Arial,sans-serif;margin:0;background:#f4f6f8;color:#222}
  header{background:#0b7a75;color:#fff;padding:14px 16px;font-size:20px}
  nav{display:flex;gap:6px;padding:8px;background:#fff;position:sticky;top:0}
  nav button{flex:1;padding:10px;border:0;border-radius:6px;background:#e3eceb;font-size:15px}
  nav button.on{background:#0b7a75;color:#fff}
  main{padding:12px;max-width:760px;margin:auto}
  .card{background:#fff;border-radius:8px;padding:12px;margin-bottom:10px;box-shadow:0 1px 3px
      #0002}
  input,select,textarea{width:100%;padding:9px;margin:4px 0 10px;border:1px solid #bbb;border-
      radius:6px;font-size:15px}
  .btn{background:#0b7a75;color:#fff;border:0;padding:10px 14px;border-radius:6px;font-size:15px}
  .btn.red{background:#c0392b}.btn.gray{background:#777}
  .row{display:flex;justify-content:space-between;align-items:center;gap:8px}
  small{color:#666}
</style>
</head>
<body>
<header id="title"></header>
<nav id="nav"></nav>
<main id="view"></main>

<script>
/* ---------- 1. Text labels (edit these to translate the app) ---------- */
const T = {
  title: "Small Clinic",
  patients: "Patients", appts: "Appointments", visits: "Visits", backup: "Backup",
  name: "Full name", phone: "Phone", age: "Age", notes: "Notes",
  add: "Add", save: "Save", del: "Delete", search: "Search...",
  date: "Date", time: "Time", patient: "Patient", status: "Status",
  diagnosis: "Diagnosis", treatment: "Treatment / Prescription", fee: "Fee",
  today: "Today", total: "Total income", export: "Export data", import: "Import data",
  none: "Nothing here yet", confirm: "Are you sure?", choose: "-- choose patient --"
};

/* ---------- 2. Data layer (saved in the browser) ---------- */
const KEY = "clinic_data_v1";
let db = { patients: [], appts: [], visits: [] };
try { db = JSON.parse(localStorage.getItem(KEY)) || db; } catch (e) {}
const save = () => { try { localStorage.setItem(KEY, JSON.stringify(db)); } catch (e) {} };
const uid = () => Date.now().toString(36) + Math.random().toString(36).slice(2, 6);
const esc = s => String(s ?? "").replace(/[&<>"]/g, c =>
    ({"&":"&amp;","<":"&lt;",">":"&gt;",'"':"&quot;"}[c]));
const pname = id => (db.patients.find(p => p.id === id) || {}).name || "?";
const $ = id => document.getElementById(id);
const val = id => $(id).value.trim();

/* ---------- 3. Navigation ---------- */
let tab = "patients", q = "";
const tabs = ["patients", "appts", "visits", "backup"];
function render() {
  $("title").textContent = T.title;
  $("nav").innerHTML = tabs.map(t =>
    `<button class="${t === tab ? "on" : ""}"
        onclick="tab='${t}';q='';render()">${T[t]}</button>`).join("");
  ({ patients: viewPatients, appts: viewAppts, visits: viewVisits, backup: viewBackup })[tab]();
}
const patientOptions = () => `<option value="">${T.choose}</option>` +
  db.patients.map(p => `<option value="${p.id}">${esc(p.name)}</option>`).join("");
/* ---------- 4. Patients ---------- */
```

```
function viewPatients() {
  const list = db.patients.filter(p => (p.name + p.phone).toLowerCase().includes(q.toLowerCase()));
  $("view").innerHTML = `
    <div class="card">
      <input id="pn" placeholder="${T.name}">
      <input id="pp" placeholder="${T.phone}" type="tel">
      <input id="pa" placeholder="${T.age}" type="number" min="0">
      <textarea id="pt" rows="2" placeholder="${T.notes}"></textarea>
      <button class="btn" onclick="addPatient()">${T.add}</button>
    </div>
    <input placeholder="${T.search}" value="${esc(q)}" oninput="q=this.value;viewPatients()">
    ${list.map(p => `
      <div class="card"><div class="row"><div>
        <b>${esc(p.name)}</b><br><small>${esc(p.phone)} | ${esc(p.age)}</small><br>
        <small>${esc(p.notes)}</small></div>
        <button class="btn red" onclick="removeItem('patients','${p.id}')">${T.del}</button>
      </div></div>`).join("") || `<p>${T.none}</p>`}`;
}
function addPatient() {
  if (!val("pn")) return;
  db.patients.push({ id: uid(), name: val("pn"), phone: val("pp"), age: val("pa"), notes: val("pt")
      });
  save(); render();
}

/* ---------- 5. Appointments ---------- */
function viewAppts() {
  const sorted = [...db.appts].sort((a, b) => (a.date + a.time).localeCompare(b.date + b.time));
  const today = new Date().toISOString().slice(0, 10);
  $("view").innerHTML = `
    <div class="card">
      <select id="ap">${patientOptions()}</select>
      <input id="ad" type="date" value="${today}">
      <input id="at" type="time">
      <button class="btn" onclick="addAppt()">${T.add}</button>
    </div>
    ${sorted.map(a => `
      <div class="card"><div class="row"><div>
        <b>${esc(pname(a.pid))}</b> ${a.date === today ? `<small>(${T.today})</small>` : ""}<br>
        <small>${esc(a.date)} ${esc(a.time)}</small></div>
        <div>
          <button class="btn gray" onclick="toggleAppt('${a.id}')">${a.done ? "Done" :
              "Pending"}</button>
          <button class="btn red" onclick="removeItem('appts','${a.id}')">${T.del}</button>
        </div></div></div>`).join("") || `<p>${T.none}</p>`}`;
}
function addAppt() {
  if (!val("ap") || !val("ad")) return;
  db.appts.push({ id: uid(), pid: val("ap"), date: val("ad"), time: val("at"), done: false });
  save(); render();
}
function toggleAppt(id) { const a = db.appts.find(x => x.id === id); a.done = !a.done; save();
    render(); }

/* ---------- 6. Visits (medical record + fee) ---------- */
function viewVisits() {
  const sorted = [...db.visits].sort((a, b) => b.date.localeCompare(a.date));
  const total = db.visits.reduce((s, v) => s + (Number(v.fee) || 0), 0);
  $("view").innerHTML = `
    <div class="card">
      <select id="vp">${patientOptions()}</select>
      <input id="vd" type="date" value="${new Date().toISOString().slice(0, 10)}">
      <input id="vg" placeholder="${T.diagnosis}">
      <textarea id="vt" rows="3" placeholder="${T.treatment}"></textarea>
      <input id="vf" type="number" min="0" placeholder="${T.fee}">
      <button class="btn" onclick="addVisit()">${T.save}</button>
    </div>
    <div class="card"><b>${T.total}: ${total}</b></div>
    ${sorted.map(v => `
      <div class="card"><div class="row"><div>
        <b>${esc(pname(v.pid))}</b> <small>${esc(v.date)}</small><br>
        ${esc(v.diag)}<br><small>${esc(v.treat)}</small><br><small>${T.fee}:
            ${esc(v.fee)}</small></div>
        <button class="btn red" onclick="removeItem('visits','${v.id}')">${T.del}</button>
      </div></div>`).join("") || `<p>${T.none}</p>`}`;
}
function addVisit() {
  if (!val("vp")) return;
  db.visits.push({ id: uid(), pid: val("vp"), date: val("vd"), diag: val("vg"), treat: val("vt"),
      fee: val("vf") });
  save(); render();
}

/* ---------- 7. Backup (export / import JSON) ---------- */
function viewBackup() {
  $("view").innerHTML = `
    <div class="card">
```

```
      <p>Copy this text and keep it safe. Paste it back to restore.</p>
      <textarea id="bk" rows="10">${esc(JSON.stringify(db))}</textarea>
      <button class="btn" onclick="importData()">${T.import}</button>
    </div>`;
}
function importData() {
  try {
    const d = JSON.parse($("bk").value);
    if (d.patients && d.appts && d.visits) { db = d; save(); tab = "patients"; render(); }
  } catch (e) { alert("Invalid data"); }
}

/* ---------- 8. Shared delete ---------- */
function removeItem(kind, id) {
  if (!confirm(T.confirm)) return;
  db[kind] = db[kind].filter(x => x.id !== id);
  if (kind === "patients") {
    db.appts = db.appts.filter(x => x.pid !== id);
    db.visits = db.visits.filter(x => x.pid !== id);
  }
  save(); render();
}

render();
</script>
</body>
</html>
```