

Performance

Metrics

First Contentful Paint	0.8 s	Time to Interactive	0.8 s
Speed Index	0.8 s	Total Blocking Time	0 ms
Largest Contentful Paint	1.9 s	Cumulative Layout Shift	0.06

Values are estimated and may vary. The [performance score is calculated](#) directly from these metrics. [See calculator.](#)

[View Original Trace](#)

Show audits relevant to:

AllFCPLCPBTCLS

Opportunities — These suggestions can help your page load faster. They don't [directly affect](#) the Performance score.

OpportunityEstimated Savings

Use HTTP/20.39 s

HTTP/2 offers many benefits over HTTP/1.1, including binary headers and multiplexing. [Learn more.](#)

☐ Show 3rd-party resources (0)

URL	Protocol
http://www.belleonaturelle.fr	http/1.1
/sass/main.css (www.belleonaturelle.fr)	http/1.1
/img/logo_pap.webp (www.belleonaturelle.fr)	http/1.1
/img/photo1.webp (www.belleonaturelle.fr)	http/1.1

URL	Protocol
/img/logo_cosmebio.webp (www.belleonaturelle.fr)	http/1.1
/scripts/horaires.js (www.belleonaturelle.fr)	http/1.1
/fonts/Delicious%20Curls%20bold.ttf (www.belleonaturelle.fr)	http/1.1

Eliminate render-blocking resources 0.13 s ^

Resources are blocking the first paint of your page. Consider delivering critical JS/CSS inline and deferring all non-critical JS/styles. [Learn more](#). FCP LCP

☐ Show 3rd-party resources (0)

URL	Transfer Size	Potential Savings
/sass/main.css (www.belleonaturelle.fr)	1.7 KiB	190 ms

Diagnostics — More information about the performance of your application. These numbers don't [directly affect](#) the Performance score.

▲ Ensure text remains visible during webfont load ^

Leverage the font-display CSS feature to ensure text is user-visible while webfonts are loading. [Learn more](#). FCP LCP





☐ Show 3rd-party resources (0)

URL	Potential Savings
/fonts/Delicious%20Curls%20bold.ttf (www.belleonaturelle.fr)	110 ms

▲ Image elements do not have explicit width and height ^

Set an explicit width and height on image elements to reduce layout shifts and improve CLS. [Learn more](#) CLS

☐ Show 3rd-party resources (0)

URL	Failing Elements
 /img/photo1.webp (www.belleonaturelle.fr)	 img
 /img/logo_cosmebio.webp (www.belleonaturelle.fr)	 img

▲ Serve static assets with an efficient cache policy — 6 resources found ^

A long cache lifetime can speed up repeat visits to your page. [Learn more](#).

☐ Show 3rd party resources (0)

URL	Cache TTL	Transfer Size
/fonts/Delicious%20Curls%20bold.ttf (www.belleonaturelle.fr)	None	79 KiB
/img/photo1.webp (www.belleonaturelle.fr)	None	29 KiB
/img/logo_cosmebio.webp (www.belleonaturelle.fr)	None	15 KiB
/img/logo_pap.webp (www.belleonaturelle.fr)	None	15 KiB
/sass/main.css (www.belleonaturelle.fr)	None	2 KiB
/scripts/horaires.js (www.belleonaturelle.fr)	None	1 KiB

Avoid chaining critical requests — 2 chains found

The Critical Request Chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. [Learn more.](#) FCP LCP

Maximum critical path latency: **250 ms**

Initial Navigation

http://www.belleonaturelle.fr

/sass/main.css (www.belleonaturelle.fr)

/fonts/Delicious%20Curls%20bold.ttf (www.belleonaturelle.fr) - **110 ms, 78.94 KiB**

/scripts/horaires.js (www.belleonaturelle.fr) - **50 ms, 0.54 KiB**

Keep request counts low and transfer sizes small — 8 requests • 142 KiB

To set budgets for the quantity and size of page resources, add a budget.json file. [Learn more.](#)

Resource Type	Requests	Transfer Size
Total	8	142.3 KiB
Font	1	78.9 KiB
Image	3	58.6 KiB
Document	1	2.5 KiB
Stylesheet	1	1.7 KiB
Script	1	0.5 KiB
Media	0	0.0 KiB
Other	1	0.0 KiB
Third-party	0	0.0 KiB

Largest Contentful Paint element — 1 element found

This is the largest contentful element painted within the viewport. [Learn More](#) LCP

Element

Element



h1


Avoid large layout shifts — 5 elements found



These DOM elements contribute most to the CLS of the page. CLS


Element

CLS Contribution




aside.horaires

0.027



nav.nav

0.014



h1

0.012



address.header__address

0.005



div.presentation__img

0.003

Passed audits (28)



Properly size images



Serve images that are appropriately-sized to save cellular data and improve load time. [Learn more.](#)

Defer offscreen images



Consider lazy-loading offscreen and hidden images after all critical resources have finished loading to lower time to interactive. [Learn more](#).

Minify CSS

Minifying CSS files can reduce network payload sizes. [Learn more](#). FCP LCP

Minify JavaScript

Minifying JavaScript files can reduce payload sizes and script parse time. [Learn more](#). FCP LCP

Reduce unused CSS

Reduce unused rules from stylesheets and defer CSS not used for above-the-fold content to decrease bytes consumed by network activity. [Learn more](#). FCP LCP

Reduce unused JavaScript

Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network activity. [Learn more](#). LCP

Efficiently encode images

Optimized images load faster and consume less cellular data. [Learn more](#).

Serve images in next-gen formats

Image formats like JPEG 2000, JPEG XR, and WebP often provide better compression than PNG or JPEG, which means faster downloads and less data consumption. [Learn more](#).

Enable text compression

Text-based resources should be served with compression (gzip, deflate or brotli) to minimize total network bytes. [Learn more](#). FCP LCP

Preconnect to required origins

Consider adding `preconnect` or `dns-prefetch` resource hints to establish early connections to important third-party origins. [Learn more](#). FCP LCP

Initial server response time was short — Root document took 40 ms

Keep the server response time for the main document short because all other requests depend on it. [Learn more](#). FCP LCP

☐ Show 3rd-party resources (0)

URL	Time Spent
http://www.belleonaturelle.fr	40 ms

Avoid multiple page redirects

Redirects introduce additional delays before the page can be loaded. [Learn more](#). FCP LCP

Preload key requests

Consider using `<link rel=preload>` to prioritize fetching resources that are currently requested later in page load. [Learn more](#). FCP LCP

Use video formats for animated content

Large GIFs are inefficient for delivering animated content. Consider using MPEG4/WebM videos for animations and PNG/WebP for static images instead of GIF to save network bytes. [Learn more](#) LCP

Remove duplicate modules in JavaScript bundles ^

Remove large, duplicate JavaScript modules from bundles to reduce unnecessary bytes consumed by network activity. TBT

Avoid serving legacy JavaScript to modern browsers ^

Polyfills and transforms enable legacy browsers to use new JavaScript features. However, many aren't necessary for modern browsers. For your bundled JavaScript, adopt a modern script deployment strategy using module/nomodule feature detection to reduce the amount of code shipped to modern browsers, while retaining support for legacy browsers. [Learn More](#) TBT

Preload Largest Contentful Paint image ^

Preload the image used by the LCP element in order to improve your LCP time. [Learn more.](#) LCP

Avoids enormous network payloads — Total size was 142 KiB ^

Large network payloads cost users real money and are highly correlated with long load times. [Learn more.](#) LCP


☐ Show 3rd-party resources (0)

URL	Transfer Size
/fonts/Delicious%20Curls%20bold.ttf (www.belleonaturelle.fr)	78.9 KiB
/img/photo1.webp (www.belleonaturelle.fr)	28.8 KiB
/img/logo_cosmebio.webp (www.belleonaturelle.fr)	15.1 KiB
/img/logo_pap.webp (www.belleonaturelle.fr)	14.7 KiB
http://www.belleonaturelle.fr	2.5 KiB
/sass/main.css (www.belleonaturelle.fr)	1.7 KiB
/scripts/horaires.js (www.belleonaturelle.fr)	0.5 KiB
/img/logo_pap.webp (www.belleonaturelle.fr)	0.0 KiB

Avoids an excessive DOM size — 81 elements ^

A large DOM will increase memory usage, cause longer [style calculations](#), and produce costly [layout reflows](#). [Learn more.](#) TBT

Statistic	Element	Value
Total DOM Elements		81
Maximum DOM Depth	<div><div></div></div> th	6

Statistic	Element	Value
	 section.phyts	
Maximum Child Elements		14

User Timing marks and measures ^

Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. [Learn more](#).

JavaScript execution time — 0.0 s ^

Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. [Learn more](#). TBT

☐ Show 3rd-party resources (0)

URL	Total CPU Time	Script Evaluation	Script Parse
http://www.belleonaturelle.fr	174 ms	15 ms	6 ms
Unattributable	86 ms	19 ms	1 ms

Minimizes main-thread work — 0.3 s ^

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. [Learn more](#) TBT

Category	Time Spent
Other	113 ms
Style & Layout	84 ms
Script Evaluation	51 ms
Rendering	29 ms
Parse HTML & CSS	22 ms
Script Parsing & Compilation	10 ms

Minimize third-party usage ^

Third-party code can significantly impact load performance. Limit the number of redundant third-party providers and try to load third-party code after your page has primarily finished loading. [Learn more](#). TBT

Lazy load third-party resources with facades ^

Some third-party embeds can be lazy loaded. Consider replacing them with a facade until they are required. [Learn more](#). TBT

Uses passive listeners to improve scrolling performance ^

Consider marking your touch and wheel event listeners as `passive` to improve your page's scroll performance. [Learn more](#).

Avoids `document.write()` ^

For users on slow connections, external scripts dynamically injected via `document.write()` can delay page load by tens of seconds. [Learn more](#).

Avoid long main-thread tasks




Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay. [Learn more](#) TBT

Avoid non-composited animations



Animations which are not composited can be janky and increase CLS. [Learn more](#) CLS



Accessibility

These checks highlight opportunities to [improve the accessibility of your web app](#). Only a subset of accessibility issues can be automatically detected so manual testing is also encouraged.

Contrast — These are opportunities to improve the legibility of your content.

▲ Background and foreground colors do not have a sufficient contrast ratio.



Low-contrast text is difficult or impossible for many users to read. [Learn more](#).


Failing Elements




h4



p




p




p


Failing Elements




p.promo




strong




strong




a




a



a




a




th


Failing Elements




th




td#1.horaires__jour



td.horaires__heure




td#2.horaires__jour




td.horaires__heure



td#3.horaires__jour



td.horaires__heure




td#4.horaires__jour


Failing Elements




td.horaires__heure




td#5.horaires__jour




td.horaires__heure




td#6.horaires__jour




td.horaires__heure



td#7.horaires__jour



td.horaires__heure



p

Failing Elements

em

p

p

p

p

p


p

p#pied

Navigation — These are opportunities to improve keyboard navigation in your application.

Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. [Learn more.](#)

Failing Elements



Additional items to manually check (10) — These items address areas which an automated testing tool cannot cover. [Learn more](#) in our guide on [conducting an accessibility review](#).

The page has a logical tab order	^
Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. Learn more.	
Interactive controls are keyboard focusable	^
Custom interactive controls are keyboard focusable and display a focus indicator. Learn more.	
Interactive elements indicate their purpose and state	^
Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. Learn more.	
The user's focus is directed to new content added to the page	^
If new content, such as a dialog, is added to the page, the user's focus is directed to it. Learn more.	
User focus is not accidentally trapped in a region	^
A user can tab into and out of any control or region without accidentally trapping their focus. Learn more.	
Custom controls have associated labels	^
Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. Learn more.	
Custom controls have ARIA roles	^
Custom interactive controls have appropriate ARIA roles. Learn more.	
Visual order on the page follows DOM order	^
DOM order matches the visual order, improving navigation for assistive technology. Learn more.	
Offscreen content is hidden from assistive technology	^
Offscreen content is hidden with display: none or aria-hidden=true. Learn more.	

HTML5 landmark elements are used to improve navigation ^

Landmark elements (`<main>`, `<nav>`, etc.) are used to improve the keyboard navigation of the page for assistive technology. [Learn more](#).

Passed audits (12) ^

`[aria-hidden="true"]` is not present on the document `<body>` ^

Assistive technologies, like screen readers, work inconsistently when `aria-hidden="true"` is set on the document `<body>`. [Learn more](#).

The page contains a heading, skip link, or landmark region ^

Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. [Learn more](#).

Document has a `<title>` element ^

The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more](#).

`<html>` element has a `[lang]` attribute ^

If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. [Learn more](#).

`<html>` element has a valid value for its `[lang]` attribute ^

Specifying a valid [BCP 47 language](#) helps screen readers announce text properly. [Learn more](#).

Image elements have `[alt]` attributes ^

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. [Learn more](#).

Links have a discernible name ^

Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. [Learn more](#).

Lists contain only `` elements and script supporting elements (`<script>` and `<template>`). ^

Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. [Learn more](#).

List items (``) are contained within `` or `` parent elements ^

Screen readers require list items (``) to be contained within a parent `` or `` to be announced properly. [Learn more](#).

`[user-scalable="no"]` is not used in the `<meta name="viewport">` element and the `[maximum-scale]` attribute is not less than 5. ^

Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. [Learn more](#).

Cells in a `<table>` element that use the `[headers]` attribute refer to table cells within the same table. ^

Screen readers have features to make navigating tables easier. Ensuring ` ` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. [Learn more.](#) |

`<th>` elements and elements with `[role="columnheader"/"rowheader"]` have data cells they describe. ^

Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. [Learn more.](#)

Not applicable (30) ^

`[accesskey]` values are unique ^

Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. [Learn more.](#)

`[aria-*)` attributes match their roles ^

Each ARIA `role` supports a specific subset of `aria-*` attributes. Mismatching these invalidates the `aria-*` attributes. [Learn more.](#)

`button`, `link`, and `menuitem` elements have accessible names ^

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more.](#)

`[aria-hidden="true"]` elements do not contain focusable descendents ^

Focusable descendents within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. [Learn more.](#)

ARIA input fields have accessible names ^

When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more.](#)

ARIA `meter` elements have accessible names ^

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more.](#)

ARIA `progressbar` elements have accessible names ^

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more.](#)

`[role]`s have all required `[aria-*)` attributes ^

Some ARIA roles have required attributes that describe the state of the element to screen readers. [Learn more.](#)

Elements with an ARIA `[role]` that require children to contain a specific `[role]` have all required children. ^

Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. [Learn more.](#)

`[role]`s are contained by their required parent element ^

Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. [Learn more.](#)

`[role]` values are valid ^

ARIA roles must have valid values in order to perform their intended accessibility functions. [Learn more.](#)

ARIA toggle fields have accessible names ^

When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more.](#)

ARIA `tooltip` elements have accessible names ^

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more.](#)

ARIA `treeitem` elements have accessible names ^

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more.](#)

`[aria-*)` attributes have valid values ^

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. [Learn more.](#)

`[aria-*)` attributes are valid and not misspelled ^

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. [Learn more.](#)

Buttons have an accessible name ^

When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. [Learn more.](#)

`<dl>`'s contain only properly-ordered `<dt>` and `<dd>` groups, `<script>`, `<template>` or `<div>` elements. ^

When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. [Learn more.](#)

Definition list items are wrapped in `<dl>` elements ^

Definition list items (``<dt>`` and ``<dd>``) must be wrapped in a parent ``<dl>`` element to ensure that screen readers can properly announce them. [Learn more.](#)

`[id]` attributes on active, focusable elements are unique ^

All focusable elements must have a unique ``id`` to ensure that they're visible to assistive technologies. [Learn more.](#)

ARIA IDs are unique ^

The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. [Learn more.](#)

No form fields have multiple labels ^

Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. [Learn more.](#)

`<frame>` or `<iframe>` elements have a title ^

Screen reader users rely on frame titles to describe the contents of frames. [Learn more.](#)

`<input type="image">` elements have `[alt]` text ^

When an image is being used as an ``<input>`` button, providing alternative text can help screen reader users understand the purpose of the button. [Learn more.](#)

Form elements have associated labels	^
Labels ensure that form controls are announced properly by assistive technologies, like screen readers. Learn more .	
The document does not use <code><meta http-equiv="refresh"></code>	^
Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. Learn more .	
<code><object></code> elements have <code>[alt]</code> text	^
Screen readers cannot translate non-text content. Adding alt text to <code><object></code> elements helps screen readers convey meaning to users. Learn more .	
No element has a <code>[tabindex]</code> value greater than 0	^
A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. Learn more .	
<code>[lang]</code> attributes have a valid value	^
Specifying a valid BCP 47 language on elements helps ensure that text is pronounced correctly by a screen reader. Learn more .	
<code><video></code> elements contain a <code><track></code> element with <code>[kind="captions"]</code>	^
When a video provides a caption it is easier for deaf and hearing impaired users to access its information. Learn more .	



Best Practices

Trust and Safety

▲ Does not use HTTPS — 7 insecure requests found	^
All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding mixed content , where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. Learn more .	
<input type="checkbox"/> Show 3rd-party resources (0)	
Insecure URL	Request Resolution
http://www.belleonaturelle.fr	Allowed
/sass/main.css (www.belleonaturelle.fr)	Allowed
/img/logo_pap.webp (www.belleonaturelle.fr)	Allowed
/img/photo1.webp (www.belleonaturelle.fr)	Allowed
/img/logo_cosmebio.webp (www.belleonaturelle.fr)	Allowed

Insecure URL	Request Resolution
/scripts/horaires.js (www.belleonaturelle.fr)	Allowed
/fonts/Delicious%20Curls%20bold.ttf (www.belleonaturelle.fr)	Allowed

Passed audits (16)

Links to cross-origin destinations are safe	^
Add `rel="noopener"` or `rel="noreferrer"` to any external links to improve performance and prevent security vulnerabilities. Learn more.	
Avoids requesting the geolocation permission on page load	^
Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. Learn more.	
Avoids requesting the notification permission on page load	^
Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. Learn more.	
Avoids front-end JavaScript libraries with known security vulnerabilities	^
Some third-party scripts may contain known security vulnerabilities that are easily identified and exploited by attackers. Learn more.	
Allows users to paste into password fields	^
Preventing password pasting undermines good security policy. Learn more.	
Displays images with correct aspect ratio	^
Image display dimensions should match natural aspect ratio. Learn more.	
Serves images with appropriate resolution	^
Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. Learn more.	
Page has the HTML doctype	^
Specifying a doctype prevents the browser from switching to quirks-mode. Learn more.	
Properly defines charset	^
A character encoding declaration is required. It can be done with a ` <meta/> ` tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. Learn more.	
Avoids <code>unload</code> event listeners	^
The <code>unload</code> event does not fire reliably and listening for it can prevent browser optimizations like the Back-Forward Cache. Consider using the <code>pagehide</code> or <code>visibilitychange</code> events instead. Learn more	
Avoids Application Cache	^
Application Cache is deprecated. Learn more.	
Detected JavaScript libraries	^

All front-end JavaScript libraries detected on the page. [Learn more.](#)

Avoids deprecated APIs ^

Deprecated APIs will eventually be removed from the browser. [Learn more.](#)

No browser errors logged to the console ^

Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. [Learn more](#)

Page has valid source maps ^

Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. [Learn more.](#)

No issues in the [Issues](#) panel in Chrome Devtools ^

Issues logged to the `Issues` panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.

Not applicable (1) ^

Fonts with `font-display: optional` are preloaded ^

Preload `optional` fonts so first-time visitors may use them. [Learn more](#)



SEO

These checks ensure that your page is optimized for search engine results ranking. There are additional factors Lighthouse does not check that may affect your search ranking. [Learn more.](#)

Additional items to manually check (1) — Run these additional validators on your site to check additional SEO best practices. ^

Structured data is valid ^

Run the [Structured Data Testing Tool](#) and the [Structured Data Linter](#) to validate structured data. [Learn more.](#)

Passed audits (14) ^

Has a `<meta name="viewport">` tag with `width` or `initial-scale` ^

Add a `<meta name="viewport">` tag to optimize your app for mobile screens. [Learn more.](#)

Document has a <title> element

The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more.](#)

Document has a meta description

Meta descriptions may be included in search results to concisely summarize page content. [Learn more.](#)

Page has successful HTTP status code

Pages with unsuccessful HTTP status codes may not be indexed properly. [Learn more.](#)

Links have descriptive text

Descriptive link text helps search engines understand your content. [Learn more.](#)

Links are crawlable

Search engines may use `href` attributes on links to crawl websites. Ensure that the `href` attribute of anchor elements links to an appropriate destination, so more pages of the site can be discovered. [Learn More](#)

Page isn't blocked from indexing

Search engines are unable to include your pages in search results if they don't have permission to crawl them. [Learn more.](#)

robots.txt is valid

If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. [Learn more.](#)

Image elements have [alt] attributes

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. [Learn more.](#)

Document has a valid hreflang

hreflang links tell search engines what version of a page they should list in search results for a given language or region. [Learn more.](#)

Document has a valid rel=canonical

Canonical links suggest which URL to show in search results. [Learn more.](#)

Document uses legible font sizes — 99.59% legible text

Font sizes less than 12px are too small to be legible and require mobile visitors to “pinch to zoom” in order to read. Strive to have >60% of page text ≥12px. [Learn more.](#)

☐ Show 3rd-party resources (0)

Source	Selector	% of Page Text	Font Size
main.css:95	.promo	0.41%	11.2px
Legible text		99.59%	≥ 12px

Document avoids plugins

Search engines can't index plugin content, and many devices restrict plugins or don't support them. [Learn more.](#)

Tap targets are sized appropriately — 100% appropriately sized tap targets



Interactive elements like buttons and links should be large enough (48x48px), and have enough space around them, to be easy enough to tap without overlapping onto other elements. [Learn more.](#)

Runtime Settings

URL	http://www.belleonaturelle.fr/
Fetch Time	Aug 2, 2021, 10:53 AM GMT+2
Device	Emulated Moto G4
Network throttling	150 ms TCP RTT, 1,638.4 Kbps throughput (Simulated)
CPU throttling	4x slowdown (Simulated)
Channel	devtools
User agent (host)	Mozilla/5.0 (X11; Linux x86_64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/92.0.4515.107 Safari/537.36
User agent (network)	Mozilla/5.0 (Linux; Android 7.0; Moto G (4)) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/90.0.4420.0 Mobile Safari/537.36 Chrome-Lighthouse
CPU/Memory Power	1949
Axe version	4.1.3

Generated by **Lighthouse** 7.5.0 | [File an issue](#)