xped



SMART HOME CATALOGUE 2019


Xped specialises in developing Internet of Things technology solutions for consumer, commercial, industrial and healthcare markets.

Xped has leveraged this expertise to develop a complete IoT ecosystem for the smart home. We have developed a flexible solution that is adaptable based on region, demographic and price sensitivity. We can package a solution or just provide specific pieces of the solution.

We have an inhouse development team that can provide bespoke solutions and white labelling. We are able to provide low entry cost 'no gateway' options through to advanced all-in-one super gateway solutions. We support industry-standard communications technologies as well as our own ADRC communications protocol technology.









•••••

Smart Home Gateway

The Smart Home Gateway is the brain that makes it possible to automate, monitor and control your home from anywhere in the world. It has a wide range of connectivity options making it compatible with thousands of devices from hundreds of manufacturers.

Together with the Xped App, you can easily create rules to automate your home. For example, turning on the lights when someone enters a room. You can also create scenes that enable several devices to be controlled together with the click of a button.











FEATURES

| • • • • • • • • • • • • • • • | | |
|-------------------------------|--|--|

| Simp | | - | _ | |
|------|----|--------|-------|--|
| | ıe | se | ю | |
| | | \sim | Г. | |

Out of home control

Power monitoring

Automation via Scenes and Rules

WiFi & Bluetooth support

Z-Wave device support

ADRC device support

COMPATIBLE DEVICES

Cameras

Lighting

Environment Sensors

Motion Sensors

Door Locks & Bells

Plugs

Switches



Xped Lighting




RGBW Globe

Our range of smart RGBW globes with up to 16 million colours available, allows for complete control of colour, brightness and warmth of your lighting.



| Power | 9W |
|------------|--------------------------|
| Voltage | 110V-240V |
| Colour | RGB (16M Colour Pallete) |
| Features | Hue / Dimming |
| Comm Types | Z-Wave |
| Geography | US, EU, AU, MY standards |



Smart Strip Lighting

Our smart strip lighting is easy to install and allows for complete control of colour, brightness and warmth that can change the mood or visual appeal in any room.



| Power | 72W |
|------------|--------------------------|
| Voltage | 110V-240V |
| Colour | RGBW |
| Features | Hue / Dimming |
| Comm Types | Z-Wave |
| Geography | US, EU, AU, MY standards |

Xped Lighting



Philips Hue White & Color

Hue is your personal wireless lighting solution that lets you control your lighting and create the right ambiance for any situation.



| w | i | F | i | |
|---|---|---|---|--|
| | | | | |

| Power | 10W |
|------------|---------------------------|
| Colour | RGBW (16M Colour Palette) |
| Features | Hue / Dimming / Whites |
| Comm Types | Hue Bridge – WiFi |
| Geography | Worldwide |



Hue Downlight

Hue downlights are perfect for lighting large areas of your home in style.



| Power | 6.5W |
|------------|---------------------------|
| Colour | RGBW (16M Colour Palette) |
| Features | Hue / Dimming / Whites |
| Comm Types | Hue Bridge – WiFi |
| Geography | Worldwide |
| | |



Xped Power



Single Switch

Our relay switch is installed behind mechanical light switches or power outlets to enable App control functionality.



| Power | 120 - 230 VAC |
|--------------|--------------------------|
| Rated Output | 15A |
| No of Relays | 1 |
| Dimensions | 40x44x20mm |
| Geography | US, EU, AU, MY standards |
| Installation | Licensed electrician |



Dual Switch

Our dual relay switch is installed behind mechanical light switches to enable App control functionality.



| Power | 120 - 230 VAC |
|--------------|--------------------------|
| Rated Output | 10A (5A per switch) |
| No of Relays | 2 |
| Dimensions | 40x44x20mm |
| Geography | US, EU, AU, MY standards |
| Installation | Licensed electrician |
| | |



Xped Power



Smart Plug

Our smart plug turns wall outlets into a smartapp controlled outlet. It can be used to control simple appliances such as fans, lamps and many other things.



| Power | 110V - 240VAC |
|-------------|--------------------------|
| Consumption | <0.5W |
| Load Power | < 3000W |
| USB Power | 5V @ 1000 mA |
| Dimensions | 77x65x42mm |
| Comm Types | Z-Wave |
| Geography | US, EU, AU, MY standards |



Smart Plug

Our premium smart plug turns wall outlets into smart app controlled outlets. It can measure the power used by the connected appliance and has a colour-changing LED ring.



| Power | 110V - 240VAC |
|-------------|--------------------------|
| Consumption | <0.5W |
| Load Power | < 2500W |
| USB Power | 5V @ 1000 mA |
| Dimensions | 52x52x35mm |
| Comm Types | Z-Wave |
| Geography | US, EU, AU, MY standards |
| | |





Contact Sensor (Door / Window)

Our Premium Contact Sensor can be used to detect when any door or window is open or closed. It features our unique tap on-boarding to add to your system in a matter of seconds.



| Power | 3V Lithium Coin Cell CR2450 |
|--------------|---------------------------------------|
| Consumption | 5μA Average |
| Features | Low battery warning, tamper detection |
| Battery Life | 5-10 years |
| Dimensions | 52x32x20mm |
| Comm Types | ADRC subgHz |
| Geography | AU, SG, MY, US |
| | |



Contact Sensor (Door / Window)

Our compact design can be mounted on any door or window frame so it can monitor the opening and closing of doors or windows.



| Power | 2 x AAA Batteries |
|---------------------|--|
| Consumption | Standby $\leq 5\mu A$, Op $\leq 35mA$ |
| Read Switch Trigger | >20mm |
| Features | Low Battery Notification |
| Dimensions | 60x30x12.5mm and 60x13x15.5mm |
| Comm Types | Z-Wave |
| Geography | US, EU, AU, MY standards |
| | |



Indoor Siren

Our Smart Siren works in conjunction with our range of sensors to provide both audible and visual alerting.



| Power | 110 - 240 VAC |
|------------|-------------------------------|
| Backup | 4 hours with internal battery |
| Alarm | Up to 95dB |
| Strobe | 4 flashes per second |
| Dimensions | 82x40mm |
| Comm Types | Z-Wave |
| Geography | US, EU, AU, MY standards |



Panic Button

Our Smart Panic Button can be used to trigger a range of events including audible and visual siren as well as notifications through the App.



| Power | 3V (CR2032 Coin Battery) |
|------------|--------------------------|
| Dimensions | 50x33x15mm |
| Comm Types | ADRC |
| Geography | AU, SG, MY, US |



Motion Sensor

Our Smart Motion Sensor detects any motion or movement within a room and is designed to be attached at any location in any room of your home.



| Power | DC 3V (CR2450 Coin Battery) |
|--------------|---|
| Consumption | Standby $\leq 15\mu A$, Op $\leq 36mA$ |
| Detect Angle | 110° |
| Detect Range | 9-12m |
| Features | Low Battery Notification |
| Dimensions | 65x65x28mm |
| Comm Types | 7-Wave |
| Commit types | Z-vvave |



Door Lock

The Yale Smart Door Lock can be accessed either via a PIN code, access card or App, whilst providing a high-quality secure locking mechanism.



| Power | DC 6V (4*1.5V AA Batteries) |
|----------------|--|
| Consumption | Standby $\leq 5\mu A$, Op $\leq 35mA$ |
| User Interface | Access Code, Access Card, Key, App |
| Features | Low Battery Notification |
| Comm Types | Z-Wave |
| Geography | US, EU, AU, MY, CN standards |



Pan / Tilt Indoor Camera

Through the Xped App, our Pan & Tilt Camera allows you to physically move the camera to provide a better view of specific areas of your room in real-time.







NIGHT

| Resolution | 720P |
|-------------------|----------------------|
| Visual Angle | 85°-90° |
| Day/Night Mode | IR-cut Auto ICR |
| Video Compression | H.264 |
| Audio Comm | Supports 2-way Audio |
| Power Supply | 5V |
| Storage | SD Card 64GB |
| IR LED distance | 5-8M |
| Comm Types | WiFi (802.11b) |
| Geography | Worldwide |
| | |



3 in 1 Camera

Our Smart 3 in 1 Camera can provide a good quality image in both daylight and up to a 20m distance at night whilst supporting 2-way audio communication.









| Resolution | 720P or 1080P |
|-------------------|------------------------|
| Visual Angle | 85°-90° |
| Day/Night Mode | IR-cut Auto ICR |
| Video Compression | H.264 |
| Audio Comm | Supports 2-way Audio |
| Power Supply | 12V |
| Storage | SD Card 64GB |
| IR LED distance | 15-20M |
| Comm Types | WiFi (IEEE802.11b/g/n) |
| Geography | Worldwide |



Netatmo Welcome

The Welcome is a full-featured home security indoor camera that provides advanced features including: night vision, facial recognition and notification of audible alarms.





| Video sensor | 4MP |
|--------------|---------------------------|
| Resolution | Up to 1920 x 1080 |
| Visual Angle | 130° |
| Storage | Micro SD card up to 32 GB |
| Comm Types | WiFi, Ethernet |
| Geography | Worldwide |



Netatmo Presence

The Presence is a full-featured home security outdoor camera that provides advanced features including 12 W LED floodlight, night vision, alerts zones and object recognition.





| Video sensor | 4MP |
|--------------|---------------------------|
| Resolution | Up to 1920 x 1080 |
| Visual Angle | 100° |
| Storage | Micro SD card up to 32 GB |
| Comm Types | WiFi |
| Geography | Worldwide |



Multi Sensor

Our multi-sensor takes the place of 6 individual sensors making it suitable for a multitude of applications including security and HVAC control.



| Power | 2xCR123A or USB |
|--------------|------------------------------|
| Battery Life | Up to 2 years |
| Motion Range | 5m field 120 degrees |
| Temperature | -10C to +50C |
| Light | 0 to 2000 Lumens |
| Humidity | 0 to 100% |
| Vibration | Used for tamper detection |
| Dimensions | 45x45x38mm |
| Geography | US, EU, AU, MY, CN standards |
| | |



Multi Sensor

Our Premium Multi Sensor is able to detect motion, temperature, humidity and ambient light. This makes it perfect for switching on lights when someone enters the room, controlling HVAC and opening curtains and blinds.



| Power | 3V Lithium Coin Cell CR2450 |
|--------------|---------------------------------------|
| Consumption | 5 uA average |
| Features | Low battery warning, tamper detection |
| Battery Life | 3-5 years |
| Dimensions | 52x32x20mm |
| Comm Type | ADRC subgHz |
| Geography | AU, SG, MY, USA |



Xped Environmental



Gas Sensor

With an inbuilt-speaker to provide an audible alert, our Smart Gas Sensor detect the concentration of natural gas in the air.



| Power | AC 100V-240V |
|-------------|----------------------------|
| Consumption | ≤ 1.5W |
| Alarm | 75dB @ 1M |
| Density | 6% LEL ±3% LEL Natural Gas |
| Dimensions | 79x68x45.5mm |
| Comm Types | Z-Wave |
| Geography | US, EU, AU, MY standards |
| | |



Temperature / Humidity Sensor

Designed with low power consumption technology, our Smart Sensor provide accurate measurements of both temperature and humidity.



| Power | 3V (CR2450 Coin Battery) |
|-------------------|----------------------------------|
| Consumption | Standby ≤ 10µA |
| Operating Ambient | Temp: -10°C-50°C Humidity: ≤ 95% |
| Dimensions | 60x60x20.8mm |
| Comm Types | Z-Wave |
| Geography | US, EU, AU, MY standards |
| | |



Xped Environmental



CO Sensor

Our Smart CO sensor can detect the concentration of Carbon Monoxide in the air and includes an-inbuilt speaker to provide an audible alert.



| Power | 3V (CR123A Lithium Battery) |
|---------------|-----------------------------|
| Consumption | Standby ≤ 10µA |
| Alarm Current | ≤ 60mA |
| Alarm | 85dB @ 3M |
| Dimensions | 60x60x49.2mm |
| Comm Types | Z-Wave |
| Geography | US, EU, AU, MY standards |



Smoke Detector

Our Smart Smoke Detector is easy to install, battery-operated, requires no electrical wiring and includes an in-built speaker for audible alarming.



| Power | 3V (CR123A Lithium Battery) |
|---------------|-----------------------------|
| Consumption | Standby ≤ 20µA |
| Alarm Current | ≤ 60mA |
| Alarm | 85dB @ 3M |
| Dimensions | 60x60x49.2mm |
| Comm Types | Z-Wave |
| Geography | US, EU, AU, MY standards |

Xped Environmental



Moisture / Leak Sensor

Perfect for detecting leaks and bursts in pipes, floods and overflows. This device also includes a temperature sensor which make it useful for the management of HVAC and underfloor heating.



| Power | CR123A battery |
|---------------|----------------------------------|
| Battery Life | < 2.5 years |
| Sensors | Water, vibration and temperature |
| Temperature | -20C to +100C |
| Consumption | Standby ≤ 5µA |
| Alarm Current | ≤ 30mA |
| Siren | 60db built-in siren |
| Dimensions | 38x84x24mm |
| Comm Types | Z-Wave |
| Geography | US, EU, AU, MY standards |
| | |



Moisture / Leak Sensor

Perfect for detecting leaks and bursts in pipes, floods and overflows. This device also includes a temperature sensor which make it useful for the management of HVAC and underfloor heating.



| Power | CR123A battery |
|---------------|----------------------------------|
| Battery Life | < 2.5 years |
| Sensors | Water, vibration and temperature |
| Temperature | -20C to +100C |
| Consumption | Standby ≤ 5µA |
| Alarm Current | ≤ 30mA |
| Dimensions | 38x84x24mm |
| Comm Types | Z-Wave |
| Geography | US, EU, AU, MY standards |
| | |



Xped Infrared



IR Blaster

Perfect for controlling AV equipment such as TVs, Blu-rays, set top boxes and HVAC equipment including air conditioners. Equipment can be controlled via smart phone app and gateway scenes that command several devices at once.



| IR Range | Up to 15m line of sight |
|---------------|---------------------------|
| IR Dispersion | 3600 |
| Database | Over 200,000 device codes |
| Power | Micro USB 5v adapter |
| Consumption | ≤ 50mW |
| Dimensions | 65x52x18mm |
| Comm Types | Bluetooth LE |
| Geography | Worldwide |
| | |



IR Blaster

The Logitech Harmony Hub has all the capabilities of the standard device but has a learning feature that allows you to add the codes for infrared equipment you own by recording them from the original remote controls.



| IR Range | Up to 15m line of sight |
|---------------|---------------------------|
| IR Dispersion | 360o |
| Database | Over 200,000 device codes |
| Power | Micro USB 5v adapter |
| Consumption | ≤ 1W |
| Dimensions | 114x109x36mm |
| Comm Types | WiFi |
| Geography | Worldwide |

Flexible and Interoperable.

Xped's Physical Gateway solution has existing compatibility with a large range of consumer products from the following brands. Xped will continue to add more device compatibility to meet evolving consumer demands.

COMPATIBLE BRANDS*

Aeotec Logitech

Amazon Nest

Fibaro Netatmo

Honeywell Philips

Lockwood Yale







PHILIPS HUE



NEST THERMOSTAT



AMAZON ECHO DOT

^{*} Note: Our solution does not support all smart products from these brands. A full list of exact products is available upon request.

Create your own branded smart home solution with Xped's white label IoT platform.

Xped's turnkey solution offers partners a complete smart home solution to sell to your customers. We provide a complete IoT platform with all of the components required to tailor a solution to meet your customers requirements. Contact Xped today to find out more.

BENEFITS

Simple licensing program

Low entry cost

Competitive licensing costs

Custom-branded solution

Expanding functionality

Flexible product range





Xped is a technology and solutions provider that is focused on IoT infrastructure with solutions for Smart Home, Professional Health and Smart Buildings.

DEVICE DISCOVERY

Device discovery, provisioning and interoperability



DEVICE

Device browser that delivers command and control to the end user



DEVICE

Device description language based on XML



GATEWAY

Business logic, rules engine, notifications, device management solutions



CLOUD

Device and Subscriber Management, OTA Updates, Virtual Gateway, API and Services Orchestration, In-App Communication and Advertising (Xerts), Data Analytics Framework









Level 6, 412 Collins Street, Melbourne VIC 3000 T +61 3 9642 0655 • E info@xped.com

www.xped.com