BAVARIAN ENDURANCE BATTLE

# Werk Sport Class Rules

## FINAL DRAFT FOR REVIEW

November 6, 2026

| Subcategory | BMW chassis with |
|---|---|
| WSSub1 | Naturally aspirated BMW engine |
| WSSub2 | Turbocharged or supercharged BMW engine |
| WSSub3 | Naturally aspirated engine from another manufacturer |
| WSSub4 | Turbocharged or supercharged engine from another manufacturer |

Mandatory companion documents: BEB General Vehicle Rules and Roll Cage Rules.

This review edition separates established provisions from proposed WSSub3 and WSSub4 completions. Remaining decisions are listed in the review appendix.

# Contents

**WS. General Werk Sport Rules 3**

WS.1. Spirit of the Class . . . 3

WS.2. Class Structure and Mandatory Compliance . . . 3

WS.3. Vehicle Eligibility and Assignment . . . 4

WS.4. Bodywork and Exterior Equipment . . . 4

WS.5. Chassis, Subframes, and Structural Fabrication . . . 6

WS.6. Suspension, Steering Rack, Wheels, and Brakes . . . 8

WS.7. Engine Management, Fuel, Exhaust, and Drivetrain . . . 9

WS.8. Fluid Lines, Fuel Shielding, and Oil Pans . . . 10

WS.9. Competition Power Integrity . . . 10

WS.10. Tire Restrictions . . . 11

WS.11. BEB Identification and Decals . . . 11

**WS-A. AERODYNAMICS AND FRONT STRUCTURE 12**

**WSSub1. BMW Chassis with a Naturally Aspirated BMW Engine 16**

**WSSub2. BMW Chassis with a Turbocharged or Supercharged BMW Engine 18**

**WSSub3. BMW Chassis with a Naturally Aspirated Engine from Another Manufacturer 21**

**WSSub4. BMW Chassis with a Turbocharged or Supercharged Engine from Another Manufacturer 23**

**Review Appendix. Decisions Before Publication 26**

Read the general WS rules, the complete WS-A aerodynamic section, and your applicable WSSub section.

# WS. General Werk Sport Rules

## WS.1. Spirit of the Class

Werk Sport celebrates creativity, craftsmanship, and beautifully built race cars. Its four subcategories give teams the freedom to explore engine swaps and develop distinctive machines for endurance competition.

That freedom must respect the conditions of a shared racetrack. Werk Sport vehicles will compete alongside slower classes, and substantial differences in speed can create dangerous closing rates. Both faster and slower drivers need time to recognize traffic, anticipate one another, and make safe decisions.

BEB will establish tire size restrictions for the Werk Sport subcategories to help contain the performance of exceptionally powerful builds and manage speed differences between classes. These restrictions are part of the class's approach to shared track safety, rather than an attempt to achieve identical performance.

Tire restrictions do not replace responsible driving. Every team must prepare and operate its vehicle with respect for the safety of all participants throughout the endurance race.

## WS.2. Class Structure and Mandatory Compliance

### WS.2.1. Four Subcategories

Werk Sport uses BMW production chassis and is divided into four subcategories:

1. WSSub1: BMW chassis with a naturally aspirated BMW engine.
2. WSSub2: BMW chassis with a turbocharged or supercharged BMW engine.
3. WSSub3: BMW chassis with a naturally aspirated engine from another manufacturer.
4. WSSub4: BMW chassis with a turbocharged or supercharged engine from another manufacturer.

Teams must read the general WS requirements, the shared WS-A aerodynamic section, and their applicable WSSub section. No subcategory obtains its rules by reference to another subcategory.

### WS.2.2. Mandatory Safety and Roll Cage Compliance

All vehicles in all four subcategories must comply with the BEB General Vehicle Rules, Roll Cage Rules, and applicable safety and conduct requirements.

Structural modification and engine development permissions do not waive or replace safety requirements. A vehicle that fails safety requirements does not become eligible merely by entering Werk Sport.

Failure to comply may result in loss of track time or removal from the event. BEB may deny track access or remove a vehicle presenting an unsafe installation until corrected and accepted by BEB officials.

## WS.3. Vehicle Eligibility and Assignment

### WS.3.1. Eligible Vehicles

BMW production vehicles of any model year originally offered for sale in the United States market are eligible, subject to the applicable subcategory and general requirements.

Eligible body configurations include sedans, coupes, convertibles, and Tourings. BMW M model vehicles and BMW M engines are permitted.

The BMW X1 is the only permitted SUV. All other SUVs are prohibited.

Vehicles must retain their recognizable BMW production body identity. Chassis, frame, body, and subframe modifications are permitted only within the express Werk Sport allowances.

### WS.3.2. Vehicles Exceeding Other Class Allowances

Vehicles whose configuration or modifications exceed the allowances of the Vintage, Dreier, Touring, Geschäftsklasse, or Zenith Class may compete in the appropriate Werk Sport subcategory, provided they satisfy Werk Sport eligibility, technical, and safety requirements.

An engine swap is not required when a vehicle enters Werk Sport because other modifications exceed its original class allowances. Original factory turbocharged BMW engine applications are eligible in WSSub2 without a swap.

A naturally aspirated BMW retaining its original engine application and remaining within its other applicable class allowances belongs in that class.

### WS.3.3. Assignment by Engine and Induction

Subcategory assignment follows the installed engine manufacturer and induction configuration. Turbocharging, supercharging, or both places a vehicle in the applicable forced induction subcategory.

Engine assemblies combining major components from different manufacturers require a classification decision before this draft is published. No engine block based classification rule is established by this draft.

### WS.3.4. Competition Weight

A numerical competition weight limit and the weighing conditions remain to be finalized. The 4,000 pound figure discussed from a reference example is not adopted as a final BEB limit in this review draft.

## WS.4. Bodywork and Exterior Equipment

### WS.4.1. Roofline and Pillars

Nonconvertible vehicles must retain their original production roofline and pillars.

Convertible vehicles must have a securely installed hardtop. Hardtop design and materials are otherwise unrestricted, subject to the BEB General Vehicle Rules.

A hardtop does not replace or reduce any roll cage requirement, including the requirements applicable to convertibles.

### WS.4.2. Fenders, Tire Coverage, and Openings

Fenders, quarter panels, and permitted extensions must completely cover the entire tire tread when viewed directly from above.

When viewed from the side, fender openings must retain a shape and height similar to the original OEM configuration.

A maximum of one vent or louver assembly above the tire is permitted per side of the vehicle. The lower portion of a fender behind a wheel may be cut and formed inward to relieve wheel well pressure.

Replacement fenders, flares, wide body additions, and their materials are unrestricted where they preserve these requirements. They must not function as aerodynamic devices beyond the allowances of WS-A.

### WS.4.3. Tire Clearance and Safe Edges

Panels, vents, flares, and surfaces surrounding a tire must be free of sharp edges, exposed points, or features capable of cutting, slashing, or puncturing the tire.

Adequate clearance must be maintained throughout the full range of steering movement and suspension travel, including compression and rebound.

### WS.4.4. Doors

Doors must retain their original production shape but are otherwise unrestricted within the BEB General Vehicle Rules and Roll Cage Rules.

Driver and front passenger doors must open from both inside and outside the vehicle. Rear doors on four door vehicles are not required to open.

Rear flares may extend onto doors provided they do not prevent either front door from opening or interfere with driver or passenger egress.

### WS.4.5. Mirrors

Mirror design and construction are unrestricted. At least two functional mirrors are required.

Mirrors must be securely installed and provide usable rearward visibility. Reflective surfaces must remain unobstructed.

### WS.4.6. Bumpers and Tow Points

Front and rear bumper design and materials are unrestricted within the aerodynamic allowances of WS-A. Front bumper reinforcement must meet WS-A.3. Retaining the OEM rear crash beam and its supporting structure is strongly recommended.

Each vehicle must have a towing attachment at both front and rear, using tow hooks, straps, or equivalent devices capable of towing or moving the vehicle.

Tow devices must attach securely to suitable structural mounting points and must not protrude in a manner that could hook, snag, or damage another vehicle during incidental contact.

### WS.4.7. Tire Spats

Tire spats may be mounted at the rear edge of the front bumper, directly ahead of the front tires, solely to direct airflow around them. They must follow the bumper or fender shape.

Viewed directly from the front with the wheels straight ahead, a spat must not extend outward beyond the outermost edge of the corresponding tire or wheel. A component functioning as a canard remains subject to WS-A.6.

### WS.4.8. Side Skirt Position and Attachment

The majority of each side skirt must remain below the bottom edge of the doors. Skirts must not extend outward beyond the outermost edges of the corresponding front and rear tires.

Suitable mechanical fasteners or mounting structures are required. Double sided tape alone is not adequate. Movement and ground sealing restrictions are governed by WS-A.10.

### WS.4.9. Hood and Trunk

Hood shape, design, and ventilation may be modified, provided the hood remains substantially similar to the original vehicle's hood in overall fitment and configuration. Vents and openings may be added, modified, or removed.

Replacement trunk lids and materials are unrestricted provided the original OEM exterior shape is maintained.

### WS.4.10. Windshield and Windows

Glass may be replaced with motorsport suitable polycarbonate, including Lexan, Makrolon, or equivalent materials.

Replacement polycarbonate windshields must be at least 1/4 inch thick. All other replacement polycarbonate windows must be at least 1/8 inch thick.

All glazing must be securely installed and comply with the BEB General Vehicle Rules. Driver and front passenger windows must remain fully lowered during competition; removal is preferred.

### WS.4.11. Sunroofs, Cowl, and Wipers

Sunroofs may be retained only where not made of glass. Assemblies may be removed and openings covered with properly constructed aluminum, carbon fiber, or steel panels. Panels must fully cover the openings and be securely attached.

Alternate windshield cowl materials are permitted provided the original OEM shape is maintained. Wiper modifications are unrestricted within the BEB General Vehicle Rules.

Custom panels creating a smooth blend between the hood and windshield are prohibited.

## WS.5. Chassis, Subframes, and Structural Fabrication

### WS.5.1. Original Structure and Permitted Exceptions

Except where expressly permitted, major modifications to the chassis, frame, unibody, floor, or firewall are prohibited.

Localized changes are permitted for component clearance, strengthening, bracing, and repair. They must be limited to their stated purpose and provide no unrelated performance benefit.

Engine and drivetrain installation allowances, the permitted complete rear suspension conversion, and the front structure allowance in WS-A.3 are express exceptions. Full tube frame conversion of the remaining production chassis is not authorized.

Nonessential body attachments, interior supports, and trim may be removed for weight reduction without compromising structural integrity. Major structural components must not be lightened or compromised.

### WS.5.2. Reinforcement and Repair

Material may be added to reinforce known weak areas, strengthen mounting areas, and repair crash damage. Seam welding is permitted.

Reinforcement and repair must preserve required suspension and subframe mounting point locations except for an expressly permitted conversion.

### WS.5.3. Wheel Well Clearance

Localized fabricated changes within wheel wells and tubs are permitted solely for tire clearance, suspension arm clearance, and suspension travel. They must not provide unrelated performance benefits or relocate suspension mounting points.

### WS.5.4. Radiator Supports and Cooling Location

Radiator supports may be replaced with fabricated structures for fitment or repair. The radiator must remain in its general factory location and receive cooling air through the same general area used by the original vehicle.

Bumper and cooling openings may be partially blocked only where sufficient openings remain to supply the airflow needed to cool the engine and associated systems. Front fabrication permission in WS-A.3 does not independently authorize radiator relocation.

### WS.5.5. Suspension and Subframe Mounting Points

Suspension mounting points on the body and subframes must retain their original OEM locations, geometry, and mounting angles. Reinforcement is permitted without altering the points themselves.

Subframes must retain their original mounting locations on the body and must not reposition suspension points relative to the vehicle.

The complete rear suspension conversion in WS.5.6 and steering rack relocation in WS.6.4 are specific exceptions limited to their stated purposes.

### WS.5.6. Original Solid or Live Rear Axle Vehicles

Vehicles originally equipped with a solid or live rear axle may convert to independent rear suspension using a complete donor subframe assembly from a mass produced road going vehicle.

Assemblies from other manufacturers, including BMW M model assemblies and components, are permitted. Donor suspension mounting point locations and geometry must be retained. Race only or aftermarket suspension geometry is prohibited under this exception.

Body attachments necessary to mount the complete donor assembly are permitted. Individual suspension mounting points within the assembly must not be relocated. Other suspension requirements apply as though the donor suspension were originally installed.

### WS.5.7. Modified, Alternate, and Tubular Subframes

Front and rear subframes may be modified to accommodate engine and drivetrain swaps, including oil pan clearance and installation of a different differential.

Similar OEM subframes from the same manufacturer may be installed where required mounting point locations are preserved. Aftermarket and fabricated tubular subframes are permitted to facilitate engine swaps while retaining all required OEM suspension and control arm mounting point locations, geometry, and angles.

Body attachment locations must remain unchanged except for WS.5.6.

### WS.5.8. Subframe Clearance Reinforcement

Every cut, notch, or removed subframe section must be reinforced to preserve rigidity and structural integrity. Clearance pockets must be boxed with a properly fabricated recessed structure, reinforced with additional material, or both.

Construction must prevent excessive flex, fatigue, cracking, failure, or breakage during sustained endurance use. All fabrication and welding must be professionally executed.

### WS.5.9. Roll Cage Extensions and Firewall Sealing

Structural tubes connecting the roll cage to the permitted front structure or nose are allowed. Materials, connections, and welding must comply with the BEB Roll Cage Rules.

The firewall must remain a continuous, fully sealed barrier between the engine and driver compartments. Tube penetrations must be completely sealed with securely installed fire resistant materials and methods compliant with the BEB General Vehicle Rules.

No gaps, open seams, or exposed openings are permitted around penetrations. Separate engine installation permissions appear in each applicable subcategory section.

## WS.6. Suspension, Steering Rack, Wheels, and Brakes

### WS.6.1. Suspension Components

Control arms, uprights, knuckles, hubs, trailing arms, and related components may be modified or replaced for camber or caster adjustment, permitted strength improvements, or repair to original condition and strength.

Replacement uprights, knuckles, and arms installing directly without modification of the required mounting interfaces are permitted. Aftermarket arms must use the original attachment points on the chassis and applicable knuckle, hub carrier, or upright.

Hubs may be replaced with aftermarket or other suitable components for strength. These permissions do not authorize relocation of fixed suspension mounting points.

### WS.6.2. Bushings, Ball Joints, and Correction Kits

Bushings, ball joints, and suspension geometry correction kits are unrestricted within the fixed mounting point requirements. Adjustment through permitted components does not authorize cutting, slotting, drilling, or relocating fixed body or subframe mounting points.

### WS.6.3. Damper Adjustment

Suspension valving adjusters are limited to four adjustments per corner. The meaning of this limit requires clarification before publication, as identified in the review appendix.

### WS.6.4. Steering Rack Relocation

Steering racks may be relocated where necessary for engine clearance. This does not authorize relocation of suspension or control arm mounting points.

Racks, mounts, shafts, joints, and tie rods must be securely installed and operate without binding or interference throughout the full steering range and suspension travel.

Extreme tie rod or joint angles capable of causing binding, accelerated wear, fatigue, or breakage are prohibited. All installations must withstand sustained endurance racing loads.

### WS.6.5. Wheels

Wheel dimensions and designs are unrestricted except for the applicable tire restrictions, coverage, clearance, mounting, and safety requirements.

Wheels must be aluminum alloy or steel. Magnesium and carbon fiber wheels are prohibited.

### WS.6.6. Brakes

Brake size and piston count are unrestricted. Systems must be suitable for the application, securely and properly installed, and compliant with the BEB General Vehicle Rules.

## WS.7. Engine Management, Fuel, Exhaust, and Drivetrain

### WS.7.1. Engine Location

Engine swaps are permitted within the engine manufacturer and induction requirements of the entered subcategory. Engines must remain in approximately the same location as the original engine, as close as practicable to the OEM position.

### WS.7.2. Engine Management and Ignition

Engine management systems and ignition components are unrestricted for naturally aspirated and forced induction engines. Components and wiring must be securely installed and comply with the BEB General Vehicle Rules.

Engine internal development permissions are stated in the applicable subcategory section.

### WS.7.3. Fuel

91 octane gasoline and E85 are permitted in all four subcategories. Nitrous oxide, nitromethane, and other supplemental chemicals or additives used to increase power are prohibited.

E85 permission does not authorize other alternate fuels or power increasing additives.

### WS.7.4. Exhaust

Exhaust systems are unrestricted provided they comply with the BEB General Vehicle Rules. Turbocharger wastegate discharge requirements appear directly in the forced induction subcategory sections.

### WS.7.5. Driven Wheels

The original driven wheel configuration must be retained unless BMW offered the same vehicle in multiple drivetrain configurations.

Conversion between those factory configurations is permitted only using the applicable OEM BMW components. For example, an AWD vehicle may convert to RWD where BMW offered the corresponding RWD configuration and the appropriate OEM parts accomplish the conversion.

This exception does not authorize a custom driven wheel configuration.

### WS.7.6. Transmissions

Transmission swaps and transmission ratios are unrestricted. Installations must meet the applicable structural, mounting, and safety requirements.

## WS.8. Fluid Lines, Fuel Shielding, and Oil Pans

### WS.8.1. Fluid Lines

All fluid carrying lines must be securely routed and supported to prevent abrasion. Lines must be suitable for the intended fluid and rated for operating pressure and temperature.

Protective sleeves or equivalent abrasion protection are recommended where fasteners, clamps, cable ties, or surrounding surfaces could rub against a line.

### WS.8.2. Fuel Component Shielding

Fuel fittings, tank covers, filler assemblies, and pump access openings must be separated from the driver compartment by a securely installed protective bulkhead or enclosure unless already isolated by a suitable firewall or trunk bulkhead.

Steel or braided stainless steel fuel lines do not require an additional covering solely under this provision. This does not waive shielding requirements for their fittings or associated components.

### WS.8.3. Oil Pan Modifications

Oil pans may be modified for subframe clearance. Modifications must be professionally fabricated. Modified seams, joints, and closure panels must be completely welded and oil tight, with no evidence of leakage.

Silicone, sealants, JB Weld, epoxy, and similar compounds must not join, patch, repair, or seal a fabricated modification. Manufacturer specified gaskets or sealants at the normal mounting flange remain permitted.

A vehicle with a leaking or improperly modified pan may not compete or return to the track until corrected and accepted by BEB officials.

## WS.9. Competition Power Integrity

### WS.9.1. Misrepresentation and Tune Manipulation

Where a competition horsepower requirement or power verification procedure is established by BEB, adjustment of ECU calibration, boost limits, rev limits, or other power controls to misrepresent competition horsepower is prohibited before, during, and after a session or verification.

A vehicle must not produce a reduced verification reading and then compete using settings exceeding its permitted power.

### WS.9.2. Switchable Maps and Controls

Switchable ECU maps or controls must not conceal, bypass, or manipulate competition power requirements, whether operated by driver or crew, on track or during dyno testing.

Tune altering switches, selectors, and mechanisms must be outside the driver's reach. Their locations and functions must be declared to BEB scrutineers. Declaration does not authorize a prohibited use.

### WS.9.3. Enforcement and Penalties

Suspected manipulation may result in suspension from track activity pending investigation. Confirmed use of an illegal tune or prohibited power level constitutes unsportsmanlike conduct and will result in removal of the vehicle and driver from the event and a ban on both from future BEB competition.

All previous BEB competition wins credited to that vehicle and driver will be removed. Associated prizes and contingency awards must be forfeited and returned for redistribution as determined by BEB.

No horsepower limit, dyno requirement, or verification procedure is created by this section. Those decisions remain open in this review draft.

## WS.10. Tire Restrictions

BEB will establish tire size restrictions for the Werk Sport subcategories to help manage performance differences and shared track safety. Specific sizes, compounds, measurement methods, and wet condition provisions remain to be finalized.

Unrestricted wheel dimensions do not waive the forthcoming tire limits or existing tire coverage and clearance requirements.

## WS.11. BEB Identification and Decals

Any windshield banner, class identification sticker, or BEB class sponsor sticker provided or mandated by BEB for the event must be applied to the vehicle's exterior in the location designated by BEB.

Required decals and banners must remain securely attached, clearly visible, and unobstructed throughout the event.

Werk Sport mirror colors, identification light colors, and subcategory markings remain to be assigned. No identification colors from another class are adopted automatically.

# WS-A. AERODYNAMICS AND FRONT STRUCTURE

### WS-A.1. General Allowances

OEM, aftermarket, and custom-fabricated aerodynamic components are permitted within the allowances and dimensional limits of this section. Materials and manufacturers are unrestricted, provided all components meet the construction and mounting requirements below.

Aerodynamic devices not expressly permitted by this section require written BEB approval before competition.

Permission to install an aerodynamic component does not authorize structural modifications beyond those expressly permitted by the Werk Sport rules.

### WS-A.2. Static Aerodynamics

All aerodynamic components must remain fixed in position while the vehicle is on track.

Powered, cockpit-adjustable, self-adjusting, and intentionally flexible aerodynamic systems are prohibited. OEM active aerodynamic systems must be removed or securely fixed in a compliant position.

Manual adjustment while the vehicle is stationary in the pits is permitted. All adjustments must be securely locked before returning to the track.

### WS-A.3. Front Structure and Fabrication

The OEM front shock towers must remain unmodified and in their original locations. Front suspension mounting points must remain in their OEM locations.

Forward of the front shock towers, the front structure may be cut, modified, or replaced to accommodate aerodynamic components, cooling systems, ducting, and their fabricated supports. A fabricated tubular front structure is permitted.

Custom splitter mounts, air-dam supports, bodywork supports, ducting mounts, and removable front assemblies are permitted.

All replacement structures must be professionally fabricated and securely attached to sound portions of the chassis. Cutting must not extend into the shock towers or compromise their supporting structure.

The completed nose must retain the recognizable OEM appearance, basic profile, and styling of the vehicle’s BMW model. OEM and replacement exterior panels are permitted. Splitters, air dams, canards, cooling openings, and fender modifications permitted by this section may alter the exterior within their respective limits.

If the OEM front bumper reinforcement is removed or modified, a securely mounted replacement bumper structure providing equivalent crash protection must be installed. Aerodynamic supports alone do not satisfy this requirement. BEB may require supporting fabrication details and may reject an inadequately constructed replacement.

### WS-A.4. Front Air Dam

An OEM, aftermarket, or fabricated front air dam is permitted.

The air dam must follow the front body outline and remain vertical within a tolerance of 5 degrees.

Separate front wings, stacked front aerodynamic elements, and independent front airfoils are prohibited. Canards meeting WS-A.6 are permitted.

### WS-A.5. Front Splitter and Undertray

One flat, horizontal front splitter is permitted.

The splitter may project no more than 7 inches forward of its intersection with the front fascia or air dam. Forward projection must be measured horizontally at the corresponding location across the nose.

The splitter and associated front undertray may extend rearward no farther than the driver-compartment front bulkhead/firewall.

A continuous strip of fascia or air-dam material at least 1 inch high must remain immediately above the splitter along its intersection with the fascia or air dam, including beneath air-intake openings.

The splitter must not incorporate additional stacked planes, separate airfoils, or shaped venturi tunnels. Structural reinforcement and securely mounted support rods are permitted.

### WS-A.6. Front Canards

A maximum of two canards or dive planes per side is permitted, confined to the front bumper area. Molded-in and separately attached canards count toward the same limit.

Canards may not extend more than 6 inches outward beyond the vertical plane through the widest part of the vehicle’s body on the corresponding side. No separate limit applies to individual canard length or surface area.

All canards must remain fixed while on track, be securely mounted, and have finished edges and corners. They must not obstruct required lighting, tow points, or safety equipment.

### WS-A.7. Rear Wing or Spoiler

One single-element rear wing or one rear spoiler is permitted. A Gurney flap is permitted and does not count as a second element.

The complete assembly, including endplates and Gurney flap, must comply with the following limits:

| Measurement | Maximum |
|---|---|
| Height above the OEM roofline | 8 inches |
| Overall width | OEM body width, excluding add-on fender flares, mirrors, door handles, and aerodynamic devices |
| Area of each endplate | 144 square inches |
| Rearward projection beyond the OEM rear bodywork profile | 12 inches |

For convertibles, the height reference is the top of the OEM windshield frame in its original location.

Height is measured vertically. Rearward projection is measured horizontally, excluding aerodynamic additions from the bodywork reference.

Multi-element rear wings and separate wings mounted over the hood, roof, or middle of the vehicle are prohibited.

Wing supports must transfer loads into suitable reinforced mounting locations. Unsupported exterior panel skins alone are not acceptable mounting structures.

### WS-A.8. Rear Diffuser

An OEM, aftermarket, or fabricated rear diffuser is permitted.

The diffuser must remain entirely rearward of the rear axle centerline and may extend no more than 6 inches beyond the rear bumper, measured horizontally.

Diffuser installation does not authorize removal or modification of structural members, suspension mounting points, or bumper reinforcement unless separately permitted by the Werk Sport rules.

The diffuser must be securely mounted and must not interfere with the tires, suspension, exhaust system, or required safety equipment.

### WS-A.9. Underbody Panels

The front splitter/undertray and rear diffuser permitted above are allowed.

An added continuous aerodynamic floor connecting the front undertray to the rear diffuser is prohibited. Fabricated venturi tunnels and underbody suction fans are prohibited.

OEM underbody panels may remain in their original locations.

Localized heat shields, cooling shields, and protective panels are permitted provided they do not form an otherwise prohibited aerodynamic floor or tunnel.

### WS-A.10. Side Skirts

Fixed side skirts attached along the rocker areas are permitted.

Sliding, sprung, actively controlled, or intentionally ground-sealing skirts are prohibited. Side skirts must not be designed to maintain contact with the track surface.

### WS-A.11. Cooling Openings, Vents, and Fenders

Hood vents, louvers, fender vents, and cooling ducts are permitted.

Cooling openings may be fabricated into the front fascia, hood, and fenders, provided required structural members, shock towers, and suspension mounting points remain compliant with the Werk Sport rules.

Bolt-on, replacement, and fabricated fender flares are permitted. Fender modifications must not create additional wings, canards, or aerodynamic tunnels outside the allowances of this section.

Cooling ducts and hoses must be securely mounted and must not interfere with steering, suspension travel, tires, driver escape, or safety equipment.

### WS-A.12. Construction, Mounting, and Condition

All aerodynamic components and supporting structures must be suitable for sustained endurance-racing use.

Mountings must withstand aerodynamic loads, vibration, and normal racing operation. Fasteners, brackets, braces, and attachment points must remain secure.

Exposed edges and corners must be finished to avoid sharp projections.

Components must not obstruct:

- Driver entry or emergency exit.
- Required lights or identification markings.
- Tow points or emergency access.
- Steering or suspension movement.
- Required safety equipment.

Loose, damaged, dragging, or partially detached aerodynamic components must be repaired or removed before the vehicle returns to the track.

BEB may require reinforcement, repair, removal, or further inspection of any component or supporting structure found unsuitable for competition.

# WSSub1. BMW Chassis with a Naturally Aspirated BMW Engine

### WSSub1.1. Eligible Vehicles and Engines

This subcategory accepts eligible BMW sedans, coupes, convertibles, Tourings, and BMW X1 vehicles equipped with a BMW engine operating in naturally aspirated form. Turbocharging and supercharging are prohibited in this subcategory.

BMW engine swaps are permitted. An original engine application is also eligible where the vehicle enters Werk Sport because its configuration or other modifications exceed another BEB class allowance. A vehicle remaining within its applicable other class rules belongs in that class.

All general Werk Sport eligibility, safety, roll cage, tire, and aerodynamic requirements apply. BMW M engines are permitted where consistent with the subcategory engine manufacturer and induction requirements.

### WSSub1.2. Engine Location

The engine must remain in approximately the same location as the original engine, installed as close as practicable to the original OEM position.

### WSSub1.3. Firewall and Transmission Tunnel Clearance

Firewall and transmission tunnel modifications are permitted where necessary to accommodate the engine and transmission installation.

Modifications must be professionally fabricated and preserve structural integrity and complete separation between the drivetrain and driver compartment.

Modified areas must have no cracks, tears, exposed openings, open seams, or unwelded joints. Fabricated closure panels must be fully welded around their entire perimeter.

This permission does not authorize relocation of suspension or subframe mounting points beyond the express general Werk Sport exceptions.

### WSSub1.4. Exhaust

Exhaust systems are unrestricted provided they comply with the BEB General Vehicle Rules.

### WSSub1.5. Engine Management, Ignition, and Wiring

Engine management is unrestricted. Factory ECU or DME tuning, chips, and aftermarket standalone ECUs are permitted. Ignition components are unrestricted.

Custom wiring is permitted where properly constructed, securely installed, protected from damage, and compliant with the BEB General Vehicle Rules.

### WSSub1.6. Engine Development

Internal engine modifications are unrestricted within the naturally aspirated engine requirement. Cylinder head swaps and combinations of components from different BMW engines are permitted.

These permissions do not waive installation, structural, fuel, or safety requirements.

### WSSub1.7. Steering Columns and Steering Racks

Steering column and steering rack swaps or modifications are permitted only where professionally executed and safe for competition. Steering rack relocation must satisfy WS.6.4.

The steering column must retain the original OEM collapsible devices and their function. Modifications must not bypass, disable, or rigidly bridge those devices.

Shafts, joints, bearings, mounts, and connections must be correctly aligned, securely installed, and operate without binding or interference throughout the full steering range and suspension travel.

Poorly fabricated, misaligned, inadequately supported, or otherwise unsafe installations are prohibited. Safety is BEB's first priority. Creativity does not excuse poor execution. A vehicle with unsafe steering may not compete until corrected and accepted by BEB officials.

### WSSub1.8. Driveshafts

Driveshaft shortening, lengthening, or other modification must be performed by a professional driveshaft specialist. The completed assembly must be balanced for its intended application.

All BMW driveshaft components required for proper support, alignment, articulation, and retention must be preserved and remain functional. An engine or transmission installation does not authorize omission of components necessary to prevent driveshaft failure.

# WSSub2. BMW Chassis with a Turbocharged or Supercharged BMW Engine

### WSSub2.1. Eligible Vehicles and Engines

This subcategory accepts eligible BMW sedans, coupes, convertibles, Tourings, and BMW X1 vehicles equipped with a BMW engine operating with turbocharging, supercharging, or both.

Turbochargers and superchargers of any type are permitted. Factory systems may be retained, modified, or replaced. Forced induction may be added to a naturally aspirated engine. Original factory turbocharged BMW engine applications are eligible without an engine swap.

All general Werk Sport eligibility, safety, roll cage, tire, and aerodynamic requirements apply. BMW M engines are permitted where consistent with the subcategory engine manufacturer and induction requirements.

### WSSub2.2. Engine Location

The engine must remain in approximately the same location as the original engine, installed as close as practicable to the original OEM position.

### WSSub2.3. Firewall and Transmission Tunnel Clearance

Firewall and transmission tunnel modifications are permitted where necessary to accommodate the engine and transmission installation.

Modifications must be professionally fabricated and preserve structural integrity and complete separation between the drivetrain and driver compartment.

Modified areas must have no cracks, tears, exposed openings, open seams, or unwelded joints. Fabricated closure panels must be fully welded around their entire perimeter.

This permission does not authorize relocation of suspension or subframe mounting points beyond the express general Werk Sport exceptions.

### WSSub2.4. Exhaust and Wastegate Discharge

Exhaust systems are unrestricted provided they comply with the BEB General Vehicle Rules.

Wastegate discharge must return into the exhaust system or discharge downward through a securely installed outlet positioned clear of vehicle components.

Open discharge must not be directed toward suspension arms, bushings, tires, brake lines, fluid lines, wiring, the floor, firewall, engine compartment components, or any other part of the vehicle. Routing must prevent exhaust gases or heat from contacting components or entering the driver compartment.

### WSSub2.5. Engine Management, Ignition, and Wiring

Engine management is unrestricted. Factory ECU or DME tuning, chips, and aftermarket standalone ECUs are permitted. Ignition components are unrestricted.

Custom wiring is permitted where properly constructed, securely installed, protected from damage, and compliant with the BEB General Vehicle Rules.

### WSSub2.6. Engine Development

Internal engine modifications and engine bolt on components are unrestricted. Cylinder head swaps and combinations of components from different BMW engines are permitted.

Alternate exhaust manifolds, piping, intercoolers, turbochargers, and superchargers are permitted.

These permissions do not waive installation, structural, fuel, or safety requirements.

### WSSub2.7. Steering Columns and Steering Racks

Steering column and steering rack swaps or modifications are permitted only where professionally executed and safe for competition. Steering rack relocation must satisfy WS.6.4.

The steering column must retain the original OEM collapsible devices and their function. Modifications must not bypass, disable, or rigidly bridge those devices.

Shafts, joints, bearings, mounts, and connections must be correctly aligned, securely installed, and operate without binding or interference throughout the full steering range and suspension travel.

Poorly fabricated, misaligned, inadequately supported, or otherwise unsafe installations are prohibited. Safety is BEB's first priority. Creativity does not excuse poor execution. A vehicle with unsafe steering may not compete until corrected and accepted by BEB officials.

### WSSub2.8. Driveshafts

Driveshaft shortening, lengthening, or other modification must be performed by a professional driveshaft specialist. The completed assembly must be balanced for its intended application.

All BMW driveshaft components required for proper support, alignment, articulation, and retention must be preserved and remain functional. An engine or transmission installation does not authorize omission of components necessary to prevent driveshaft failure.

### WSSub2.9. Turbocharger Heat Protection

Turbochargers, turbine housings, exhaust manifolds, downpipes, and wastegate discharge pipes produce substantial heat. Fuel components, wiring, electronics, fluid lines, and other heat sensitive components must be positioned as far as practicable from these heat sources.

Where adequate separation cannot be achieved, exposed hoses and wiring must be enclosed in fire sleeves rated for the application. Other heat sensitive components must have suitable fire resistant enclosures or heat shields.

Turbocharger turbine housings must have securely installed turbo heat blankets suitable for the application. Protective sleeves, shields, and blankets do not make an otherwise hazardous installation acceptable.

### WSSub2.10. Intercoolers and Charge Cooling

Air to air and water to air intercoolers are permitted. Supercharger cooler cores, reservoirs, pots, and bowls are permitted.

All components, piping, and hoses must be securely mounted and supported to prevent loosening, movement, or detachment. As much piping as practicable must remain within the bodywork. This does not require routing through the driver compartment.

Distilled water is the only permitted fluid in any water to air intercooler or charge cooling circuit. Coolant, antifreeze, and additives are prohibited.

Charge cooling water lines within the driver compartment must use steel braided hose suitable for the operating pressure and temperature. Lines, fittings, and connections exposed to the driver must be separated from the driver by securely installed aluminum or steel shielding positioned to prevent hot water or steam from spraying the driver following a rupture.

Steel braiding alone does not satisfy the shielding requirement.

### WSSub2.11. Hazardous Installations

BEB may deny track access or remove a vehicle from competition if its installation, heat protection, or discharge routing presents a hazard. The vehicle may not compete or return to the track until corrected and accepted by BEB officials.

# WSSub3. BMW Chassis with a Naturally Aspirated Engine from Another Manufacturer

**Proposed completion for review. The engine manufacturer and induction category are established; the detailed provisions below require confirmation before publication.**

### WSSub3.1. Eligible Vehicles and Engines

This subcategory accepts eligible BMW sedans, coupes, convertibles, Tourings, and BMW X1 vehicles equipped with an engine from another manufacturer operating in naturally aspirated form. Turbocharging and supercharging are prohibited in this subcategory.

All general Werk Sport eligibility, safety, roll cage, tire, and aerodynamic requirements apply.

### WSSub3.2. Engine Location

The engine must remain in approximately the same location as the original engine, installed as close as practicable to the original OEM position.

### WSSub3.3. Firewall and Transmission Tunnel Clearance

Firewall and transmission tunnel modifications are permitted where necessary to accommodate the engine and transmission installation.

Modifications must be professionally fabricated and preserve structural integrity and complete separation between the drivetrain and driver compartment.

Modified areas must have no cracks, tears, exposed openings, open seams, or unwelded joints. Fabricated closure panels must be fully welded around their entire perimeter.

This permission does not authorize relocation of suspension or subframe mounting points beyond the express general Werk Sport exceptions.

### WSSub3.4. Exhaust

Exhaust systems are unrestricted provided they comply with the BEB General Vehicle Rules.

### WSSub3.5. Engine Management, Ignition, and Wiring

Engine management is unrestricted. Factory ECU or DME tuning, chips, and aftermarket standalone ECUs are permitted. Ignition components are unrestricted.

Custom wiring is permitted where properly constructed, securely installed, protected from damage, and compliant with the BEB General Vehicle Rules.

### WSSub3.6. Engine Development

Internal engine modifications are unrestricted within the naturally aspirated engine requirement. Cylinder head and component changes are proposed to be unrestricted within the engine manufacturer classification and induction requirements. Mixed manufacturer major component classification remains unresolved.

These permissions do not waive installation, structural, fuel, or safety requirements.

### WSSub3.7. Steering Columns and Steering Racks

Steering column and steering rack swaps or modifications are permitted only where professionally executed and safe for competition. Steering rack relocation must satisfy WS.6.4.

The steering column must retain the original OEM collapsible devices and their function. Modifications must not bypass, disable, or rigidly bridge those devices.

Shafts, joints, bearings, mounts, and connections must be correctly aligned, securely installed, and operate without binding or interference throughout the full steering range and suspension travel.

Poorly fabricated, misaligned, inadequately supported, or otherwise unsafe installations are prohibited. Safety is BEB's first priority. Creativity does not excuse poor execution. A vehicle with unsafe steering may not compete until corrected and accepted by BEB officials.

### WSSub3.8. Driveshafts

Driveshaft fabrication, shortening, lengthening, or other modification must be performed by a professional driveshaft specialist. The completed assembly must be balanced for its intended application.

Components necessary for correct support, alignment, articulation, and retention must be suitable for the installed drivetrain and remain functional. A custom engine or transmission interface must not omit the support or retention necessary to prevent driveshaft failure.

# WSSub4. BMW Chassis with a Turbocharged or Supercharged Engine from Another Manufacturer

**Proposed completion for review. The engine manufacturer and induction category are established; the detailed provisions below require confirmation before publication.**

### WSSub4.1. Eligible Vehicles and Engines

This subcategory accepts eligible BMW sedans, coupes, convertibles, Tourings, and BMW X1 vehicles equipped with an engine from another manufacturer operating with turbocharging, supercharging, or both.

Turbochargers and superchargers of any type are permitted. Factory systems may be retained, modified, or replaced. Forced induction may be added to a naturally aspirated engine.

All general Werk Sport eligibility, safety, roll cage, tire, and aerodynamic requirements apply.

### WSSub4.2. Engine Location

The engine must remain in approximately the same location as the original engine, installed as close as practicable to the original OEM position.

### WSSub4.3. Firewall and Transmission Tunnel Clearance

Firewall and transmission tunnel modifications are permitted where necessary to accommodate the engine and transmission installation.

Modifications must be professionally fabricated and preserve structural integrity and complete separation between the drivetrain and driver compartment.

Modified areas must have no cracks, tears, exposed openings, open seams, or unwelded joints. Fabricated closure panels must be fully welded around their entire perimeter.

This permission does not authorize relocation of suspension or subframe mounting points beyond the express general Werk Sport exceptions.

### WSSub4.4. Exhaust and Wastegate Discharge

Exhaust systems are unrestricted provided they comply with the BEB General Vehicle Rules.

Wastegate discharge must return into the exhaust system or discharge downward through a securely installed outlet positioned clear of vehicle components.

Open discharge must not be directed toward suspension arms, bushings, tires, brake lines, fluid lines, wiring, the floor, firewall, engine compartment components, or any other part of the vehicle. Routing must prevent exhaust gases or heat from contacting components or entering the driver compartment.

### WSSub4.5. Engine Management, Ignition, and Wiring

Engine management is unrestricted. Factory ECU or DME tuning, chips, and aftermarket standalone ECUs are permitted. Ignition components are unrestricted.

Custom wiring is permitted where properly constructed, securely installed, protected from damage, and compliant with the BEB General Vehicle Rules.

### WSSub4.6. Engine Development

Internal engine modifications and engine bolt on components are unrestricted. Cylinder head and component changes are proposed to be unrestricted within the engine manufacturer classification and induction requirements. Mixed manufacturer major component classification remains unresolved.

Alternate exhaust manifolds, piping, intercoolers, turbochargers, and superchargers are permitted.

These permissions do not waive installation, structural, fuel, or safety requirements.

### WSSub4.7. Steering Columns and Steering Racks

Steering column and steering rack swaps or modifications are permitted only where professionally executed and safe for competition. Steering rack relocation must satisfy WS.6.4.

The steering column must retain the original OEM collapsible devices and their function. Modifications must not bypass, disable, or rigidly bridge those devices.

Shafts, joints, bearings, mounts, and connections must be correctly aligned, securely installed, and operate without binding or interference throughout the full steering range and suspension travel.

Poorly fabricated, misaligned, inadequately supported, or otherwise unsafe installations are prohibited. Safety is BEB's first priority. Creativity does not excuse poor execution. A vehicle with unsafe steering may not compete until corrected and accepted by BEB officials.

### WSSub4.8. Driveshafts

Driveshaft fabrication, shortening, lengthening, or other modification must be performed by a professional driveshaft specialist. The completed assembly must be balanced for its intended application.

Components necessary for correct support, alignment, articulation, and retention must be suitable for the installed drivetrain and remain functional. A custom engine or transmission interface must not omit the support or retention necessary to prevent driveshaft failure.

### WSSub4.9. Turbocharger Heat Protection

Turbochargers, turbine housings, exhaust manifolds, downpipes, and wastegate discharge pipes produce substantial heat. Fuel components, wiring, electronics, fluid lines, and other heat sensitive components must be positioned as far as practicable from these heat sources.

Where adequate separation cannot be achieved, exposed hoses and wiring must be enclosed in fire sleeves rated for the application. Other heat sensitive components must have suitable fire resistant enclosures or heat shields.

Turbocharger turbine housings must have securely installed turbo heat blankets suitable for the application. Protective sleeves, shields, and blankets do not make an otherwise hazardous installation acceptable.

### WSSub4.10. Intercoolers and Charge Cooling

Air to air and water to air intercoolers are permitted. Supercharger cooler cores, reservoirs, pots, and bowls are permitted.

All components, piping, and hoses must be securely mounted and supported to prevent loosening, movement, or detachment. As much piping as practicable must remain within the bodywork. This does not require routing through the driver compartment.

Distilled water is the only permitted fluid in any water to air intercooler or charge cooling circuit. Coolant, antifreeze, and additives are prohibited.

Charge cooling water lines within the driver compartment must use steel braided hose suitable for the operating pressure and temperature. Lines, fittings, and connections exposed to the driver must be separated from the driver by securely installed aluminum or steel shielding positioned to prevent hot water or steam from spraying the driver following a rupture.

Steel braiding alone does not satisfy the shielding requirement.

### WSSub4.11. Hazardous Installations

BEB may deny track access or remove a vehicle from competition if its installation, heat protection, or discharge routing presents a hazard. The vehicle may not compete or return to the track until corrected and accepted by BEB officials.

# Review Appendix. Decisions Before Publication

**This appendix is separate from the competition rules. It records remaining decisions for this review draft and is not an additional set of permissions.**

### R.1. WSSub3 and WSSub4

The four category definitions are established. Detailed other manufacturer engine development and installation rules have not yet been agreed to the same extent as WSSub1 and WSSub2. Their sections are proposed completions for review, including the adapted driveshaft wording and engine component allowances.

### R.2. Mixed Manufacturer Engines

Decide how to classify an engine combining major components from different manufacturers. Classifying by engine block was recommended but has not been adopted.

### R.3. Tires

Set sizes and compounds, measurement and enforcement methods, front and rear limits if different, and wet condition provisions for each subcategory. No numerical tire limit has been invented in this draft.

### R.4. Competition Weight

Confirm whether a maximum or minimum competition weight will apply and how driver and fuel are treated when weighing. The 4,000 pound maximum came from a supplied example accompanied by an instruction to establish BEB's own numbers; it is not treated as a finalized value here.

### R.5. Horsepower and Verification

Decide whether performance regulation will use tire restrictions alone or also regulated horsepower. Establish any power limit and verification procedure before applying the power based enforcement provisions. No dyno certification procedure has been added.

### R.6. Damper Adjustment

Confirm whether four adjustments per corner means four independent damping functions rather than four clicks or settings. The draft retains the original limit without silently adopting that interpretation.

### R.7. Identification

Assign mirror housing color, front and rear identification light colors, required illumination, and SUB1 through SUB4 markings.

### R.8. General Rulebook Compatibility

Before publication, check this complete class document against the current BEB General Vehicle Rules and Roll Cage Rules. In particular, reconcile fuel permission for E85, glazing thickness and installation, interior equipment, fire protection, cooling, and steering requirements. This draft does not represent a completed audit against those separate documents.

### R.9. Fabrication and Aerodynamic Boundaries

The exact approved WS-A aerodynamic text is retained. It overrides earlier conflicting permissions for splitter tunnels and fences, sets the convertible wing reference at the OEM windshield frame, and requires replacement front bumper crash protection where the OEM reinforcement is removed or modified.

Front shock towers remain unmodified. Radiator location remains governed by the shared chassis rule. The complete donor rear suspension conversion is an express exception to original mounting point requirements. No broader rear tube frame conversion is authorized.

The fender rule retains the earlier maximum of one vent or louver assembly above the tire per side; WS-A.11 permits fender vents generally. Confirm whether that specific count should remain. The existing common tire spat permission remains separate from canards, while any device functioning as a canard must meet WS-A.6.