BAVARIAN ENDURANCE BATTLE

Werk Sport Class Rules

COMPETITION RULES

November 6, 2026

Subcategory	BMW chassis with
WSSub1	Naturally aspirated BMW engine not originally offered for the entered chassis
WSSub2	Turbocharged or supercharged BMW engine
WSSub3	Naturally aspirated engine from another manufacturer
WSSub4	Turbocharged or supercharged engine from another manufacturer

Mandatory companion documents: BEB General Vehicle Rules and Roll Cage Rules.

Tire specifications and size restrictions will be announced separately.

Contents

WS. General Werk Sport Rules 3

WS.1. Spirit of the Class . . . 3

WS.2. Class Structure and Mandatory Compliance . . . 3

WS.3. Vehicle Eligibility and Assignment . . . 4

WS.4. Bodywork and Exterior Equipment . . . 4

WS.5. Chassis, Subframes, and Structural Fabrication . . . 6

WS.6. Suspension, Steering Rack, Wheels, and Brakes . . . 8

WS.7. Engine Management, Fuel, Exhaust, and Drivetrain . . . 9

WS.8. Fluid Lines, Fuel Shielding, and Oil Pans . . . 10

WS.9. Engine Power and Event Conduct . . . 11

WS.10. Tire Requirements . . . 11

WS.11. Werk Sport Identification . . . 11

WS-A. AERODYNAMICS AND FRONT STRUCTURE 12

WSSub1. BMW Chassis with a Naturally Aspirated BMW Engine Swap 16

WSSub2. BMW Chassis with a Turbocharged or Supercharged BMW Engine 17

WSSub3. BMW Chassis with a Naturally Aspirated Engine from Another Manufacturer 20

WSSub4. BMW Chassis with a Turbocharged or Supercharged Engine from Another Manufacturer 21

Read the general WS rules, the complete WS-A aerodynamic section, and your applicable WSSub section.

WS. General Werk Sport Rules

WS.1. Spirit of the Class

Werk Sport celebrates creativity, craftsmanship, and beautifully built race cars. Its four subcategories give teams the freedom to explore engine swaps and develop distinctive machines for endurance competition.

That freedom must respect the conditions of a shared racetrack. Werk Sport vehicles will compete alongside slower classes, and substantial differences in speed can create dangerous closing rates. Both faster and slower drivers need time to recognize traffic, anticipate one another, and make safe decisions.

BEB will establish tire size restrictions for the Werk Sport subcategories to help contain the performance of exceptionally powerful builds and manage speed differences between classes. These restrictions are part of the class's approach to shared track safety, rather than an attempt to achieve identical performance.

Tire restrictions do not replace responsible driving. Every team must prepare and operate its vehicle with respect for the safety of all participants throughout the endurance race.

WS.2. Class Structure and Mandatory Compliance

WS.2.1. Four Subcategories

Werk Sport uses BMW production chassis and is divided into four subcategories:

1. WSSub1: BMW chassis with a naturally aspirated BMW engine swapped from a different BMW chassis application. The installed engine must not be an engine originally offered by BMW for the entered vehicle's chassis. Replacing an engine with another of its original type does not qualify.
2. WSSub2: BMW chassis with a turbocharged or supercharged BMW engine.
3. WSSub3: BMW chassis with a naturally aspirated engine from another manufacturer.
4. WSSub4: BMW chassis with a turbocharged or supercharged engine from another manufacturer.

Teams must read the general WS requirements, the shared WS-A aerodynamic section, and their applicable WSSub section.

WS.2.2. Mandatory Safety and Roll Cage Compliance

All vehicles in all four subcategories must comply with the BEB General Vehicle Rules, Roll Cage Rules, and applicable safety and conduct requirements.

Structural modification and engine development permissions do not waive or replace safety requirements. A vehicle that fails safety requirements does not become eligible merely by entering Werk Sport.

Failure to comply may result in loss of track time or removal from the event. BEB may deny track access or remove a vehicle presenting an unsafe installation until corrected and accepted by BEB officials.

WS.2.3. Express Class Exceptions

The limited tubular front structure permitted by WS-A.3 is an express Werk Sport allowance for a production chassis vehicle; it does not authorize a full tube chassis vehicle.

The rear door exception in WS.4.4 and the open wastegate outlet location exceptions in WSSub2.4 and WSSub4.4 apply only to their stated subjects. All other applicable general safety requirements remain mandatory.

WS.3. Vehicle Eligibility and Assignment

WS.3.1. Eligible Vehicles

BMW production vehicles of any model year originally offered for sale in the United States market are eligible, subject to the applicable subcategory and general requirements.

Eligible body configurations include sedans, coupes, convertibles, and Tourings. BMW M model vehicles and BMW M engines are permitted.

The BMW X1 is the only permitted SUV. All other SUVs are prohibited.

Vehicles must retain their recognizable BMW production body identity. Chassis, frame, body, and subframe modifications are permitted only within the express Werk Sport allowances.

WS.3.2. Vehicles Exceeding Other Class Allowances

Vehicles whose configuration or modifications exceed the allowances of the Vintage, Dreier, Touring, Geschäftsklasse, or Zenith Class may compete in the appropriate Werk Sport subcategory, provided they satisfy Werk Sport eligibility, technical, and safety requirements.

Vehicles must meet their entered subcategory's specific eligibility requirements. WSSub1 requires a BMW engine swap. Original factory turbocharged or supercharged BMW engine applications are eligible in WSSub2 without a swap.

A naturally aspirated BMW retaining its original engine application and remaining within its other applicable class allowances belongs in that class.

WS.3.3. Assignment by Engine and Induction

Subcategory assignment follows the installed engine and induction configuration. Turbocharging, supercharging, or both places a vehicle in the applicable forced induction subcategory. WSSub1 requires a naturally aspirated BMW engine not originally offered by BMW for the entered vehicle's chassis.

WS.3.4. Maximum Competition Weight

Maximum competition weight is 4,000 pounds.

WS.4. Bodywork and Exterior Equipment

WS.4.1. Roofline and Pillars

Nonconvertible vehicles must retain their original production roofline and pillars.

Convertible vehicles must have a securely installed hardtop. Hardtop design and materials are otherwise unrestricted, subject to the BEB General Vehicle Rules.

A hardtop does not replace or reduce any roll cage requirement, including the requirements applicable to convertibles.

WS.4.2. Fenders, Tire Coverage, and Openings

Fenders, quarter panels, and permitted extensions must completely cover the entire tire tread when viewed directly from above.

When viewed from the side, fender openings must retain a shape and height similar to the original OEM configuration.

The lower portion of a fender behind a wheel may be cut and formed inward to relieve wheel well pressure.

Replacement fenders, flares, wide body additions, and their materials are unrestricted where they preserve these requirements. They must not function as aerodynamic devices beyond the allowances of WS-A.

WS.4.3. Tire Clearance and Safe Edges

Panels, vents, flares, and surfaces surrounding a tire must be free of sharp edges, exposed points, or features capable of cutting, slashing, or puncturing the tire.

Adequate clearance must be maintained throughout the full range of steering movement and suspension travel, including compression and rebound.

WS.4.4. Doors

Doors must retain their original production shape but are otherwise unrestricted within the applicable BEB safety requirements.

Driver and front passenger doors must open from both inside and outside the vehicle. Rear doors on four door vehicles may remain inoperative. This is an express Werk Sport exception to the general requirement that every door open from outside.

Rear flares may extend onto doors provided they do not prevent either front door from opening or interfere with driver or passenger egress. Other applicable requirements for secure door closure and disabled locking mechanisms remain mandatory.

WS.4.5. Mirrors

Three functional mirrors are required: one exterior mirror on each side and one interior mirror. Mirror design and construction are unrestricted.

Mirrors must be securely installed and provide usable rearward visibility. Reflective surfaces must remain unobstructed. Exterior mirror housings must be red as required by WS.11.4.

WS.4.6. Bumpers and Tow Points

Front and rear bumper design and materials are unrestricted within the aerodynamic allowances of WS-A. Front bumper reinforcement must meet WS-A.3. Retaining the OEM rear crash beam and its supporting structure is strongly recommended.

Each vehicle must have a towing attachment at both front and rear, using tow hooks, straps, or equivalent devices capable of towing or moving the vehicle.

Tow devices must attach securely to suitable structural mounting points and must not protrude in a manner that could hook, snag, or damage another vehicle during incidental contact.

WS.4.7. Tire Spats

Tire spats may be mounted at the rear edge of the front bumper, directly ahead of the front tires, solely to direct airflow around them. They must follow the bumper or fender shape.

Viewed directly from the front with the wheels straight ahead, a spat must not extend outward beyond the outermost edge of the corresponding tire or wheel. A component functioning as a canard remains subject to WS-A.6.

WS.4.8. Side Skirt Position and Attachment

The majority of each side skirt must remain below the bottom edge of the doors. Skirts must not extend outward beyond the outermost edges of the corresponding front and rear tires.

Suitable mechanical fasteners or mounting structures are required. Double sided tape alone is not adequate. Movement and ground sealing restrictions are governed by WS-A.10.

WS.4.9. Hood and Trunk

Hood shape, design, and ventilation may be modified, provided the hood remains substantially similar to the original vehicle's hood in overall fitment and configuration. Vents and openings may be added, modified, or removed.

Replacement trunk lids and materials are unrestricted provided the original OEM exterior shape is maintained.

WS.4.10. Windshield and Windows

Glass may be replaced with motorsport suitable polycarbonate, including Lexan, Makrolon, or equivalent materials.

Replacement polycarbonate windshields must be at least 1/4 inch thick. All other replacement polycarbonate windows must be at least 1/8 inch thick.

All glazing must be securely installed and comply with the BEB General Vehicle Rules. Driver and front passenger windows must remain fully lowered during competition; removal is preferred.

WS.4.11. Sunroofs, Cowl, and Wipers

Sunroofs may be retained only where not made of glass. Assemblies may be removed and openings covered with properly constructed aluminum, carbon fiber, or steel panels. Panels must fully cover the openings and be securely attached.

Alternate windshield cowl materials are permitted provided the original OEM shape is maintained. Wiper modifications are unrestricted within the BEB General Vehicle Rules.

Custom panels creating a smooth blend between the hood and windshield are prohibited.

WS.5. Chassis, Subframes, and Structural Fabrication

WS.5.1. Original Structure and Permitted Exceptions

Except where expressly permitted, major modifications to the chassis, frame, unibody, floor, or firewall are prohibited.

Localized changes are permitted for component clearance, strengthening, bracing, and repair. They must be limited to their stated purpose and provide no unrelated performance benefit.

Engine and drivetrain installation allowances, the permitted complete rear suspension conversion, and the front structure allowance in WS-A.3 are express exceptions. Full tube frame conversion of the remaining production chassis is not authorized.

Nonessential body attachments, interior supports, and trim may be removed for weight reduction without compromising structural integrity. Major structural components must not be lightened or compromised.

WS.5.2. Reinforcement and Repair

Material may be added to reinforce known weak areas, strengthen mounting areas, and repair crash damage. Seam welding is permitted.

Reinforcement and repair must preserve required suspension and subframe mounting point locations except for an expressly permitted conversion.

WS.5.3. Wheel Well Clearance

Localized fabricated changes within wheel wells and tubs are permitted solely for tire clearance, suspension arm clearance, and suspension travel. They must not provide unrelated performance benefits or relocate suspension mounting points.

WS.5.4. Radiator Supports and Cooling Location

Radiator supports may be replaced with fabricated structures for fitment or repair. The radiator must remain in its general factory location and receive cooling air through the same general area used by the original vehicle.

Bumper and cooling openings may be partially blocked only where sufficient openings remain to supply the airflow needed to cool the engine and associated systems. Front fabrication permission in WS-A.3 does not independently authorize radiator relocation.

WS.5.5. Suspension and Subframe Mounting Points

Suspension mounting points on the body and subframes must retain their original OEM locations, geometry, and mounting angles. Reinforcement is permitted without altering the points themselves.

Subframes must retain their original mounting locations on the body and must not reposition suspension points relative to the vehicle.

The complete rear suspension conversion in WS.5.6 and steering rack relocation in WS.6.3 are specific exceptions limited to their stated purposes.

WS.5.6. Original Solid or Live Rear Axle Vehicles

Vehicles originally equipped with a solid or live rear axle may convert to independent rear suspension using a complete donor subframe assembly from a mass produced road going vehicle.

Assemblies from other manufacturers, including BMW M model assemblies and components, are permitted. Donor suspension mounting point locations and geometry must be retained. Race only or aftermarket suspension geometry is prohibited under this exception.

Body attachments necessary to mount the complete donor assembly are permitted. Individual suspension mounting points within the assembly must not be relocated. Other suspension requirements apply as though the donor suspension were originally installed.

WS.5.7. Modified, Alternate, and Tubular Subframes

Front and rear subframes may be modified to accommodate engine and drivetrain swaps, including oil pan clearance and installation of a different differential.

Similar OEM subframes from the same manufacturer may be installed where required mounting point locations are preserved. Aftermarket and fabricated tubular subframes are permitted to facilitate engine swaps while retaining all required OEM suspension and control arm mounting point locations, geometry, and angles.

Body attachment locations must remain unchanged except for WS.5.6.

WS.5.8. Subframe Clearance Reinforcement

Every cut, notch, or removed subframe section must be reinforced to preserve rigidity and structural integrity. Clearance pockets must be boxed with a properly fabricated recessed structure, reinforced with additional material, or both.

Construction must prevent excessive flex, fatigue, cracking, failure, or breakage during sustained endurance use. All fabrication and welding must be professionally executed.

WS.5.9. Roll Cage Extensions and Firewall Sealing

Structural tubes connecting the roll cage to the permitted front structure or nose are allowed. Materials, connections, and welding must comply with the BEB Roll Cage Rules.

The firewall must remain a continuous, fully sealed barrier between the engine and driver compartments. Tube penetrations must be completely sealed with securely installed fire resistant materials and methods compliant with the BEB General Vehicle Rules.

No gaps, open seams, or exposed openings are permitted around penetrations. Separate engine installation permissions appear in each applicable subcategory section.

WS.6. Suspension, Steering Rack, Wheels, and Brakes

WS.6.1. Suspension Components

Control arms, uprights, knuckles, hubs, trailing arms, and related components may be modified or replaced for camber or caster adjustment, permitted strength improvements, or repair to original condition and strength.

Replacement uprights, knuckles, and arms installing directly without modification of the required mounting interfaces are permitted. Aftermarket arms must use the original attachment points on the chassis and applicable knuckle, hub carrier, or upright.

Hubs may be replaced with aftermarket or other suitable components for strength. These permissions do not authorize relocation of fixed suspension mounting points.

WS.6.2. Bushings, Ball Joints, and Correction Kits

Bushings, ball joints, and suspension geometry correction kits are unrestricted within the fixed mounting point requirements. Adjustment through permitted components does not authorize cutting, slotting, drilling, or relocating fixed body or subframe mounting points.

WS.6.3. Steering Rack Relocation

Steering racks may be relocated where necessary for engine clearance. This does not authorize relocation of suspension or control arm mounting points.

Racks, mounts, shafts, joints, and tie rods must be securely installed and operate without binding or interference throughout the full steering range and suspension travel.

Extreme tie rod or joint angles capable of causing binding, accelerated wear, fatigue, or breakage are prohibited. All installations must withstand sustained endurance racing loads.

WS.6.4. Wheels

Wheel dimensions and designs are unrestricted except for the applicable tire restrictions, coverage, clearance, mounting, and safety requirements.

Wheels must be aluminum alloy or steel. Magnesium and carbon fiber wheels are prohibited.

WS.6.5. Brakes

Brake size and piston count are unrestricted. Systems must be suitable for the application, securely and properly installed, and compliant with the BEB General Vehicle Rules.

WS.7. Engine Management, Fuel, Exhaust, and Drivetrain

WS.7.1. Engine Location

Engine swaps are permitted within the engine manufacturer and induction requirements of the entered subcategory. Engines must remain in approximately the same location as the original engine, as close as practicable to the OEM position.

WS.7.2. Engine Management and Ignition

Engine management systems and ignition components are unrestricted for naturally aspirated and forced induction engines. Components and wiring must be securely installed and comply with the BEB General Vehicle Rules.

Engine internal development permissions are stated in the applicable subcategory section.

WS.7.3. Permitted Fuel

Only commercially available pump gasoline rated 91 AKI is permitted in all four Werk Sport subcategories.

E85, other alternate fuels, race fuel, octane boosters, separately added additives, nitrous oxide, nitromethane, and other supplemental power increasing chemicals are prohibited.

All engines, including turbocharged and supercharged engines, must be tuned for the permitted fuel.

WS.7.4. Exhaust

Exhaust systems are unrestricted provided they comply with the BEB General Vehicle Rules. Turbocharger wastegate discharge requirements appear directly in the forced induction subcategory sections.

WS.7.5. Driven Wheels

The original driven wheel configuration must be retained unless BMW offered the same vehicle in multiple drivetrain configurations.

Conversion between those factory configurations is permitted only using the applicable OEM BMW components. For example, an AWD vehicle may convert to RWD where BMW offered the corresponding RWD configuration and the appropriate OEM parts accomplish the conversion.

This exception does not authorize a custom driven wheel configuration.

WS.7.6. Transmissions

Transmission swaps and transmission ratios are unrestricted. Installations must meet the applicable structural, mounting, and safety requirements.

WS.7.7. Driveshaft Construction and Installation

OEM, aftermarket, custom fabricated, and adapted driveshafts are permitted. Retaining an OEM BMW driveshaft is not mandatory.

Fabrication, shortening, lengthening, and balancing must be performed by a professional driveshaft specialist.

The completed installation must preserve the safety functions of the original drivetrain arrangement, including suitable support, articulation, retention, and protection against separation.

Driveshaft length, geometry, joint operating angles, alignment, and balance must be appropriate for the installed drivetrain, full operating range, and anticipated rotational speeds. Binding, interference, unsafe joint angles, and excessive vibration are prohibited.

Properly designed and securely mounted driveshaft safety loops are strongly recommended. Loops must be positioned and constructed to restrain a failed or disconnected driveshaft, preventing it from entering the driver compartment, dropping onto the track, or creating a hazard to other vehicles.

Loops must provide adequate clearance for normal driveshaft movement without contact or interference.

WS.8. Fluid Lines, Fuel Shielding, and Oil Pans

WS.8.1. Fluid Lines

All fluid carrying lines must be securely routed and supported to prevent abrasion. Lines must be suitable for the intended fluid and rated for operating pressure and temperature.

Protective sleeves or equivalent abrasion protection are recommended where fasteners, clamps, cable ties, or surrounding surfaces could rub against a line.

WS.8.2. Fuel Component Shielding

Fuel fittings, tank covers, filler assemblies, and pump access openings must be separated from the driver compartment by a securely installed protective bulkhead or enclosure unless already isolated by a suitable firewall or trunk bulkhead.

Steel or braided stainless steel fuel lines do not require an additional covering solely under this provision. This does not waive shielding requirements for their fittings or associated components.

WS.8.3. Oil Pan Modifications

Oil pans may be modified for subframe clearance. Modifications must be professionally fabricated. Modified seams, joints, and closure panels must be completely welded and oil tight, with no evidence of leakage.

Silicone, sealants, JB Weld, epoxy, and similar compounds must not join, patch, repair, or seal a fabricated modification. Manufacturer specified gaskets or sealants at the normal mounting flange remain permitted.

A vehicle with a leaking or improperly modified pan may not compete or return to the track until corrected and accepted by BEB officials.

WS.9. Engine Power and Event Conduct

Engine horsepower and boost levels are unrestricted, subject to the entered subcategory's induction, technical, and safety requirements. BEB will regulate performance through tire size restrictions, which will be announced later.

All Werk Sport vehicles and drivers are subject to the incident limits, penalties, and removal provisions established in the BEB General Event/Race Rules. Unrestricted power does not waive driver conduct or safety requirements.

WS.10. Tire Requirements

Tire specifications and size restrictions for all four Werk Sport subcategories will be announced later. Wheel permissions do not waive tire coverage, clearance, or safety requirements.

WS.11. Werk Sport Identification

WS.11.1. Front Lights

All Werk Sport vehicles must have headlights emitting white light. If the original headlights are removed or absent, at least two white lights must be installed in the original headlight locations.

WS.11.2. Rear Identification Light

A dedicated white pod light must be securely and rigidly mounted at the rear, facing rearward and clearly visible to following drivers. It must maintain its position and orientation throughout competition and be aimed to avoid dazzling drivers.

The pod does not replace functioning brake lights or required red rear running lights. Standard taillights do not replace the required white pod.

WS.11.3. Continuous Illumination

The white front lights and rear white pod must remain illuminated throughout the race. Required red rear running lights must also remain illuminated, and brake lights must operate when braking.

WS.11.4. Mirror Housings

Exterior mirror housings must be red. Paint, securely applied wrap, Plasti Dip, or another safe coloring method is permitted.

Reflective surfaces must remain unobstructed and functional. Liveries and advertising must not obscure or alter the red identification.

WS.11.5. Mandatory BEB Decals and Banners

Any windshield banner, class identification sticker, or BEB class sponsor sticker provided or mandated by BEB for the event must be applied to the vehicle's exterior in the location designated by BEB.

Required decals and banners must remain securely attached, clearly visible, and unobstructed throughout the event.

WS-A. AERODYNAMICS AND FRONT STRUCTURE

WS-A.1. General Allowances

OEM, aftermarket, and custom-fabricated aerodynamic components are permitted within the allowances and dimensional limits of this section. Materials and manufacturers are unrestricted, provided all components meet the construction and mounting requirements below.

Aerodynamic devices not expressly permitted by this section require written BEB approval before competition.

Permission to install an aerodynamic component does not authorize structural modifications beyond those expressly permitted by the Werk Sport rules.

WS-A.2. Static Aerodynamics

All aerodynamic components must remain fixed in position while the vehicle is on track.

Powered, cockpit-adjustable, self-adjusting, and intentionally flexible aerodynamic systems are prohibited. OEM active aerodynamic systems must be removed or securely fixed in a compliant position.

Manual adjustment while the vehicle is stationary in the pits is permitted. All adjustments must be securely locked before returning to the track.

WS-A.3. Front Structure and Fabrication

The OEM front shock towers must remain unmodified and in their original locations. Front suspension mounting points must remain in their OEM locations.

Forward of the front shock towers, the front structure may be cut, modified, or replaced to accommodate aerodynamic components, cooling systems, ducting, and their fabricated supports. A fabricated tubular front structure is permitted.

Custom splitter mounts, air-dam supports, bodywork supports, ducting mounts, and removable front assemblies are permitted.

All replacement structures must be professionally fabricated and securely attached to sound portions of the chassis. Cutting must not extend into the shock towers or compromise their supporting structure.

The completed nose must retain the recognizable OEM appearance, basic profile, and styling of the vehicle’s BMW model. OEM and replacement exterior panels are permitted. Splitters, air dams, canards, cooling openings, and fender modifications permitted by this section may alter the exterior within their respective limits.

If the OEM front bumper reinforcement is removed or modified, a securely mounted replacement bumper structure providing equivalent crash protection must be installed. Aerodynamic supports alone do not satisfy this requirement. BEB may require supporting fabrication details and may reject an inadequately constructed replacement.

WS-A.4. Front Air Dam

An OEM, aftermarket, or fabricated front air dam is permitted.

The air dam must follow the front body outline and remain vertical within a tolerance of 5 degrees.

Separate front wings, stacked front aerodynamic elements, and independent front airfoils are prohibited. Canards meeting WS-A.6 are permitted.

WS-A.5. Front Splitter and Undertray

One flat, horizontal front splitter is permitted.

The splitter may project no more than 7 inches forward of its intersection with the front fascia or air dam. Forward projection must be measured horizontally at the corresponding location across the nose.

The splitter and associated front undertray may extend rearward no farther than the driver-compartment front bulkhead/firewall.

A continuous strip of fascia or air-dam material at least 1 inch high must remain immediately above the splitter along its intersection with the fascia or air dam, including beneath air-intake openings.

The splitter must not incorporate additional stacked planes, separate airfoils, or shaped venturi tunnels. Structural reinforcement and securely mounted support rods are permitted.

WS-A.6. Front Canards

A maximum of two canards or dive planes per side is permitted, confined to the front bumper area. Molded-in and separately attached canards count toward the same limit.

Canards may not extend more than 6 inches outward beyond the vertical plane through the widest part of the vehicle’s body on the corresponding side. No separate limit applies to individual canard length or surface area.

All canards must remain fixed while on track, be securely mounted, and have finished edges and corners. They must not obstruct required lighting, tow points, or safety equipment.

WS-A.7. Rear Wing or Spoiler

One single-element rear wing or one rear spoiler is permitted. A Gurney flap is permitted and does not count as a second element.

The complete assembly, including endplates and Gurney flap, must comply with the following limits:

Measurement	Maximum
Height above the OEM roofline	8 inches
Overall width	OEM body width, excluding add-on fender flares, mirrors, door handles, and aerodynamic devices
Area of each endplate	144 square inches
Rearward projection beyond the OEM rear bodywork profile	12 inches

For convertibles, the height reference is the top of the OEM windshield frame in its original location.

Height is measured vertically. Rearward projection is measured horizontally, excluding aerodynamic additions from the bodywork reference.

Multi-element rear wings and separate wings mounted over the hood, roof, or middle of the vehicle are prohibited.

Wing supports must transfer loads into suitable reinforced mounting locations. Unsupported exterior panel skins alone are not acceptable mounting structures.

WS-A.8. Rear Diffuser

An OEM, aftermarket, or fabricated rear diffuser is permitted.

The diffuser must remain entirely rearward of the rear axle centerline and may extend no more than 6 inches beyond the rear bumper, measured horizontally.

Diffuser installation does not authorize removal or modification of structural members, suspension mounting points, or bumper reinforcement unless separately permitted by the Werk Sport rules.

The diffuser must be securely mounted and must not interfere with the tires, suspension, exhaust system, or required safety equipment.

WS-A.9. Underbody Panels

The front splitter/undertray and rear diffuser permitted above are allowed.

An added continuous aerodynamic floor connecting the front undertray to the rear diffuser is prohibited. Fabricated venturi tunnels and underbody suction fans are prohibited.

OEM underbody panels may remain in their original locations.

Localized heat shields, cooling shields, and protective panels are permitted provided they do not form an otherwise prohibited aerodynamic floor or tunnel.

WS-A.10. Side Skirts

Fixed side skirts attached along the rocker areas are permitted.

Sliding, sprung, actively controlled, or intentionally ground-sealing skirts are prohibited. Side skirts must not be designed to maintain contact with the track surface.

WS-A.11. Cooling Openings, Vents, and Fenders

Hood vents, louvers, fender vents, and cooling ducts are permitted.

Cooling openings may be fabricated into the front fascia, hood, and fenders, provided required structural members, shock towers, and suspension mounting points remain compliant with the Werk Sport rules.

Bolt-on, replacement, and fabricated fender flares are permitted. Fender modifications must not create additional wings, canards, or aerodynamic tunnels outside the allowances of this section.

Cooling ducts and hoses must be securely mounted and must not interfere with steering, suspension travel, tires, driver escape, or safety equipment.

WS-A.12. Construction, Mounting, and Condition

All aerodynamic components and supporting structures must be suitable for sustained endurance-racing use.

Mountings must withstand aerodynamic loads, vibration, and normal racing operation. Fasteners, brackets, braces, and attachment points must remain secure.

Exposed edges and corners must be finished to avoid sharp projections.

Components must not obstruct:

- Driver entry or emergency exit.
- Required lights or identification markings.
- Tow points or emergency access.
- Steering or suspension movement.
- Required safety equipment.

Loose, damaged, dragging, or partially detached aerodynamic components must be repaired or removed before the vehicle returns to the track.

BEB may require reinforcement, repair, removal, or further inspection of any component or supporting structure found unsuitable for competition.

WSSub1. BMW Chassis with a Naturally Aspirated BMW Engine Swap

WSSub1.1. Eligible Vehicles and Engines

WSSub1 accepts eligible BMW chassis fitted with a naturally aspirated BMW engine not originally offered by BMW for the entered chassis. The engine must be swapped from a different BMW chassis application. Replacing an engine with another of its original type does not qualify. BMW M engines are permitted.

An engine swap is required.

Turbocharging and supercharging are prohibited in WSSub1.

WSSub1.2. Engine Location

The engine must remain in approximately the same location as the original engine, installed as close as practicable to the original OEM position.

WSSub1.3. Firewall and Transmission Tunnel Clearance

Firewall and transmission tunnel modifications are permitted where necessary to accommodate the engine and transmission installation.

Modifications must be professionally fabricated and preserve structural integrity and complete separation between the drivetrain and driver compartment.

Modified areas must have no cracks, tears, exposed openings, open seams, or unwelded joints. Fabricated closure panels must be fully welded around their entire perimeter.

This permission does not authorize relocation of suspension or subframe mounting points beyond the express general Werk Sport exceptions.

WSSub1.4. Exhaust

Exhaust systems are unrestricted provided they comply with the BEB General Vehicle Rules.

WSSub1.5. Engine Management, Ignition, and Wiring

Engine management is unrestricted. Factory ECU or DME tuning, chips, and aftermarket standalone ECUs are permitted. Ignition components are unrestricted.

Custom wiring is permitted where properly constructed, securely installed, protected from damage, and compliant with the BEB General Vehicle Rules.

WSSub1.6. Engine Development and BMW Component Combinations

Engine modifications are unrestricted within WSSub1's naturally aspirated BMW engine swap requirement.

Any combination of OEM BMW engine components from any BMW production application is permitted. This includes combinations of engine blocks, cylinder heads, intake manifolds, and other BMW engine components, regardless of whether BMW originally offered them together.

These combinations must be professionally assembled and installed and comply with all applicable Werk Sport safety requirements.

WSSub1.7. Steering Columns and Steering Racks

Steering column and steering rack swaps or modifications are permitted only where professionally executed and safe for competition. Steering rack relocation must satisfy WS.6.3.

The steering column must retain the original OEM collapsible devices and their function. Modifications must not bypass, disable, or rigidly bridge those devices.

Shafts, joints, bearings, mounts, and connections must be correctly aligned, securely installed, and operate without binding or interference throughout the full steering range and suspension travel.

Poorly fabricated, misaligned, inadequately supported, or otherwise unsafe installations are prohibited. Safety is BEB's first priority. Creativity does not excuse poor execution. A vehicle with unsafe steering may not compete until corrected and accepted by BEB officials.

WSSub2. BMW Chassis with a Turbocharged or Supercharged BMW Engine

WSSub2.1. Eligible Vehicles and Engines

WSSub2 accepts eligible BMW sedans, coupes, convertibles, Tourings, and BMW X1 vehicles using any of the following:

1. An original factory supplied turbocharged or supercharged BMW engine.
2. A swapped BMW engine equipped with turbocharging, supercharging, or both.
3. A BMW production engine fitted with a custom or aftermarket turbocharging or supercharging system.

BMW M engines are permitted. An engine swap is not required for factory forced induction applications.

Turbochargers and superchargers of any type are permitted. Factory systems may be retained, modified, or replaced. All applicable installation, heat protection, charge cooling, fuel, structural, tire, aerodynamic, and safety requirements remain mandatory.

WSSub2.2. Engine Location

The engine must remain in approximately the same location as the original engine, installed as close as practicable to the original OEM position.

WSSub2.3. Firewall and Transmission Tunnel Clearance

Firewall and transmission tunnel modifications are permitted where necessary to accommodate the engine and transmission installation.

Modifications must be professionally fabricated and preserve structural integrity and complete separation between the drivetrain and driver compartment.

Modified areas must have no cracks, tears, exposed openings, open seams, or unwelded joints. Fabricated closure panels must be fully welded around their entire perimeter.

This permission does not authorize relocation of suspension or subframe mounting points beyond the express general Werk Sport exceptions.

WSSub2.4. Exhaust and Wastegate Discharge

Exhaust systems are unrestricted provided they comply with the BEB General Vehicle Rules, except for the specific wastegate outlet location allowance below.

Wastegate discharge may return into the exhaust system or discharge downward toward the track surface through a securely installed outlet.

Open wastegate dumps are exempt from the general exhaust outlet location requirements, provided discharge is not directed toward tires, brake lines, fuel components, wiring, suspension components, bushings, the vehicle floor, firewall, or other heat sensitive or safety critical components.

Discharge must not enter the driver compartment. Firewall sealing and applicable heat protection requirements remain mandatory.

WSSub2.5. Engine Management, Ignition, and Wiring

Engine management is unrestricted. Factory ECU or DME tuning, chips, and aftermarket standalone ECUs are permitted. Ignition components are unrestricted.

Custom wiring is permitted where properly constructed, securely installed, protected from damage, and compliant with the BEB General Vehicle Rules.

WSSub2.6. Engine Development

Internal engine modifications and engine bolt on components are unrestricted. Cylinder head swaps and combinations of components from different BMW engines are permitted.

Alternate exhaust manifolds, piping, intercoolers, turbochargers, and superchargers are permitted.

These permissions do not waive installation, structural, fuel, or safety requirements.

WSSub2.7. Steering Columns and Steering Racks

Steering column and steering rack swaps or modifications are permitted only where professionally executed and safe for competition. Steering rack relocation must satisfy WS.6.3.

The steering column must retain the original OEM collapsible devices and their function. Modifications must not bypass, disable, or rigidly bridge those devices.

Shafts, joints, bearings, mounts, and connections must be correctly aligned, securely installed, and operate without binding or interference throughout the full steering range and suspension travel.

Poorly fabricated, misaligned, inadequately supported, or otherwise unsafe installations are prohibited. Safety is BEB's first priority. Creativity does not excuse poor execution. A vehicle with unsafe steering may not compete until corrected and accepted by BEB officials.

WSSub2.8. Turbocharger Heat Protection

Turbochargers, turbine housings, exhaust manifolds, downpipes, and wastegate discharge pipes produce substantial heat. Fuel components, wiring, electronics, fluid lines, and other heat sensitive components must be positioned as far as practicable from these heat sources.

Where adequate separation cannot be achieved, exposed hoses and wiring must be enclosed in fire sleeves rated for the application. Other heat sensitive components must have suitable fire resistant enclosures or heat shields.

Turbocharger turbine housings must have securely installed turbo heat blankets suitable for the application. Protective sleeves, shields, and blankets do not make an otherwise hazardous installation acceptable.

WSSub2.9. Intercoolers and Charge Cooling

Air to air and water to air intercoolers are permitted. Supercharger cooler cores, reservoirs, pots, and bowls are permitted.

Water to air intercoolers and associated cooling components may be installed remotely anywhere within the vehicle, including the driver compartment, provided they are securely mounted and comply with the protection requirements below.

All components, piping, and hoses must be securely mounted and supported against loosening, movement, or detachment. As much piping as practicable must remain within the bodywork. This does not require routing through the driver compartment.

Distilled water is the only permitted fluid in any water to air intercooler or charge cooling circuit. Coolant, antifreeze, and additives are prohibited.

Charge cooling water lines within the driver compartment must use steel braided hose rated for the system's fluid, operating pressure, and temperature. Cabin lines, including all fittings and connections, must be fully enclosed within an aluminum or steel protective tunnel separating them from the driver.

Remotely installed reservoirs, cooler assemblies, and other components exposed to the driver must have suitable aluminum or steel enclosures to prevent hot water or steam from reaching the driver following a leak or rupture. Steel braiding alone does not satisfy the enclosure requirement.

No installation may obstruct driver entry, emergency exit, visibility, or required safety equipment.

WSSub2.10. Hazardous Installations

BEB may deny track access or remove a vehicle from competition if its installation, heat protection, or discharge routing presents a hazard. The vehicle may not compete or return to the track until corrected and accepted by BEB officials.

WSSub3. BMW Chassis with a Naturally Aspirated Engine from Another Manufacturer

WSSub3.1. Eligible Vehicles and Engines

This subcategory accepts eligible BMW sedans, coupes, convertibles, Tourings, and BMW X1 vehicles equipped with an engine from another manufacturer operating in naturally aspirated form. Turbocharging and supercharging are prohibited in this subcategory.

All general Werk Sport eligibility, safety, roll cage, tire, and aerodynamic requirements apply.

WSSub3.2. Engine Location

The engine must remain in approximately the same location as the original engine, installed as close as practicable to the original OEM position.

WSSub3.3. Firewall and Transmission Tunnel Clearance

Firewall and transmission tunnel modifications are permitted where necessary to accommodate the engine and transmission installation.

Modifications must be professionally fabricated and preserve structural integrity and complete separation between the drivetrain and driver compartment.

Modified areas must have no cracks, tears, exposed openings, open seams, or unwelded joints. Fabricated closure panels must be fully welded around their entire perimeter.

This permission does not authorize relocation of suspension or subframe mounting points beyond the express general Werk Sport exceptions.

WSSub3.4. Exhaust

Exhaust systems are unrestricted provided they comply with the BEB General Vehicle Rules.

WSSub3.5. Engine Management, Ignition, and Wiring

Engine management is unrestricted. Factory ECU or DME tuning, chips, and aftermarket standalone ECUs are permitted. Ignition components are unrestricted.

Custom wiring is permitted where properly constructed, securely installed, protected from damage, and compliant with the BEB General Vehicle Rules.

WSSub3.6. Engine Development

Engine modifications and component combinations are unrestricted within the naturally aspirated subcategory requirements, subject to the following block restriction.

The engine block must be an OEM production block originally manufactured for a vehicle manufacturer's production engine. Aftermarket engine blocks of any brand or type are prohibited.

Aftermarket cylinder heads, intake manifolds, and other engine components are permitted.

All installation, structural, fuel, and safety requirements remain mandatory.

WSSub3.7. Steering Columns and Steering Racks

Steering column and steering rack swaps or modifications are permitted only where professionally executed and safe for competition. Steering rack relocation must satisfy WS.6.3.

The steering column must retain the original OEM collapsible devices and their function. Modifications must not bypass, disable, or rigidly bridge those devices.

Shafts, joints, bearings, mounts, and connections must be correctly aligned, securely installed, and operate without binding or interference throughout the full steering range and suspension travel.

Poorly fabricated, misaligned, inadequately supported, or otherwise unsafe installations are prohibited. Safety is BEB's first priority. Creativity does not excuse poor execution. A vehicle with unsafe steering may not compete until corrected and accepted by BEB officials.

WSSub4. BMW Chassis with a Turbocharged or Supercharged Engine from Another Manufacturer

WSSub4.1. Eligible Vehicles and Engines

This subcategory accepts eligible BMW sedans, coupes, convertibles, Tourings, and BMW X1 vehicles equipped with an engine from another manufacturer operating with turbocharging, supercharging, or both.

Turbochargers and superchargers of any type are permitted. Factory systems may be retained, modified, or replaced. Forced induction may be added to a naturally aspirated engine.

All general Werk Sport eligibility, safety, roll cage, tire, and aerodynamic requirements apply.

WSSub4.2. Engine Location

The engine must remain in approximately the same location as the original engine, installed as close as practicable to the original OEM position.

WSSub4.3. Firewall and Transmission Tunnel Clearance

Firewall and transmission tunnel modifications are permitted where necessary to accommodate the engine and transmission installation.

Modifications must be professionally fabricated and preserve structural integrity and complete separation between the drivetrain and driver compartment.

Modified areas must have no cracks, tears, exposed openings, open seams, or unwelded joints. Fabricated closure panels must be fully welded around their entire perimeter.

This permission does not authorize relocation of suspension or subframe mounting points beyond the express general Werk Sport exceptions.

WSSub4.4. Exhaust and Wastegate Discharge

Exhaust systems are unrestricted provided they comply with the BEB General Vehicle Rules, except for the specific wastegate outlet location allowance below.

Wastegate discharge may return into the exhaust system or discharge downward toward the track surface through a securely installed outlet.

Open wastegate dumps are exempt from the general exhaust outlet location requirements, provided discharge is not directed toward tires, brake lines, fuel components, wiring, suspension components, bushings, the vehicle floor, firewall, or other heat sensitive or safety critical components.

Discharge must not enter the driver compartment. Firewall sealing and applicable heat protection requirements remain mandatory.

WSSub4.5. Engine Management, Ignition, and Wiring

Engine management is unrestricted. Factory ECU or DME tuning, chips, and aftermarket standalone ECUs are permitted. Ignition components are unrestricted.

Custom wiring is permitted where properly constructed, securely installed, protected from damage, and compliant with the BEB General Vehicle Rules.

WSSub4.6. Engine Development

Engine modifications and component combinations are unrestricted within the forced induction subcategory requirements, subject to the following block restriction.

The engine block must be an OEM production block originally manufactured for a vehicle manufacturer's production engine. Aftermarket engine blocks of any brand or type are prohibited.

Aftermarket cylinder heads, intake manifolds, and other engine components are permitted.

Alternate exhaust manifolds, piping, intercoolers, turbochargers, and superchargers are permitted.

All installation, structural, fuel, and safety requirements remain mandatory.

WSSub4.7. Steering Columns and Steering Racks

Steering column and steering rack swaps or modifications are permitted only where professionally executed and safe for competition. Steering rack relocation must satisfy WS.6.3.

The steering column must retain the original OEM collapsible devices and their function. Modifications must not bypass, disable, or rigidly bridge those devices.

Shafts, joints, bearings, mounts, and connections must be correctly aligned, securely installed, and operate without binding or interference throughout the full steering range and suspension travel.

Poorly fabricated, misaligned, inadequately supported, or otherwise unsafe installations are prohibited. Safety is BEB's first priority. Creativity does not excuse poor execution. A vehicle with unsafe steering may not compete until corrected and accepted by BEB officials.

WSSub4.8. Turbocharger Heat Protection

Turbochargers, turbine housings, exhaust manifolds, downpipes, and wastegate discharge pipes produce substantial heat. Fuel components, wiring, electronics, fluid lines, and other heat sensitive components must be positioned as far as practicable from these heat sources.

Where adequate separation cannot be achieved, exposed hoses and wiring must be enclosed in fire sleeves rated for the application. Other heat sensitive components must have suitable fire resistant enclosures or heat shields.

Turbocharger turbine housings must have securely installed turbo heat blankets suitable for the application. Protective sleeves, shields, and blankets do not make an otherwise hazardous installation acceptable.

WSSub4.9. Intercoolers and Charge Cooling

Air to air and water to air intercoolers are permitted. Supercharger cooler cores, reservoirs, pots, and bowls are permitted.

Water to air intercoolers and associated cooling components may be installed remotely anywhere within the vehicle, including the driver compartment, provided they are securely mounted and comply with the protection requirements below.

All components, piping, and hoses must be securely mounted and supported against loosening, movement, or detachment. As much piping as practicable must remain within the bodywork. This does not require routing through the driver compartment.

Distilled water is the only permitted fluid in any water to air intercooler or charge cooling circuit. Coolant, antifreeze, and additives are prohibited.

Charge cooling water lines within the driver compartment must use steel braided hose rated for the system's fluid, operating pressure, and temperature. Cabin lines, including all fittings and connections, must be fully enclosed within an aluminum or steel protective tunnel separating them from the driver.

Remotely installed reservoirs, cooler assemblies, and other components exposed to the driver must have suitable aluminum or steel enclosures to prevent hot water or steam from reaching the driver following a leak or rupture. Steel braiding alone does not satisfy the enclosure requirement.

No installation may obstruct driver entry, emergency exit, visibility, or required safety equipment.

WSSub4.10. Hazardous Installations

BEB may deny track access or remove a vehicle from competition if its installation, heat protection, or discharge routing presents a hazard. The vehicle may not compete or return to the track until corrected and accepted by BEB officials.