BAVARIAN ENDURANCE BATTLE

Dreier Class Rules

E30 / E36 / E46 / E9x

COMPETITION RULES | NOVEMBER 3, 2026

Mandatory companion documents: BEB General Vehicle Rules and Roll Cage Rules.

Contents

DC 1. Class Introduction and Competitive Philosophy 2

DC 2. E30 Requirements and Allowances 3

DC 3. E36 Requirements and Allowances 4

DC 4. E46 Requirements and Allowances 5

DC 5. E9x Requirements and Allowances 6

DC 6. Requirements Applicable to All Chassis 7

DC 7. Prohibitions Applicable to All Chassis 14

Read your chassis section, then the requirements and prohibitions applicable to all chassis.

DC 1. Class Introduction and Competitive Philosophy

DC 1.1. Spirit of the Class

The Dreier Class brings together eligible BMW E30, E36, E46, and E9x vehicles for endurance competition. Each generation offers capable engines, responsive handling, and a strong foundation for race preparation.

Older cars may have simpler engine management and less developed factory technology, while newer cars benefit from advances in engine design, electronics, and chassis development. Each generation brings different strengths to the same race.

DC 1.2. Competitive Opportunity

BEB provides specific development allowances to give these generations an opportunity to compete together. The objective is competitive opportunity, not identical horsepower, lap times, or overall performance.

A 12 hour endurance race rewards more than engine output. Reliability, preparation, fuel management, pit strategy, teamwork, and driver consistency all contribute to the result.

These rules establish the maximum permitted modifications, not mandatory upgrades. Teams may retain stock equipment or use any combination of permitted upgrades within the applicable limits for their chassis and engine.

DC 1.3. Class Scope

The Dreier Class covers eligible non M BMW E30, E36, E46, and E9x vehicles. Touring body configurations compete under the Touring Class rules.

These allowances apply exclusively to the Dreier Class and do not establish permissions for any other BEB class.

DC 1.4. How to Read These Rules

Read the section for the vehicle's chassis, followed by the requirements applicable to all chassis in DC 6 and the common prohibitions in DC 7.

DC 2 applies only to the E30. DC 3 applies only to the E36. DC 4 applies only to the E46. DC 5 applies only to the E9x.

A chassis specific allowance is an exception to a common restriction only where expressly stated. Permission for one chassis does not extend to another chassis. Engine eligibility remains governed by DC 6.2.

DC 2. E30 Requirements and Allowances

DC 2.1. Application

The additional allowances in this section apply exclusively to eligible E30 chassis competing in the Dreier Class. They do not authorize engine swaps or expand engine eligibility.

DC 2.2. Camshafts

Aftermarket camshafts are permitted in eligible original E30 engines operating in naturally aspirated form.

Teams may retain factory camshafts or install aftermarket camshafts. No individual camshaft approval, brand restriction, or numerical duration or lift limit applies under this allowance.

Camshaft permission does not independently authorize changes to displacement, compression, the rotating assembly, intake manifolds, or throttle bodies. Cylinder head work is addressed in DC 6.4.

DC 2.3. Engine Management

The factory DME or an aftermarket standalone ECU is permitted. Software tuning and compatible calibration changes are permitted with either system.

DC 2.4. Airflow Meter Conversions and Bypass

Conversion from the original airflow meter to a modern MAF system is permitted, including the necessary conversion electronics and compatible calibration. Larger or performance MAF units are expressly permitted for M20 engines.

Eligible E30 vehicles equipped with a permitted standalone ECU may operate without an active airflow meter using MAP, speed density, or throttle position based engine load calculation. Teams may alternatively retain the original airflow meter or use a permitted MAF conversion.

DC 2.5. Distributor and Ignition Conversion

Removal of the original distributor and conversion to a crank trigger ignition system with individual ignition coils controlled by a permitted standalone ECU are allowed.

All components must be securely installed. This allowance does not authorize modification of the engine's rotating assembly.

DC 2.6. Fuel System and Headers

Aftermarket fuel systems, including higher pressure fuel pumps, are permitted. Aftermarket exhaust headers are permitted.

Fuel, fuel system installation, and exhaust requirements applicable to all chassis appear in DC 6.7 and DC 6.8.

DC 2.7. Differential Changes

Differential changes are permitted only where the replacement installs using the original OEM mounting points without modification or relocation. Installation must be a direct bolt on fit.

Cutting, welding, drilling new mounting locations, or altering the subframe or differential mounting points to accommodate the replacement is prohibited. The common donor component requirements in DC 6.14 also apply.

DC 2.8. Five Lug Conversions

Conversion from the original four lug wheel mounting configuration to a five lug configuration is permitted.

The conversion must retain the original OEM suspension mounting points and comply with the class restrictions on suspension geometry, subframes, and BMW M model components.

All hubs, bearings, wheel mounting hardware, and associated components must be suitable for the application and securely installed. Wheel spacers must match the converted hub and wheel bolt pattern.

DC 3. E36 Requirements and Allowances

DC 3.1. Application

This section applies to eligible E36 vehicles using an original engine application permitted by DC 6.2.

DC 3.2. Engine Management

The factory DME or an aftermarket standalone ECU is permitted. Software tuning and compatible calibration changes are permitted with either system.

Standalone ECU permission does not waive the camshaft, airflow metering, or VANOS requirements below.

DC 3.3. Camshafts

Aftermarket camshafts are permitted in eligible M50 and M52 engines operating in naturally aspirated form. Teams may retain factory camshafts or install aftermarket camshafts.

No individual camshaft approval, brand restriction, or numerical duration or lift limit applies under this allowance.

All other eligible E36 engine families must retain factory specification camshafts.

Camshaft permission does not independently authorize changes to displacement, compression, the rotating assembly, intake manifolds, or throttle bodies. Cylinder head work is addressed in DC 6.4.

DC 3.4. Airflow Metering

The original factory specification airflow metering system must remain in active operation. M50 and M52 engines must retain their original factory specification MAF system.

Larger MAF units, alternative performance MAF conversions, and airflow meter bypass are prohibited. Standalone ECU permission does not authorize removal, bypass, or disabling of the factory airflow metering system.

DC 3.5. VANOS

Where equipped, the original OEM VANOS hardware must be retained without modification. Performance hardware, disabling, and deletion are prohibited.

VANOS tuning is permitted only through software changes to the factory DME. Standalone ECU permission does not independently authorize VANOS tuning.

Permitted aftermarket camshafts must operate with the original unmodified VANOS hardware.

DC 4. E46 Requirements and Allowances

DC 4.1. Application

This section applies to eligible E46 vehicles using an original engine application permitted by DC 6.2.

DC 4.2. Engine Management

The vehicle's original factory DME hardware must be retained; software tuning is permitted. Aftermarket standalone ECUs are prohibited.

DC 4.3. Camshafts

Factory specification camshafts are required. Aftermarket camshafts are prohibited. Software tuning permission does not authorize camshaft replacement with performance components.

DC 4.4. Airflow Metering

The original factory specification MAF system must remain in active operation. Larger or performance MAF conversions and airflow meter bypass are prohibited.

DC 4.5. VANOS

The original OEM VANOS hardware must be retained without modification. Performance hardware, disabling, and deletion are prohibited.

VANOS tuning is permitted through software changes to the factory DME.

DC 5. E9x Requirements and Allowances

DC 5.1. Application

This section applies to eligible naturally aspirated E9x vehicles using an original engine application permitted by DC 6.2. Touring body configurations compete under the Touring Class rules.

DC 5.2. Engine Management

The vehicle's original factory DME hardware must be retained; software tuning is permitted. Aftermarket standalone ECUs are prohibited.

DC 5.3. Camshafts

Factory specification camshafts are required. Aftermarket camshafts are prohibited. Software tuning permission does not authorize camshaft replacement with performance components.

DC 5.4. Airflow Metering

The original factory specification airflow metering system must remain in active operation. Larger or performance MAF conversions and airflow meter bypass are prohibited.

DC 5.5. VANOS

The original OEM VANOS hardware must be retained without modification. Performance hardware, disabling, and deletion are prohibited.

VANOS tuning is permitted through software changes to the factory DME.

DC 6. Requirements Applicable to All Chassis

DC 6.1. Mandatory Compliance

All vehicles must comply with the Bavarian Endurance Battle General Vehicle Rules and Roll Cage Rules in addition to these class requirements. No exceptions are permitted.

Convertible vehicles must comply with all applicable convertible requirements. A factory roof, retractable roof, or rollover protection system does not replace the required competition roll cage.

DC 6.2. Engine Eligibility

Vehicles must use an engine originally offered by BMW for the vehicle's specific chassis and body configuration under United States market OEM specifications.

An engine's availability in another chassis or body configuration does not independently make it eligible. Development allowances do not expand eligible engine applications.

DC 6.3. Engine Internals

Except for the original cylinder head work permitted in DC 6.4 and the camshaft allowances expressly stated in the applicable chassis section, engine internals must remain stock and conform to the original OEM specifications for the eligible engine.

The rotating assembly must retain its original OEM configuration. The common internal engine prohibitions appear in DC 7.3.

DC 6.4. Cylinder Head

The cylinder head must remain the original OEM type for the eligible engine. Modifications to the original cylinder head to improve airflow and performance are permitted.

This is an exception to the stock internal requirements and does not authorize modifications to the engine block or rotating assembly. Camshafts remain governed by the applicable chassis section.

DC 6.5. Ignition System

Ignition system upgrades are permitted on all eligible chassis. The additional E30 distributor removal and crank trigger conversion allowance appears in DC 2.5.

DC 6.6. Air Filters and Intake Pipes

Cold air intake systems, aftermarket air filters, air filter housings, and intake pipes are permitted on all eligible chassis and engines.

These installations must comply with the airflow metering and engine management requirements stated in the applicable chassis section. This permission does not independently authorize changes to intake manifolds or throttle bodies.

DC 6.7. Fuel System and Fuel

Fuel system upgrades are permitted on all eligible chassis. All modifications, components, and installation methods must comply with the fuel system requirements in the BEB General Vehicle Rules.

Only 91 octane gasoline is permitted, without the fuel additives, boosters, alternate fuels, or fuel aids prohibited in DC 7.6.

DC 6.8. Exhaust System

Exhaust system modifications are unrestricted within the requirements of the BEB General Vehicle Rules. Aftermarket headers are permitted on all eligible chassis.

All exhaust components, routing, mounting, and discharge locations must comply with the BEB exhaust requirements.

DC 6.9. Alternator

The alternator must remain OEM for the vehicle's application.

DC 6.10. Cooling System

Cooling system upgrades are permitted, including aftermarket electric fans, aluminum radiators, and upgraded cooling piping.

All components must be suitable for their intended use, securely installed, and free of leaks. All cooling modifications must comply with the BEB General Vehicle Rules.

Distilled water is the only permitted cooling system fluid.

DC 6.11. Oil Pan Baffles

Internal oil pan baffles are permitted solely to help prevent oil starvation. This exception does not authorize other modification of the OEM oil pan or lubrication system, except for the cooler installations in DC 6.12.

DC 6.12. Oil Coolers and Power Steering Coolers

Aftermarket engine oil coolers and power steering coolers are permitted.

All coolers, brackets, lines, and fittings must be securely installed to prevent loosening, movement, or detachment during competition.

Hoses must be designed for the intended fluid and rated for the system's operating temperature and pressure. Connections must use appropriate AN fittings or equivalent fittings designed for the application.

All hoses must be secured and protected from extreme heat, sharp edges, abrasion, and moving components. Both systems must remain leak free throughout competition and comply with the BEB General Vehicle Rules.

DC 6.13. Transmissions

Automatic or five speed manual transmissions are permitted. Manual transmission swaps are allowed even if BMW did not originally offer a manual transmission for that specific model in the United States market.

The transmission must have been offered in a non M BMW model within the vehicle's corresponding chassis generation. Related body configurations within that generation are eligible donors even where their individual chassis codes differ.

This permission does not authorize transmissions from unrelated chassis generations or six speed manual transmissions.

DC 6.14. Differentials and Axles

Differentials and axles from BMW coupe or sedan models of any chassis generation are permitted, provided they are not BMW M model components.

This permission does not authorize modification or relocation of subframes or suspension mounting points. E30 differential installations must additionally meet the direct bolt on restriction in DC 2.7.

DC 6.15. Interior and Dashboards

The interior must comply with the BEB General Vehicle Rules. The original dashboard is optional and may be removed. An aftermarket racing dashboard, custom instrument panel, or standalone cluster is permitted.

Every dashboard, panel, instrument, and mounting component must be securely attached to prevent detachment during competition or an accident. Installations must have no hazardous sharp edges or exposed projections.

Dashboards, panels, instruments, and mounting hardware must not restrict, delay, or interfere with rapid driver exit or obstruct driver visibility in any way.

Nonstructural interior brackets, mounts, and utility supports may be removed only where removal does not compromise chassis structural integrity. The work must be performed by a qualified shop or professional capable of distinguishing nonstructural attachments from structural components.

DC 6.16. Auxiliary Panels and Wiring

Additional panels for switches, controllers, instruments, or electronic equipment are permitted. Panels and attached equipment must be securely mounted with properly tightened fasteners and must not present sharp edges or other hazards.

Wiring throughout the entire interior must be organized, secured, and protected against abrasion, heat, and moving components. It must be routed away from surfaces capable of cutting, pinching, or stripping its insulation.

Suitable grommets or protective fittings must be installed where wiring passes through metal panels or other openings. All electrical installations must comply with the BEB General Vehicle Rules.

DC 6.17. Safety Equipment and Driver Cooling

All mandatory interior safety equipment and systems must comply with the BEB General Safety Requirements, General Vehicle Rules, and Roll Cage Rules. Interior modification permissions do not waive mandatory safety requirements.

NACA ducts, air ducts, and hoses may be installed within a side window frame solely for driver cooling. Components must be securely mounted and must not obstruct visibility or interfere with rapid driver exit.

DC 6.18. Driver Seat Supports and Headroom

OEM brackets, rails, and raised supports beneath the driver's seat may be removed or modified to gain headroom. The OEM floor pan must remain unmodified and in its original position, as verified from underneath the vehicle.

Where OEM mounting structures are removed, a strong replacement structure with a lower profile must reinforce the floor and support the seat securely. Mounting the seat directly to thin OEM floor sheet metal without a supporting reinforcement structure is prohibited.

All seat installations must comply with the BEB General Vehicle Rules. Teams with questions must email info@bavarianendurancebattle.com with photographs and an explanation of the proposed design before modification or final welding.

DC 6.19. Body Appearance and Replacement Panels

Vehicles must retain the recognizable appearance and original production body configuration of the eligible vehicle. All fenders and quarter panels must be present.

Aftermarket hoods, fenders, and other replacement panels are permitted where they preserve the vehicle's recognizable identity. Fender flares, wings, splitters, spoilers, and diffusers are permitted within the requirements below.

DC 6.20. Tire Clearance, Flares, and Body Kits

All panels, fenders, flares, body kits, and surfaces surrounding a tire must be free of sharp edges, exposed points, or features capable of cutting, slashing, or puncturing the tire.

Adequate clearance must be maintained throughout the full range of steering movement and suspension travel, including compression and rebound. No hazardous surface may enter the tire's operating space.

Fenders may be rolled or flared, and additional flares may be installed, to cover the tires when viewed directly from above. Coverage is assessed from above, not from the front or rear. Except for permitted body kits, flares may extend only as far as necessary for that coverage.

Aftermarket body kits are permitted where they preserve the vehicle's recognizable identity and satisfy the same tire clearance and puncture prevention requirements. Body kit permission does not authorize structural changes. Aerodynamic components must meet DC 6.29 and DC 6.30.

DC 6.21. Roof Accessories and Panoramic Sunroofs

Roof utility rails, where equipped, may be removed. Removal must not leave exposed holes or openings into the interior. Resulting openings must be properly sealed using securely attached materials and methods compliant with the BEB General Vehicle Rules.

Panoramic sunroof assemblies, where equipped, must be removed and replaced with metal or impact resistant composite panels. Replacement panels must fully cover and seal the openings and be securely fastened with rivets or appropriate hardware to prevent loosening or detachment.

DC 6.22. Windshield and Windows

The windshield may be replaced with impact resistant polycarbonate specifically designed for motorsport windshield use. All materials and installations must comply with the BEB General Vehicle Rules.

Driver and front passenger windows must comply with the BEB requirements for removal or the required open position. All other windows may be replaced with Lexan or equivalent motorsport grade polycarbonate.

Replacement glazing must be securely installed and free of sharp edges or other hazards. Tint and acrylic glazing restrictions appear in DC 7.8.

DC 6.23. OEM Structures and Subframes

Except for the specific permissions for nonstructural interior attachments, seat supports, reinforcement, roll cage clearance, seat tunnel clearance, and shock tower clearance in these rules, the following OEM structures must remain unmodified and in their original locations:

1. Frame rails, rear frame cross beam, unibody structure, subframes, and suspension crossmembers, as applicable.
2. Strut and shock towers.
3. Inner or inboard wheel well sides, including all nonhorizontal portions.
4. Rocker panels.
5. Transmission tunnel.
6. Floor pan.
7. Windshield frame.

Except for the welded reinforcement allowance in DC 6.24, subframes must remain unmodified and in their original OEM locations. OEM replacement subframes from sedan or coupe models within the same chassis generation are permitted only where they install without alteration of any mounting point and preserve every original suspension mounting point location and geometry.

DC 6.24. Reinforcement, Welding, and Cage or Seat Clearance

Welded reinforcement kits and reinforcement plates are permitted on all eligible chassis, including the front subframe, rear subframe, chassis, and unibody.

Reinforcement around suspension and subframe mounting points is permitted, but the mounting points themselves must remain unchanged. Reinforcement must not modify, relocate, slot, enlarge, or change the geometry, angle, position, or location of any suspension mounting point or subframe mounting point.

This allowance permits reinforcement only. It does not authorize redesign of a subframe or changes to its original installed position. It is a specific exception to the unmodified subframe requirement in DC 6.23.

Seam and stitch welding are permitted on the body or unibody for reinforcement without changing suspension or subframe mounting point geometry, angle, position, or location, or otherwise modifying or relocating protected structural components. Subframe reinforcement remains limited to the express allowance above.

Unibody B pillars may be notched for roll cage door bars only where the notched area is welded to the bar or bars extending into the pillar. All cage construction must comply with the BEB Roll Cage Rules.

The transmission tunnel may be modified solely to install and center a competition driver seat. Localized notching, bending, or shaping is permitted only where necessary for seat clearance. The floor pan must remain in its original OEM position.

Adequate clearance from the driveshaft and other rotating components must be maintained. The tunnel must retain structural integrity and remain fully sealed, without holes, cracks, open seams, exposed openings, or compromised sheet metal.

Where notched, a properly shaped metal plate at least as thick as the original OEM sheet metal must close the opening and be continuously welded around its entire perimeter, 360 degrees.

DC 6.25. Aftermarket Suspension

Aftermarket suspension components are permitted on all eligible chassis, provided they retain the original OEM suspension mounting points and comply with the structural and subframe requirements.

This permission does not authorize changes to the original OEM location or angle of fixed suspension mounting points or modification or relocation of subframes.

DC 6.26. Camber and Caster Plates

Aftermarket camber and caster plates are permitted at the original OEM upper suspension mounting locations. Alignment adjustment through these plates is permitted.

The vehicle's fixed OEM suspension mounting points must not be relocated or altered.

DC 6.27. Shock Tower Clearance and Reinforcement

Limited shock tower trimming is permitted only for the clearance necessary to install camber or caster plates. Where cutting would weaken a tower, welded reinforcement is required to preserve structural integrity.

Neither trimming nor reinforcement may change the geometry, angle, position, or location of fixed OEM suspension mounting points. This is a specific exception to the unmodified shock tower requirement.

DC 6.28. Sway Bars

Aftermarket sway bars are permitted on all eligible chassis, provided they attach at the original OEM sway bar mounting locations.

DC 6.29. General Aerodynamics and Front Devices

Aerodynamic devices must remain securely fixed in their selected position while the vehicle is moving. Mechanical adjusters are permitted. Adjustment may occur only before the race, during pit stops while stationary, or after the race.

Except for canards, devices may extend no more than 2 inches beyond the body on either side. Where a body kit or flares are installed, devices may extend no farther than the outermost bodywork, including the kit or flares. Rear wings and spoilers must meet the narrower body width limit in DC 6.30.

Front wings, spoilers, foils, and splitters may extend no more than 7 inches forward of the outermost front bodywork or fascia. No part may extend higher than the lowest part of the hood.

A splitter or undertray may extend rearward no farther than the front bulkhead or firewall of the driver compartment.

One pair of canards is permitted: one on each side, for a maximum of two total. They must be structurally sound, securely attached, and static while moving. Canards are exempt from the general width limits.

DC 6.30. Rear Wing, Spoiler, and Trunk Mounting

A single element rear wing or spoiler is permitted within these limits:

1. Height: No part may extend more than 5 inches above the roofline.

2. Width: No wider than the body, excluding flared fenders, mirrors, splitters, and door handles.

3. End plates: Maximum area of 144 square inches per end plate.

4. Rearward extension: Maximum of 12 inches beyond the rearmost bodywork.

A Gurney flap is permitted. For a convertible, roofline refers to the original factory roof in its fully raised and closed position.

Supports may attach to the trunk lid or suitable mounting structures within the trunk compartment. Trunk lid mounts must be adequately reinforced to distribute aerodynamic loads and prevent deformation, loosening, or detachment.

Supports within the trunk may pass through the lid. Resulting openings must be properly fitted and sealed, and the lid must remain securely installed. Wing installation does not authorize removal of the rear window or trunk lid.

All mounts and supports must be securely constructed and attached. They must not interfere with the rear bumper's impact area or extend rearward beyond the bumper where another vehicle could contact them in an accident.

Mounting permission does not authorize modification or relocation of OEM frame rails or other protected structural components.

DC 6.31. Aftermarket Brakes

Aftermarket brake systems and larger brakes are permitted on all eligible E30, E36, E46, and E9x chassis, provided they fit within the class's permitted wheel sizes once those requirements are published.

Systems must be designed for the specific vehicle application, properly installed, and must not compromise braking safety or reliability. Components must come from an identifiable, reputable manufacturer, regardless of where purchased.

Teams must select equipment that protects their drivers and other participants. BEB may reject an unsafe or questionable brake installation and require correction before the vehicle competes.

DC 6.32. Wheels, Spacers, and Mounting Hardware

Wheel spacers are permitted where designed for the application, with bolt patterns matched to the hub and wheel. They must be hub centric, dimensionally matched to both, and made from high strength aluminum alloy.

All wheel mounting hardware must be racing grade and comply with the BEB General Vehicle Rules. When spacers are used, racing grade wheel studs and matching lug nuts are mandatory. Hardware must be heavy duty and suitable for the application, with the correct conical lug nut seat for the wheel.

Bolt on spacers using separate hub attachment hardware must use high tensile grade mounting hardware. All wheels and spacers must be securely installed and satisfy the tire clearance requirements.

An E30 may retain its original bolt pattern or use the five lug conversion permitted in DC 2.8.

DC 6.33. Wheel Sizes and Tires

Permitted wheel sizes, tire specifications, and tire limits remain pending. These requirements will be updated and published soon.

DC 6.34. White Class Identification Lights

All vehicles must have headlights emitting white light. If the original headlights are removed or absent, at least two white lights must be installed in the original headlight locations.

A dedicated white pod light must be installed at the rear, facing rearward and clearly visible to following drivers. It must be securely and rigidly mounted to maintain its position and orientation throughout competition.

The rear white pod is mandatory and does not replace required functioning brake lights. Standard taillights or rear driving lights do not replace the pod.

The white front lights and rear white pod must remain illuminated at all times during the race to provide a consistent class identifier.

DC 6.35. Orange Mirror Housings and Exterior Finish

Exterior mirror housings must be orange to identify the Dreier Class. Paint, securely applied wrap, Plasti Dip, or another safe method is permitted.

Only the housings are subject to the color requirement. Reflective mirror surfaces must remain unobstructed and functional.

Factory finishes, paint, wraps, liveries, artwork including art cars, and sponsor advertising are permitted. They must not obscure or alter the orange mirror identification. Safety equipment and mandatory identification features must remain visible and functional.

DC 6.36. Windshield Banners and Race Numbers

Windshield banner requirements will be published as event development progresses. Race number format, placement, designation, dimensions, colors, and number frame requirements will be announced as finalized.

Mandatory number locations will be the same for every car, regardless of livery, artwork, paint, wrap, or sponsor advertising. Teams must accommodate the required locations within their designs.

DC 7. Prohibitions Applicable to All Chassis

DC 7.1. BMW M Models and Components

BMW M models are prohibited. BMW M model components may not be swapped into a vehicle, including transmissions, differentials, axles, and subframes.

DC 7.2. Forced Induction

Turbocharged and supercharged engines are prohibited, including factory equipped applications. Vehicles with forced induction must compete in the Unlimited Werk Sport Class.

DC 7.3. Unauthorized Engine Changes

Engine swaps outside the eligible original applications are prohibited. Aftermarket cylinder heads and head swaps from other engine models or families are prohibited.

Except for the express camshaft and original cylinder head permissions, internal components may not be changed, altered, or upgraded to increase performance or displacement. Stroker configurations and rotating assembly components from other engine families are prohibited.

An engine management, ignition, intake, or camshaft permission does not independently authorize other engine modifications.

DC 7.4. Structural and Mounting Point Changes

Unauthorized cutting, modification, relocation, or alteration of protected OEM structures or subframes is prohibited. Suspension and subframe mounting points must remain unchanged. Welded reinforcement is permitted only within DC 6.24. Subframes from other chassis generations are prohibited.

Body panels, body kits, aerodynamic devices, drivetrain components, and five lug conversions do not establish additional structural exceptions.

DC 7.5. Active Aerodynamics

Active or dynamic aerodynamic systems are prohibited, including electronic, self adjusting, and OEM active systems.

DC 7.6. Fuel and Cooling Additives

Fuel additives, octane boosters, alternate fuels, and fuel aids of any kind are strictly prohibited. Coolant, antifreeze, and cooling system additives are prohibited.

DC 7.7. Fluid Leaks and Unsafe Installations

Engine oil and power steering fluid leaks or spills are strictly prohibited. Any vehicle leaking or spilling either fluid must leave the racing surface as soon as safely possible and may not return until corrected and approved by BEB officials.

Loose or unsecured hoses, wiring, panels, and equipment are prohibited. Unbranded, untraceable, or disreputable brake systems are prohibited. No installation may compromise required safety equipment or driver egress.

DC 7.8. Body and Glazing Restrictions

Open wheel configurations are prohibited. Tint of any kind is prohibited on the windshield and all remaining windows. Acrylic glazing, commonly sold as Plexiglas, is prohibited.