



Exploring
World Trade
Networks

V. Batagelj

World trade
datasets

Matrix layout

Normalizations

Skeletons

Conclusions

References

Exploring World Trade Networks

Vladimir Batagelj

IMFM Ljubljana and IAM UP Koper

ARS'25

Tenth International Workshop on Social Network Analysis

30-31 October 2025, Naples (Italy)



Outline

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets

Matrix layout

Normalizatoins

Skeletons

Conclusions

References

- 1 World trade datasets
- 2 Matrix layout
- 3 Normalizatoins
- 4 Skeletons
- 5 Conclusions
- 6 References



Vladimir Batagelj: vladimir.batagelj@fmf.uni-lj.si

Current version of slides (October 30, 2025 at 00:48): [slides PDF](#)

<https://github.com/bavla/wNets/>



World trade datasets

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets

Matrix layout

Normalizations

Skeletons

Conclusions

References

We will discuss some approaches to **exploratory analysis** of weighted dense temporal networks of moderate size. For illustration, we use world trade data.

WTO and UN comtrade and some other institutions are collecting world trade data. The problem with the collected data is missing data and inconsistencies.

An early version of world trade flows was provided by NBER ([Feenstra et al.(2005)]; [download](#)).

The French research center CEPII is providing a consolidated version of the UN comtrade data as a database [BACI/CEPII](#) [[Gaulier and Zignago\(2010\)](#)].

An application of the network analysis to the BACI data was done already by de Benedictis et al.

[[De Benedictis et al.\(2014\)](#), [Hoang et al.\(2023\)](#)].



BACI data

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets

Matrix layout

Normalizations

Skeletons

Conclusions

References

Each BACI trade flow is described by 6 quantities:

- Year,
- Product category (HS 6-digit code),
- Exporter (ISO 3-digit country code),
- Importer (ISO 3-digit country code),
- Value of the trade flow (in thousands current USD),
- Quantity (in metric tons)

HS codes: [Harmonized Commodity Description and Coding Systems \(HS\)](#), [Classifications on economic statistics](#), [Harmonized System Codes \(HS Code 2017 - Current\)](#).

Currently, there are around 5300 different HS codes. They are hierarchically organized. The 97 2-digit codes are also called *chapters*. They are joined into 21 *sections*. This enables the user to study the data at different granularity levels. In this presentation, we will limit our attention to the top level – the total trade flow values between countries in a year.



Weighted temporal multi-relational network

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets

Matrix layout

Normalizations

Skeletons

Conclusions

References

The BACI data essentially determine a *weighted temporal multi-relational network* $\mathcal{N} = (\mathcal{V}, (\mathcal{L}_h)_{h \in HS}, w, \mathcal{T})$ where \mathcal{V} is the set of world countries, relation \mathcal{L}_h is the set of links with the HS code h , $w : \mathcal{L} \rightarrow \mathbb{R}^+$ is the flow value (in thousands current USD), and $\mathcal{T} = 1996 : 2023$ is the observed range of years.

In a temporal network, nodes $v \in \mathcal{V}$ and links $e \in \mathcal{L}$ are not necessarily present or active in all time points. Let $T(v)$ be the *activity set* of time points for node v and $T(e)$ the activity set of time points for link $e \in \mathcal{L}$. Besides the presence/absence of nodes and links also their properties can change through time – the weight w becomes a *temporal quantity* [Batagelj and Praprotnik(2016)]

$$w(t) = \begin{cases} w'(t) & t \in T(w) \\ \text{\#} & t \in \mathcal{T} \setminus T(w) \end{cases}$$

where $T(w)$ is the *activity time set* of w , $w'(t)$ is the value of w in an instant $t \in T(w)$, and \# denotes the value *undefined*.



Weighted temporal multi-relational network

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets

Matrix layout

Normalizations

Skeletons

Conclusions

References

A *time slice* of \mathcal{N} in an instant $t \in \mathcal{T}$ is called the network $\mathcal{N}(t) = (\mathcal{V}(t), \mathcal{L}(t), w)$ where $\mathcal{V}(t) = \{v \in \mathcal{V} : t \in T(v)\}$ and $\mathcal{L}(t) = \{e \in \mathcal{L} : t \in T(e)\}$.

They can also be considered weighted multiway network data on four sets of nodes: Exporters, Importers, HS codes, and Years, with the flow value as a weight.

We converted the BACI data into Pajek format at the total, section, and chapter levels ([to Pajek](#), [GitHub](#)).

In this presentation, we limit our attention to **time slices** of the **totally aggregated network**.

World trade 2023 graph

spring embedder

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets


Matrix layout

Normalizatoins

Skeletons

Conclusions

References





WT 2023 binary matrix layout

nodes ordered by wdeg

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets


Matrix layout

Normalizatoins

Skeletons

Conclusions

References



World trade 2019 aggregated flows distribution

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets


Matrix layout

Normalizatoins

Skeletons

Conclusions

References





Comments

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets

Matrix layout

Normalizations

Skeletons

Conclusions

References

- Larger, $n > 20$, dense graphs can't be presented readably with a graphical layout. For WT2023 the number of nodes is $n = 226$ and the density $\gamma = 0.6068$. For dense graphs of moderate size (up to some hundreds of nodes), a better option is the matrix representation.
- What about weights? They can be represented by link thickness or levels of grey of matrix cells. The problem is a very large range and the distribution of weights – most weights give almost white cells. For WT2023 $w_{\min} = 0.001$ and $w_{\max} = 456484584$. Monotonic transformations such as $w' = a \cdot w$, $a > 0$ or $w' = \sqrt{w}$ or $w' = \log(w)$, etc. In our case, we used $w' = (1000 \cdot w)^{0.08}$.
- A better ordering of rows can be obtained by network clustering [Batagelj et al.(2014)]. Additional reordering of subtrees can be made manually using Pajek by reordering nodes in the hierarchy.



Corrected Euclidean distance and Salton index

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets

Matrix layout

Normalizations

Skeletons

Conclusions

References

Corrected Euclidean distance

$$D[u, v] = \sqrt{(w[u, v] - w[v, u])^2 + (w[u, u] - w[v, v])^2 + \sum_{t: t \neq u, t \neq v} (w[u, t] - w[v, t])^2}$$

Corrected Salton index of the link $(u, v) \in \mathcal{L}$

$$S[u, v] = \frac{w[u, .] \bullet w[v, .] + (w[u, u] - w[u, v]) \cdot (w[v, v] - w[v, u])}{\sqrt{w[u, .]^2 \cdot w[v, .]^2}}$$

where $\mathbf{x} \bullet \mathbf{y} = \sum_i x_i \cdot y_i$ and $\mathbf{x}^2 = \mathbf{x} \bullet \mathbf{x}$.

$$S[\alpha u, \beta v] = S[u, v], \text{ for } \alpha, \beta > 0$$



Weighted matrix WT2019

order determined by clustering + manual editing

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets


Matrix layout

Normalizatoins

Skeletons

Conclusions

References





Comments

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets

Matrix layout

Normalizatoins

Skeletons

Conclusions

References

- center-periphery
- blocks

| | | | |
|---------------------|--------------------|-----------------|-------------------|
| LC Lucia | CR Costa Rica | AF Afghanistan | AI Anguilla |
| VC S Vincent Grenad | DO Dominican R | UZ Uzbekistan | TC Turks Caicos |
| AG Antigua Barbuda | EC Ecuador | KG Kyrgyzstan | MS Montserrat |
| BB Barbados | GT Guatemala | MN Mongolia | AS American Samoa |
| BM Bermuda | UY Uruguay | TJ Tajikistan | GU Guam |
| GY Guyana | CO Colombia | TM Turkmenistan | TK Tokelau |
| GD Grenada | PE Peru | | KP DPR Korea |
| BZ Belize | PA Panama | | KY Cayman Is |
| SR Suriname | TT Trinidad Tobago | | KN S Kitts Nevis |
| JM Jamaica | SV El Salvador | | VG Br Virgin Is |
| BS Bahamas | HN Honduras | | DM Dominica |
| | NI Nicaragua | | CW Curaçao |
| | BO Bolivia | | AW Aruba |



World trade 2019 Salton

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets


Matrix layout

Normalizatoins

Skeletons

Conclusions

References





Normalizations – activity or Balassa index

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets

Matrix layout

Normalizatoins

Skeletons

Conclusions

References

In networks with weights with a large range usually a few strong nodes prevail. To diminish or neutralize the influence of size on results different normalizations were proposed and used [Batagelj and Mrvar(2003), Matveeva et al.(2023)].

Let $T = \sum_{e \in \mathcal{L}} w(e)$ and for $(u, v) \in \mathcal{L}$ (Balassa index)

$$A(u, v) = \frac{w[u, v] \cdot T}{\text{woutdeg}(u) \cdot \text{windeg}(v)}$$

then the *activity normalization* w'

$$w'(u, v) = \log_2 A(u, v)$$

World trade 2023 activity

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets


Matrix layout

Normalizatoins

Skeletons

Conclusions

References





Skeletons

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets

Matrix layout

Normalizatoins

Skeletons

Conclusions

References

To get insight into the structure of a large network we can reduce it to its skeleton by removing less important links and/or nodes [Batagelj (2011)].

- Most often the spanning tree, link cut, or node cut are used.
- In the closest k -neighbor skeleton for each node only the largest k incident links are preserved. Invariant for monotonic transformations.
- The Pathfinder algorithm was proposed in the 1980s by Schvaneveldt [Schvaneveldt et al.(1988), Schvaneveldt(1990), Batagelj et al.(2014)]. It removes from the network with a dissimilarity weight all links that do not satisfy the triangle inequality – if a shorter path exists that connects the link's end-nodes then the link is removed.
- Cores are a very efficient tool to determine the most cohesive (active) subnetworks [2]. The subset of nodes $\mathbf{C} \subseteq \mathcal{V}$ induces a P_s core at level t if for all $v \in \mathbf{C}$ it holds $w\deg_{\mathbf{C}}(v) \geq t$, and \mathbf{C} is the maximum such subset.



P_s cores

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets

Matrix layout

Normalizatoins

Skeletons

Conclusions

References

| | Rank | Id | 1995 Value | Id | 2019 Value | Id | 2023 Value |
|--|------|-----|---------------|-----|---------------|----|---------------|
| | 1 | US | 257693269 | MX | 658761422 | MX | 799627502 |
| | 2 | CA | 257693269 | US | 658761422 | US | 799627502 |
| | 3 | GB | 234199078 | CN | 658761422 | CN | 799627502 |
| | 4 | JP | 234199078 | CA | 658761422 | CA | 799627502 |
| | 5 | IT | 234199078 | JP | 520093954 | KR | 628044889 |
| | 6 | DE | 234199078 | KR | 504015412 | JP | 628044889 |
| | 7 | BE | 234199078 | DE | 504015412 | DE | 628044889 |
| | 8 | FR | 234199078 | GB | 500566393 | GB | 594923889 |
| | 9 | NL | 234199078 | FR | 500566393 | IT | 594923889 |
| | 10 | N/A | 162498504 | NL | 500566393 | FR | 594923889 |
| | 11 | KR | 162498504 | IT | 468723319 | NL | 594923889 |
| | 12 | HK | 162498504 | BE | 452244774 | BE | 590202643 |
| | 13 | CN | 162498504 | HK | 441557136 | A* | 512227117 |
| | 14 | ES | 143785957 | N/A | 435748876 | HK | 512227117 |
| | 15 | CH | 136849606 | ES | 403209053 | CH | 511548201 |
| | 16 | SG | 136849606 | CH | 398697522 | ES | 511548201 |
| | 17 | MX | 135153628 | VN | 398697522 | VN | 511548201 |
| | 18 | MY | 126873428 | SG | 395561634 | IN | 511548201 |
| | 19 | TH | 104745321 | IN | 395561634 | AU | 511548201 |
| | 20 | AT | 94004220 | AU | 395561634 | MY | 509054674 |
| | 21 | SE | 93440360 | MY | 383134139 | SG | 509054674 |
| | 22 | AU | 87125103 | RU | 383134139 | TH | 466862364 |
| | 23 | ID | 79999822 | PL | 359390045 | PL | 450228447 |
| | 24 | BR | 70865384 | TH | 343993122 | AE | 446632123 |
| | 25 | DK | 68975678 | AE | 310082847 | BR | 437245724 |
| | 26 | IE | 68975678 | ID | 310082847 | ID | 437245724 |
| | 27 | NO | 68022683 | BR | 310082847 | RU | 435325632 |
| | 28 | SA | 67949085 | SA | 310082847 | TR | 411617795 |
| | 29 | RU | 64736216 | CZ | 274596220 | SA | 411617795 |
| | 30 | FI | 61497981 | AT | 274174974 | IE | 349367822 |



World trade closest neighbor skeletons

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets


Matrix layout

Normalizatoins

Skeletons

Conclusions

References



World trade 2023 closest neighbor skeletons

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets


Matrix layout

Normalizations

Skeletons

Conclusions

References



World trade Pathfinder skeletons

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets


Matrix layout

Normalizatoins

Skeletons

Conclusions

References



WT2023s Pathfinder skeleton

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets


Matrix layout

Normalizations

Skeletons

Conclusions

References





Pajek skeletons

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets

Matrix layout

Normalizatoins

Skeletons

Conclusions

References

```
select the network WT19t
Network/Create new network/Transform/Remove/All arcs except/
    k with highest [1]
Draw network
Kamada-Kawai, manual edit, export picture in SVG
select the network WT19s
Network/Create new network/Transform/Line values/Power [-1]
Network/Create new network/Transform/Reduction/Pathfinder [10] [OK]
select the network WT19s as the second network
Networks/Cross-intersection/Second
Draw network
Kamada-Kawai, manual edit, export picture in SVG
```



Conclusions

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets

Matrix layout

Normalizations

Skeletons

Conclusions

References

- BACI is a gold mine.
- Margin labels in large matrices are not very handy – SVG/JS support with tooltips.
- We intend to look at the data also as a multiway network.



Acknowledgments

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets

Matrix layout

Normalizations

Skeletons

Conclusions

References

The computational work reported in this presentation was performed using R and Pajek. The code and data are available at

This work is supported in part by the Slovenian Research Agency (research program P1-0294 and research projects J5-2557, J1-2481, and J5-4596), and prepared within the framework of the COST action CA21163 (HiTEc).



References |

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets

Matrix layout

Normalizatoins

Skeletons

Conclusions

References

- Vladimir Batagelj, Patrick Doreian, Anuška Ferligoj, Nataša Kejžar (2014) Understanding Large Temporal Networks and Spatial Networks: Exploration, Pattern Searching, Visualization and Network Evolution. Wiley. ISBN: 978-0-470-71452-2
- Batagelj, Vladimir: Large-Scale Network Analysis. in John Scott, Peter J. Carrington eds. The SAGE Handbook of Social Network Analysis SAGE Publications, 2011.
- Batagelj, V., & Mrvar, A. (2003). Density based approaches to network analysis; Analysis of Reuters terror news network. Workshop on link analysis for detecting complex behavior (LinkKDD2003). Retrieved August 27, 2003, from <http://www.cs.cmu.edu/dunja/LinkKDD2003/papers/Batagelj.pdf>
- Batagelj, V., Praprotnik, S. (2016) An algebraic approach to temporal network analysis based on temporal quantities. *Social Network Analysis and Mining*, 6(1), 1-22
- Batagelj, V.: On fractional approach to the analysis of linked networks. *Scientometrics* 123 (2020), pages621–633. [Springer](#)



References II

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets

Matrix layout

Normalizatoins

Skeletons

Conclusions

References

- Batagelj, V, Zaveršnik, M (2011) Fast algorithms for determining (generalized) core groups in social networks. *Advances in Data Analysis and Classification*, Volume 5, Number 2, 129–145.
- De Benedictis, Luca and Nenci, Silvia and Santoni, Gianluca and Tajoli, Lucia and Vicarelli, Claudio, Network Analysis of World Trade Using the BACI-CEPII Dataset (January 2014). *Banque de France Working Paper No. 471*, Available at SSRN: <https://ssrn.com/abstract=2374354> or <http://dx.doi.org/10.2139/ssrn.2374354>
- Gaulier, G. and Zignago, S. (2010) BACI: International Trade Database at the Product-Level. The 1994-2007 Version. CEPII Working Paper, N 2010-23.
- Hoang, V.P., Piccardi, C. & Tajoli, L. Reshaping the structure of the World Trade Network: a pivotal role for China?. *Appl Netw Sci* 8, 35 (2023). <https://doi.org/10.1007/s41109-023-00560-9>
- Robert C. Feenstra, Robert E. Lipsey, Haiyan Deng, Alyson C. Ma and Hengyong Mo: World Trade Flows: 1962-2000. NBER Working Papers 11040, January 2005. <https://www.nber.org/papers/w11040>



References III

Exploring
World Trade
Networks

V. Batagelj

World trade
datasets

Matrix layout

Normalizatoins

Skeletons

Conclusions

References

-  Nataliya Matveeva, Vladimir Batagelj, Anuška Ferligoj Scientific collaboration of post-Soviet countries: the effects of different network normalizations *Scientometrics*, Volume 128, issue 8 2023, Pages: 4219 – 4242
-  Schvaneveldt, R. W. (Editor) (1990). *Pathfinder associative networks: Studies in knowledge organization*. Norwood, NJ: Ablex. [book](#)
-  Schvaneveldt, R. W., Dearholt, D. W., & Durso, F. T. (1988). Graph theoretic foundations of Pathfinder networks. *Computers and Mathematics with Applications*, 15, 337-345.