



Projections of weighted two-mode networks


Vladimir Batagelj

IMFM Ljubljana, IAM UP Koper, and NRU HSE Moscow

Applied Statistics 2022

Ljubljana, September 19–21, 2022

- 1 Two-mode networks
- 2 Projections
- 3 Outer product decomposition
- 4 Fractional approach
- 5 References



Vladimir Batagelj: vladimir.batagelj@fmf.uni-lj.si

Current version of slides (September 20, 2022 at 02:21): [slides PDF](#)

<https://github.com/bavla/NormNet/blob/main/docs/>

Two-mode networks

Projections of
weighted
two-mode
networks

V. Batagelj

Two-mode
networks

Projections

Outer product
decomposition

Fractional
approach

References

In a *two-mode* (affiliation or bipartite) network $\mathcal{N} = ((U, V), L, w)$ the set of nodes is split into two disjoint sets (*modes*) U and V . Each link $e \in L$ has one end-node in the set U and the other end-node in the set V . The function $w : L \rightarrow \mathbb{R}$ assigns to each link its weight.

In general, the weight can be measured on different measurement scales (counts, ratio, interval, ordinal, nominal, binary, TQ, etc.).

NAMES OF PARTICIPANTS OF GROUP I	CODE NUMBERS AND DATES OF SOCIAL EVENTS REPORTED IN <i>Old City Herald</i>													
	(1) 6/27	(2) 3/2	(3) 4/12	(4) 9/26	(5) 2/25	(6) 5/19	(7) 3/15	(8) 9/16	(9) 4/8	(10) 6/10	(11) 2/23	(12) 4/7	(13) 11/21	(14) 8/3
1. Mrs. Evelyn Jefferson.....	x	x	x	x	x	x	x	x	x
2. Miss Laura Mandeville.....	x	x	x	x	x	x	x	x	x
3. Miss Theresa Anderson.....	...	x	x	x	x	x	x	x	x
4. Miss Brenda Rogers.....	x	...	x	x	x	x	x	x
5. Miss Charlotte McDowd.....	x	x	...	x
6. Miss Frances Anderson.....	x	...	x	x	...	x
7. Miss Eleanor Nye.....	x	x	x	x
8. Miss Pearl Ogleshorpe.....	x	x	...	x	x
9. Miss Ruth DeSand.....	x	...	x	x	x
10. Miss Verne Sanderson.....	x	x	x	x	x
11. Miss Myra Liddell.....	x	x	x	x	...	x
12. Miss Katherine Rogers.....	x	x	x	x	...	x	x	x
13. Mrs. Sylvia Avondale.....	x	x	x	x	...	x	x	x
14. Mrs. Nora Fayette.....	x	x	...	x	x	x	x	x	x
15. Mrs. Helen Lloyd.....	x	x	...	x	x	x
16. Mrs. Dorothy Murchison.....	x	x
17. Mrs. Olivia Carleton.....	x
18. Mrs. Flora Price.....	x

Davis: Southern women, 1941 [9]

Two-mode network matrix and some notions

The network *matrix* UV of a two-mode network \mathcal{UV} is defined as

$$UV[u, v] = \begin{cases} w(u, v) & (u, v) \in L \\ \square & \text{otherwise} \end{cases}$$

We represent number 0 with two symbols, 0 (weight 0) and \square (no link) where $\square = 0$ with rules $\square + a = a$ and $\square \cdot a = \square$.

The function $\delta : \{\mathbf{false}, \mathbf{true}\} \rightarrow \{0, 1\}$ is determined by $\delta(\mathbf{false}) = 0$ and $\delta(\mathbf{true}) = 1$. We will also use some additional functions:

out/in-degree $N(u)$ is the set of neighbors of node u

$$\text{od}_{UV}(u) = \sum_{v \in V} \delta((u, v) \in L) = |N(u)| \text{ and}$$

$$\text{id}_{UV}(v) = \sum_{u \in U} \delta((u, v) \in L) = |N(v)|$$

weighted out/in-degree (row/column sums)

$$\text{wod}_{UV}(u) = \sum_{v \in V} UV[u, v], \quad \text{wid}_{UV}(v) = \sum_{u \in U} UV[u, v] \text{ and}$$

$$\text{wod}_{UV}(u/t) = \sum_{v \in N(u) \cap N(t)} UV[u, v].$$



Some notions

Projections of
weighted
two-mode
networks

V. Batagelj

Two-mode
networks

Projections

Outer product
decomposition

Fractional
approach

References

It holds $N(u) \cap N(t) \neq \emptyset \Rightarrow \text{wod}_{UV}(u/t) \neq \square$.

We denote $U_{[d]} = \{u \in U : \text{od}(u) \geq d\}$ and
 $\mathcal{UV}_{[d]} = ((U_{[d]}, V), L(U_{[d]}), w|_{U_{[d]}})$.

$$\hat{U} = \{u \in U : \text{wod}(u) \neq 0\}$$

The *total weight* of links in the network $\mathcal{N} = (V, L, w)$

$$T(\mathbf{N}) = \sum_{(u,v) \in L} w(u,v) = \sum_{u,v} N[u,v] = \sum_u \text{wod}_N(u) = \sum_v \text{wid}_N(v)$$

There are three main approaches to the analysis of two-mode networks:

- ① treat the two-mode network as an ordinary one-mode network (degrees, components, etc.) considering a bipartition to sets U and V .
- ② apply special methods developed for the analysis of two-mode networks (two-mode hubs and authorities, two-mode cores, 4-ring weights, blockmodeling, etc.).
- ③ transform (project) the two-mode network to a corresponding one-mode (weighted) network and use the usual methods (link cuts, cores, islands, skeletons, clustering, etc.) to analyze it.

In this talk, we will discuss the last option and limit our attention to numerical and binary scales.



Projections

Projections of
weighted
two-mode
networks

V. Batagelj

Two-mode
networks

Projections

Outer product
decomposition

Fractional
approach

References

$\mathcal{UV} = ((U, V), L, w)$ – two-mode network with a network matrix \mathbf{UV} .

$p : \mathbf{UV} \rightarrow \mathbf{VV}$ *projection*, $\mathbf{VV} = [p(v, z)]$; and
 \mathcal{VV} the corresponding (ordinary, one-mode) network

- 1 undirected projection: $p(v, z) = p(z, v)$, resemblance
 - similarity: $p(v, z) \leq \min(p(v, v), p(z, z))$
 - dissimilarity: $p(v, z) \geq \max(p(v, v), p(z, z))$
- 2 directed projection: $\exists v, z : p(v, z) \neq p(z, v)$ ([2], [11])

Many projections are based on the multiplication of networks.



Multiplication of networks

Projections of
weighted
two-mode
networks

V. Batagelj

Two-mode
networks

Projections

Outer product
decomposition

Fractional
approach

References

The *product* $\mathbf{C} = \mathbf{A} \cdot \mathbf{B}$ of two compatible matrices $\mathbf{A}_{I \times K}$ and $\mathbf{B}_{K \times J}$ is defined in the standard way

$$C[i, j] = \sum_{k \in K} A[i, k] \cdot B[k, j]$$

(it can be extended to semirings !!!)

The product of two compatible networks $\mathcal{N}_A = ((I, K), L_A, a)$ and $\mathcal{N}_B = ((K, J), L_B, b)$ is the network $\mathcal{N}_C = ((I, J), L_C, c)$ where $L_C = \{(i, j) : c[i, j] \neq \square\}$ and the weight c is determined by the matrix \mathbf{C} , $c(i, j) = C[i, j]$.

Multiplication of networks

Projections of
weighted
two-mode
networks

V. Batagelj


Two-mode
networks

Projections

Outer product
decomposition

Fractional
approach

References



In binary networks \mathcal{N}_A and \mathcal{N}_B , the value of $C[i,j]$ of $\mathbf{C} = \mathbf{A} \cdot \mathbf{B}$ counts the number of ways we can go from the node $i \in I$ to the node $j \in J$ passing through K , $C[i,j] = |N_A(i) \cap N_B(j)|$.

$$C[i,j] = \sum_{k \in N_A(i) \cap N_B(j)} A[i,k] \cdot B[k,j]$$



Standard projections

Projections of
weighted
two-mode
networks

V. Batagelj

Two-mode
networks

Projections

Outer product
decomposition

Fractional
approach

References

A standard approach to the analysis of a two-mode network UV is to transform it into the corresponding one-mode networks determined by:

row projection to U : $UU = \text{row}(UV) = UV \cdot UV^T$, or
column projection to V : $VV = \text{col}(UV) = UV^T \cdot UV$

and analyze the obtained weighted network.

$$\text{col}(UV) = UV^T \cdot UV = UV^T \cdot (UV^T)^T = \text{row}(UV^T)$$

$$\text{row}(UV) = \text{col}(UV^T)$$

We will limit our discussion to column projections.



Outer product decomposition

Projections of
weighted
two-mode
networks

V. Batagelj

Two-mode
networks

Projections

Outer product
decomposition

Fractional
approach

References

For vectors $x = [x_1, x_2, \dots, x_n]$ and $y = [y_1, y_2, \dots, y_m]$ their *outer product* $x \circ y$ is defined as a matrix

$$x \circ y = [x_i \cdot y_j]_{n \times m}$$

then we can express the product \mathbf{C} of two compatible matrices \mathbf{A} and \mathbf{B} as the *outer product decomposition*

$$\mathbf{C} = \mathbf{A} \cdot \mathbf{B} = \sum_k \mathbf{H}_k \quad \text{where} \quad \mathbf{H}_k = \mathbf{A}[\cdot, k] \circ \mathbf{B}[k, \cdot],$$

$\mathbf{A}[\cdot, k]$ is the k -th column of matrix \mathbf{A} , and $\mathbf{B}[k, \cdot]$ is the k -th row of matrix \mathbf{B} .

On the basis of outer product decomposition we have

$$T(\mathbf{C}) = T\left(\sum_k \mathbf{H}_k\right) = \sum_k T(\mathbf{H}_k) \quad \text{and} \quad T(\mathbf{H}_k) = \text{wid}_A(k) \cdot \text{wod}_B(k)$$



Structure of projection

Projections of
weighted
two-mode
networks

V. Batagelj

Two-mode
networks

Projections

Outer product
decomposition

Fractional
approach

References

In words

- 1 the product network is a sum of complete subgraphs;
- 2 the contribution of a node $k \in K$ to the total T is $T(\mathbf{H}_k)$.

This means that the nodes with different weighted degrees in K are not equally represented in the projection.

For a column projection $\mathbf{V}\mathbf{V} = \text{col}(\mathbf{U}\mathbf{V})$, a real-life network \mathcal{UV} can contain nodes $u \in U$ of degree 0 (in WA, works with no author) and 1 (in WA, single author works). Nodes from U of degree 0 do not contribute to the matrix $\mathbf{V}\mathbf{V}$, and nodes of degree 1 contribute only to its neighbor's diagonal entry.

$$n(\mathbf{UV}) = [n(UV)[u, v]]$$

$$n(UV)[u, v] = \begin{cases} \frac{UV[u, v]}{\text{wod}_{UV}(u)} & u \in \hat{U} \\ 0 & u \notin \hat{U} \end{cases}$$

$$T(n(\mathbf{UV})) = \sum_{u \in U} \text{wod}_{n(UV)}(u) = \sum_{u \in \hat{U}} 1 = |\hat{U}|$$

Interpretation: probabilistic co-linkage.

Fractional co-appearance: $\mathbf{Cn} = n(\mathbf{UV})^T \cdot n(\mathbf{UV})$,

$$Cn[v, z] = \sum_{u \in \hat{U}} \frac{UV[u, v] \cdot UV[u, z]}{\text{wod}(u)^2}$$

$$Cn[v, z] = Cn[z, v], \quad T(u) = T(\mathbf{H}_u) = \text{wod}_{n(UV)}(u)^2$$

$$T(\mathbf{Cn}) = \sum_{u \in U} \text{wod}_{n(UV)}(u)^2 = \sum_{u \in \hat{U}} 1 = |\hat{U}|$$

Total weight preserving normalization

$$s(UV)[u, v] = \begin{cases} \frac{UV[u, v]}{\sqrt{\text{wod}_{UV}(u)}} & u \in \hat{U} \\ 0 & u \notin \hat{U} \end{cases}$$

$$\text{wod}_n(UV)(u) = \begin{cases} 1 & u \in \hat{U} \\ 0 & u \notin \hat{U} \end{cases}, \quad \text{wod}_s(UV)(u) = \begin{cases} \sqrt{\text{wod}_{UV}(u)} & u \in \hat{U} \\ 0 & u \notin \hat{U} \end{cases}$$

Total weight preserving projection: $\mathbf{Cs} = s(\mathbf{UV})^T \cdot s(\mathbf{UV})$

$$Cs[v, z] = \sum_{u \in \hat{U}} \frac{UV[u, v] \cdot UV[u, z]}{\text{wod}(u)}$$

$$Cs[v, z] = Cs[z, v], \quad T(u) = \text{wod}_s(UV)(u)^2 = \text{wod}_{UV}(u)$$

$$T(\mathbf{Cs}) = \sum_{u \in U} \text{wod}_s(UV)(u)^2 = \sum_{u \in \hat{U}} \text{wod}_{UV}(u) = T(\mathbf{UV})$$

Embedding primary node values

Node values $c : U \rightarrow \mathbb{R}_0^+$ – impact factor, number of citations, ...

$$x(UV)[u, v] = \begin{cases} \frac{\sqrt{c(u)}}{\text{wod}_{UV}(u)} UV[u, v] & u \in \hat{U} \\ 0 & u \notin \hat{U} \end{cases}$$

$$\text{wod}_{x(UV)}(u) = \begin{cases} \sqrt{c(u)} & u \in \hat{U} \\ 0 & u \notin \hat{U} \end{cases}$$

Embedded primary node values: $\mathbf{Cx} = x(\mathbf{UV})^T \cdot x(\mathbf{UV})$

$$Cx[v, z] = \sum_{u \in \hat{U}} \frac{c(u)}{\text{wod}(u)^2} UV[u, v] \cdot UV[u, z], \quad Cx[v, z] = Cx[z, v]$$

$$T(u) = \sum_{v \in V} \sum_{z \in V} Cx[v, z] = \frac{c(u)}{\text{wod}(u)^2} \sum_{v \in V} UV[u, v] \cdot \sum_{z \in V} UV[u, z] = c(u)$$

$$T(\mathbf{Cx}) = \sum_{u \in U} \text{wod}_{x(UV)}(u)^2 = \sum_{u \in \hat{U}} c(u)$$



Binarization and left and right (fractional) contribution

Projections of
weighted
two-mode
networks

V. Batagelj

Two-mode
networks

Projections

Outer product
decomposition

Fractional
approach

References

Binarization: $b(\mathbf{UV})$: $b(UV)[u, v] = \delta(UV[u, v] \neq \square)$

Left contribution: $L(\mathbf{UV}) = \mathbf{UV} \cdot b(\mathbf{UV})^T$

$$L(UV)[u, t] = \sum_{v \in V} UV[u, v] \cdot b(UV)[t, v] = \text{wod}_{UV}(u/t)$$

Left fractional contribution: $\ell(\mathbf{UV}) = n(\mathbf{UV}) \cdot b(\mathbf{UV})^T$

$$\ell(UV)[u, t] = \frac{1}{\text{wod}_{UV}(u)} \sum_{v \in V} UV[u, v] \cdot b(UV)[t, v] = \frac{\text{wod}_{UV}(u/t)}{\text{wod}_{UV}(u)} \leq 1$$

Right fractional contribution: $r(\mathbf{UV}) = b(\mathbf{UV}) \cdot n(\mathbf{UV})^T$

$$r(UV)[u, t] = \frac{1}{\text{wod}_{UV}(t)} \sum_{v \in V} b(UV)[u, v] \cdot UV[t, v] = \frac{\text{wod}_{UV}(t/u)}{\text{wod}_{UV}(t)}$$

$$r(UV)[u, t] = \ell(UV)[t, u]$$

$$\begin{aligned} VV_X[u, t] &= \text{meanX}(\ell(UV)[u, t], r(UV)[u, t]) \\ &= \text{meanX}(\ell(UV)[u, t], \ell(UV)[t, u]) \end{aligned}$$

$$VV_A[u, t] = \frac{1}{2}(\ell(UV)[u, t] + \ell(UV)[t, u]) - \text{arithmetic mean}$$

$$VV_m[u, t] = \min(\ell(UV)[u, t], \ell(UV)[t, u]) - \text{minimum}$$

$$VV_M[u, t] = \max(\ell(UV)[u, t], \ell(UV)[t, u]) - \text{maximum}$$

$$VV_G[u, t] = \sqrt{\ell(UV)[u, t] \cdot \ell(UV)[t, u]} - \text{geometric, Salton}$$

$$VV_H[u, t] = 2(\ell(UV)[u, t]^{-1} + \ell(UV)[t, u]^{-1})^{-1} - \text{harmonic, Dice}$$

$$VV_J[u, t] = (\ell(UV)[u, t]^{-1} + \ell(UV)[t, u]^{-1} - 1)^{-1} - \text{Jaccard}$$

Note: $\ell(\mathbf{UV})$ can be computed from $L(\mathbf{UV})$

$$L(UV)[u, u] = \text{wod}_{UV}(u/u) = \text{wod}_{UV}(u).$$

It holds: $VV_X[u, t] = VV_X[t, u]$, $VV_X[u, t] \in [0, 1]$ and $VV_J[u, t] \leq VV_m[u, t] \leq VV_H[u, t] \leq VV_G[u, t] \leq VV_A[u, t] \leq VV_M[u, t]$.



Conclusions

Projections of
weighted
two-mode
networks

V. Batagelj

Two-mode
networks

Projections

Outer product
decomposition

Fractional
approach

References

- some projections (Salton, Jaccard, etc.) can be approached also considering a projection matrix as a table of the inner products of rows/columns.
- in principle we can base a projection on any resemblance measure between rows/columns (related to our question(s))
- <https://github.com/bavla/NormNet/>



Acknowledgments

Projections of
weighted
two-mode
networks

V. Batagelj

Two-mode
networks








Projections

Outer product
decomposition

Fractional
approach

References

This work is supported in part by the Slovenian Research Agency (research program P1-0294 and research projects J1-9187 and J5-2557), and prepared within the framework of the HSE University Basic Research Program.

-  Batagelj, V.: Pajek / Example – Slovenian magazines and journals. Dagstuhl seminar, 2001. [WWW](#)
-  Batagelj, V., Mrvar, A. (2003). Density-based approaches to network analysis; Analysis of Reuter's terror news network. Workshop on Link Analysis for Detecting Complex Behavior (LinkKDD2003), August 27, 2003. [PDF](#)
-  Batagelj, V, Cerinšek, M.: On bibliographic networks. Scientometrics 96 (2013), pages 845–864. [Springer](#)
-  Batagelj, V., Doreian, P., Ferligoj, A., Kejžar, N.: Understanding Large Temporal Networks and Spatial Networks. [Wiley](#) 2014.
-  Batagelj, V.: On fractional approach to the analysis of linked networks. Scientometrics 123 (2020), pages 621–633. [Springer](#)
-  Batagelj, V., Maltseva, D.: Temporal bibliographic networks. Journal of Informetrics, 14 (2020) 1, 101006.
-  Batagelj, V. (2021). Analysis of the Southern women network using the fractional approach. Social Networks 68, 229–236.



Borgatti, S.P., Halgin, D.S. (2014) Analyzing Affiliation Networks. Chapter 28 in The SAGE Handbook of Social Network Analysis. John Scott, Peter J. Carrington (Eds.), Sage.



Davis, A., Gardner, BB., Gardner, MR. (1941) Deep South. University of Chicago Press, Chicago, IL.



Deza, M.M., Deza, E. (2013) Encyclopedia of Distances. Springer.



Jana Krejčí: Multi-Criteria Decision Making with a new Fuzzy Approach; Pairwise Comparison Matrices and their Fuzzy Extension. Springer 2018.



Leydesdorff, L. (2008). On the normalization and visualization of author co-citation data: Salton's Cosine versus the Jaccard index. Journal of the American Society for Information Science and Technology, 59(1), 77-85.



Pajek datasets: Journals / Slovenian magazines and journals 1999 and 2000. [WWW](http://www.pajek.net)