

Weighted
two-mode
projections

V. Batagelj

Introduction

Collaboration
counting

Fractional
approach

Strict
fractional
collaboration

Computing

Conclusions

References

On weighted two-mode network projections

Vladimir Batagelj
UP FAMNIT Koper

1338. sredin seminar
Ljubljana, August 9, 2023

Outline

Weighted
two-mode
projections

V. Batagelj

Introduction

Collaboration
counting

Fractional
approach


Strict
fractional
collaboration

Computing

Conclusions

References

- 1 Introduction
- 2 Collaboration counting
- 3 Fractional approach
- 4 Strict fractional collaboration
- 5 Computing
- 6 Conclusions
- 7 References



Vladimir Batagelj: vladimir.batagelj@fmf.uni-lj.si
Current version of slides (August 9, 2023 at 17:30): [PDF](#)
European science

Motivation

Weighted
two-mode
projections

V. Batagelj

Introduction

Collaboration
counting

Fractional
approach

Strict
fractional
collaboration

Computing

Conclusions

References

In the paper [4] we studied the collaboration (co-authorship) between scientists from different post-Soviet countries. We decided to repeat the study on the European countries. It turned out that there are different ways how we can define a network describing the co-authorship collaboration between countries. Some options are discussed in this paper.

From the Centre for Science & Technology Studies (CWTS), Leiden University, NL we obtained data for the years 2000-2022.

Some exploratory analyses

Europe 2019 by levels

Weighted two-mode projections

V. Batagelj

Introduction


Collaboration counting

Fractional approach

Strict fractional collaboration

Computing

Conclusions



Europe by levels

Europe 2019 closest neighbor skeleton

Weighted two-mode projections

V. Batagelj

Introduction

Collaboration counting


Fractional approach

Strict fractional collaboration

Computing

Conclusions

References



Europe closest neighbor

Europe 2019 PathFinder skeleton

Weighted two-mode projections

V. Batagelj

Introduction

Collaboration counting


Fractional approach

Strict fractional collaboration

Computing

Conclusions

References



Europe PathFinder skeleton

Two-mode networks

Weighted
two-mode
projections

V. Batagelj

Introduction

Collaboration
counting

Fractional
approach

Strict
fractional
collaboration

Computing

Conclusions

References

In a *two-mode* (affiliation or bipartite) network $\mathcal{N} = ((U, V), L, w)$ the set of nodes is split into two disjoint sets (*modes*) U and V . Each link $e \in L$ has one end-node $u \in U$ and the other end-node $v \in V$, $\text{ext}(e) = (u, v)$. The function $w : L \rightarrow \mathbb{R}$ assigns to each link its weight.

NAME OF PARTICIPANTS OF GROUP I	CODE NUMBERS AND DATES OF SOCIAL EVENTS REPORTED IN <i>Old City Herald</i>													
	(1) 6/27	(2) 3/2	(3) 4/12	(4) 9/26	(5) 2/25	(6) 5/19	(7) 3/15	(8) 9/16	(9) 4/8	(10) 6/10	(11) 2/23	(12) 4/7	(13) 11/21	(14) 8/3
1. Mrs. Evelyn Jefferson.....	X	X	X	X	X	X	X		X					
2. Miss Laura Mandeville.....	X	X	X		X	X	X	X						
3. Miss Theresa Anderson.....		X	X	X	X	X	X	X						
4. Miss Brenda Rogers.....	X		X	X	X	X	X	X						
5. Miss Charlotte McDowd.....			X	X	X		X							
6. Miss Frances Anderson.....			X		X		X		X					
7. Miss Eleanor Nye.....				X	X	X	X	X						
8. Miss Pearl Oglethorpe.....					X			X		X				
9. Miss Ruth DeSand.....						X	X	X	X					
10. Miss Verne Sanderson.....							X	X	X	X			X	
11. Miss Mym Liddell.....								X	X	X	X		X	
12. Miss Katherine Rogers.....									X	X	X		X	X
13. Mrs. Sylvia Avondale.....									X	X	X		X	X
14. Mrs. Nora Fayette.....									X	X	X	X	X	X
15. Mrs. Helen Lloyd.....									X	X		X	X	
16. Mrs. Dorothy Murchison.....									X	X				
17. Mrs. Olivia Carleton.....									X		X			
18. Mrs. Flora Price.....									X		X			

Davis: Southern women, 1941

Two-mode network matrix and some notions

Weighted
two-mode
projections

V. Batagelj

Introduction

Collaboration
counting

Fractional
approach

Strict
fractional
collaboration

Computing
Conclusions

References

In general, the weight can be measured on different measurement scales (counts, ratio, interval, ordinal, nominal, binary, TQ, etc.).

We extend the semiring $(\mathbb{R} \cup \{\square\}, +, \cdot)$ with a new zero \square with rules $\square + a = a$ and $\square \cdot a = a \cdot \square = \square$.

The network **matrix** $\mathbf{M} = [m[u, v]]$ of a two-mode network \mathcal{N} is defined as

$$m[u, v] = \begin{cases} \sum_{e \in L : \text{ext}(e) = (u, v)} w(u, v) & \exists e \in L : \text{ext}(e) = (u, v) \\ \square & \text{otherwise} \end{cases}$$

Multiplication of networks

Weighted
two-mode
projections

V. Batagelj

Introduction

Collaboration
counting

Fractional
approach

Strict
fractional
collaboration

Computing

Conclusions

References

The *product* $\mathbf{C} = \mathbf{A} \cdot \mathbf{B}$ of two compatible matrices $\mathbf{A}_{I \times K}$ and $\mathbf{B}_{K \times J}$ is defined in the standard way

$$C[i, j] = \sum_{k \in K} A[i, k] \cdot B[k, j]$$

(it can be extended to semirings !!!)

The product of two compatible networks $\mathcal{N}_A = ((I, K), L_A, a)$ and $\mathcal{N}_B = ((K, J), L_B, b)$ is the network $\mathcal{N}_C = ((I, J), L_C, c)$ where $L_C = \{(i, j) : c[i, j] \neq \square\}$ and the weight c is determined by the matrix \mathbf{C} , $c(i, j) = C[i, j]$.

Multiplication of networks

Weighted two-mode projections

V. Batagelj

Introduction

Collaboration counting


Fractional approach

Strict fractional collaboration

Computing

Conclusions

References



In binary networks \mathcal{N}_A and \mathcal{N}_B , the value of $C[i,j]$ of $\mathbf{C} = \mathbf{A} \cdot \mathbf{B}$ counts the number of ways we can go from the node $i \in I$ to the node $j \in J$ passing through K , $C[i,j] = |\mathcal{N}_A(i) \cap \mathcal{N}_B(j)|$.

$$C[i,j] = \sum_{k \in \mathcal{N}_A(i) \cap \mathcal{N}_B(j)} A[i,k] \cdot B[k,j]$$

Projections of binary two-mode networks

Weighted two-mode projections

V. Batagelj

Introduction

Collaboration
counting

Fractional
approach

Strict
fractional
collaboration

Computing

Conclusions

References

Most of the bibliometric networks are obtained by a projection of a non-weighted network represented by a binary matrix. For example from the authorship network WA describing the authorship relation of the set of works (papers, books, reports, etc.) W by the authors from the sets A . It is represented by a matrix $WA = [wa[w, a]]$ where $wa[w, a] = 1$ iff a is an author of the work w and 0 otherwise. We get the co-authorship (counting) network Co_A determined by the projection

$$Co_A = WA^T \cdot WA$$

... Projections of binary two-mode networks

Weighted two-mode projections

V. Batagelj

Introduction

Collaboration
counting

Fractional
approach

Strict
fractional
collaboration

Computing

Conclusions

References

As we know [2]

- For $a \neq b$, $co_A[a, b] =$ number of works co-authored by authors a and b .
- $co_A[a, a] =$ number of works from W written by the author a .
- The works with a large number of coauthors are "overrepresented" in the network Co_A – for example, the co-authorship of authors of a paper with 2 authors counts the same as the co-authorship between any pair of authors of the paper with 1000 co-authors; a paper with 1000 co-authors adds 1000000 links to projection network; while a single author paper only a loop. For this reason, the number $co_A[a, b]$ is not the best measure for measuring the collaboration intensity.

Weighted projections

Weighted two-mode projections

V. Batagelj

Introduction

Collaboration
counting

Fractional
approach

Strict
fractional
collaboration

Computing

Conclusions

References

The case of collaboration between countries is slightly different because the two-mode network WC is weighted. Actually, we could get it as $WC = WA \cdot AC$ where AC is the author-to-country affiliation network. This view opens a possibility to deal with authors affiliated to different countries provided that $\sum_c ac[a, c] = 1$. If the affiliations are changing through time the temporal quantities can be used [3].

To obtain a collaboration network between a set of countries C based on a set of works W , we start with a two-mode network WC described by a matrix $WC = [wc[w, c]]$ where

$$wc[w, c] = \text{number of authors of the work } w \text{ from the country } c$$

Authors counting collaboration

Weighted
two-mode
projections

V. Batagelj

Introduction

Collaboration
counting

Fractional
approach

Strict
fractional
collaboration

Computing

Conclusions

References

In the network WC we can consider all authors of selected works W by adding to the set of countries C also the "country" Others. Instead of countries, other partitions of the set of authors can be used, for example, institutions.

We will use $T(N) = \sum_{e \in L} w(e)$ to denote the total sum of weights of all links of the network $N = (V, L, w)$.

The *authors counting collaboration* network Co_C described by the matrix \mathbf{Co}_C is obtained by projection

$$\mathbf{Co}_C = \mathbf{WC}^T \cdot \text{bin}(\mathbf{WC})$$

where $\text{bin}(\mathbf{WC}) = [\widehat{wc}[w, c]]$, and $\widehat{wc}[w, c] = 1$ iff $wc[w, c] \neq 0$ and 0 otherwise.

... Authors counting collaboration

What are the meaning of the entries $co_C[a, b]$ and their properties?

- a For $a \neq b$, $co_C[a, b] = \sum_w wc[w, a] \cdot \widehat{wc}[w, b]$ – number of appearances of **authors** from the country a in works co-authored also by some author from the country b . We will denote this number $wdeg_{WC}(a/b)$.
- b $co_C[a, a] = \sum_w wc[w, a] \cdot \widehat{wc}[w, a] = wdeg_{WC}(a)$ – number of appearances of authors from the country a in works from W ; a column sum for country a in the matrix **WC**.
- c From a simple example

$$WC = \begin{matrix} & \begin{matrix} c_1 & c_2 & c_3 \end{matrix} \\ \begin{matrix} w_1 \\ w_2 \\ w_3 \\ w_4 \\ w_5 \\ w_6 \end{matrix} & \left[\begin{matrix} 0 & 2 & 1 \\ 2 & 1 & 0 \\ 1 & 3 & 1 \\ 3 & 0 & 2 \\ 2 & 3 & 1 \\ 1 & 0 & 3 \end{matrix} \right] \end{matrix}$$

$$Co_C = \begin{matrix} & \begin{matrix} c_1 & c_2 & c_3 \end{matrix} \\ \begin{matrix} c_1 \\ c_2 \\ c_3 \end{matrix} & \left[\begin{matrix} 9 & 5 & 7 \\ 7 & 9 & 8 \\ 7 & 3 & 8 \end{matrix} \right] \end{matrix}$$

we see that the matrix **CoC** is in general not symmetric – there can exist pairs a, b such that $co_C[a, b] \neq co_C[b, a]$.

... Authors counting collaboration

Weighted two-mode projections

V. Batagelj

Introduction

Collaboration
counting

Fractional
approach

Strict
fractional
collaboration

Computing

Conclusions

References

- d Consider a row sum $R(a)$ for the country a in the matrix \mathbf{CoC} .
We get

$$R(a) = \sum_b co_C[a, b] = \sum_w wc[w, a] \cdot \sum_b \widehat{wc}[w, b] = \sum_w wc[w, a] \cdot \deg_{WC}(w)$$

Since in the network WC only works W with co-authors from at least 2 countries are considered, we have $\deg_{WC}(w) \geq 2$ and we can continue $R(a) \geq 2 \sum_w wc[w, a] = 2 \text{wdeg}_{WC}(a)$. Now, combined with \mathbf{b} , we finally get

$$\sum_{b: b \neq a} co_C[a, b] \geq \text{wdeg}_{WC}(a) = co_C[a, a]$$

The sum of the out-diagonal entries in the a row of the matrix \mathbf{CoC} is larger or equal to its diagonal entry.

From the example in c we see that this property does not hold for columns – see the column c_2 .

... Authors and works counting collaboration

- e For the diagonal values of the network \mathbf{Co}_C it holds
 $coc[c, c] = \text{wdeg}_{WC}(c)$

$$coc[c, c] = \sum_w wc[w, c] \cdot \widehat{wc}[w, c] = \sum_w wc[w, c] = \text{wdeg}_{WC}(c)$$

Therefore $\sum_c coc[c, c] = T(WC)$.

- f In the case when also the matrix \mathbf{WC} is binary,
 $\text{bin}(\mathbf{WC}) = \mathbf{WC}$, we deal with the standard projection
mentioned in the introduction $\mathbf{Co}_C = \mathbf{WC}^T \cdot \mathbf{WC}$. In the **works
counting collaboration** network $\mathbf{Co}_b = \text{bin}(\mathbf{WC})^T \cdot \text{bin}(\mathbf{WC})$ its
weight $co_b[a, b]$ counts **works**: $co_b[a, b] =$ number of works
from W co-authored by authors from countries a and b , and
 $co_b[a, a] =$ number of works from W co-authored by authors
from the country a . Note that the inequality from d still holds
(and also for columns).

Normalizations

Weighted
two-mode
projections

V. Batagelj

Introduction
Collaboration
counting

Fractional
approach

Strict
fractional
collaboration

Computing
Conclusions
References

For binary networks, we define their normalized versions: *standard*
 $n(\mathbf{WA}) = [wan[w, a]]$

$$wan[w, a] = \frac{wa[w, a]}{\max(1, \deg_{\mathbf{WA}}(w))}$$

and *strict* (or Newman's) $N(\mathbf{WA}) = [waN[w, a]]$

$$waN[w, a] = \frac{wa[w, a]}{\max(1, \deg_{\mathbf{WA}}(w) - 1)}$$

Using the normalized networks we define the *standard fractional projection*

$$\mathbf{Co}_n = n(\mathbf{WA})^T \cdot n(\mathbf{WA})$$

and the *strict fractional projection*

$$\mathbf{Co}_N = D_0(n(\mathbf{WA})^T \cdot N(\mathbf{WA}))$$

where the function $D_0(\mathbf{M})$ sets the diagonal of a square matrix \mathbf{M} to 0.

We know [1] that if $\deg_{\mathbf{WA}}(w) > 0$, each work $w \in W$ contributes equally, a unit 1, to the total weight of links in \mathbf{Co}_n . The same holds for \mathbf{Co}_N if $\deg_{\mathbf{WA}}(w) > 1$.

Standard weighted projection

Weighted
two-mode
projections

V. Batagelj

Introduction

Collaboration
counting

Fractional
approach

Strict
fractional
collaboration

Computing

Conclusions

References

To extend the fractional projections to weighted two-mode networks we define for the *standard* case $n(\mathbf{WC}) = [wcn[w, c]]$

$$wcn[w, c] = \frac{wc[w, c]}{\max(1, \text{wdeg}_{\mathbf{WC}}(w))}$$

Again we have $T(\mathbf{Co}_n) = |W|$ for $\mathbf{Co}_n = n(\mathbf{WC})^T \cdot n(\mathbf{WC})$.

$$\mathbf{Co}_b = \begin{matrix} & c_1 & c_2 & c_3 \\ c_1 & \left[\begin{array}{ccc} 5 & 3 & 4 \\ 3 & 4 & 3 \\ 4 & 3 & 5 \end{array} \right] \\ c_2 & & & \\ c_3 & & & \end{matrix} \quad \mathbf{Co}_n = \begin{matrix} & c_1 & c_2 & c_3 \\ c_1 & \left[\begin{array}{ccc} 1.0180556 & 0.5088889 & 0.5230556 \\ 0.5088889 & 1.1655556 & 0.4255556 \\ 0.5230556 & 0.4255556 & 0.9013889 \end{array} \right] \\ c_2 & & & \\ c_3 & & & \end{matrix}$$

Computation in R

Strict weighted projection

Weighted two-mode projections

V. Batagelj

Introduction

Collaboration
counting

Fractional
approach

Strict
fractional
collaboration

Computing

Conclusions

References

There is no obvious way how to define the strict normalization for weighted networks.

There is another possible view on fractional projections. The definition of matrix $n(\mathbf{WA})$ can be written as $n(\mathbf{WA}) = \mathbf{d}_n \cdot \mathbf{WA}$ and similarly $N(\mathbf{WA}) = \mathbf{d}_N \cdot \mathbf{WA}$ where \mathbf{d}_n is a diagonal $W \times W$ matrix with $d_n[w, w] = 1 / \max(1, \deg_{\mathbf{WA}}(w))$ and \mathbf{d}_N with $d_N[w, w] = 1 / \max(1, \deg_{\mathbf{WA}}(w) - 1)$. In both cases we get ($\mathbf{d}^T = \mathbf{d}$)

$$\mathbf{Co}_n = n(\mathbf{WA})^T \cdot n(\mathbf{WA}) = \mathbf{WA}^T \cdot \mathbf{d}_n \cdot \mathbf{d}_n \cdot \mathbf{WA}$$

$$\mathbf{Co}_N = n(\mathbf{WA})^T \cdot N(\mathbf{WA}) = \mathbf{WA}^T \cdot \mathbf{d}_n \cdot \mathbf{d}_N \cdot \mathbf{WA}$$

Because a product of diagonal matrices is a diagonal matrix, $\text{diag}(a_w) \cdot \text{diag}(b_w) = \text{diag}(a_w \cdot b_w)$, both cases have a common form $\mathbf{WA}^T \cdot \mathbf{d} \cdot \mathbf{WA}$. It can be related to the weighted scalar product. Maybe this form can lead also to the extension of strict projection for weighted two-mode networks.

... Strict weighted projection

Weighted
two-mode
projections

V. Batagelj

Introduction

Collaboration
counting

Fractional
approach

Strict
fractional
collaboration

Computing
Conclusions

References

Let us look at a simple example. Assume, that a work w has authors from three countries a , b , and c . Then, since the co-authors inside the same country do not count, its contribution $T(w)$ to the total weight, see the contribution matrix

$$\text{Co}_C(w) = \begin{bmatrix} & a & & b & & c \\ a & \mathbf{0} & & wc[w, a] \cdot wc[w, b] & & wc[w, a] \cdot wc[w, c] \\ b & & wc[w, b] \cdot wc[w, a] & \mathbf{0} & & wc[w, b] \cdot wc[w, c] \\ c & & wc[w, c] \cdot wc[w, a] & & wc[w, c] \cdot wc[w, b] & \mathbf{0} \end{bmatrix},$$

is $T(w) = \sum_{e,f \in \{a,b,c\} \wedge e \neq f} wc[w, e] \cdot wc[w, f]$. By the rule of product and the rule of sum from basic combinatorics [5], $T(W)$ is equal to twice the number of all co-authorships of authors from different countries – pairs (a, b) and (b, a) are representing co-authorship of authors a and b .

... Strict weighted projection

Weighted two-mode projections

V. Batagelj

Introduction

Collaboration
counting

Fractional
approach

Strict
fractional
collaboration

Computing

Conclusions

References

To make $T_N(w) = 1$ we must set the entry $d_N[w, w]$ of the diagonal matrix \mathbf{d}_N for the weighted network \mathbf{WC} to
 $d_N[w, w] = 1/T(w) = 1/(\text{wdeg}_{WC}(w)^2 - \sum_c wc[w, c]^2)$.

Note that $\sum_c wc[w, c] = \text{wdeg}_{WC}(w)$ and

$$\text{wdeg}_{WC}(w)^2 - \sum_c wc[w, c]^2 = \sum_{e, f: e \neq f} wc[w, e] \cdot wc[w, f]$$

The left side of this equality is computationally more convenient.

Introduction

Collaboration
counting

Fractional
approach

Strict
fractional
collaboration

Computing

Conclusions

References

... Strict weighted projection

It is easy to see that we made a good guess – in the corresponding projection $\mathbf{Co}_N = D_0(\mathbf{WC}^T \cdot \mathbf{d}_N \cdot \mathbf{WC})$ each work contributes equally, a unit 1, to the total of link weights.

$$T_N(w) = d_N[w, w] \cdot \sum_{e, f: e \neq f} wc[w, e] \cdot wc[w, f] = 1$$

Therefore

$$T(\mathbf{Co}_N) = \sum_w T_N(w) = |W|$$

For our example from Section 2 c we get

$$\mathbf{Co}_N = \begin{matrix} & c_1 & c_2 & c_3 \\ c_1 & 0.000000 & 0.9870130 & 1.1623377 \\ c_2 & 0.987013 & 0.0000000 & 0.8506494 \\ c_3 & 1.162338 & 0.8506494 & 0.0000000 \end{matrix}$$

with $T(\mathbf{Co}_N) = 6$.

Weighted projections

Weighted two-mode projections

V. Batagelj

Introduction

Collaboration
counting

Fractional
approach

Strict
fractional
collaboration

Computing

Conclusions

References

C is a set of countries of our interest. If it is used, $\text{others} \in C$. \mathcal{W} is a list of metadata about the works from the selected bibliographic data source, co-authored by authors from at least two different countries from $C \setminus \{\text{others}\}$. All four projection matrices \mathbf{Co}_b , \mathbf{Co}_n , \mathbf{Co}_C , and \mathbf{Co}_N can be constructed in a single run through the list using the Algorithm given in the following slides.

Computing weighted projections I

Weighted
two-mode
projections

V. Batagelj

Introduction

Collaboration
counting

Fractional
approach

Strict
fractional
collaboration

Computing

Conclusions

References

```
1: function PROJECTIONS( $\mathcal{W}, C$ )
2:    $Cob \leftarrow Con \leftarrow CoC \leftarrow CoN \leftarrow matrix(0, nrow = |C|, ncol = |C|)$ 
3:   for  $w \in \mathcal{W}$  do
4:     from the metadata of work  $w$  determine the list of pairs
        $Lw = ((a, ca)), \quad a - \text{author. } ca - \text{country of } a$ 
5:      $Cw \leftarrow empty$ 
6:     for  $(a, ca) \in Lw$  do
7:        $c \leftarrow ca$  if  $ca \in C$  else others
8:       if  $c \notin Cw$  then
9:          $Cw[c] \leftarrow 0$ 
10:      end if
11:       $Cw[c] \leftarrow Cw[c] + 1$ 
12:    end for
13:    write ID of  $w$  and  $Cw$  to the file WC
14:     $wdegw \leftarrow \sum_{c \in Cw} Cw[c]$ 
15:     $sqw \leftarrow \sum_{c \in Cw} Cw[c]^2$ 
16:     $dnw \leftarrow 1/wdegw^2$ 
17:     $dNw \leftarrow 1/(wdegw^2 - sqw)$ 
```

Computing weighted projections II

Weighted two-mode projections

V. Batagelj

Introduction

Collaboration
counting

Fractional
approach

Strict
fractional
collaboration

Computing

Conclusions

References

```
18:      for  $e \in Cw$  do
19:          for  $f \in Cw$  do
20:               $Cob[e, f] \leftarrow Cob[e, f] + 1$ 
21:               $CoC[e, f] \leftarrow CoC[e, f] + Cw[e]$ 
22:               $Con[e, f] \leftarrow Con[e, f] + Cw[e] \cdot Cw[f] \cdot dnw$ 
23:              if  $e \neq f$  then
24:                   $CoN[e, f] \leftarrow CoN[e, f] + Cw[e] \cdot Cw[f] \cdot dNw$ 
25:              end if
26:          end for
27:      end for
28:  end for
29:  return  $Cob, Con, CoC, CoN$ 
30: end function
```

Test in R

Notes on the implementation of the algorithm

Weighted two-mode projections

V. Batagelj

Introduction

Collaboration
counting

Fractional
approach

Strict
fractional
collaboration

Computing

Conclusions

References

- A natural implementation of the counters Cw is as a dictionary.
- Line 13 is optional. It creates the file WC describing the two-mode network WC .
- Networks Co_b , Co_n , and Co_N are symmetric. They can be represented by an undirected network with the weight of an edge $(e : f)$ equal to twice the computed value, except for loops. The computation can be restricted to pairs (e, f) for which $e \leq f$.

Conclusions

Weighted
two-mode
projections

V. Batagelj

Introduction

Collaboration
counting

Fractional
approach

Strict
fractional
collaboration

Computing

Conclusions

References

In the paper, we derived the results in terms of the binary authorship network WA and the weighted network WC . The results hold in general for similar weighted two-mode networks such as

- (journals, universities, number of published articles of authors from the university u in the journal j in the selected time interval),
- (territorial units, universities, number of students from the territorial unit t studying this year at the university u),
- (web resources (movies or music tracks), types of resource, number of times the resource r of type t was downloaded in the selected time interval),
- (retail chain customers (chain card owners), (types of) products, the value of the product p bought by the customer c in the selected time interval),

etc.

References |

Weighted two-mode projections

V. Batagelj

Introduction

Collaboration
counting

Fractional
approach

Strict
fractional
collaboration

Computing

Conclusions

References

-  Batagelj, V: On fractional approach to analysis of linked networks. *Scientometrics* 123 (2020) 2: 621-633
<https://doi.org/10.1007/s11192-020-03383-y>
-  Batagelj, V, Cerinšek, M: On bibliographic networks. *Scientometrics* 96 (2013) 3, 845-864.
<https://doi.org/10.1007/s11192-012-0940-1>
-  Batagelj, V, Maltseva, D: Temporal bibliographic networks. *Journal of Informetrics*, Volume 14, Issue 1, February 2020, 101006.
<https://doi.org/10.1016/j.joi.2020.101006>
-  Matveeva, N., Batagelj, V., Ferligoj, A.: Scientific collaboration of post-Soviet countries: the effects of different network normalizations. *Scientometrics* 128 (2023), 4219–4242.
<https://doi.org/10.1007/s11192-023-04752-z>
-  Wikipedia: Combinatorial principles.
https://en.wikipedia.org/wiki/Combinatorial_principles