

Towards a format for describing networks

Format elements

Vladimir Batagelj^{1,2,3,4}[0000–0002–0240–9446],
Tomaž Pisanski^{1,2}[0000–0002–1257–5376], Iztok Savič¹[0000–0002–3994–4805],
Ana Slavec¹[0000–0002–0171–2144], and Nino Bašić^{1,2}[0000–0002–6555–8668]

¹ UP FAMNIT Koper

² IMFM Ljubljana

³ UL FMF Ljubljana

⁴ `vladimir.batagelj@fmf.uni-lj.si`

⁵ `https://github.com/bavla/netsJSON`

version: March 14, 2025 at 21:47

Abstract. The key components that a common format for describing networks should include are discussed.

Keywords: First keyword · Second keyword · Third keyword

1 Introduction

2 Nets and NetsJSON

For dealing with networks with properties with structured values (for example, temporal quantities) we are developing a Python package Nets [?].

For describing temporal networks we initially, extending Pajek format, defined and used the Ianus format.

In 2015 we started to develop a new format based on JSON – we named it netJSON. On February 26, 2019 the format was renamed to NetsJSON because of the collision with `http://netjson.org/rfc.html`.

NetsJSON has two versions: a *basic* and a *general* version. Current implementation of the Nets / TQ library supports only the basic version. Nets.

Besides for a *description* of networks with structured values, NetsJSON should *envelope* (most of) existing network description formats [?] (archiving, conversion) and provide input data for D3.js *visualizations*.

2.1 Informal description of the basic netsJSON format

```
{  
  "netsJSON": "basic",
```

```

"info": {
  "org":1, "nNodes":n, "nArcs":mA, "nEdges":mE,
  "simple":TF, "directed":TF, "multirel":TF, "mode":m,
  "network":fName, "title":title,
  "time": { "Tmin":tm, "Tmax":tM, "Tlabs": {labs} },
  "meta": [events], ...
},
"nodes": [
  { "id":nodeId, "lab":label, "x":x, "y":y, ... },
  ***
]
"links": [
  { "type":arc/edge, "n1":nodeID1, "n2":nodeID2, "rel":r, ... }
  ***
]
}

```

where ... are user-defined properties and *** is a sequence of such elements.

Basic netsJSON format An event description can contain fields:

```

{ "date": date,
  "title": short description,
  "author": name,
  "desc": long description,
  "url": URL,
  "cite": reference,
  "copy": copyright
}

```

for describing temporal networks a node element and a link element has an additional required property `tq`

Example 1, Franzosi's violence network / UTF-8 no sig

2.2 Description of networks using a spreadsheet

How to describe a network \mathcal{N} ? In principle the answer is simple – we list its components \mathcal{V} , \mathcal{L} , \mathcal{P} , and \mathcal{W} .

The simplest way is to describe a network \mathcal{N} by providing $(\mathcal{V}, \mathcal{P})$ and $(\mathcal{L}, \mathcal{W})$ in a form of two tables.

As an example, let us describe a part of network determined by the following works:

Generalized blockmodeling, Clustering with relational constraint, Partitioning signed social networks, The Strength of Weak Ties

There are nodes of different types (modes): persons, papers, books, series, journals, publishers; and different relations among them: `author_of`, `editor_of`, `contained_in`, `cites`, `published_by`.

Both tables are often maintained in Excel. They can be exported as text in CSV (Comma Separated Values) format.

bibNodes.csv

```

name;mode;country;sex;year;vol;num;fPage;lPage;x;y
"Batagelj, Vladimir";person;SI;m;;;;;809.1;653.7
"Doreian, Patrick";person;US;m;;;;;358.5;679.1
"Ferligoj, Anuška";person;SI;f;;;;;619.5;680.7
"Granovetter, Mark";person;US;m;;;;;145.6;660.5
"Moustaki, Irini";person;UK;f;;;;;783.0;228.0
"Mrvar, Andrej";person;SI;m;;;;;478.0;630.1
"Clustering with relational constraint";paper;;;1982;47;;413;426;684.1;380.1
"The Strength of Weak Ties";paper;;;1973;78;6;1360;1380;111.3;329.4
"Partitioning signed social networks";paper;;;2009;31;1;1;11;408.0;337.8
"Generalized Blockmodeling";book;;;2005;24;;1;385;533.0;445.9
"Psychometrika";journal;;;;;;741.8;086.1
"Social Networks";journal;;;;;;321.4;236.5
"The American Journal of Sociology";journal;;;;;;111.3;168.9
"Structural Analysis in the Social Sciences";series;;;;;;310.4;082.8
"Cambridge University Press";publisher;UK;;;;;534.3;238.2
"Springer";publisher;US;;;;;884.6;174.0

```

bibNodes.csv

In large networks, to avoid the empty cells, we split a network to some sub-networks – a collection.

bibLinks.csv

```

from;relation;to
"Batagelj, Vladimir";authorOf;"Generalized Blockmodeling"
"Doreian, Patrick";authorOf;"Generalized Blockmodeling"
"Ferligoj, Anuška";authorOf;"Generalized Blockmodeling"
"Batagelj, Vladimir";authorOf;"Clustering with relational constraint"
"Ferligoj, Anuška";authorOf;"Clustering with relational constraint"
"Granovetter, Mark";authorOf;"The Strength of Weak Ties"
"Granovetter, Mark";editorOf;"Structural Analysis in the Social Sciences"
"Doreian, Patrick";authorOf;"Partitioning signed social networks"
"Mrvar, Andrej";authorOf;"Partitioning signed social networks"
"Moustaki, Irini";editorOf;"Psychometrika"
"Doreian, Patrick";editorOf;"Social Networks"
"Generalized Blockmodeling";containedIn;"Structural Analysis in the Social Sciences"
"Clustering with relational constraint";containedIn;"Psychometrika"
"The Strength of Weak Ties";containedIn;"The American Journal of Sociology"
"Partitioning signed social networks";containedIn;"Social Networks"
"Partitioning signed social networks";cites;"Generalized Blockmodeling"
"Generalized Blockmodeling";cites;"Clustering with relational constraint"
"Structural Analysis in the Social Sciences";publishedBy;"Cambridge University Press"
"Psychometrika";publishedBy;"Springer"

```

bibLinks.csv

2.3 Factorization and description of large networks

To save space and improve computing efficiency we often replace values of categorical variables with integers. In R this encoding is called a *factorization*.

We enumerate all possible values of a given categorical variable (coding table) and afterward replace each value with the corresponding index in the coding table.

This approach is used in most programs dealing with large networks. Unfortunately, the coding table is often a kind of meta-data.

CSV2Pajek.R

```

# transforming CSV file to Pajek files
# by Vladimir Batagelj, June 2016
# setwd("C:/Users/batagelj/work/Python/graph/SVG/EUSN")
# colC <- c(rep("character",4),rep("numeric",7)); nas=c("", "NA", "NaN")
colC <- c(rep("character",4),rep("numeric",5)); nas=c("", "NA", "NaN")
nodes <- read.csv2("bibNodes.csv",encoding='UTF-8',colClasses=colC,na.strings=nas)
n <- nrow(nodes); M <- factor(nodes$mode); S <- factor(nodes$sex)
mod <- levels(M); sx <- levels(S); S <- as.numeric(S); S[is.na(S)] <- 0
links <- read.csv2("bibLinks.csv",encoding='UTF-8',colClasses="character")

```

```

F <- factor(links$from,levels=nodes$name,ordered=TRUE)
T <- factor(links$to,levels=nodes$name,ordered=TRUE)
R <- factor(links$relation); rel <- levels(R)
net <- file("bib.net","w"); cat("vertices ",n,"\\n",file=net)
clu <- file("bibMode.clu","w"); sex <- file("bibSex.clu","w")
cat("%",file=clu); cat("%",file=sex)
for(i in 1:length(mod)) cat(" ",i,mod[i],file=clu)
cat("\\nvertices ",n,"\\n",file=clu)
for(i in 1:length(sx)) cat(" ",i,sx[i],file=sex)
cat("\\nvertices ",n,"\\n",file=sex)
for(v in 1:n) {
  cat(v," ",nodes$name[v],"\\n",sep="",file=net);
  cat(M[v],"\\n",file=clu); cat(S[v],"\\n",file=sex)
}
for(r in 1:length(rel)) cat("arcs :",r," ",rel[r],"\\n",sep="",file=net)
cat("arcs\\n",file=net)
for(a in 1:nrow(links))
  cat(R[a],": ",F[a]," ",T[a]," 1 1 ",rel[R[a]],"\\n",sep="",file=net)
close(net); close(clu); close(sex)

```

CSV2Pajek.R

bib.net

```

*vertices 16
1 "Batagelj, Vladimir"
2 "Doreian, Patrick"
3 "Fertigj, Anuška"
4 "Granovetter, Mark"
5 "Moustaki, Irini"
6 "Mrvar, Andrej"
7 "Clustering with relational constraint"
8 "The Strength of Weak Ties"
9 "Partitioning signed social networks"
10 "Generalized Blockmodeling"
11 "Psychometrika"
12 "Social Networks"
13 "The American Journal of Sociology"
14 "Structural Analysis in the Social Sciences"
15 "Cambridge University Press"
16 "Springer"
*arcs :1 "authorOf"
*arcs :2 "cites"
*arcs :3 "containedIn"
*arcs :4 "editorOf"
*arcs :5 "publishedBy"
1: 1 10 1 1 "authorOf"
1: 2 10 1 1 "authorOf"
1: 3 10 1 1 "authorOf"
1: 1 7 1 1 "authorOf"
1: 3 7 1 1 "authorOf"
1: 4 8 1 1 "authorOf"
4: 4 14 1 1 "editorOf"
1: 2 9 1 1 "authorOf"
1: 6 9 1 1 "authorOf"
4: 5 11 1 1 "editorOf"
4: 2 12 1 1 "editorOf"
3: 10 14 1 1 "containedIn"
3: 7 11 1 1 "containedIn"
3: 8 13 1 1 "containedIn"
3: 9 12 1 1 "containedIn"
2: 9 10 1 1 "cites"
2: 10 7 1 1 "cites"
5: 14 15 1 1 "publishedBy"
5: 11 16 1 1 "publishedBy"

```

bib.net, bibMode.clu, bibSex.clu; bib.paj, bib.ini.

Reading Pajek files in R




Fig. 1. Bibliographic network – picture / Pajek

3 Network formats

3.1 Format

Gephi – Supported Graph Formats

- GEXF 1.3 primer

- Cons matrix – large networks

- Cons neighbors – node properties

- Tomaž Pisanski et al. – Vega

- Primož Potočnik et al. – catalogues

- $N = (V, L, P, W)$ tables (V, P) (L, W)

- Mixed links directed/undirected

- Multiple links

- Additional data about values, algebraic structures

- Metadata (Dublin Core, FAIR, Schema)

- Python page on network DS Python Patterns - Implementing Graphs

- Factorization

- Values – semiring weights (Semirings)

- Structured values: TQs, records, distributions

- Values – functions: PERT, circuits, modeling

- IDs - in network science often missing; individuals/classes -is a-

- Alternative labels for display (short, other languages)

- Collections of networks

- Operations and transformations on networks: extensions (new yearly data), constrictive description (NetML), intersection, union, ... product; derived networks

- Contexts !!! – matching IDs in different contexts

- Generalizations: multiway, hypernets, bikes

- Size: huge networks

- Metadata, updates, comments

- Default values

- KG \mathcal{G} networks (single relation, type of units)

4 Conclusions

- 1.
- 2.
- 3.

4.1 Acknowledgments

The computational work reported in this paper was performed using a collection of R functions `bibmat` and the program Pajek for analysis of large networks [?]. The code and data are available at Github/Bavla [?].

This work is supported in part by the Slovenian Research Agency (research program P1-0294, research program CogniCom (0013103) at the University of Primorska, and research projects J5-2557, J1-2481, and J5-4596), and prepared within the framework of the COST action CA21163 (HiTEc).

References

1. Arroyuelo, D., Hogan, A., Navarro, G., Reutter, J., Vrgoč, D.: Tackling challenges in implementing large-scale graph databases. *Communications of the ACM* **67**(8), 40–44 (2024)
2. Batagelj, V.: Social network analysis, large-scale (2009)
3. Batagelj, V.: Analysis and visualization of large networks (20/21 October 2005), slides
4. Chen, L., Zhang, H., Chen, Y., Guo, W.: Blank nodes in RDF. *J. Softw.* **7**(9), 1993–1999 (2012)
5. Ehrlinger, L., Wöß, W.: Towards a definition of knowledge graphs. *SEMANTiCS (Posters, Demos, SuCCESS)* **48**(1-4), 2 (2016)
6. Hartig, O., Champin, P.A., Kellogg, G., Seaborne, A. (eds.): RDF 1.2 Concepts and Abstract Syntax (25 February 2025), <https://www.w3.org/TR/rdf12-concepts/>, W3C Working Draft
7. Hayes, J., et al.: A graph model for RDF. Darmstadt University of Technology/University of Chile (2004), <https://users.dcc.uchile.cl/~cgutierrr/papers/rdfgraphmodel.pdf>
8. Hogan, A., Blomqvist, E., Cochez, M., d’Amato, C., de Melo, G., Gutiérrez, C., Kirrane, S., Labra Gayo, J.E., Navigli, R., Neumaier, S., Ngonga Ngomo, A.C., Polleres, A., Rashid, S.M., Rula, A., Schmelzeisen, L., Sequeda, J.F., Staab, S., Zimmermann, A.: Knowledge Graphs. No. 22 in *Synthesis Lectures on Data, Semantics, and Knowledge*, Springer (2021). <https://doi.org/10.2200/S01125ED1V01Y202109DSK022>, <https://kgbook.org/>
9. Hogan, A., Blomqvist, E., Cochez, M., d’Amato, C., Melo, G.D., Gutierrez, C., Kirrane, S., Gayo, J.E.L., Navigli, R., Neumaier, S., et al.: Knowledge graphs. *ACM Computing Surveys (Csur)* **54**(4), 1–37 (2021)
10. Hogan, A., Dong, X.L., Vrandečić, D., Weikum, G.: Large language models, knowledge graphs and search engines: A crossroads for answering users’ questions. *arXiv preprint arXiv:2501.06699* (2025)
11. Nguyen, V., Leeka, J., Bodenreider, O., Sheth, A.: A formal graph model for RDF and its implementation. *arXiv preprint arXiv:1606.00480* (2016), <https://arxiv.org/abs/1606.00480>
12. Paulheim, H.: Knowledge graph refinement: A survey of approaches and evaluation methods. *Semantic web* **8**(3), 489–508 (2016)
13. Tomaszuk, D., Hyland-Wood, D.: RDF 1.1: Knowledge representation and data integration language for the web. *Symmetry* **12**(1), 84 (2020)
14. Wilkinson, M.D., Dumontier, M., Aalbersberg, I.J., Appleton, G., Axton, M., Baak, A., Blomberg, N., Boiten, J.W., da Silva Santos, L.B., Bourne, P.E., et al.: The fair guiding principles for scientific data management and stewardship. *Scientific data* **3**(1), 1–9 (2016)
15. Zhong, L., Wu, J., Li, Q., Peng, H., Wu, X.: A comprehensive survey on automatic knowledge graph construction. *ACM Computing Surveys* **56**(4), 1–62 (2023)

16. Zloch, M., Acosta, M., Hienert, D., Conrad, S., Dietze, S.: Charaterizing RDF graphs through graph-based measures—framework and assessment. *Semantic Web* **12**(5), 789–812 (2021)