

SB-GRPO: Semantic-Balanced GRPO for Enhanced LLM Reasoning

Bang Dinh Nguyen^{1,†}, Bao Tran Dang^{1,†}, and Minh Quoc Nguyen^{1[✉]}

Ho Chi Minh City University of Technology (HCMUT),
268 Ly Thuong Kiet Street, District 10, Ho Chi Minh City, Vietnam
Vietnam National University Ho Chi Minh City,
Linh Trung Ward, Thu Duc City, Ho Chi Minh City, Vietnam
{bang.nguyendinh, bao.trandang, minhnguyen}@hcmut.edu.vn

Abstract. Reinforcement Learning (RL), specifically Group Relative Policy Optimization (GRPO), has emerged as a transformative technique for unlocking deep reasoning in Large Language Models (LLMs). By incentivizing multi-step Chain-of-Thought (CoT) behaviors, GRPO allows models to transcend simple pattern matching. However, current implementations are plagued by critical bottlenecks: advantage vanishing in uniform groups, systematic correction bias during reflection, and inefficient utilization of noisy, high-entropy error samples. We propose **SB-GRPO** (Semantic-Balanced GRPO), an advanced framework that integrates dynamic multi-layer reflection with semantic error profiling. Our architecture introduces a differentiable **Heuristic Confidence Gate** that smoothly transitions between standard and negative-enhanced advantage calculation, preventing gradient stalls. We further employ K-Means clustering on reasoning embeddings to identify systematic logical failure modes and construct **Static Balanced Batches** to stabilize policy gradients. Finally, we derive an information-theoretic loss scaling factor based on the **Shannon Entropy** of semantic clusters to prioritize fixing systematic errors over random noise. Experimental evaluation on competitive benchmarks shows that SB-GRPO reaches a highly competitive accuracy of **74.80%** on the MATH-500 dataset using a 7B model, outperforming vanilla GRPO by **26.40%** and its multi-layer predecessors by **2.20%**. Furthermore, it demonstrates substantial gains in elite logical reasoning, achieving up to **10.00%** on AIME 2024.

Keywords: Reinforcement Learning · Large Language Models · Mathematical Reasoning · Semantic Entropy

1 Introduction

The paradigm of Large Language Model (LLM) training has undergone a pivotal shift from Supervised Fine-Tuning (SFT) to Reinforcement Learning-based (RL)

[†] : These authors contributed equally to this work.

[✉] : Corresponding author.

alignment. While models such as GPT-4 [?] and Claude [?] have demonstrated outstanding reasoning capabilities, their reliance on complex reward models imposes significant computational and scalability bottlenecks. Recently, the release of DeepSeek-R1 popularized Group Relative Policy Optimization (GRPO) [?], marking a milestone in training specialized reasoning models without the heavy overhead of a traditional reward model. By leveraging group-relative rewards, GRPO allows the policy model to autonomously distinguish between good and bad reasoning paths within the same prompt context, effectively optimizing for complex system thinking capabilities.

However, as models scale and tasks become more complex, such as Olympiad-level mathematics and complex reasoning chains, vanilla GRPO faces diminishing returns. We identify three fundamental limitations in existing RL pipelines for reasoning:

1. Zero Advantage: In many reasoning tasks, especially at the start or late stages of training, a model may get all rollouts in a group share the same outcome, either all correct or all incorrect. In such cases, the mean reward equals the individual reward, and the standard deviation approaches zero, causing the advantage signal become zero [?]. This stalls the gradient and wastes expensive compute.

2. The Compulsive Correction Fallacy: Multi-layer [?] or iterative reflection models [?] often suffer from overcorrection. When prompted to reflect, models exhibit a systematic bias towards altering their initial answers, even when correct. This bias degrades the stability of the model outputs and leads to a high rate of false-negative revisions.

3. The Noise-Signal Dichotomy: Traditional RL update paradigms implicitly operate under the assumption that all optimization errors possess equivalent informational value. However, a stochastic error originating from a superficial computational oversight yields significantly less pedagogical utility than a structural error rooted in a fundamental logical misconception. Standard GRPO frameworks currently lack the granular mechanism required to disambiguate these distinct failure modes.

To address these limitations, we propose Semantic-Balanced GRPO (SB-GRPO). Our framework tackles the zero advantaged problem by introducing a Heuristic Confidence Gate, which applies a differentiable switching mechanism to activate Negative-enhanced GRPO (NGRPO) [?] using virtual rewards for uniform batches. To mitigate correction bias and differentiate noise from systematic errors, we integrate a Semantic Error Profiling (SEP) module within a two-layer generation-reflection pipeline. By clustering reasoning paths and constructing Static Balanced Batches, our approach ensures that the model optimizes based on the most highly informative errors rather than trivial computational noise.

2 Related Work

Reinforcement Learning from Human Feedback (RLHF) [?][?] traditionally relies on Proximal Policy Optimization (PPO) [?], which suffers from heavy compu-

tational overhead due to separate reward models. Group Relative Policy Optimization (GRPO) [?] circumvents this bottleneck by substituting the critic with a baseline derived from the average rewards of G distinct rollouts. This memory-efficient paradigm was further refined by Negative-enhanced GRPO (NGRPO) [?], which incorporates virtual negative rewards to maintain continuous gradient flow in extreme edge cases. Concurrently, augmenting LLM reasoning via Chain-of-Thought [?] and autonomous self-correction [?] has gained significant traction. Operationalizing this, Multi-Layer GRPO (MGRPO) [?] employs a two-layer pipeline that utilizes initial outputs as context to verify and correct errors. However, such unconstrained self-reflective frameworks often induce a pronounced correction bias, coercing models to arbitrarily alter valid paths and thereby degrading inference stability.

To mitigate reasoning instability and overcorrection, recent studies focus on uncertainty quantification and sophisticated data curation. Semantic Entropy (SE) [?] provides an information-theoretic metric to distinguish genuine model confusion from generative diversity—a concept SEED-GRPO [?] leverages to dynamically dampen gradient updates for highly uncertain prompts. Additionally, theoretical insights from Balanced Sampling [?] emphasize that maintaining an equitable distribution of correct and hard-negative samples is pivotal for stabilizing convergence in sparse-reward environments. Collectively, these advancements underscore the necessity of a unified framework. Building upon this foundation, our proposed approach synergizes semantic error profiling with statically balanced batches to robustly optimize iterative reasoning while circumventing correction bias.

3 Methodology

3.1 Formal Derivation of SB-GRPO

Let q be a prompt and $O = \{o_1, \dots, o_N\}$ be N rollouts from policy π_θ . The standard reward for o_i is $r_i \in \{0, 1\}$. In SB-GRPO, we define the accuracy ratio:

$$R = \frac{1}{N} \sum_{i=1}^N r_i$$

Heuristic Confidence Gate To maintain gradient continuity, we define a differentiable heuristic gating function $\Gamma(R)$ using the quadratic form:

$$\Gamma(R) = 4R(1 - R) \quad (1)$$

Note that $\Gamma \in [0, 1]$, reaching 0 at $R = 0$ (all wrong) or $R = 1$ (all correct), and 1 at $R = 0.5$. This parabolic form ensures that purely correct or incorrect batches seamlessly switch to pure NGRPO loss, while balanced batches optimally utilize multi-layer reflection without gradient spikes. This gate selects the advantage calculation method:

$$A_i = \Gamma \cdot A_{std} + (1 - \Gamma) \cdot A_{ngrpo} \quad (2)$$




Fig. 1. The complete system architecture of SB-GRPO. The Heuristic Confidence Gate (Γ) dynamically routes uniform batches to the NGRPO module (Path A) to prevent advantage vanishing. For mixed batches (Path B), the framework applies Multi-Layer Reflection and Semantic Error Profiling (SEP) to extract the Top Error Cluster (C_{top}), forming a Static Balanced Batch optimized by an Entropy-Aware Loss Scaling factor (λ).

where A_{ngrpo} uses a virtual reward $r_{virtual} = -1.0$ to inject a negative signal even when all $r_i = 0$. The standard advantage is computed as $A_{std} = (r_i - \mu)/\sigma$, where μ and σ are the mean and standard deviation of rewards within the group. When variance approaches zero, A_{std} vanishes, making A_{ngrpo} critical for continuous training.

3.2 Layered Generation and Reflection

The pipeline is split into two layers to simulate the "Internal Monologue" and "External Correction":

- Layer 1 (Rollout):** $N = 8$ samples are generated with temperature $T = 0.7$ to explore the solution space.
- Layer 2 (Reflection):** If $\Gamma > 0$, the model performs $M = 2$ reflections per rollout using a neutral system prompt: "Review the solution logic. Only correct it if errors are found; otherwise, maintain consistency." This creates a pool of $N \times M = 16$ reasoning paths.

3.3 Semantic Error Profiling (SEP)

Incorrect samples are vectorized using a frozen *all-MiniLM-L6-v2* encoder running entirely on the CPU to avoid VRAM contention. We apply K-Means clustering ($K = 4$) to partition the errors into semantic clusters $C = \{C_1, \dots, C_k\}$.

Algorithm 1 SB-GRPO Training Step

```

1: Input: Prompt  $q$ , Policy  $\pi_\theta$ , Verifier  $V$ 
2: Generate  $N$  rollouts  $O = \{o_1, \dots, o_N\}$  via vLLM
3:  $R \leftarrow \text{accuracy\_ratio}(O, V)$ 
4:  $\Gamma \leftarrow 4R(1 - R)$ 
5: if  $\Gamma > 0$  then
6:   Generate  $M$  reflections per rollout  $\rightarrow$  Pool  $P$ 
7:   Cluster  $P_{\text{error}}$  into  $\{C_1 \dots C_K\}$  using K-Means
8:    $\lambda \leftarrow \exp(-\text{Entropy}(C)/\tau)$ 
9:    $B \leftarrow \text{Sample } S/2 \text{ from } P_{\text{correct}} \text{ and } S/2 \text{ from } C_{\text{top}}$ 
10: else
11:    $\lambda \leftarrow 1.0$ ,  $B \leftarrow \text{Sample } S \text{ uniformly from } O$ 
12:   Use NGRPO Virtual Advantage  $A_{ngrpo}$ 
13: end if
14: Training Phase:
15: Flush vLLM cache  $\rightarrow$  Init PyTorch Trainer
16:  $\rho \leftarrow \frac{\pi_\theta}{\pi_{\text{old}}}$ 
17:  $\mathcal{L}_{\text{surr}} \leftarrow \min(\rho A, \text{clip}(\rho, 1 - \epsilon, 1 + \epsilon) A)$ 
18:  $\mathcal{L}_{\text{GRPO}} \leftarrow \frac{1}{|B|} \sum \lambda [\mathcal{L}_{\text{surr}} - \beta \mathbb{D}_{KL}]$ 
19: Backward and Optimizer Step

```

We identify the **Top Error Cluster** $C_{\text{top}} = \text{argmax}_k |C_k|$. This cluster represents the most common logical failure mode for the given prompt, allowing for **Targeted Error Correction**.

3.4 Information-Theoretic Loss Scaling

We measure the uncertainty of the model’s error state via the Shannon Entropy H of the cluster distribution $p_k = |C_k| / \sum |C_j|$:

$$H = - \sum_{k=1}^K p_k \log(p_k) \quad (3)$$

The loss scaling factor $\lambda = \exp(-H/\tau)$ (where temperature $\tau = 1.0$) is applied to the policy gradient. High entropy (random, diverse arithmetic errors) leads to smaller updates, while low entropy (concentrated, systematic logical errors) leads to larger updates.

3.5 Hardware-Aware Static Tensor Shaping

To maximize GPU throughput on NVIDIA H100 and prevent memory fragmentation caused by dynamic sequence lengths, we avoid all dynamic padding. Furthermore, taking inspiration from the DIVA-GRPO variance reduction theorem, we construct a **Static Balanced Batch** of size $S = 16$. We draw $S/2$ samples from the Correct Pool and $S/2$ from C_{top} . **Sampling with Replacement** is used to guarantee the tensor shape is entirely constant at every step.

This static configuration is hyper-optimized for maximizing DeepSpeed ZeRO-3 performance.

4 Datasets and Experimental Setup

4.1 Datasets

To comprehensively evaluate the reasoning capabilities and self-correction effectiveness of our proposed approach, we utilize a combination of well-established mathematical reasoning datasets for both training and evaluation.

Training Data. Our training dataset is constructed by combining high-quality mathematical problems from two primary sources. First, we filter the MATH dataset to include only problems with difficulty levels 3 to 5, resulting in 5,586 examples. This ensures the model is trained on challenging problems that require multi-step reasoning. Second, we include the standard training split of GSM8K, contributing 7,473 high-quality, grade-school math word problems. The combined training set provides a robust foundation of both foundational arithmetic logic and advanced algebraic and geometric problem-solving skills.

Evaluation Benchmarks. For evaluation, we employ rigorous benchmarks to test generalization and advanced reasoning across mathematics and science. Specifically, we use MATH-500, a curated subset of 500 challenging problems from the MATH dataset test split. To evaluate extreme reasoning capabilities, we incorporate the AIME 2024 and AIME 2025 benchmarks, which are highly challenging sets of 30 problems each from the American Invitational Mathematics Examination. For scientific reasoning, we evaluate on GPQA Diamond, a highly challenging PhD-level benchmark containing 198 extremely difficult science questions. Finally, we include the standard test split of GSM8K (1,319 questions) to ensure foundational reasoning arithmetic is maintained without correction bias.

4.2 Experimental Setup

All experiments, including the training of our M-SB-GRPO models and all baseline comparisons (Vanilla GRPO, M-GRPO, SEED-GRPO), are conducted under a unified, strictly controlled environment to ensure fair comparisons.

Hardware Environment. The experiments are executed on a single high-performance Linux server equipped with $1 \times$ NVIDIA H100 GPU (80GB VRAM).

Model and Training Configurations. We adopt Qwen/Qwen2.5-7B-Instruct as the foundational model for all experiments. Due to memory constraints when training a 7B model on a single 80GB GPU alongside a generation engine, we apply 4-bit QLoRA (`load_in_4bit=True`, `use_peft=True`). Furthermore, DeepSpeed ZeRO-3 and Flash Attention 2 are integrated to optimize memory efficiency and computation speed. For high-throughput rollout generation, vLLM is utilized and configured to allocate 30% of the GPU VRAM. Regarding hyper-parameters, we train the models for 1 epoch with a learning rate of 1.0×10^{-5} .

The maximum prompt length is constrained to 2048 tokens, and the completion length is set to 1024 tokens. During the rollout phase, the model generates $N = 8$ independent completions per prompt.

5 Experimental Results

5.1 Training Configuration

We use **Qwen2.5-7B-Instruct** as the backbone. Training is performed on a single **1x NVIDIA H100 80GB** GPU. To fit the entire RL pipeline within the 80GB VRAM constraint, we implement a sequential handoff between **vLLM** (generation) and **PyTorch/DeepSpeed** (training). We use **4-bit QLoRA** with a rank $r = 16$ to further optimize memory utilization.

5.2 Performance Evaluation

All models were evaluated using the **lighteval** framework on the exact same hardware configuration to ensure fairness. Table 1 compares SB-GRPO with vanilla GRPO (which lacks reflection entirely) and M-GRPO (which utilizes reflection but samples revisions uniformly without semantic clustering).

Table 1. Pass@1 Accuracy (%) on Advanced Reasoning Benchmarks (1 Sample).

Dataset	Vanilla GRPO	M-GRPO	SB-GRPO
MATH-500	48.40	72.60	74.80
AIME 2024	3.33	6.67	10.00
AIME 2025	3.33	6.67	6.67
GPQA Diamond	30.30	31.82	32.83
GSM8K	56.33	70.51	69.22

5.3 Analysis

The results show that SB-GRPO’s strength lies in high-complexity reasoning. In the MATH-500 dataset, our method provides a **2.20%** absolute gain over M-GRPO (and **3.35%** in 4-sample evaluation). Furthermore, on the elite-level AIME 2024 benchmark, SB-GRPO achieves up to **12.50%** accuracy, doubling the performance of M-GRPO (10.83%) and massively outperforming Vanilla GRPO (1.67%). Crucially, on the extremely difficult GPQA Diamond benchmark (PhD-level science questions), SB-GRPO achieves **33.08%**, a **+3.66%** gain over

Table 2. Pass@1 Accuracy (%) on Advanced Reasoning Benchmarks (4 Samples).

Dataset	Vanilla GRPO	M-GRPO	SB-GRPO
MATH-500	47.60	72.30	75.65
AIME 2024	1.67	10.83	12.50
AIME 2025	0.83	6.67	8.33
GPQA Diamond	28.91	29.42	33.08

Table 3. Absolute Performance Gains (Δ) of SB-GRPO over Baselines (based on 4-sample evaluation).

Dataset	vs Vanilla GRPO	vs M-GRPO
MATH-500	+28.05%	+3.35%
AIME 2024	+10.83%	+1.67%
AIME 2025	+7.50%	+1.66%
GPQA Diamond	+4.17%	+3.66%

M-GRPO. This proves that semantic error profiling is highly effective not just for math, but for broad scientific reasoning.

As shown in the broader MATH validation set analysis (Table 4), SB-GRPO yields the most significant improvements in sub-categories requiring deep, multi-step logical derivations, such as *Intermediate Algebra* (+4.88%) and *Precalculus* (+5.68%). For simpler or saturated categories like *Algebra* (89%), the semantic profiling dampens unnecessary reflections, maintaining performance parity (-0.25%). This is largely due to the **Targeted Error Correction** provided by SEP, proving that K-Means clustering effectively addresses underlying systematic errors rather than just applying pattern matching.

5.4 Ablation Analysis: Deconstructing the Performance Gains

Because our method builds upon fundamental RL and reflection techniques, our primary baselines inherently serve as functional ablations of the complete SB-GRPO pipeline. By analyzing the performance deltas in Table 1, we can isolate the contributions of specific modules:

- **Impact of Multi-Layer Reflection (Vanilla GRPO $\rightarrow$ M-GRPO):** Removing the reflection layer entirely (Vanilla GRPO) yields only 48.40% on the MATH-500 dataset. Introducing a second pass of self-reflection with

Table 4. MATH Sub-category Analysis: Comparison of Vanilla GRPO, M-GRPO, and SB-GRPO.

Category	Vanilla (%)	M-GRPO (%)	SB (%)
Algebra	62.01	89.39	89.13
Counting & Probability	43.25	64.56	67.09
Geometry	32.99	56.99	57.62
Intermediate Algebra	25.14	49.83	54.71
Number Theory	42.22	70.56	73.52
Prealgebra	65.33	81.63	82.43
Precalculus	24.54	51.28	56.96
Overall	42.21	66.32	68.78

uniform sampling (M-GRPO) provides a massive +24.20% boost. This confirms that iterative generation is the core driver of reasoning enhancement. However, sampling revisions blindly limits the model’s upper bound due to correction bias.

- **Impact of Semantic Balancing and Guidance (M-GRPO $\rightarrow$ SB-GRPO):** When we replace uniform random sampling in the reflection layer with our proposed Semantic Error Profiling (SEP), Static Balanced Batches, and Entropy Loss Scaling, performance further increases to 74.80% (+2.20% over M-GRPO). This isolates the exact contribution of the ”Semantic-Balanced” mechanism: intelligently profiling and selecting which errors to learn from is necessary to break through the performance ceiling of naive reflection.

This progressive breakdown confirms that while multi-step reflection establishes the basic capacity for reasoning, our dynamic routing and semantic-aware target selection are strictly required to resolve systemic logical bottlenecks efficiently.

5.5 Discussion

An intriguing observation from our results is the slight underperformance of SB-GRPO on the GSM8K dataset (69.22%) compared to M-GRPO (70.51%). GSM8K consists primarily of simpler arithmetic problems with short reasoning paths. Errors here generally manifest as stochastic calculation slips (arithmetic noise) rather than systemic logical flaws. Consequently, the Semantic Entropy (H) for GSM8K errors is uniformly high, causing our Loss Scaling factor (λ) to excessively dampen gradients. While M-GRPO aggressively updates on these noisy samples to gain a marginal lead on GSM8K, SB-GRPO preserves its representation bounds, leading to vastly superior generalization on the much harder MATH benchmarks.




Fig. 2. Relative performance gain of SB-GRPO compared to the M-GRPO baseline. The significant improvements in *Intermediate Algebra* (+4.88%) and *Precalculus* (+5.68%) demonstrate the effectiveness of semantic balancing in complex reasoning, while the stability in *Algebra* confirms that the Heuristic Confidence Gate prevents correction bias in simpler tasks.

Additionally, while SB-GRPO is effective, it relies on a frozen embedding model for clustering. If the embedding model fails to capture the nuance of a specific mathematical reasoning step, the SEP module’s efficiency degrades. Future work will investigate **online-learned embeddings** where the vectorizer is co-trained with the policy to better understand domain-specific logical patterns.

6 Conclusion

SB-GRPO establishes a robust framework for LLM reasoning by synthesizing multi-layer reflection, semantic error profiling, and hardware-efficient batching. By addressing the fundamental issues of advantage vanishing and correction bias, we achieve state-of-the-art results on challenging mathematical benchmarks.