


Plotting in Python

Python does not have built in plotting capabilities, but there is a plethora of useful packages specialized to all kinds of plots. Here is a very incomplete list of my favorites:


- [Matplotlib](http://matplotlib.org/gallery.html) (<http://matplotlib.org/gallery.html>)

Matplotlib is the standard when it comes to plotting in Python. It is very useful for visualization for publications and can also be included in applications.




- [Bokeh](http://bokeh.pydata.org/en/latest/) (<http://bokeh.pydata.org/en/latest/>)

Bokeh is useful to create beautiful interactive plots.




- [Plotly](https://plot.ly/python/) (<https://plot.ly/python/>)

Similar to Bokeh, but more flexible. Plotly has api to other languages and a nice webinterface to style plots.



- [Mayavi](http://code.enthought.com/projects/mayavi/) (<http://code.enthought.com/projects/mayavi/>)

Not really a plotting tool, but a specialized package for 3D data visualization.



What we will do

We will work primarily in `matplotlib` to cover the basics of what you will need for the projects and scientific plotting in general.

Matplotlib, as the name suggests, has strong similarities to Matlab and learning it makes it easy to plot in both languages. The `pyplot` module makes python work like matlab in many aspects.

To use matplotlib we need to do the following setup:


```
In [1]: %matplotlib inline
import numpy as np           # we will need numpy
import matplotlib.pyplot as plt # and this is for plotting
```

Line 1 lets matplotlib output images directly in the notebook. If you just use `%matplotlib` the output is opened in a new window.

And now we can plot:

```
In [2]: xv=[1,2,3,4]  
        yv=[5,1,4,0]  
        plt.plot(xv,yv)
```

```
Out[2]: [<matplotlib.lines.Line2D at 0x1051fe0f0>]
```



It really is that easy!

Understanding our plot

It is important to note that in the code above we imported `matplotlib.pyplot`. Pyplot is the part of matplotlib (MPL) we will use mostly. It is a collection of functions that can be used for the easy creation of plots. Luckily the inner workings of MPL are mostly hidden from us users. `plt` commands create plots which consist of a.

To really work with MPL (or any other plotting library) though, it is important to understand how plots are build up.

Plots in MPL have the following components:

- *figures*: A canvas to draw on
 - *axis*: Coordinate systems to put data in
 - *ticks*: labels and dimensions of the axis

MPL also uses the concept of *current plot*. Whenever you issue a `plot` command, it is drawn on your current figure if there is one, otherwise it opens a new plot.

Plots are created by `plot` commands but not displayed directly, usually you need to use the `plt.show()` command to show the figure on screen.

```
{python}  
plt.plot(x,y)  
plt.show()
```


In this notebook we do not need to do this, because Jupyter takes care of that if we use `%matplotlib inline` command.

Styling our plot

We can modify our plot after we created it using the `setp` function:

```
In [3]: x = np.linspace(-np.pi, np.pi, 256)
y = np.sin(x)
myplot = plt.plot(x,y,'k--')
plt.setp(myplot,linewidth=3.0)
```

Out[3]: [None]



Calling `plt.setp(myplot)` shows us all the available arguments:

```
In [4]: plt.setp(myplot)
```

```

agg_filter: unknown
alpha: float (0.0 transparent through 1.0 opaque)
animated: [True | False]
antialiased or aa: [True | False]
axes: an :class:`~matplotlib.axes.Axes` instance
clip_box: a :class:`~matplotlib.transforms.Bbox` instance
clip_on: [True | False]
clip_path: [ (:class:`~matplotlib.path.Path`, :class:`~matplotlibli
b.transforms.Transform`) | :class:`~matplotlib.patches.Patch` | No
ne ]
color or c: any matplotlib color
contains: a callable function
dash_capstyle: ['butt' | 'round' | 'projecting']
dash_joinstyle: ['miter' | 'round' | 'bevel']
dashes: sequence of on/off ink in points
drawstyle: ['default' | 'steps' | 'steps-pre' | 'steps-mid' | 's
teps-post']
figure: a :class:`~matplotlib.figure.Figure` instance
fillstyle: ['full' | 'left' | 'right' | 'bottom' | 'top' | 'none
']
gid: an id string
label: string or anything printable with '%s' conversion.
linestyle or ls: ['solid' | 'dashed', 'dashdot', 'dotted' | (off
set, on-off-dash-seq) | ``'-'' | ``'--'' | ``'-.''' | ``':'' |
``'None'' | ``' '' | ``'``']
linewidth or lw: float value in points
marker: :mod:`A valid marker style <matplotlib.markers>`
markeredgecolor or mec: any matplotlib color
markeredgewidth or mew: float value in points
markerfacecolor or mfc: any matplotlib color
markerfacecoloralt or mfcalt: any matplotlib color
markersize or ms: float
markevery: [None | int | length-2 tuple of int | slice | list/ar
ray of int | float | length-2 tuple of float]
path_effects: unknown
picker: float distance in points or callable pick function ``fn(
artist, event)``
pickradius: float distance in points
rasterized: [True | False | None]
sketch_params: unknown
snap: unknown
solid_capstyle: ['butt' | 'round' | 'projecting']
solid_joinstyle: ['miter' | 'round' | 'bevel']
transform: a :class:`~matplotlib.transforms.Transform` instance
url: a url string
visible: [True | False]
xdata: 1D array
ydata: 1D array
zorder: any number

```

Styles


The defaults of MPL are not the most beautiful out there, so luckily we can set better defaults using styles:

```
In [5]: print(plt.style.available)
plt.style.use('ggplot')
```

```
['classic', 'seaborn-whitegrid', 'seaborn-white', 'seaborn-ticks',
'seaborn-talk', 'seaborn-deep', 'seaborn-poster', 'seaborn-bright',
, 'seaborn-darkgrid', 'ggplot', 'seaborn-pastel', 'fivethirtyeight',
, 'grayscale', 'seaborn-colorblind', 'dark_background', 'seaborn-
dark-palette', 'seaborn-dark', 'seaborn-muted', 'seaborn-paper', '
bmh', 'seaborn-notebook']
```

```
In [6]: plt.plot(x,y)
```

```
Out[6]: [<matplotlib.lines.Line2D at 0x1053d9f60>]
```




Legends

Legends can be added to get an overview of different plot components. Let's create a new figure to draw on:

```
In [7]: fig = plt.figure()
ax = plt.axes()
random = np.random.random(x.shape)-.5
ax.plot(x,y)
ax.plot(x, y, color="blue", linestyle="-", label="sine")
ax.plot(x, random, color="red", linestyle="-", label="random")
ax.legend(loc='upper left')
```


Out[7]: <matplotlib.legend.Legend at 0x10544ada0>



Labels and Titles

```
In [8]: ax.set_xlabel("a.u.")
ax.set_ylabel("a.u.")
ax.set_title("Sine and random noise")
fig
```

Out[8]:




Ticks

```
In [9]: ax.set_xticks([-np.pi, -np.pi/2, 0, np.pi/2, np.pi])
ax.set_xticklabels([r'$-\pi$', r'$-\pi/2$', r'$0$', r'$+\pi/2$', r'$+\pi$'])

ax.set_yticks([-1, 0, +1])
ax.set_yticklabels([r'$-1$', r'$0$', r'$+1$'])
fig
```


Out[9]:



Saving our work


You can save each plot in different formats:

```
In [10]: plt.plot(x,y)
plt.savefig('foo.png', dpi=600, format='png',orientation='landscape'
')
```



If you want to save a figure that is not your current figure:

```
In [11]: fig.savefig("sine.png")
```



Axes

Axes are the areas on your figure where your actual data lives. You can put numbers on axes and fill them with different data.

Let's plot the eye of sauron:


```

In [12]: plt.style.use("dark_background")
t = np.linspace(0,100,1000)
s = np.sin(t)/(t+1)
c = np.cos(t)/np.sqrt((t+1))

ax1 = plt.axes([.1,.1,2,2])
ax2 = plt.axes([1.3,.2,.3,.3])
ax3 = plt.axes([1.7,.2,.3,.3])
ax2.plot(t,s)
ax3.plot(t,c)
ax1.plot(s,c, 'red')
ax1.plot(s+0.005,c+0.01, 'yellow')

```

Out[12]: [



Ok, pretty close.



Subplots

The `subplot` command creates new *axis* in a regular grid that can be easily accessed. Using the `subplot` command we can plot different data on each of the created axis.

Calling the `subplot` command with a different 3rd argument can be seen as moving the cursor to a different location. Each plot directive after the `subplot` call will be done on the according subplot/axes.

subplot(2,2,1)


subplot(2,2,2)

subplot(2,2,3)

subplot(2,2,4)

```
In [13]: plt.style.use("ggplot")
plt.subplot(2,2,1)
plt.plot(t, c, color="blue", linewidth=1.0, linestyle="-")
plt.subplot(2,2,2)
# Plot sine using green color with a continuous line of width 1 (pixels)
plt.plot(t, s, color="green", linewidth=1.0, linestyle="--")
plt.subplot(2,2,3)
plt.plot(x,y)
plt.subplot(2,2,4)
plt.plot(x,random)
```


Out[13]: [



Another example:

```
In [14]: plt.figure(figsize=(9,3))
plt.subplot(1,3,1)
plt.plot(t,s)
plt.subplot(1,3,2)
plt.plot(t,c)
plt.subplot(1,3,3)
plt.plot(s,c)
```

Out[14]: [




Shared axis

In the above example it would make sense to make at least the y-axis shared to keep scaling and save space. For this we need to assign axis manually using the `subplots` command:

```
In [15]: f, (ax1, ax2, ax3) = plt.subplots(1, 3,
                                           sharey=True,
                                           sharex=False,
                                           figsize=(9,3))

ax1.plot(t,s)
ax2.plot(t,c)
ax3.plot(s,c)
```

Out[15]: [



Animation

```

In [16]: import numpy as np
import matplotlib.pyplot as plt
import matplotlib.animation as animation

fig, (ax1, ax2, ax3) = plt.subplots(1, 3,
                                   sharey=True,
                                   sharex=False,
                                   figsize=(9,3))


p1, = ax1.plot([],[])
p2, = ax2.plot([],[])
p3, = ax3.plot([],[])
t = np.linspace(0,100,2000)
x = np.sin(t)/(t+1)
y = np.cos(t)/np.sqrt(t+1)
ax1.set_ylim((-0.5,1))
ax1.set_xlim((0,100))
ax2.set_xlim((0,100))
ax3.set_xlim((-0.5,0.5))

def animate(i):
    p1.set_data(t[0:i*10],x[0:i*10])
    p2.set_data(t[0:i*10],y[0:i*10])
    p3.set_data(x[0:i*10],y[0:i*10])
    return p1,p2,p3

# Init only required for blitting to give a clean slate.
def init():
    p1.set_data(np.ma.array(t, mask=True),np.ma.array(x, mask=True)
    )
    p2.set_data(np.ma.array(t, mask=True),np.ma.array(y, mask=True)
    )
    p3.set_data(np.ma.array(x, mask=True),np.ma.array(y, mask=True)
    )
    return p1,p2,p3

ani = animation.FuncAnimation(fig, animate, np.arange(1, 200), init
_func=init,
                                interval=10, blit=True)


```



```

In [17]: ani.save('ani.gif', writer="imagemagick", fps=30, dpi=50)

```

Matplotlib resources:

To get inspiration and further help look at the MPL website. Here are a few things you might want to have a look at before doing the exercise:

- In this notebook, whenever you are in a code block and press `Shift+Tab` you will get a popup that tries to help you, repeatedly press and it becomes even more helpful
- [Gallery](http://matplotlib.org/gallery.html) (<http://matplotlib.org/gallery.html>) of beautiful plots
- [Examples](http://matplotlib.org/examples/index.html) (<http://matplotlib.org/examples/index.html>) for (almost) everything you can do with MPL
- [Pyplot](http://matplotlib.org/api/pyplot_summary.html) (http://matplotlib.org/api/pyplot_summary.html) documentation that tells you how to use the commands available

Exercises

Exercise 1

a)

First you will plot a real time series dataset. In the same folder as this notebook there is a `.csv` file containing the expression of cell cycle dependent yeast genes. Your task is to visualize these.

We prepared a snippet that handles the reading of the csv file and gives you three variables:


- `data`: contains the expression changes over time
- `times`: the measurement times
- `genes`: names of the included genes

```
In [18]: from numpy import genfromtxt
import csv
data = genfromtxt('genes.csv', delimiter=',', skip_header=1)[: ,1:]
with open('genes.csv') as f:
    times = csv.reader(f).__next__()[1:]
    times = [int(t) for t in times]
    genes = [x[0] for x in csv.reader(f)]
```

Plot all the time series into one plot

To include the correct x-axis you might need to create a matrix of the same dimensions as the data. Use your *numpy* skills in repeating and reshaping for this!


```
In [19]: plt.style.use("ggplot")
f, ax = plt.subplots(1,1)
time_matrix = np.repeat([times], data.T.shape[1], axis=0)
ax.plot(time_matrix.T,data.T)
plt.savefig('ex1.png')
```



Add labels and a title

Use the plot you made above and add some descriptions.


```
In [20]: plt.style.use("ggplot")
f, ax = plt.subplots(1,1)
time_matrix = np.repeat([times], data.T.shape[1], axis=0)
ax.plot(time_matrix.T,data.T)
ax.set_title('Gene expression over time')
ax.set_xlabel('time [min]')
ax.set_ylabel('Gene expression [fold-change]')
plt.savefig('ex1.png')
```



Add a legend

Here you will need to do each plot separately in a for loop to include labels.

```
In [21]: for i, gene in enumerate(genes):
          plt.plot(times, data[i,:], label=gene)
          plt.legend(loc='upper right', bbox_to_anchor=(1.3,1), frameon=True,
                    fancybox=True)
          plt.savefig("ex1_legend.png")
```




b)

Plot the mean and standard deviation at each time point. To add errorbars look at [this](http://matplotlib.org/examples/pylab_examples/errorbar_limits.html) (http://matplotlib.org/examples/pylab_examples/errorbar_limits.html) example.

```
In [22]: line, caps, errs = plt.errorbar(times, data.mean(axis=0), yerr=data
        .std(axis=0))
        plt.setp(line, linewidth=2)
        plt.setp(caps, color='b')
        plt.setp(errs, alpha=.5)
```

Out[22]: [None]




Exercise 2

Plot the corellation between different time points as scatter plots.

```
In [23]: x = data[:,5]
y = data[:,6]
plt.scatter(x,data[:,10])
```

Out[23]: <matplotlib.collections.PathCollection at 0x109015208>




Exercise 3

Look at the examples in matplotlib. Can you do a histogram of all measurements?

```
In [24]: plt.hist(np.reshape(data, (-1,1)), bins=20)
```

```
Out[24]: (array([ 4.,  1.,  1.,  4.,  9., 16., 24., 17., 19., 15.,
, 13.,
          13., 21., 19., 12., 19.,  8.,  5.,  7.,  3.]),
array([-1.99602631, -1.68119522, -1.36636412, -1.05153303, -0.736
70194,
        -0.42187084, -0.10703975,  0.20779134,  0.52262244,  0.837
45353,
        1.15228463,  1.46711572,  1.78194681,  2.09677791,  2.411
609 ,
        2.7264401 ,  3.04127119,  3.35610228,  3.67093338,  3.985
76447,
        4.30059556])),
<a list of 20 Patch objects>)
```




Exercise 4

Put the last 2 plots into one figure using subplots.

```
In [25]: plt.subplot(121)
plt.hist(np.reshape(data, (-1,1)), bins=20)
plt.subplot(122)
plt.scatter(x,data[:,10])
```

Out[25]: <matplotlib.collections.PathCollection at 0x108496cf8>



Further material

<http://www.scipy-lectures.org/intro/matplotlib/matplotlib.html#other-types-of-plots-examples-and-exercises> (<http://www.scipy-lectures.org/intro/matplotlib/matplotlib.html#other-types-of-plots-examples-and-exercises>)

Bonus

Extend the above animation with a dot at the tip of the line.


```
In [26]: import numpy as np
import matplotlib.pyplot as plt
import matplotlib.animation as animation
plt.style.use("ggplot")

fig, (ax1, ax2, ax3) = plt.subplots(1, 3,
                                   sharey=True,
                                   sharex=False,
                                   figsize=(9,3))


p1a, = ax1.plot([],[])
p1b, = ax1.plot([],[])
p2a, = ax2.plot([],[])
p2b, = ax2.plot([],[])
p3a, = ax3.plot([],[])
p3b, = ax3.plot([],[])

t = np.linspace(0,100,2000)
x = np.sin(t)/(t+1)
y = np.cos(t)/np.sqrt(t+1)
ax1.set_ylim((-0.5,1))
ax1.set_xlim((0,100))
ax2.set_xlim((0,100))
ax3.set_xlim((-0.5,0.5))


def animate(i):
    p1a.set_data(t[0:i*10],x[0:i*10])
    p1b.set_data(t[i*10],x[i*10])
    plt.setp(p1b,'marker','o','color','r')
    p2a.set_data(t[0:i*10],y[0:i*10])
    p2b.set_data(t[i*10],y[i*10])
    plt.setp(p2b,'marker','o','color','r')
    p3a.set_data(x[0:i*10],y[0:i*10])
    p3b.set_data(x[i*10],y[i*10])
    plt.setp(p3b,'marker','o','color','r')
    return p1a,p2a,p3a

# Init only required for blitting to give a clean slate.
def init():
    p1.set_data(np.ma.array(t, mask=True),np.ma.array(x, mask=True))
    )
    p2.set_data(np.ma.array(t, mask=True),np.ma.array(y, mask=True))
    )
    p3.set_data(np.ma.array(x, mask=True),np.ma.array(y, mask=True))
    )
    return p1,p2,p3

ani = animation.FuncAnimation(fig, animate, np.arange(1, 200), init_func=init,
                             interval=10, blit=True)
```



```
In [27]: ani.save('ani2.gif', writer="imagemagick", fps=30, dpi=50)
```



```
In [ ]:
```