# Improving language models by retrieving from trillions of tokens

Mikhail Domanin

# Retrieval Augmented Generation (RAG)

- We separate linguistic information and knowledge about the world
- Knowing the language is enough:

its popularity spread by word-of-mouth to allow Herbert to start working full \_\_\_\_\_


Need information from additional sources:

The Dune film was released in \_\_\_\_\_

## Retrieval-Enhanced TRansfOrmer (RETRO)

- Text quality is comparable to GPT-3
- Uses 7.5 billion parameters, instead of 185 billion for GPT-3 Da Vinci (that is, 4%)






## How to build database?



Key (BERT sentence embedding)	Value (text. neighbor and completion chunks. Each up to 64 tokens in length)	
	Dune is a 2021 American epic science fiction film directed by Denis Villeneuve	NEIGHBOR
	It is the first of a planned two-part adaptation of the 1965 novel by Frank Herbert	COMPLETION
	Dune is a 1965 science fiction novel by American author Frank Herbert	NEIGHBOR
	originally published as two separate serials in Analog magazine	COMPLETION
	•••	

## How to find k-nearest



## How to find k-nearest


- Use Scann to find k-nearest
- Time complexity: O(logT); T dictionary size
- 10 ms to find k-nearest

## Example


RETRIEVE

The Dune film was released in INPUT EMBED WITH BERT Nearest Neighbor 1 SENTENCE EMBEDDING Dune is a 2021 American epic science fiction film directed by Denis Villeneuve 2) QUERY It is the first of a planned two-part adaptation approximate nearest of the 1965 novel by Frank Herbert neighbor **Database** Nearest Neighbor 2 Dune is a 1984 American epic science fiction film written and directed by David Lynch and based on the 1965 Frank Herbert novel of the same name

# Example




## **RETRO Architecture**



**RETRO Transformer** 


#### RETRO architecture


- Encoder block: self-attention + FFNN
- Decoder block: ATTN + FFNN
- RETRO decoder block: ATTN + Chunked Cross Attention (CCA) + FFNN



**RETRO Transformer** 

#### **Chunked cross-attention (CCA)**





## Comparable architectures

**Baseline Transformer** 


- Replace LayerNorm with RMSNorm
- Relative position encodings

RETRO [Off]

Without retrieval data

RETRO [On]

## Some results (Top 1 result)



# Advantages

- Easily add new information
- It's possible to use internet as a database
- Much fewer parameters => easier to fit

#### Literature

- https://arxiv.org/abs/2112.04426 The main article
- <a href="https://habr.com/ru/articles/648705/">https://habr.com/ru/articles/648705/</a> Short russian adoptation of the main article
- https://www.promptingguide.ai/techniques/rag An article about RAG