





Favourites

(Registration is mandatory!)

Updated 30-04-2024

[Home](#)

Your requests

Project name	Connector name	Date of request	Amount (running m)	Location	Country / State	
Hamburg harbour	MF64	2024-02-29	500 running m	Hamburg	Germany	
River Rhine	MF64	2024-02-29	1.500 running m	Cologne	Germany	

Favourite connectors

Connector name	Seen on date
MF63	2024-02-29
MF130	2024-02-29

Disclaimer

SteelWall connectors generally comply with the European standards and are manufactured by certified steel processing companies. All figures are approximate and may vary. Bar twists are possible up to 2 mm per meter. Tolerance of steel thickness ± 1 mm. Length tolerance up to ± 200 mm. Degree details refer to the connector bar axes. Welding base of LPB, FD and MF connectors can be straight or bevelled. We reserve the right to make technical changes. We refer to DIN EN 12063. Please check the sheet pile interlocks with a physical sample section of the desired connector for compatibility.

User information

- About SteelWall
- Registration
- Newsletter
- Languages and measures

Legal advice

[Imprint](#)

[Privacy policy](#)

[General terms and conditions](#)

Last website update: 01. Mar. 2024
Copyright by SteelWall ISH GmbH
Connectors designed by Richard Heindl

steelwall.eu

- Africa
- Asia
- Australia
- Caribbean
- Europe
- India
- New Zealand
- South America

steelwallus.com

- North America
- South East Asia
- Japan
- Oceania

MF-pipe.com

MF-Pipe is a division
of SteelWall

