

Technical Summary

AI Gmail Email Classifier | Apps Script implementation notes

Architecture

- Google Apps Script runs the automation on a time-driven trigger.
- GmailApp searches unread inbox threads and processes up to 20 per run.
- OpenAI receives subject, sender, and a 500-character body snippet.
- The model returns JSON: categoryId, confidence, and reason.
- The script validates the category and applies Gmail labels.
- Errors are appended to a Google Sheets log.

Safety And Maintainability

- OpenAI API key is stored in Script Properties, not hardcoded.
- Categories are configured at the top of the script.
- A processed label prevents duplicate classification.
- Low-confidence output falls back to Other.
- Errors are logged instead of failing silently.
- The README includes deployment and setup instructions.

Files Included

File	Purpose
src/Code.gs	Main Apps Script workflow
appsscript.json	Manifest and OAuth scopes
README.md	Setup and usage instructions
docs/portfolio-case-study.md	Detailed project explanation
docs/upwork-portfolio-copy.md	Text for Upwork portfolio

Adaptation Options

- Change categories for a specific business inbox.
- Route quote requests or complaints to a CRM instead of only applying labels.
- Send Slack, email, or SMS alerts for urgent categories.
- Add confidence and reason fields to the Google Sheets log.
- Extend the workflow to Google Workspace admin or shared inbox scenarios.