HUI ZHOU ACUMAGNETCH FACTORY

INSPECTION REPORT OF OUTGOING

NO:Q202505056
Date:May/22/2025

CUSTOMER:REXAINC	ORDER NO.TH20250314012
PART NO:R16064	OTAL QUANTITY:13164PCS
DRAWING R16065	SAMPLING QUANTITY:100PCS
PART DESCRIPTION: 24Pole	PRODUCTION DATE:May/16-19/2025
MATERIALS:MAGNET TP-F26S	INSPECTION :May/22/2025
NUMBER OF CATIVITS: 1	LOT NO:20250424001-28001
INSPECTION QUANTITY 100PCS OK	INSPECTOR:Guimei Lin

NO./ITEM	STANDARD	INSTRUMENT											SAMPLING QUANTITY	DEFECT QUANTITY
1	50.05±0.15	B	50.03	50.01	50.00	50.04	50.02	50.03	50.02	50.04	50.03	50.00	100PCS	0PCS
2	42.83±0.15	B	42.77	42.75	42.76	42.73	42.75	42.76	42.77	42.75	42.76	42.74	100PCS	0PCS
3	9.86+0.15	B	9.92	9.89	9.90	9.92	9.98	9.87	9.90	9.92	9.89	9.88	100PCS	0PCS
4	29.37±0.1	B	29.38	29.40	29.38	29.40	39.39	29.38	29.39	29.37	29.41	29.40	100PCS	0PCS
5	39.68±0.15	B	39.73	39.71	39.70	39.68	39.70	39.69	39.67	39.70	39.71	39.68	100PCS	0PCS
6	16.21±0.15	B	16.29	16.31	16.29	16.29	16.30	16.32	16.29	16.28	16.31	16.30	100PCS	0PCS
7	3.51±0.05	B	3.54	3.53	3.55	3.54	3.53	3.55	3.54	3.53	3.55	3.53	100PCS	0PCS
8	1.68±0.05	E	1.63通								1.73止		315PCS	0PCS
9	5.23±0.1	B	5.27	5.28	5.27	5.30	5.27	5.30	5.29	5.28	5.30	5.29	100PCS	0PCS
10	11.02±0.1	B	11.05	11.07	11.02	11.06	11.05	11.04	11.05	11.06	11.04	11.05	100PCS	0PCS
11	23.72±0.1	C	23.75	23.73	23.72	23.68	23.74	23.73	23.71	23.70	23.70	23.72	100PCS	0PCS
12	23.71±0.1	B	23.69	23.71	23.68	23.67	23.69	23.70	23.71	23.68	23.69	23.71	100PCS	0PCS
13	19.16±0.1	B	19.13	19.15	19.14	19.13	19.15	19.13	19.14	19.15	19.14	19.12	100PCS	0PCS
14	14.375+0.05/+0	E	14.375通								14.425止		315PCS	0PCS
15	6.58±0.05	C	6.58	6.59	6.58	6.59	6.57	6.59	6.58	6.58	6.58	6.57	100PCS	0PCS
16	0.25	C	0.09	0.08	0.07	0.11	0.11	0.09	0.08	0.07	0.09	0.10	100PCS	0PCS
17	1.6MM磁力	L	247	250	248	252	250	246	254	251	248	249	100PCS	0PCS
18	15±0.75°	J	15°11′	15°22′	15°13′	15°18′	15°08′	15°18′	15°10′	15°22′	15°17′	15°13′	50PCS	0PCS
19	3.7±0.5°	J	见附页										30PCS	0PCS
20	A标识	A	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	315PCS	0PCS

Instruments:
(A)View (B) Caliper (C) Height Gages (D) Projector (E) Pin Gage (F) Micrometer G) Magnet Gauss Meter (H) Block Gauge
(I) Disk Micrometer (J) Magnet Flux Meter (K) 2.5 Coordinate Measuring Meter (L) Computer Magnet Oriving Apparatus
(M) Magnetic Impression Paper (N) 3 Coordinate Measuring Meter

APPROVED BY

角度数据

序号	角度	
	15±0.75°	3.7±0.5°
1	15°14′	3.71°
2	15°18′	3.58°
3	15°10′	3.83°
4	15°25′	3.50°
5	15°17′	3.71°
6	15°22′	3.62°
7	15°10′	3.58°
8	15°25′	3.80°
9	15°13′	3.73°
10	15°09′	3.53°
11	15°20′	3.60°
12	15°15′	3.71°
13	15°20′	3.82°
14	15°24′	3.51°
15	15°23′	3.75°
16	15°12′	3.78°
17	15°07′	3.60°
18	15°21′	3.52°
19	15°14′	3.74°
20	15°18′	3.78°
21	15°10′	3.63°
22	15°25′	3.58°
23	15°24′	3.67°
24	15°28′	3.53°
25	15°10′	3.66°
26	15°22′	3.71°
27	15°16′	3.85°
28	15°20′	3.72°
29	15°14′	3.63°
30	15°27′	3.71°

测试人:Guimei Lin

WORD排版 版鸭 创建自版鸭