

Recall:

If $A = \begin{bmatrix} \mathbf{v}_1 & \dots & \mathbf{v}_n \end{bmatrix}$ is an $m \times n$ matrix then:

- 1) $\text{Col}(A) = \text{Span}(\mathbf{v}_1, \dots, \mathbf{v}_n)$
- 2) $\text{Nul}(A) = \{\mathbf{v} \in \mathbb{R}^n \mid A\mathbf{v} = \mathbf{0}\}$

Construction of a basis of $\text{Col}(A)$

Lemma

Let V be a vector space, and let $\mathbf{v}_1, \dots, \mathbf{v}_p \in V$. If a vector \mathbf{v}_i is a linear combination of the other vectors then

$$\text{Span}(\mathbf{v}_1, \dots, \mathbf{v}_p) = \text{Span}(\mathbf{v}_1, \dots, \mathbf{v}_{i-1}, \mathbf{v}_{i+1}, \dots, \mathbf{v}_p)$$

Upshot. One can construct a basis of a vector space V as follows:

- Start with a set of vectors $\{\mathbf{v}_1, \dots, \mathbf{v}_p\}$ such that $\text{Span}(\mathbf{v}_1, \dots, \mathbf{v}_p) = V$.
- Keep removing vectors without changing the span, until you get a linearly independent set.

Example. Find a basis of $\text{Col}(A)$ where A is the following matrix:

$$A = \begin{bmatrix} 1 & 0 & 2 & 0 & 1 & 0 \\ 0 & 1 & 3 & 0 & -1 & 0 \\ 0 & 0 & 0 & 1 & 3 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 \\ 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix}$$

Example. Find a basis of $\text{Col}(A)$ where A is the following matrix:

$$A = \begin{bmatrix} -3 & 6 & -1 & 1 & -7 \\ 1 & -2 & 2 & 3 & -1 \\ 2 & -4 & 5 & 8 & -4 \end{bmatrix}$$

Construction of a basis of $\text{Nul}(A)$

Example. Find a basis of $\text{Nul}(A)$ where A is the following matrix:

$$A = \begin{bmatrix} -3 & 6 & -1 & 1 & -7 \\ 1 & -2 & 2 & 3 & -1 \\ 2 & -4 & 5 & 8 & -4 \end{bmatrix}$$

Upshot. If A is matrix then:

$\dim \text{Col}(A) =$ the number of pivot columns of A

$\dim \text{Nul}(A) =$ the number of non-pivot columns of A

Definition

If A is a matrix then:

- the dimension of $\text{Col}(A)$ is called the *rank* of A and it is denoted $\text{rank}(A)$
- the dimension of $\text{Nul}(A)$ is called the *nullity* of A .

The Rank Theorem

If A is an $m \times n$ matrix then

$$\text{rank}(A) + \dim \text{Nul}(A) = n$$

Low rank matrices in data analysis

	<i>exam 1</i>	<i>exam 2</i>	<i>exam 3</i>	<i>exam 4</i>
student 1	2	1	3	10
student 2	4	2	6	20
student 3	10	5	15	50
student 4	2	1	3	10
student 5	0	0	0	0
student 6	6	3	9	40