PeriGen, Inc.

PeriWatch® Tracings™ System Requirements

PeriGen
Advanced
Perinatal Systems

Table of Contents

Standard / Enterprise Model (Multi-Facilities) Server Requirements 3
PeriWatch Tracings – Enterprise Main DB/Application Server VM 3
PeriWatch Decision Support Server – Enterprise Server VM 4
PeriWatch Tracings - Test/Training/Custom Reports VM 5
Small Site Configuration (<1000 births annually and <10 monitoring locations) 5
PeriWatch Tracings – Small Site Configuration VM Specification 5
Virtual Servers 6
Archive Storage 6
Client / Workstation Requirements 6
Thin-Client Technologies 7
Network (For Workstations and Data Acquisition) 7
Tracing Data Acquisition 7
Fetal Monitor Compatibility 8

©PeriGen, Inc. – Confidential and Proprietary
This document may not be copied without express written permission.

Standard / Enterprise Model (Multi-Facilities) Server Requirements

- A full enterprise implementation of PeriWatch Tracings and Decision Support modules requires a base configuration of 3 server VMs as follows:
    - PeriWatch Tracings Application/DB/HL7 Interface VM
    - PeriWatch Decision Support Modules VM: PeriWatch Cues™, Curve™ and HUB™
    - PeriWatch Tracings Test/Train/Custom Reports VM
- See "Small Site configuration" section for sites <1000 births annually and <10 monitored locations
- System sizing is based on peak utilization and as a function of total monitored areas. Sizing below is based on projected requirements for approximately 5 years.
- Final configuration and optimization based on actual enterprise layout will be determined at system implementation planning stage
- Physical servers (if required) must follow custom/sizing configuration by PeriGen.

PeriWatch Tracings – Enterprise Main DB/Application Server VM

# of Monitored locations (1)	50	100	200
# of vCPUs	4	8	8
GB RAM	12	16	20
Volume C: OS	60 GB	60 GB	60 GB
Volume D: Applications	40 GB	40 GB	40 GB

SQL storage requirement when hosted on the local server:

Volume E: SQLData	260 GB	330 GB	400 GB
Volume F: SQLTransactionLog	50 GB	50 GB	50 GB
Volume G : SQLBackup	260 GB	330 GB	400 GB

Bandwidth and performance requirements If SQL server is hosted on a separate cluster or farm:

Transactions / sec	10-50	20-100	40-200
Disk Reads (MMB/sec)	2-60	4-120	8-240
Disk Writes (MB/sec)	1-20	2-40	5-80
Database Size G	260 GB	330 GB	400 GB
Transaction Logs	50 GB	50 GB	50 GB

(1) The CPU necessary on the Server comes from estimating the number of workstations simultaneously using the PeriWatch Tracings Client. This number is often difficult to compute. Monitored locations are easier to determine thus the table above shows Monitored locations. However, it assumes that each Monitored location is running a PeriWatch Tracings Client and there are no more than 10% additional workstations simultaneously doing the same. If it is anticipated that this will not be the case, then it will become necessary to adjust the CPU resources accordingly.

©PeriGen, Inc. – Confidential and Proprietary
This document may not be copied without express written permission.

- Gigabit Ethernet (Number of NICs may change depending on load and storage considerations)
- Microsoft Windows 2008 R2 Service Pack 1 or Windows Server 2012 R2
    - Internet Information Services (IIS) installed
    - ASP.NET
    - Windows Authentication
- MS SQL 2014 SP2 with Reporting Services
- The following ports should be free and available for use:
- TCP: 80, 91, 92, 443, 7100, 7200, 7802, 7803, 8000-8020, UDP: 11002
- Microsoft Web Services Enhancements (WSE) 3.0
- VC++ 2008 SP1 Redistributable, VC++ 2010 SP1 Redistributable
- .Net 3.5 SP1, .Net 4.7.1

PeriWatch Decision Support Server – Enterprise Server VM

# of Monitored locations	50	100	200
# of vCPUs	2	4	4
GB RAM*	8	12	16
Volume C: OS	40 GB	40 GB	40 GB
Volume D: Applications/SQL*	100 GB	100 GB	100 GB

* Sizing based on the use of all Decision Support modules (Cues, Curve and HUB). May be optimized depending on actual installed modules

- Gigabit Ethernet (Number of NICs may change depending on load and storage considerations)
- Microsoft Windows 2008 R2 Service Pack 1 or Windows Server 2012 R2
    - Internet Information Services (IIS) installed
    - ASP.NET
    - Windows Authentication
- MS SQL 2014 Express or higher with Reporting Services
- The following ports should be free and available for use:
- TCP: 91, 92, 7100, 7200, 7802, 7803, 8000-8020, 8201, 8202 and UDP: 11002
- VC++ 2008 SP1 Redistributable, VC++ 2010 SP1 Redistributable
- .Net 3.5 SP1, .Net 4.6.2 or higher

©PeriGen, Inc. – Confidential and Proprietary
This document may not be copied without express written permission.

PeriWatch Tracings - Test/Training/Custom Reports VM

- A minimum of 1 TEST/Train server is mandatory. More servers can be instantiated as needed
- 4 vCPUs
- 8GB RAM
- Storage requirements per volume:
  - C: Operating system - 60 GB
  - D: Applications/SQLData/Logs - 200 GB
- Gigabit Ethernet
- Microsoft Windows 2008 R2 Service Pack 1 or Windows Server 2012 R2
  - Internet Information Services (IIS) installed
  - ASP.NET
  - Windows Authentication
- MS SQL 2014 SP2 with Reporting Services
- The following ports should be free and available for use:
- TCP: 80, 91, 92, 443, 7100, 7200, 7802, 7803, 8000-8020, UDP: 11002
- Microsoft Web Services Enhancements (WSE) 3.0
- VC++ 2008 SP1 Redistributable, VC++ 2010 SP1 Redistributable
- .Net 3.5 SP1, .Net 4.7.1

Small Site Configuration (<1000 births annually and <10 monitoring locations)

- A small site configuration application to <1000 birth and under 10 monitored locations
- With such a small load, all application modules can be consolidated on the primary Application/DB production server
- System sizing is based on peak utilization and as a function of total monitored areas. Sizing below is based on projected requirements for approximately 5 years.
- Final configuration and optimization based on actual enterprise layout will be determined at system implementation planning stage
- If required, physical server(s) option should be equivalent to the VM specifications below.
- Any deviation from the Small Site definition above will require a custom sizing by PeriGen.
- A test server is still mandatory for any configuration

PeriWatch Tracings – Small Site Configuration VM Specification

# of Monitored locations	10
# of vCPUs	4
GB RAM	12
Volume C: OS	60 GB
Volume D: Applications	40 GB
Volume E: SQLData	300 GB
Volume F: SQLTransactionLog	50 GB
Volume G : SQLBackup	250 GB

©PeriGen, Inc. – Confidential and Proprietary
This document may not be copied without express written permission.

- Gigabit Ethernet (Number of NICs may change depending on load and storage considerations)
- Microsoft Windows 2008 R2 Service Pack 1 or Windows Server 2012 R2
    - Internet Information Services (IIS) installed
    - ASP.NET
    - Windows Authentication
- MS SQL 2014 SP2 with Reporting Services
- The following ports should be free and available for use:
- TCP: 80, 91, 92, 443, 7100, 7200, 7802, 7803, 8000-8020, 8201, 8202 and UDP: 11002
- VC++ 2008 SP1 Redistributable, VC++ 2010 SP1 Redistributable
- .Net 3.5 SP1, .Net 4.7.1

Virtual Servers

- VMware (6.X and above) and Hyper-V is currently supported for all the configurations above as long as it is part of an enterprise virtualization infrastructure (not on standalone server).
- Other platforms will require extra validation services

Archive Storage

- SAN or NAS storage can be used for long term encrypted archive storage (customer supplied)
- Archive storage requirements is based on storage requirement of 5 MB per birth.
- Illustration:
    - 8000 births annually for the entire enterprise
    - 8000 births per year x 5MB = 40GB/year.

Client / Workstation Requirements

- Microsoft Windows 7 or 10 Professional 32/64-bit (SP1)
- 2GB RAM. 250 MB of available memory should be reserved for PeriWatch Tracings modules.
- 1280x1024 (4:3) is the recommended standard minimal resolution supported by the system.
- 1024x768 (4:3) is supported with PeriWatch <u>but not supported</u> when Cues & Curve modules are purchased.
- Higher resolutions in 16:9 or 16:10 aspect rations are supported only in native resolution (non-native resolutions or aspect ratios will result in a stretched representation of fetal tracings and are not supported)
- .NET Framework 3.5 Service Pack 1
- .NET Framework 4.7.1 or higher Full client profile
- Microsoft Visual C++ Redistributable 2008 SP1 and 2010 SP1 (x86/x64).
- Microsoft Web Services Enhancements (WSE) 3.0
- Wireless network is not recommended for the PeriWatch Tracings application. If required, PeriGen will collaborate with the customer to confirm that PeriWatch application performs as expected on the site's wireless environment.
- Large Screen displays of non-interactive multi-tracing Surveillance or Census screens are supported in full screen in native resolutions only (typically 1920x1080). Different resolutions

©PeriGen, Inc. – Confidential and Proprietary
This document may not be copied without express written permission.

may require separate validation procedures and must be verified in advance with PeriGen personnel

- IMPORTANT: Interaction and acknowledgement with Fetal Alerts must be done on designated workstations where their MAC address is fixed and mapped in the PeriWatch administrative configuration. These stations are designated "Alerting Stations" and must typically be fixed thick clients.

Thin-Client Technologies

- Citrix or VMware View deployments of PeriWatch Tracings client application is now supported for all stations providing station hostname running the thin-client instance is uniquely identified for each session. Using the server names or synthetic host names is not supported.
- Citrix server / VMware view server sizing should be aligned with PeriWatch Client requirements and number of concurrent session requirements (see previous section). Precise server and memory recommendations are a function of overall site load. Recommendations will be finalized during system implementation.

Network (For Workstations and Data Acquisition)

- Switched Ethernet network, 100 Mbit or better
- CAT5+ dedicated cabling between each monitoring area and networking closet. Point-to-point configuration recommended.
- Proprietary cables between the fetal monitor and wall-plate are provided by PeriGen.

Tracing Data Acquisition

PeriGen provide a proprietary, secure and resilient solution dedicated to the store and forward of tracing data across the system:

- PeriWatch DAS™, a 16 port RS485 to Ethernet device with internal cache. Total number of DAS devices should be determined by total number of monitoring locations, physical vicinity to the networking closets and a 75% port utilization for port redundancy.
- PeriWatch Single gang wall-plate – For bedside wall mounted data collection from a single monitor (with Ethernet pass-through). Typically, one wall-plate is required per monitoring location.
- PeriWatch Dual gang wall-plate – For bedside wall mounted data collection from up to two fetal monitors (with Ethernet pass-through). Dual gang wall-plates are optional.

©PeriGen, Inc. – Confidential and Proprietary
This document may not be copied without express written permission.

Fetal Monitor Compatibility

Vendor	Protocol compatibility	Type	Interface card / Firmware	Description
Philips	1371	* 1350A and B * 50XM series	M1350-66532 or M1350-66536 * Firmware: **C01.03 and above**	DB9 pin serial connector for RS232 interface. Firmware software must support option C13.
Philips	1371	Avalon FM20 Avalon FM30 Avalon FM40 Avalon FM50	Firmware: **F.0X and above.**	DB9 pin serial connector for RS232 interface. Firmware software must support option C13.
GE/Corometrics	1371	118	J09-J10	DB9 RS232 serial interface
GE/Corometrics	1371	120/170/250 Series	J09-J10-J11	RJ11 RS232 serial interface

* Philips 1350 A/B and 50XM are presently out of support by Philips. Although the serial protocol is still supported, PeriGen cannot be held responsible for known issues with these fetal monitors with firmware versions lower than **C01.03.** Known issues include a very high frequency of SP02 measurements sent to the electronic tracing when the paper recorder door is open, and no paper is in the-0 tray.

©PeriGen, Inc. – Confidential and Proprietary
This document may not be copied without express written permission.