

[E] LIQUID_eKYC_017_SDKApplyAPI_v1.3.6

Revision history

- 2020/04/22 v1.0 Created
- 2020/11/17 v1.1 Made corrections to the specifications of invalidating the verification token
- 2020/12/02 v1.2
 - Added features for individual number document collection
 - Added error code: Specified Applicant ID is already used (CE00002)
 - Changed value type descriptions from Japanese to English
- 2021/08/05 v1.3.0 Organized features related to individual number document collection, and separated them into the individual number apply API. 2: Operation assignment priority
 - Add request item: operation assignment priority
 - Add error code: Applicant ID not found (CE00001)
 - Delete error code: Specified Applicant ID is already used (CE00002)
- 08/30/2021 v1.3.1 Made minor correction
- 2021/11/17 v1.3.2 Added information about restrictions and Applicant ID
- 2023/9/26 v1.3.3 Added redirect URL for requests and redirect URL on error
- 2023/10/24 v1.3.4 Changed the character limit to 1000 for the redirect URL for request items and the redirect URL for errors
- 2024/08/27 v1.3.5 Changed timeout period for authentication tokens
- 2024/11/01 v1.3.6
 - Add request item : Preferred language
 - Changed "Request item" description : "Redirect URL for requests" and "Redirect URL on error"

Overview

- Creates application data to run KYC through LIQUID eKYC SDK
- Builds a system with LIQUID eKYC SDK and issues verification tokens for communication between the server and your app

Specification

- When Applicant ID has not been registered
 - Creates new application data for the designated Applicant ID and assigns a new verification token to it.
- When Applicant ID has been registered
 - If Activation Function is not executed yet (status = application incomplete)
 - Creates new application data and assigns a new verification token to it.
 - Invalidate the existing verification token
 - If the newest application is complete and the KYC result is NG
 - Creates new application data and assigns a new verification token to it.
 - If the newest application has expired
 - Creates new application data and assigns a new verification token to it.
 - Anything other than the above
 - Returns "The application of designated Applicant ID cannot be resubmitted (CE00003)"
- If the API is made for a Applicant ID other than the KYC, the non-existent Applicant ID (CE00001) will be returned.
- The timeout limit of the verification token

- 90 minutes

About Applicant ID

- Applicant ID is an ID that uniquely identifies an user who submitted the KYC request
- Applicant IDs should be issued by your organization
- **The same Applicant ID can be used until the KYC result is registered as OK. But once the KYC result is registered as OK, the Applicant ID may not be reused**
- **For this reason, please manage the User IDs managed within your organization and Applicant IDs as having 1:N (many) relationships**

Restrictions

- Max 100 requests/minute

Error cases

- Applicant ID not found (CE00001)
- The application of designated Applicant ID cannot be resubmitted (CE00003)
- System Error

API Specification

- URL
 - Staging: https://(Unique URL for each organization)/v1/sdk/applications
 - Production: https://(Unique URL for each organization)/v1/sdk/applications
- Protocol: https
- Method: POST
- Request: JSON
- Response: JSON

Request detail

HTTP header

	論理名 (Logical Name)	物理名 (Physical Name)	JSONデータ 型 (JSON Data Type)	データ属性 (Value Type)	文字数上限 (Char. Limit)	必須 (Req?)	フォーマット (Format)	説明 (Description)
1	API Key	Refer to Common Spec.				○	Refer to Common Spec.	

Body

	論理名 (Logical Name)	物理名 (Physical Name)	JSONデータ 型 (JSON Data Type)	データ属性 (Value Type)	文字数上限 (Char. Limit)	必須 (Req?)	フォーマット (Format)	説明 (Description)
1	Applicant ID	Refer to Common Spec.				○	Refer to Common Spec.	

2	Operation assignment priority	operation_assignment_priority	string	Number	1		Specify the priority of KYC check in Manager as a number. (1: high priority, 9: low priority) Only numbers 1 to 9 can be specified.
3	Redirect URL	redirect_url	string	URL	1000		Redirected to the JPKI (Japanese Public Key Infrastructure) LIQUID eKYCアプリ・AppClip(JPKI+アプリ) application after completion of the application. With the redirect URL check function ON (OFF by default), an incorrect redirect URL (CE00027) is returned when a redirect URL or error redirect URL, other than the FQDN preset for each client, is specified.
4	Error redirect URL	error_redirect_url	string	URL	1000		Redirects in the event of errors in public personal authentication applications . LIQUID eKYCアプリ・AppClip(JPKI+アプリ) With the redirect URL check function ON (OFF by default), an incorrect redirect URL (CE00027) is returned when a redirect URL or error redirect URL, other than the FQDN preset for each client, is specified.
5	Preferred language	preferred_language	string	Alphabet(Half-width)	2		Specify the preferred "language code" to be used when displaying the LIQUID eKYC app and App Clip (JPKI+ apps.) Please note that the LIQUID eKYC SDK is not applicable. <<Please refer to "APIGenericCode">>

Response detail

Body

論理名 (Logical Name)	物理名 (Physical)	JSONデータ 型	データ属性 (Value Type)	文字数上限 (Char. Limit)	必須 (Req?)	フォーマット	説明 (Description)
-----------------------	-------------------	--------------	-----------------------	------------------------	--------------	--------	---------------------

	Name)		(JSON Data Type)				(Format)	
1	Verification Token	token	string	Alphanumeric (Half-width)		○		

HTTP Status Code

1	Code	説明(Description)
2	201	Success

Usage Examples

Request body

```
{
  "applicant_id":"111902224425",
  "operation_assignment_priority":"1"
}
```

Response body

```
{
  "token":"365b5431030d3401756f912a5e80921c2c9189fccf1e355eb54ffaf5ba2e6e49"
}
```