



# PO022-12D-3B-3 PO022-24D-3B-3

## **Features**

Size: 92 x 92 x 15.5 mm (3.6" x 3.6" x 0.6")

Airflow: 25 CFM

85 g (3.0 oz) Weight:

Noise: 32 dBA

AWG (UL1007, UL2468) Lead Wire:

Impeller/Frame: Reinforced Plastic (UL94V-0)

Bearings: Sealed Ball




**QU** UL E101153




CSA LR83514

## **Dimensions - mm**



## Air Flow vs Air Pressure



#### **Performance**

| Туре           | Rated<br>Voltage<br>(V) | Rated Current (A) |       | Max Air<br>Flow | Max Air<br>Pressure   | Noise* | Operating Voltage | Operating<br>Temperature | Life<br>Expectancy |
|----------------|-------------------------|-------------------|-------|-----------------|-----------------------|--------|-------------------|--------------------------|--------------------|
|                |                         | Locked            | Moved | (CFM)           | (In H <sub>2</sub> O) | (dBA)  | (V)               | (°C)                     | (Hr)<br>(@ 25°C)   |
| PO022-12D-3B-3 | 12                      | 0.28              | 0.20  | 24.7            | 0.12                  | 32     | 10.2~13.8         | -10~ +60                 | 50,000             |
| PO022-24D-3B-3 | 24                      | 0.16              | 0.10  | 24.7            | 0.12                  | 32     | 20.4~27.6         | -10~ +60                 | 50,000             |

<sup>\*</sup>Measured 1 m from side of fan