




Weight: 0.31g Unit: mm



AND620HW

InGaN High Brightness White Light Emission

- 5 mm (T1-3/4) Package
- Fluorescence Type
- Low drive current: 1 to 20 mA DC
- Excellent On-Off contrast ratio
- Fast response time, capable of pulse operation
- High power intensity – suitable for LCD backlights, switches, displays, keys, illuminated ads, & substitution for micro incandescent lamps, outdoor message signboards, emergency lighting, reading lamps
- High reliability/ high efficiency/ high luminous output

Maximum Ratings ($T_a = 25^{\circ}\text{C}$)

Characteristics	Symbol	Rating	Unit
Forward Current	I_F	20	mA
Reverse Voltage	V_R	5	V
Power Dissipation	P_D	100	mW
Operating Temperature Range	T_{Opr}	-25 to 85	C
Storage Temperature Range	T_{Sig}	-25 to 100	C

Electro-Optical Characteristics ($T_a = 25^{\circ}\text{C}$)

Characteristics	Symbol	Test Condition	Minimum	Typical	Maximum	Unit
Forward Voltage	V_F	$I_F = 20 \text{ mA}$	–	3.6	4.0	V
Reverse Current	I_R	$V_R = 5 \text{ V}$	–	–	10	μA
Luminous Intensity	I_V	$I_F = 20 \text{ mA}$	2,800	4,800	–	mcd
Wavelength=550nm						
Chromaticity Coordinates	x	$I_F = 10 \text{ mA}$	–	.29	–	
	y	$I_F = 10 \text{ mA}$	–	.30	–	
Full Viewing Angle	θ	$I_V = 1/2 \text{ Peak}$	–	20	–	degree

Precaution

Please be careful of the following:

1. Soldering temperature: 260 C max.
Soldering time: 5 sec. max.
Soldering portion of lead: up to 1.6 mm from the body of the device
2. The lead can be formed up to 5 mm from the body of the device without forming stress.
Soldering should be performed after the lead forming.
3. Absolute secure counter measures against static electricity and surge should be taken when handling these products. It is recommended to use wrist band or antistatic gloves when handling these LEDs.

