

A series of yellow geometric shapes, including a large trapezoid and several rounded squares, arranged in a descending staircase pattern on the left side of the slide.

Cryptocurrencies for the Masses

Scaling Blockchain

SEHYUN CHUNG
ALPIN YUKSELOGLU

Table of Contents

01 Background

02 Taproot

03 Sharding

04 Segregated Witness

05 Lightning Network

06 Plasma, Optimistic Rollups



Meet Your Lecturers



Sehyun Chung

Education/Xcelerator



Alpin Yukseloglu

Consulting/Xcelerator



Background



What is the Scalability Problem?

Goal:

Provide all of the services that a blockchain offers to all users,
independent of how many users there are



What is the Scalability Problem?




Volume of
Transactions



Block Time



Scalability Triangle



TPS Comparisons

How does Bitcoin compare with other traditional payment systems*?

	Average	High Load / Maximum
Bitcoin	3 tps	3.2 tps
PayPal*,**	150 tps	450 tps
VISA***	2,000 tps	56,000 tps

*debatably an unfair comparison/metric, but people care about it anyways



Layer 1 vs. Layer 2

Layer 1

- refers to the main blockchain architecture
- e.g. the Bitcoin Blockchain, the Ethereum Blockchain

L1 Solutions

- changes made **on-chain** that improve scalability

Layer 2

- refers to a secondary framework or protocol that is built on top of an existing blockchain
- e.g. the Lightning Network, Ethereum Plasma

L2 Solutions

- changes made **off-chain** that improve scalability





QUESTIONS?

Layer 1



What Layer 1 scaling solutions have you heard of?



Taproot

Problems before Taproot

- Signature verification is slow, but required **everywhere** in the network
 - case 1: when validating a new block
 - case 2: when a node newly connects (or reconnects) to the network
- Users can see many details of a transaction (all scripts, multisignature, etc.)



Taproot + Schnorr

- Schnorr is a type of signature, Taproot is the Bitcoin upgrade (BIP) that uses Schnorr
- Taproot combines Schnorr, Merkelized Abstract Syntax Trees (MAST)
- Idea: If signature validation is faster, much of the network can run faster (more throughput)
- Taproot replaces ECDSA signatures with Schnorr Signatures
- Schnorr benefits:
 - key aggregation
 - verification in linear time



Benefits of Taproot + Schnorr

- allows multiple signers in a transaction to create an aggregate public key and an aggregate signature so multisig ends up **looking** the same and **costing** the same as a single signature
 - 30-75% savings on multisig
- allows for **batch validation**
 - a process in which many signatures can be verified *at once*, faster than than verifying each signature individually
 - this speedup grows logarithmically with the number of sigs to verify, so verifying 1 billion signatures (IBD) could be 4x as fast!
- when a transaction has many scripts, they do not need to be revealed or evaluated on the network



Benefits of Taproot

- More Privacy:
 - many transaction types (multisig, scripts, etc.) look the same as regular transaction
 - impossible for user monitoring the network to figure out if a transaction was signed by one person or multiple people
 - all scripts of a transaction are not broadcast for everyone to see
- Functionality
 - enables very large k of n multisig
 - can use much larger scripts





QUESTIONS?

Segregated Witness (L1 + L2)

Problems before Segwit:

- transaction malleability
- inefficient script versioning system
- inefficient signature hashing operations
- historic signature data everywhere



Inside Transactions

Before

```
[ ... ]  
"Vin" : [  
  "txid": "0627052b6f28912f2703066a912ea577f2ce4da4caa5a5fbd8a57286c345c2f2",  
  "vout": 0,  
    "scriptSig": "<Sehyun's scriptSig>",  
]  
[ ... ]
```

After


```
[ ... ]  
"Vin" : [  
  "txid": "0627052b6f28912f2703066a912ea577f2ce4da4caa5a5fbd8a57286c345c2f2",  
  "vout": 0,  
    "scriptSig": "",  
]  
[ ... ]  
"witness": "<Sehyun's witness data>"  
[ ... ]
```



Mirrored Signature Tree

Q: How can we verify that the correct signatures were included with each transaction in the first place?

A: Construct a merkle tree of signatures that mirrors the merkle tree of transactions



Script Versioning and Signature Hashing

Scripts

- a series of opcodes
- To implement changes, one had to replace an extra opcode with the new one
- Segwit introduced version numbers so that upgrading to a new script version could be done by simply increasing this version number
- made upgrades to Schnorr and MAST much easier!

Signature Hashing

- resolved the issue of quadratic time signature hashing by only requiring each byte to be hashed at most twice



Pros/Cons

Pros:

- Fixes Transaction Malleability
 - Allows Lightning Network and sidechains to work
- Soft Fork
- Increased efficiency
- Increased Block Size
- Smaller Size of Blockchain

Cons:


- One-time linear capacity increase
- Obligated wallets to upgrade
- Better ways to solve malleability exist, but had to keep into account the needs of developers, miners, and users






QUESTIONS?

Sharding



Sharding

Sharding is the idea of not requiring every miner to be working on every single block, essentially creating parallel but connected blockchains.




Sharding

Node categories:

- super-full node
- top-level node
- single-shard node
- light node

Some challenges:

- Cross-shard communication
- Single-shard takeover





QUESTIONS?

Layer 2



What Layer 2 scaling solutions have you heard of?



Lightning Network

Recall:

- Every transaction is put onto the blockchain
- 6 block confirmation time
 - ~1 hour wait time
- Each transaction has a transaction fee
 - Inconsistent
 - Not economical for low-value items
 - Micro-payments impossible



Layer 2

Lightning Network

Idea:

Don't put every transaction on the blockchain



Lightning Network

Idea:

Don't put every transaction on the blockchain

Problem:


Can Alice and Bob make payments between themselves
without always needing to consult the blockchain?



Payment Channels

Idea:

- What if Alice and Bob maintain a private balance sheet
 - update the private balance sheet with every payment
 - only consult the blockchain when they want to settle the balance



Payment Channels

Q: What if either Alice or Bob try to cheat the other by settling early, or never?

A: Incorporate fallbacks using bitcoin Script to create blockchain-enforceable contracts between Alice and Bob so that neither party can cheat the other, while maintaining the private balance sheet functionality!



Payment Channels


Observation:

- If either Alice or Bob cheat
 - can always override and take all the money in the deposit.
- If Alice and Bob always cooperate
 - don't have to touch the blockchain, except when creating the payment channel and settling the balance.
- Only two transactions on the blockchain (initial and settlement)
 - Supports arbitrary number of local transactions between Alice and Bob



Lightning Network

Alice sends money to Charlie through this hypothetical payment channel network




Pros/Cons

Pros:

- Assuming enough capital, *people can make payments instantly*
- No need to wait for confirmation times
- Only use Bitcoin blockchain to settle disputes and close out payment channels (super efficient)
- Only pay transaction fees on channel open/close
- 3 TPS => 10,000's+ TPS

Cons:

- Nodes need to keep **large amounts** of capital locked up in payment channels
- **Risk of centralization** since only nodes with significant capital can afford to run payment channels for long
- Tendency towards *hub-and-spoke* topology





QUESTIONS?

Raiden Network Scalability

- Ethereum's Payment Channel Network
 - Lightning, on Ethereum
 - Only occasionally updates main chain for settlements
 - Smart contract
 - ERC20-compliant token transfers



Plasma

- Nested blockchains
- Child chain attached to main (“root”) chain
- Set of smart contracts (no change to consensus)
- Fraud proofs – builds “court system”
- Struggles with supporting operations more complex than payments
- Scalability with enforceability
- Compatible with sharding, rollups etc.



Source: <https://www.youtube.com/watch?v=nf1iEbBtbCE>




Optimistic Rollups

- Data storage on-chain, computation off-chain
- Employs fraud proofs to verify correctness of off-chain computation
- Supports more complex operations (i.e. smart contracts)
- Ready for deployment!
- Provides less of an increase in scalability than other solutions



Scalability Triangle





QUESTIONS?

Ethereum 2.0

- Great scalability use case to track:
 - Phase 0: Transition to Proof of Stake
 - Phase 1: Data Sharding
 - Phase 2: State + Execution (computation and smart contracts)
 - Phase 3+: Other scaling solutions
- Multiple year timeline, but existing scaling solutions like optimistic rollups show a lot of promise for short-term scaling



ethereum 2.0

Source: <https://forkast.news/vitalik-buterin-explains-ethereum-2-0s-four-phases-sharding-scaling-proof-of-stake-and-more/>





THANK YOU