



# CSIS-1400

Final Prep

# Scope

- Sope of a local variable

# Local Variables

- Where can they be declared?
- Are they default initialized?
- When do they need to be initialized?

# Primitive Types

- How many primitive types are there?
- List primitive types

`double x = 7;`

Check all statements that divide x in half:

a) `x /= 2;`

b) `x = x / x;`

c) `x -= x / 2;`

d) `x *= 1 / 2;`

e) `x = (x > x / 2) ? x / 2 : 1 / 2 * x;`

`double x = 7;`

Check all statements that divide x in half:

a) `x /= 2;`

b) `x = x / x;`

c) `x -= x / 2;`

d) `x *= 1 / 2;`

e) `x = (x > x / 2) ? x / 2 : 1 / 2 * x;`



# Array of type double:

```
double[] quizResults = new double[7];
```

# Example:

```
double[] quizResults = new double[7];
```

quizResults[0]

0.0

quizResults[1]

0.0

quizResults[2]

0.0

quizResults[3]

0.0

quizResults[4]

0.0

quizResults[5]

0.0

quizResults[6]

0.0



# Example:

```
double[] quizResults = new double[7];
```

quizResults[0]

0.0

quizResults[1]

0.0

quizResults[2]

0.0

quizResults[3]

0.0

quizResults[4]

0.0

quizResults[5]

0.0

quizResults[6]

0.0

Default values

# Example:

```
double[] quizResults = new double[7];
```

quizResults[0]

0.0

quizResults[1]

0.0

quizResults[2]

0.0

quizResults[3]

0.0

quizResults[4]

0.0

quizResults[5]

0.0

quizResults[6]

0.0

Indices: from 0 to quizResults.length - 1

# Example:

```
double[] quizResults = new double[7];
```

```
quizResults[0] = 89.5;
```

```
quizResults[2] = 94;
```

```
quizResults[4] = 92.5;
```

# Example:

```
double[] quizResults = new double[7];
```

quizResults[0]

89.5

quizResults[1]

0.0

quizResults[2]

94

quizResults[3]

0.0

quizResults[4]

92.5

quizResults[5]

0.0

quizResults[6]

0.0

# Example:

```
double[] quizResults = new double[7];
```

quizResults[0]

89.5

quizResults[1]

0.0

quizResults[2]

94

quizResults[3]

0.0

quizResults[4]

92.5

quizResults[5]

0.0

quizResults[6]

0.0

Elements of a  
value-type array  
include the actual  
value (e.g. 89.5)

# Array of type string:

```
String[] names = new String[4];
```

# Example:

```
String[] names = new String[4];
```

names[0]

null

names[1]

null

names[2]


null

names[3]

null

# Example:

```
String[] names = new String[4];
```





# Example:

```
String[] names = new String[4];
```

names[0]

null

names[1]

null

names[2]

null

names[3]

null

Indices: from 0 to names.length - 1

# Example:

```
String[] names = new String[4];
```


```
names[0] = "Tim";
```

```
names[1] = "Mary";
```

```
names[2] = "Ben";
```


# Example:

```
String[] names = new String[4];
```



# Example:

```
String[] names = new String[4];
```



Elements of a reference-type array include a reference to the actual object

# **TODO:** Arrays

How do you declare an array variable?

How do you access an array element?

What is the first / last index of array myArray?

How do you pass an array argument to a method?

Can an array be resized (yes / no) ?

# TODO: Arrays

How do you declare an array variable?

`type[] myArray;`      e.g. `int[] iArray;`

How do you access an array element?

What is the first / last index of array `myArray`?

How do you pass an array argument to a method?

Can an array be resized (yes / no) ?

# TODO: Arrays

How do you declare an array variable?

`type[] myArray;`                      e.g. `int[] iArray;`

How do you access an array element?

`myArray[index]`                      e.g. `iArray[3]`

What is the first / last index of array `myArray`?

How do you pass an array argument to a method?

Can an array be resized (yes / no) ?

# TODO: Arrays

How do you declare an array variable?

`type[] myArray;`                      e.g. `int[] iArray;`

How do you access an array element?

`myArray[index]`                      e.g. `iArray[3]`

What is the first / last index of array `myArray`?

first index: `0`                      last index: `myArray.length - 1`

How do you pass an array argument to a method?

Can an array be resized (yes / no) ?



# TODO: Arrays

How do you declare an array variable?

`type[] myArray;`                      e.g. `int[] iArray;`

How do you access an array element?

`myArray[index]`                      e.g. `iArray[3]`

What is the first / last index of array `myArray`?

first index: `0`                      last index: `myArray.length - 1`

How do you pass an array argument to a method?

pass the name                      e.g. `myMethod(myArray)`

Can an array be resized (yes / no) ?

# TODO: Arrays

**How do you declare an array variable?**

`type[] myArray;`                      e.g. `int[] iArray;`

**How do you access an array element?**

`myArray[index]`                      e.g. `iArray[3]`

**What is the first / last index of array myArray?**

`first index: 0`                      `last index: myArray.length - 1`

**How do you pass an array argument to a method?**

`pass the name`                      e.g. `myMethod(myArray)`

**Can an array be resized (yes / no) ?**

`NO, it can not be resized once it has been created`



# Arrays:

**How do you use an array initializer?**

# Arrays:

How do you use an array initializer?

List comma separated array elements in curly braces

e.g.:

```
int[] iArray = {10, 20, 30, 40};
```

```
String[] strArray = {"Tim", "Don", "Pat"};
```

```
Point[] ptArray = {new Point(2,3), new Point(4, 1)};
```



# EXERCISE 1

# TODO:

Circle all expressions that subtract 1 of the array element on index i?

- `--arrayName[i]`
- `arrayName--[i]`
- `arrayName[i]--`
- `arrayName[i--]`
- `arrayName[--i]`

Circle all expressions that subtract 1 of the array element on index i?

- `--arrayName[i]`
- `arrayName--[i]`
- `arrayName[i]--`
- `arrayName[i--]`
- `arrayName[--i]`

Circle all expressions that subtract 1 of the array element on index i?

- `--arrayName[i]`
- `arrayName--[i]`
- `arrayName[i]--`
- `arrayName[i--]`
- `arrayName[--i]`

The array name is immediately followed by the index



Circle all expressions that subtract 1 of the array element on index i?

- `--arrayName[i]`
- `arrayName--[i]`
- `arrayName[i]--`
- `arrayName[i--]`
- `arrayName[--i]`

The array name is immediately followed by the index

Here the index itself is decremented, not the element on that index

# Enhanced for Statement **foreach loop**

- Syntax:

```
for ( type name : arrayNames )  
{  
    statement(name)  
}
```

*arrayName* ... name of array through which we iterate.

*type* ... must match array's element type.

# Enhanced for Statement (for-each loop)

## Pro:

- **Clear and concise syntax**
  - makes code easier to read
- **Robust**
  - Avoids off-by-1 errors

# Enhanced for Statement (for-each loop)

## Con:

- Can't re-assign elements
- Provides no index


If you need to assign new elements or access the index use the counter controlled for loop



## EXERCISE 2


# Passing Arrays to Methods

- You can pass **single array elements** or the whole array




## 7.7 Passing Arrays to Methods

- You can pass **single array elements** or the **whole array**



## 7.7 Passing Arrays to Methods


- You can pass **single array elements** or the **whole array**






## 7.7 Passing Arrays to Methods

- You can pass **single array elements** or the **whole array**



## 7.7 Passing Arrays to Methods

- You can pass **single array elements** or the **whole array**



Whatever you pass as an argument needs to match the parameter type in the method declaration

# Passing array elements:

Variable declaration:

```
int[] iArray = { 2, 4, 6, 8 };
```

Method declaration:

```
void printTriangle (int size)
{
    // print triangle
}
```

# Passing array elements:

Variable declaration:

```
int[] iArray = { 2, 4, 6, 8 };
```

Method declaration:

```
void printTriangle (int size)
{
    // print triangle
}
```

Method call:

```
printTriangle(iArray[1]);
```

# Passing array elements:

Variable declaration:

```
int[] iArray = { 2, 4, 6, 8 };
```

Method declaration:

```
void printTriangle (int size)
{
    // print triangle
}
```

**int** is no longer mentioned, but whatever is passed has to be of type int

Method call:

```
printTriangle (iArray[1]) ;
```

# Passing arrays:

Variable declaration:

```
int[] iArray = { 2, 4, 6, 8 };
```

Method declaration:

```
void printArray (int[] iArray)
{
    for(int el : iArray)
    {
        System.out.printf("%d ", el);
    }
}
```

# Passing arrays:

Variable declaration:

```
int[] iArray = { 2, 4, 6, 8 };
```

Method declaration:

```
void printArray (int[] iArray)
{
    for(int el : iArray)
    {
        System.out.printf("%d ", el);
    }
}
```

Method call:

```
printArray(iArray);
```

# Passing arrays:

Variable declaration:

```
int[] iArray = { 2, 4, 6, 8 };
```

Method declaration:

```
void printArray (int[] iArray)
{
    for(int el : iArray)
    {
        System.out.printf("%d ", el);
    }
}
```

**int[]** is no longer mentioned, but whatever is passed has to be of type int[]

Method call:

```
printArray(iArray);
```



# Passing arrays:

Variable declaration:

```
int[] iArray = { 2, 4, 6, 8 };
```

Method declaration:

```
void printArray (int[] iArray)
{
    for(int el : iArray)
    {
        System.out.printf("%d ", el);
    }
}
```

Method call:

```
printArray(iArray);
```

`int[]` is no longer mentioned, but whatever is passed has to be of type `int[]`

You pass the name or the array



T / T[ ] / ArrayList<T>

e.g.

String

String[]


ArrayList<String>



## EXERCISE 3α

# ArrayList vs Array

ArrayList	Array
can grow and shrink	fixed size
reference types only	primitive and referenct types
	very efficient



Be prepared for an exercise where you have to write some code using methods from class `Arrays` and/or `ArrayList<E>`

Class `Arrays`

Class `ArrayList<E>`

#### Example 4:

Code reading: ArrayList or array:

Print the output produced by the method below. Pay attention to details like new lines etc.

```
ArrayList<String> treeList = new ArrayList<String>();  
treeList.add("oak");  
treeList.add("ash");  
treeList.add("fir");  
  
System.out.println(treeList);  
  
treeList.add(2, "banyan");  
treeList.remove("oak");  
  
for (String tree: treeList)  
{  
    System.out.printf("%s ", tree);  
}
```

#### Example 4:

Code reading: ArrayList or array:

Print the output produced by the method below. Pay attention to details like new lines etc.

```
ArrayList<String> treeList = new ArrayList<String>();  
treeList.add("oak");  
treeList.add("ash");  
treeList.add("fir");
```

```
System.out.println(treeList);
```

```
treeList.add(2, "banyan");  
treeList.remove("oak");
```

```
for (String tree: treeList)  
{  
    System.out.printf("%s ", tree);  
}
```

**[oak, ash, fir]**  
**ash banyan fir**

# Method / Ctor Overloading

- What is method / constructor overloading?
- Why do people overload methods / constructors?



# Enum rules and restrictions:

- All enum types are **reference types**.
- **enum declaration**: comma-separated list of enum constants
- **enum** constants are **implicitly final**
- **enum** constants are **implicitly static**.
- static method **values** returns array of the enum's constants.



```
enum Season { WINTER, SPRING, SUMMER, FALL }
```

implicitly static and final



All Uppercase

```
enum Season { WINTER, SPRING, SUMMER, FALL }
```

implicitly static and final

All Uppercase

NO double  
quotes

```
enum Season { WINTER, SPRING, SUMMER, FALL }
```

implicitly static and final

# Java API

Match the functionality provided to one of those 4 types

- Scanner
- Math
- Arrays
- ArrayList

## Example 5

Random **A**

I need to simulate tossing a coin 2000 times

I need to calculate the square root of 15

Math **B**

I need to print the first 10 digits of pi

I need to read in the title of the missing book

Scanner **C**

I'd like to set the value of all elements in my byte array to 6

It returns a value between 25 and 100

Arrays **D**

I need to sort an all the points in a given array

I need the user to enter his gpa

## Exercise 5

Random **A**

I need to simulate tossing a coin 2000 times **A**

I need to calculate the square root of 15 **B**

Math **B**

I need to print the first 10 digits of pi **B**

I need to read in the title of the missing book **C**

Scanner **C**


I'd like to set the value of all elements in my byte array to 6 **D**

It returns a value between 25 and 100 **A**

Arrays **D**

I need to sort all the points in a given array **D**

I need the user to enter his gpa **C**







## EXERCISE 6



# STATIC

How is a static field different from an instance field?

Give an example of a static field / instance field


# STATIC

How is a static field different from an instance field?

Give an example of a static field / instance field

How is a static method different from an instance method

Give an example when to use a static method / instance  
method



There will be examples similar to those on  
the **array quiz**, the **loop quiz** and/or the  
**accessing instance methods quiz**

**Please review the quiz prep materials.**



## EXERCISE 7